



Einfach. Sicher.



PRESTANDADEKLARATION

DoP 0203

för Upat Express Anchor IMC (Metallankare för användning i betong)

SV

1. <u>Produkttypens unika identifikationskod:</u>	DoP 0203		
2. <u>Avsedd användning/avsedda användningar:</u>	Infästning i efterhand i osprucken betong. Se bilaga, särskilt bilagor B1- B3 Upat Vertriebs GmbH, Bebelstraße 11, 79108 Freiburg im Breisgau, Tyskland		
3. <u>Tillverkare:</u>			
4. <u>Tillverkarens representant:</u>	-		
5. <u>System för bedömning och fortlöpande kontroll av prestanda:</u>	1		
6. <u>Europeiskt bedömningsdokument:</u> Europeisk teknisk bedömning: Tekniskt bedömningsorgan: Anmält/anmällda organ:	EAD 330232-01-0601, (Edition 12/ 2019) ETA-10/0169; 2020-07-14 DIBT- Deutsches Institut für Bautechnik 1343 MPA Darmstadt / 2873 TU Darmstadt		
7. <u>Angiven prestanda:</u> Mekanisk hållfasthet och stabilitet (BWR 1) Karakteristisk bärformåga för spänning (för statisk och kvasi-statisk belastning):	Stålets motståndskraft: Motstånd mot att skruven dras ut:	Bilagor C1 Bilagor C1	$E_s = 210\,000 \text{ MPa}$
	Motstånd i betongkonen: Kraftighet:	Bilagor C1 Bilagor C1	$k_{cr,N} = \text{NPD}$
	Minsta kant- och axelavstånd: Kantavstånd för att slippa sprickor under last:	Bilagor C3 Bilagor C1	
Karakteristisk bärformåga för skjutning (för statisk och kvasi-statisk belastning), Metod A:	Motstånd i stålet (tvärlast): Motstånd mot fläckning:	Bilagor C2 Bilagor C2	
Karakteristiskt motstånd och Förskjutningar för seismiska prestandakategorier C1 och C2:	Motstånd mot draglast, förskjutningar, kategori C1: Motstånd mot draglast, förskjutningar, kategori C2: Motstånd mot tvärlast, förskjutningar, kategori C1: Motstånd mot tvärlast, förskjutningar, kategori C2: Faktor cirkulärt hål:	NPD NPD NPD NPD NPD	
Karakteristisk motstånd för förenklad design:	Metod B: Metod C:	NPD NPD	
Förskjutningar och Hållbarhet:	Förskjutningar under statisk och kvasistatisk belastning: Hållbarhet:	Bilagor C3 Bilagor A4, B1	
Säkerhet vid brand (BWR 2) Reaktion vid brand: Motståndskraft mot eld:	Klass (A1) Brandmotstånd i stålet (tvärlast): Brandmotstånd mot utdrag (draglast): Brandmotstånd i stålet (tvärlast):	NPD NPD NPD	



Einfach. Sicher.



8. Lämplig teknisk dokumentation och/eller särskild teknisk dokumentation: -

Prestandan för ovanstående produkt överensstämmer med den angivna prestandan. Denna prestandadeklaration har utfärdats i enlighet med förordning (EU) nr 305/2011 på eget ansvar av den tillverkare som anges ovan.

Undertecknad på tillverkarens vägnar av:

ppm. Thilo Pregartner

Thilo Pregartner, Dr.-Ing.
Tumlingen, 2020-07-27

i.V. P. Schilinger

Peter Schilinger, Dipl.-Ing.

Denna DoP har förberetts på olika språk. I händelse av tvist om tolkningen ska den engelska versionen alltid råda.

Bilagan innehåller frivilliga och kompletterande information på engelska som överskrider (det specifika språkets) lagkrav.

Specific Part

1 Technical description of the product

The Upat Express Anchor IMC is an anchor made of zinc plated, hot-dip galvanised or stainless steel which is placed into a drilled hole and anchored by torque-controlled expansion.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the fastener is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the fastener of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi-static loading)	See Annex C 3, C 1
Characteristic resistance to shear load (static and quasi-static loading)	See Annex C 2
Displacements (static and quasi-static loading)	See Annex C 3
Characteristic resistance and displacements for seismic performance categories C1 and C2	No performance assessed
Durability	See Annex B 1

3.2 Safety in case of fire (BWR 2)


Essential characteristic	Performance
Reaction to fire	Class A1
Resistance to fire	No performance assessed

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base


In accordance with the European Assessment Document EAD 330232-01-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1


Cone bolt manufactured by cold - forming:



Cone bolt manufactured by turning:



- ① Cone bolt (cold – formed or turned)
- ② Expansion sleeve
- ③ Hexagon nut
- ④ Washer



(Fig. not to scale)


Upat Express Anchor IMC

Product description
Installed condition

Annex A 1

Appendix 2/ 11

IMC for use with standard and reduced anchorage depth ($h_{ef, sta}$ and $h_{ef, red}$)



Product label, example:

U-IMC 12/10 R


Brand | type of fastener
placed at marking area 2 or 3

Thread size / max. thickness oft he fixture (t_{fix}) for $h_{ef, sta}$
identification R or HDG placed at marking area 2

Table A2.1: Letter-code on marking area 1 and maximum thickness of fixture t_{fix} [mm]:

marking	A	B	C	D	E	F	G	H	I	K	L	M	N	O	P	R	S	T	U	V	W	X	Y	Z	
max. t_{fix} for $h_{ef, sta}$	M6-M20	5	10	15	20	25	30	35	40	45	50	60	70	80	90	100	120	140	160	180	200	250	300	350	400
max. t_{fix} for $h_{ef, red}$	M8, M10	15	20	25	30	35	40	45	50	55	60	70	80	90	100	110	130	150	170	190	210	260	310	360	410
	M12, M16	20	25	30	35	40	45	50	55	60	65	75	85	95	105	115	135	155	175	195	215	265	315	365	415
	M20	30	35	40	45	50	55	60	65	70	75	85	95	105	115	125	145	165	185	205	225	275	325	375	425

IMC K for use with reduced anchorage depth only ($h_{ef, red}$):



Product label, example:

U-IMC 12/10 K R

Brand | type of fastener
placed at marking area 2 or 3

Thread size / max. thickness oft he fixture (t_{fix})
identification K for $h_{ef, red}$
identification R or HDG placed on marking area 2

Table A2.2: Letter-code on marking area 1 and maximum thickness of fixture t_{fix} [mm]:

Markierung	-A-	-B-	-C-	-D-	-E-	-F-	-G-	-H-	-I-	-K-	-L-	-M-	-N-	-O-	-P-	-R-	-S-	-T-	-U-	-V-	-W-	-X-	-Y-	-Z-	
max. t_{fix} for $h_{ef, red}$	M8-M20	5	10	15	20	25	30	35	40	45	50	60	70	80	90	100	120	140	160	180	200	250	300	350	400

Identification for $h_{ef, red}$ is the letter-code between 2 hyphen

(Fig. not to scale)

Upat Express Anchor IMC

Product description
Product label and letter code

Annex A 2




Table A3.1: Anchor dimensions [mm]

Part	Designation	IMC, IMC R						
		M6	M8	M10	M12	M16	M20	
1	Cone bolt	M	M6	M8	M10	M12	M16	
		$\varnothing d_0$	5,9	7,9	9,9	11,9	15,9	
		$\varnothing d_k$	5,2	7,1	8,9	10,8	14,5	
2	Expansion sleeve	m	10	11,5	13,5	16,5	21,5	
3	Hexagon nut	SW	10	13	17	19	24	
4	Washer	t_s	1,0	1,4	1,8	2,3	2,7	
		$\varnothing d_s$	11,5	15	19	23	29	
Thickness of fixture		t_{fix}	0	0	0	0	0	
		\geq	200	200	250	300	400	
		\leq	200	200	250	300	500	
Length of fastener		L_{min}	45	56	71	86	120	
		=	245	261	316	396	520	
		L_{max}	654					

(Fig. not to scale)

Upat Express Anchor IMC

Product description

Dimensions

Annex A 3

Table A4.1: Materials IMC (zinc plated $\geq 5\mu\text{m}$, ISO 4042:2018)

Part	Designation	Material
1	Cone bolt	Cold form steel or free cutting steel
2	Expansion sleeve	Cold strip, EN 10139:2016 ¹⁾
3	Hexagon nut	Steel, property class min. 8, EN ISO 898-2:2012
4	Washer	Cold strip, EN 10139:2013

¹⁾ Optional stainless steel EN 10088:2014

Table A4.2: Materials IMC HDG (hot-dip galvanised $\geq 50\mu\text{m}$, ISO 10684: 2004 ²⁾)

Part	Designation	Material
1	Cone bolt	Cold form steel or free cutting steel
2	Expansion sleeve	Stainless steel EN 10088:2014
3	Hexagon nut	Steel, property class min. 8, EN ISO 898-2:2012
4	Washer	Cold strip, EN 10139:2016

¹⁾ Alternative method sherardized $\geq 50 \mu\text{m}$, EN 13811:2003

Table A4.3: Materials IMC R

Part	Designation	Material
1	Cone bolt	Stainless steel EN 10088:2014
2	Expansion sleeve	Stainless steel EN 10088:2014
3	Hexagon nut	Stainless steel EN 10088:2014 ISO 3506-2: 2009; property class min. 70
4	Washer	Stainless steel EN 10088:2014

Upat Express Anchor IMC

Product description

Materials

Annex A 4

Appendix 5/ 11

Specifications of intended use

Anchorages subject to:

Express Anchor IMC, IMC R		M6 ¹⁾	M8 ¹⁾	M10	M12	M16	M20
Material	Steel	Zinc plated Hot-dip galvanized HDG	- ²⁾		✓	✓	
	Stainless steel	R			✓		
	Static and quasi-static loads				✓		
	Reduced anchorage depth	- ²⁾			✓		
	Uncracked concrete				✓		

¹⁾ Use of IMC 6 (gvz/R) and IMC 8 (gvz/HDG/R) with $h_{ef} = 30\text{mm}$ restricted to anchoring of structural components which are statically indeterminate

²⁾ Anchor type not part of the assessment

Base materials:

- Reinforced or unreinforced normal concrete without fibres of strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions: **IMC, IMC HDG**
- For all other conditions according to EN 1993-1-4:2015-10 corresponding to corrosion resistance class CRC III **IMC R**

Design:

- Anchorages are to be designed under the responsibility of an engineer experienced in anchorages and concrete work
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.)
- Design of fastenings according to EN 1992-4:2018 and TR 055

Upat Express Anchor IMC

Intended Use
Specifications

Annex B 1


Table B2.1: Installation parameters

Type of anchor / size IMC, IMC R	M6	M8	M10	M12	M16	M20
Nominal drill hole diameter $d_0 =$	6	8	10	12	16	20
Cutting diameter of drill bit $d_{cut} \leq$	6,45	8,45	10,45	12,50	16,50	20,55
Standard anchorage depth $h_{ef,sta} =$	30 ¹⁾	40	50	65	80	105
Reduced anchorage depth $h_{ef,red} =$	[mm] - ²⁾	30 ¹⁾	40	50	65	80
Standard drill hole depth $h_{1,sta} \geq$	40	56	68	85	104	135
Reduced drill hole depth $h_{1,red} \geq$	- ²⁾	46 ¹⁾	58	70	89	110
Diameter of clearance hole in the fixture $d_f \leq$	7	9	12	14	18	22
Required torque moment IMC (zinc plated)	4	15	30	50	100	200
Required torque moment IMC (hot-dip galvanized)	T _{inst} = [Nm] - ³⁾	15	30	40	70	200
Required torque moment IMC R	4	10	20	35	80	150

¹⁾ Use restricted to anchoring of structural components which are statically indeterminate

²⁾ No performance assessed

³⁾ Anchor type not part of the assessment



h_{ef} = Effective embedment depth

t_{fix} = Thickness of the fixture

h_1 = Depth of drill hole to deepest point

h_{min} = Minimum thickness of concrete member

T_{inst} = Required setting torque

(Fig. not to scale)

Upat Express Anchor IMC

Intended Use







Installation parameters

Annex B 2

Appendix 7/ 11

Installation instructions

- Fastener installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Use of the fastener only as supplied by the manufacturer without exchanging the components of the fastener
- Checking before placing the fastener to ensure that the strength class of the concrete in which the fastener is to be placed is in the range given and is not lower than that of the concrete to which the characteristic loads apply
- Check of concrete being well compacted, e.g. without significant voids
- Hammer or hollow drilling
- Drill hole created perpendicular +/- 5° to concrete surface, positioning without damaging the reinforcement
- In case of aborted hole: new drilling at a minimum distance twice the depth of the aborted drill hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application

Hollow drilling 	<p>Continue with step 3, 4 and 5</p>				
Hammer drilling 	    				
	1	2	3	4	5

No.	Description	
1	Create drill hole with hammer drill	Create drill hole with hollow drill and vacuum cleaner
2	Clean drill hole	-
3		Set anchor
4		Expand anchor with prescribed installation torque T_{inst}
5		Finished installation

Types of drills	
Hammer drill	
Hollow drill	

Upat Express Anchor IMC Intended Use Installation instructions	Annex B 3 Appendix 8/ 11
---	--

Table C1.1: Characteristic values of **tension** resistance under static and quasi-static action

Type of anchor / size	M6	M8	M10	M12	M16	M20
Steel failure for standard and reduced anchorage depth IMC						
Characteristic resistance IMC	N _{Rk,s} [kN]	8,3	16,5	27,2	41,6	77,9
Partial factor	γ _{Ms} ¹⁾ [-]	1,5	1,4	1,4	1,4	1,5
Steel failure for standard and reduced anchorage depth IMC R						
Characteristic resistance IMC R	N _{Rk,s} [kN]	10,6	16,5	27,2	41,6	78
Partial factor	γ _{Ms} ¹⁾ [-]	1,5	1,4	1,4	1,4	1,5
Pullout failure for standard anchorage depth IMC, IMC R						
Characteristic resistance C20/25	N _{Rk,p} [kN]	6 ⁴⁾	12,5	17,4	25,8	35,2
Pullout failure for reduced anchorage depth IMC, IMC R						
Characteristic resistance C20/25	N _{Rk,p} [kN]	-5)	6 ⁴⁾	12,5	17,4	25,8
Increasing factors for N _{Rk,p}	C25/30				1,12	
	C30/37				1,22	
	C35/45				1,32	
	C40/50				1,41	
	C45/55				1,50	
	C50/60				1,58	
Installation factor	γ _{inst} [-]				1,0	
Concrete cone and splitting failure for standard anchorage depth IMC, IMC R						
Effective anchorage depth	h _{ef, sta} [mm]	30 ⁴⁾	40	50	65	80
Factor for uncracked concrete	k _{ucr,N} [-]				11,0 ²⁾	
Spacing	S _{cr,N}				3 h _{ef, sta}	
Edge distance	C _{cr,N}	[mm]			1,5 h _{ef, sta}	
Spacing (splitting failure)	S _{cr,sp}		130 ⁴⁾	190	200	290
Edge distance (splitting failure)	C _{cr,sp}		65 ⁴⁾	95	100	145
Characteristic resistance to splitting	N ⁰ _{Rk,sp} [kN]				min {N ⁰ _{Rk,c} , N _{Rk,p} } ³⁾	
Concrete cone and splitting failure for reduced anchorage depth IMC, IMC R						
Effective anchorage depth	h _{ef, red} [mm]	-5)	30 ⁴⁾	40	50	65
Factor for uncracked concrete	k _{ucr,N} [-]				11,0 ²⁾	
Spacing	S _{cr,N}				3 h _{ef, red}	
Edge distance	C _{cr,N}	[mm]			1,5 h _{ef, red}	
Spacing (splitting failure)	S _{cr,sp}		-5)	190 ⁴⁾	200	290
Edge distance (splitting failure)	C _{cr,sp}		-5)	95 ⁴⁾	100	145
					175	185

¹⁾ In absence of other national regulations

²⁾ Based on concrete strength as cylinder strength

³⁾ N⁰_{Rk,c} according to EN 1992-4:2018

⁴⁾ Use restricted to anchoring of structural components which are statically indeterminate

⁵⁾ No performance assessed

Upat Express Anchor IMC

Performances

Characteristic values of **tension** resistance

Annex C 1

Table C2.1: Characteristic values of **shear** resistance under static and quasi-static action

Type of anchor / size		M6	M8	M10	M12	M16	M20
Installation factor	γ_{inst} [-]					1,0	
Steel failure without lever arm for standard and reduced anchorage depth							
Characteristic resistance	IMC $V^0_{Rk,s}$ [kN]	6,0 ²⁾	13,3	21,0	31,3	55,1	67
	IMC R	5,3 ²⁾	12,8	20,3	27,4	51	86
Steel failure with lever arm for standard anchorage depth							
Characteristic bending moment	IMC $M^0_{Rk,s}$ [Nm]	9,4 ²⁾	26,2	52,3	91,6	232,2	422
	IMC R	8 ²⁾	26	52	85	216	454
Steel failure with lever arm for reduced anchorage depth							
Characteristic bending moment	IMC $M^0_{Rk,s}$ [Nm]	- ³⁾	19,9 ²⁾	45,9	90,0	226,9	349
	IMC R	-	21 ²⁾	47	85	216	353
Partial factor steel failure	γ_{Ms} ¹⁾ [-]				1,25		
Factor for ductility	k_7				1,0		
Concrete pyout failure for standard anchorage depth IMC, IMC R							
Factor for pyout failure	k_8 [-]	1,4	1,8	2,1	2,3	2,3	2,3
Concrete pyout failure for reduced anchorage depth IMC, IMC R							
Factor for pyout failure	k_8 [-]	- ³⁾	1,8	2,1	2,3	2,3	2,3
Concrete edge failure for standard anchorage depth IMC, IMC R							
Effective length of anchor	$l_{f,sta}$ [mm]	30 ²⁾	40	50	65	80	105
Effective diameter of anchor	d_{nom}	6	8	10	12	16	20
Concrete edge failure for reduced anchorage depth IMC, IMC R							
Effective length of anchor	$l_{f,red}$ [mm]	- ³⁾	30 ²⁾	40	50	65	80
Effective diameter of anchor	d_{nom}	- ³⁾	8	10	12	16	20

¹⁾ In absence of other national regulations

²⁾ Use restricted to anchoring of structural components which are statically indeterminate

³⁾ No performance assessed

Upat Express Anchor IMC

Performances

Characteristic values of **shear** resistance

Annex C 2

Table C3.1: Minimum thickness of concrete members, minimum spacing and minimum edge distance

Type of anchor / size IMC, IMC R	M6	M8	M10	M12	M16	M20	
Standard anchorage depth	Effective anchorage depth $h_{ef, sta}$	30 ²⁾	40	50	65	80	105
	Minimum thickness of member	100	100	100	120	160	200
	Minimum spacing s_{min} [mm]	40	40	50 (70 ¹⁾)	70	90 (120 ¹⁾)	120
	Minimum edge distance c_{min}	40	40 (45 ¹⁾)	50 (55 ¹⁾)	70	90 (80 ¹⁾)	120
Reduced anchorage depth	Effective anchorage depth $h_{ef, red}$	- ³⁾	30 ²⁾	40	50	65	80
	Minimum thickness of member	- ³⁾	100	100	100	120	160
	Minimum spacing s_{min} [mm]	- ³⁾	40 (50 ¹⁾)	50	70	90	120 (140 ¹⁾)
	Minimum edge distance c_{min}	- ³⁾	40 (45 ¹⁾)	80	100	120	120

¹⁾ Values for IMC R

²⁾ Use restricted to anchoring of structural components which are statically indeterminate

³⁾ No performance assessed

Table C3.2: Displacements under static and quasi static **tension** loads

Type of anchor / size IMC, IMC R	M6	M8	M10	M12	M16	M20
Standard anchorage depth $h_{ef, sta}$ [mm]	30	40	50	65	80	105
Tension load C20/25 N [kN]	2,8	6,1	8,5	12,6	17,2	25,8
Displacements $\frac{\delta_{N0}}{\delta_{N\infty}}$ [mm]	1,9	0,6	0,9	1,5 (1,9 ¹⁾)	1,8	1,8 (2,0 ¹⁾)
Reduced anchorage depth $h_{ef, red}$	- ²⁾	30	40	50	65	80
Tension load C20/25 N [kN]	- ²⁾	2,8	6,1	8,5	12,6	17,2
Displacements $\frac{\delta_{N0}}{\delta_{N\infty}}$ [mm]	0,4	0,7	0,7	0,9	1,0	1,6 (1,7 ¹⁾)

¹⁾ Values for IMC R

²⁾ No performance assessed

Table C3.3: Displacements under static and quasi static **shear** loads

Type of anchor / size IMC, IMC R	M6	M8	M10	M12	M16	M20
Shear load IMC V [kN]	3,4	7,6	12,0	17,9	31,5	38,2
Displacements IMC $\frac{\delta v_0}{\delta v_\infty}$ [mm]	0,7	1,5	1,6	2,0	3,0	2,6
Shear load IMC R V [kN]	3,0	7,3	11,6	15,7	29,1	49,0
Displacements IMC R $\frac{\delta v_0}{\delta v_\infty}$ [mm]	1,5	1,4	2,1	2,6	2,7	4,6

Upat Express Anchor IMC

Performances

Minimum thickness of concrete members, minimum spacing and minimum edge distance
Displacements due to tension and shear loads

Annex C 3