

DECLARATION OF PERFORMANCE

DoP 0200

for Bolt Anchor Upat MAX, MAX R, MAX HCR (Mechanical anchor for use in concrete)

EN

1. <u>Unique identification code of the product-type:</u>	DoP 0200	
2. <u>Intended use/es:</u>	Post-installed fastening in cracked or uncracked concrete.	
3. <u>Manufacturer:</u>	See appendix, especially annexes Upat Vertriebs GmbH, Bebelstraße 11, 79108 Freiburg im Breisgau, Germany	B1- B6
4. <u>Authorised representative:</u>	-	
5. <u>System/s of AVCP:</u>	1	
6. <u>European Assessment Document:</u>	EAD 330232-00-0601	
European Technical Assessment:	ETA-10/0170; 2020-04-28	
Technical Assessment Body:	DIBt- Deutsches Institut für Bautechnik	
Notified body/ies:	1343 MPA Darmstadt / 2873 TU Darmstadt	
7. <u>Declared performance/s:</u>		
Mechanical resistance and stability (BWR 1)		
Characteristic resistance to tension load (static and quasi-static loading):	Resistance to steel failure: Resistance to pull-out failure:	Annex C1 Annex C1
	Resistance to concrete cone failure: Robustness:	Annex C1 Annex C1
	Minimum edge distance and spacing: Edge distance to prevent splitting under load:	Annexes B3, B4 Annex C1
	Displacements under static and quasi-static loading:	Annex C5
Characteristic resistance to shear load (static and quasi-static loading):	Resistance to steel failure (shear load): Resistance to pry-out failure: Resistance to concrete edge failure: Displacements under static and quasi-static loading:	Annex C2 Annex C2 Annex C2 Annex C5
	Durability:	Annexes A4, B1
Characteristic resistance and displacements for seismic performance categories C1 and C2:	Resistance to steel failure: Resistance to pull-out failure: Fracture elongation: Factor annular gap: Displacements:	Annex C4 Annex C4 >8% Annex C4 Annex C5
Safety in case of fire (BWR 2)		
Reaction to fire: Resistance to fire:	Class (A1) Fire resistance to steel failure (tension load): Fire resistance to pull-out failure (tension load): Fire resistance to steel failure (shear load):	Annex C3 Annex C3 Annex C3



Einfach. Sicher.



8. Appropriate Technical Documentation and/or Specific -
Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ppm. Thilo Pregartner

Thilo Pregartner, Dr.-Ing.
Tumlingen, 2020-05-12

i.V. P. Schillinger

Peter Schillinger, Dipl.-Ing.

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.

The Appendix includes voluntary and complementary information in English language exceeding the (language-neutrally specified) legal requirements.

Specific Part

1 Technical description of the product

The Upat Anchor bolt MAX is an anchor made of galvanised steel (MAX) or made of stainless steel (MAX R) or high corrosion resistant steel (MAX HCR) which is placed into a drilled hole and anchored by torque-controlled expansion.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the fastener is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the fastener of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi-static loading)	See Annex B 3, C 1
Characteristic resistance to shear load (static and quasi-static loading)	See Annex C 2
Displacements (static and quasi-static loading)	See Annex C 5
Characteristic resistance and displacements for seismic performance categories C1 and C2	See Annex C 4
Durability	See Annex B 1


3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Class A1
Resistance to fire	See Annex C 3


4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with the European Assessment Document EAD 330232-00-0601 the applicable European legal act is: [96/582/EC].



The system to be applied is: 1



Cone bolt manufactured by cold - forming:



- ① Expansion sleeve
- ② Cone bolt (cold – formed or turned)
- ③ Washer
- ④ Hexagon nut
- ⑤ Upat MAX dome nut



(Fig. not to scale)


Upat Anchor bolt MAX, MAX R, MAX HCR

Product description
Installed condition

Annex A 1

Appendix 2/ 16

Product label and letter-code:



Product label, example: MAX 12/30 R

Brand | type of fastener

placed at marking area 2 or marking area 3

Thread size / max. thickness of the fixture (t_{fix})
identification R or HCR placed at marking area 2

MAX: carbon steel, galvanized

MAX R: stainless steel

MAX HCR: high corrosion resistant steel

Table A2.1: Letter - code at marking area 1:

Marking	(a)	(b)	(c)	(d)	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(K)
Max. t_{fix}	5	10	15	20	5	10	15	20	25	30	35	40	45	50
B ≥ [mm]	M6	-			45	50	55	60	65	70	75	80	85	90
	M8	40	45	-	50	55	60	65	70	75	80	85	90	95
	M10	45	50	55	60	65	70	75	80	85	90	95	100	105
	M12	55	60	65	70	75	80	85	90	95	100	105	110	120
	M16	70	75	80	85	90	95	100	105	110	115	120	125	130
	M20				105	110	115	120	125	130	135	140	145	150
	M24	-			130	135	140	145	150	155	160	165	170	175

Marking	(L)	(M)	(N)	(O)	(P)	(R)	(S)	(T)	(U)	(V)	(W)	(X)	(Y)	(Z)
Max. t_{fix}	60	70	80	90	100	120	140	160	180	200	250	300	350	400
B ≥ [mm]	M6	100	110	120	130	140	160	180	200	220	240	290	340	390
	M8	105	115	125	135	145	165	185	205	225	245	295	345	395
	M10	120	130	140	150	160	180	200	220	240	260	310	360	410
	M12	130	140	150	160	170	190	210	230	250	270	320	370	420
	M16	145	155	165	175	185	205	225	245	265	285	335	385	435
	M20	160	170	180	190	200	220	240	260	280	300	350	400	450
	M24	185	195	205	215	225	245	265	285	305	325	375	425	475

Calculation existing h_{ef} for installed fasteners:

$$\text{existing } h_{ef} = B \text{ (according to table A2.1)} - \text{existing } t_{fix}$$

Thickness of the fixture t_{fix} including thickness of fastener plate t and e.g. thickness of grout layer t_{grout}
or other non-structural layers

(Fig. not to scale)

Upat Anchor bolt MAX, MAX R, MAX HCR

Product description
Product label and letter code

Annex A 2

Product dimensions




Table A3.1: Dimensions [mm]

Part	Designation	MAX, MAX R, MAX HCR						
		M6	M8	M10	M12	M16	M20	M24
1	Expansion sleeve	Sheet thickness	0,8	1,3	1,4	1,6	2,4	3,0
2	Cone bolt	Thread size M	6	8	10	12	16	20
		L_G	10	19	26	31	40	57
3	Washer	t_s	1,4	1,8	2,3	2,7		3,7
		$\varnothing d_s$		11	15	19	23	36
4 & 5	Hexagon nut / Upat MAX dome nut	Wrench size	10	13	17	19	24	30
5	L_D	\geq	-	22	27	33	-	
6	Upat filling disc FFD	t	=	6			7	8

(Fig. not to scale)

Upat Anchor bolt MAX, MAX R, MAX HCR

Product description
Dimensions

Annex A 3

Appendix 4/ 16

Table A4.1: Materials MAX (ISO 4042:2018/Zn5/An(A2K))

Part	Designation	Material
1	Expansion sleeve	Cold strip, EN 10139:2016 or stainless steel EN 10088:2014
2	Cone bolt	Cold form steel or free cutting steel
3	Washer	Cold strip, EN 10139:2016
4	Hexagon nut	Steel, property class min. 8, EN ISO 898-2:2012

Table A4.2: Materials MAX R

Part	Designation	Material
1	Expansion sleeve	Stainless steel EN 10088:2014
2	Cone bolt	
3	Washer	
4	Hexagon nut	Stainless steel EN 10088:2014; ISO 3506-2:2018; property class – min. 70

Table A4.3: Materials MAX HCR

Part	Designation	Material
1	Expansion sleeve	Stainless steel EN 10088:2014
2	Cone bolt	High corrosion resistant steel EN 10088:2014
3	Washer	High corrosion resistant steel EN 10088:2014
4	Hexagon nut	High corrosion resistant steel EN 10088:2014; ISO 3506-2:2018; property class – min. 70

(Fig. not to scale)

Upat Anchor bolt MAX, MAX R, MAX HCR

Product description
Materials**Annex A 4**

Appendix 5/ 16

Specifications of intended use

Anchorage subject to:

Size	MAX, MAX R, MAX HCR						
	M6	M8	M10	M12	M16	M20	M24
Static and quasi-static loads							
Cracked and uncracked concrete					✓		
Fire exposure							
Seismic performance category	C1	-			✓		-
C2 ¹⁾		-			✓		-

¹⁾ MAX HCR: Only valid for cold-formed version (according to Annex A1)

Base materials:

- Compacted reinforced and unreinforced normal weight concrete without fibres (cracked and uncracked) according to EN 206-1:2013+A1:2016
- Strength classes C20/25 to C50/60 according to EN 206-1:2013+A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (MAX, MAX R, MAX HCR)
- Structures subject to external atmospheric exposure (including industrial and marine environment) and to permanently damp internal condition, if no particular aggressive conditions exist (MAX R, MAX HCR)
- Structures subject to external atmospheric exposure and permanently damp internal condition, if other particular aggressive conditions exist (MAX HCR)

Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where deicing materials are used)

Design:

- Anchorages are to be designed under the responsibility of an engineer experienced in anchorages and concrete work
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.)
- Design of fastenings according to EN 1992-4:2018 and EOTA Technical Report TR 055
- For effective embedment depth $h_{ef} < 40$ mm only statically indeterminate fixings (e.g. light-weight suspended ceilings with internal exposure) are covered by the ETA

Upat Anchor bolt MAX, MAX R, MAX HCR

Intended Use
Specifications


Annex B 1

Appendix 6/ 16

Table B2.1: Installation parameters

Size	$d_0 =$	MAX, MAX R, MAX HCR						
		M6	M8	M10	M12	M16	M20	M24
Nominal drill hole diameter	$d_0 =$	6	8	10	12	16	20	24
Maximum bit diameter with hammer or hollow drilling	$d_{cut,max}$ [mm]	6,40	8,45	10,45	12,5	16,5	20,55	24,55
Maximum bit diameter with diamond drilling		-	8,15		12,25	16,45	20,50	24,40
Overall fastener embedment depth in the concrete (L)	$h_{nom} \geq$ [mm]	46,5 (6,5)	44,5 (9,5)	52,0 (12)	63,5 (13,5)	82,5 (17,5)	120 (20)	148,5 (23,5)
Depth of drill hole to deepest point	$h_1 \geq$	$h_{nom} + 5$					$h_{nom} + 10$	
Diameter of clearance hole in the fixture	$d_f \leq$ [mm]	7	9	12	14	18	22	26
Required setting torque	$T_{inst} =$ [Nm]	8	20	45	60	110	200	270
Excess length after hammering-in the cone bolt (for Upat dome nut applications according to Annex B6)	$O =$ [mm]	-		12	16	20	-	

Setting gauge MAX SL-H
for anchor with Upat MAX dome nut:



h_{ef} = Effective embedment depth

t_{fix} = Thickness of the fixture

h_1 = Depth of drill hole to deepest point

h = Thickness of the concrete member

h_{min} = Minimum thickness of concrete member

h_{nom} = Overall fastener embedment depth in the concrete

T_{inst} = Required setting torque

(Fig. not to scale)

Upat Anchor bolt MAX, MAX R, MAX HCR

Intended Use
Installation parameters

Annex B 2

Appendix 7 / 16

Table B3.1: Minimum thickness of concrete members, minimum spacing and minimum edge distance

Size	MAX, MAX R, MAX HCR						
	M6	M8	M10	M12	M16	M20	M24
Minimum edge distance							
Uncracked concrete	c _{min}	45	40	45	55	65	95 135
Cracked concrete						85	100
Corresponding spacing	s [mm]	according to Annex B4					
Minimum thickness of concrete member	h _{min}	80		100	140	160	200
Thickness of concrete member	h ≥	max. {h _{min} ; h ₁ ¹⁾ + 30}			max. {h _{min} ; h ₁ ¹⁾ + 2 · d _o }		
Minimum spacing							
Uncracked concrete	s _{min}	35	40 35	40	50	65	95 100
Cracked concrete							
Corresponding edge distance	c [mm]	according to Annex B4					
Minimum thickness of concrete member	h _{min}	80		100	140	160	200
Thickness of concrete member	h ≥	max. {h _{min} ; h ₁ ¹⁾ + 30}			max. {h _{min} ; h ₁ ¹⁾ + 2 · d _o }		
Minimal splitting area							
Uncracked concrete	A _{sp,req} [-1000 mm ²]	5,1	18	37	54	67	100 117,5
Cracked concrete		1,5	12	27	40	50	77 87,5

¹⁾ h₁ according to Annex B2

Splitting failure applied for minimum edge distance and spacing in dependence of the h_{ef}

For the calculation of minimum spacing and minimum edge distance of anchors in combination with different embedment depths and thicknesses of concrete members the following equation shall be fulfilled:

$$A_{sp,req} < A_{sp,ef}$$

A_{sp,req} = required splitting area

A_{sp,ef} = effective splitting area (according to Annex B4)


Upat Anchor bolt MAX, MAX R, MAX HCR

Intended Use

Minimum thickness of member, minimum spacing and edge distance


Annex B 3

Table B4.1: Effective splitting area $A_{sp,ef}$ with member thickness $h > h_{ef} + 1,5 \cdot c$ and $h \geq h_{min}$



Single anchor and group of anchors with $s > 3 \cdot c$	$A_{sp,ef} = (6 \cdot c) \cdot (h_{ef} + 1,5 \cdot c)$	[mm ²]	with $c \geq c_{min}$
Group of anchors with $s \leq 3 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot (h_{ef} + 1,5 \cdot c)$	[mm ²]	with $c \geq c_{min}$ and $s \geq s_{min}$

Table B4.2: Effective splitting area $A_{sp,ef}$ with member thickness $h \leq h_{ef} + 1,5 \cdot c$ and $h \geq h_{min}$



Single anchor and group of anchors with $s > 3 \cdot c$	$A_{sp,ef} = 6 \cdot c \cdot \text{existing } h$	[mm ²]	with $c \geq c_{min}$
Group of anchors with $s \leq 3 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot \text{existing } h$	[mm ²]	with $c \geq c_{min}$ and $s \geq s_{min}$

Edge distance and axial spacing shall be rounded to at least 5 mm

(Fig. not to scale)

Upat Anchor bolt MAX, MAX R, MAX HCR

Intended Use

Minimum thickness of member, minimum spacings and edge distances






Annex B 4

Installation instructions:

- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Use of the anchor only as supplied by the manufacturer without exchanging the components of the anchor
Exception: Upat MAX dome nut.
- Checking before placing the anchor to ensure that the strength class of the concrete in which the anchor is to be placed is in the range given and is not lower than that of the concrete to which the characteristic loads apply
- Check of concrete being well compacted, e.g. without significant voids
- Hammer, hollow or diamond drilling according to Annex B5
- Drill hole created perpendicular +/- 5° to concrete surface, positioning without damaging the reinforcement
- In case of aborted hole: new drilling at a minimum distance twice the depth of the aborted drill hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application
- It must be ensured that in case of fire local spalling of the concrete cover does not occur
- Fastenings in stand-off installation or with a grout layer under seismic action are not covered
- In case of seismic applications the fastener shall be positioned outside of critical regions (e.g. plastic hinges) of the concrete structure

Installation instructions: Drilling and cleaning the hole

Types of drills and cleaning

Hammer drill		 1: Drill the hole	 2: Clean the hole
Hollow drill		 1: Drill the hole with automatic cleaning	-
Diamond drill, for non seismic applications only and \geq drill $\varnothing 8$		 1: Drill the hole	 2: Clean the hole


Upat Anchor bolt MAX, MAX R, MAX HCR

Intended Use
Installation instructions


Annex B 5

Installation instructions: Installation of the anchor


HEXAGON NUT:



3: Set the fastener




4: Apply T_{inst}




5: Installed fastener

Upat MAX DOME NUT:


Option 1: Push through installation with setting gauge SL-H:




3: Set the fastener using setting gauge




4: Check offset



5: Turn on the washer and Upat MAX dome nut




6: Apply T_{inst}




7: Installed fastener


Option 2: Push through installation with hexagon nut:



3: Set the fastener





4: check setting position: Visible one turn of a thread



4.1: Remove nut

Upat FILLING DISC FFD optional for seismic C2 application or minimizing the annular gap:

Optional	<p>The gap between bolt and fixture may be filled with mortar (compressive strength $\geq 50 \text{ N/mm}^2$ e.g. UPM 33) after step 7 (for eliminating the annular gap). The filling disc is additional to the standard washer. The thickness of the filling disc must be considered for definition of t_{fix}. Countersunk of the filling disc in direction to the anchor plate.</p>	 
----------	--	---

Upat Anchor bolt MAX, MAX R, MAX HCR

Intended Use
Installation instructions

Annex B 6

Table C1.1: Characteristic **tension** resistance under static and quasi-static action

Size	MAX, MAX R, MAX HCR							
	M6	M8	M10	M12	M16	M20	M24	
Steel failure								
Characteristic resistance	MAX MAX R/HCR	N _{Rk,s} [kN]	7,6 11,4	16,6 17,0	28,3 29,0	43,2 44,3	67,0 70,6	123,3 124,9
Partial factor for steel failure	γ _{Ms¹⁾}	[-]				1,5		
Pullout failure								
Effective embedment depth for calculation	h _{ef} [mm]	40	35 - < 45	45	40 - 60	50 - 70	65 - 85	100 125
Characteristic resistance in cracked concrete C20/25	N _{Rk,p} [kN]	1,5	5,5	8	13	20	27,0	34,4 48,1
Characteristic resistance in uncracked concrete C20/25		10,5	14		20	22	38,6	49,2 68,8
Increasing factors for N _{Rk,p} for cracked and uncracked concrete	C25/30					1,12		
	C30/37					1,22		
	C35/45					1,32		
	C40/50					1,41		
	C45/55					1,50		
	C50/60					1,58		
Installation factor	γ _{inst} [-]					1,0		
Concrete cone and splitting failure								
Factor for uncracked concrete	k _{ucr,N} [-]					11,0 ²⁾		
Factor for cracked concrete	k _{cr,N}					7,7 ²⁾		
Characteristic spacing	s _{cr,N} [mm]					3 · h _{ef}		
Characteristic edge distance	c _{cr,N}					1,5 · h _{ef}		
Spacing	s _{cr,sp}					2 · c _{cr,sp}		
Edge distance for h = 80	c _{cr,sp} [mm]	40	2,4 · h _{ef}	2 · h _{ef}	-	-		
Edge distance for h = 100			2 · h _{ef}	2,4 · h _{ef}	2 · h _{ef}	-		
Edge distance for h = 120				1,9 · h _{ef}	2,1 · h _{ef}	-		
Edge distance for h = 140					1,5 · h _{ef}	2 · h _{ef}	-	
Edge distance for h = 160					2,4 · h _{ef}	2,2 · h _{ef}	-	
Edge distance for h = 200							-	
Characteristic resistance to splitting	N ⁰ _{Rk,sp} [kN]						min {N ⁰ _{Rk,c} ; N _{Rk,p} } ³⁾	

¹⁾ In absence of other national regulations

2) Based on concrete strength as cylinder strength

3) $N_{Rk,c}^0$ according to EN 1992-4:2018

Upat Anchor bolt MAX MAX B MAX HCB

Performances

Performances
Characteristic values of resistance under tension loads

Annex C 1

Table C2.1: Characteristic values of **shear** resistance under static and quasi-static action

Size	MAX, MAX R, MAX HCR							
	M6	M8	M10	M12	M16	M20	M24	
Steel failure without lever arm								
Characteristic resistance	MAX MAX R/HCR	$V^0_{Rk,s}$ [kN]	5,9 8,8	13,6 16,8	21,4 26,5	30,6 38,3	55,0 69,8	
Partial factor for steel failure	$\gamma_{Ms}^{1)}$	[-]	1,25					
Factor for ductility	k_7		1,0					
Steel failure with lever arm and Concrete prout failure								
Effective embedment depth for calculation	h_{ef} [mm]	40	45	60	70	85	100	
Characteristic bending resistance	MAX MAX R/HCR	$M^0_{Rk,s}$ [Nm]	11,4 10,7	26 29	52 59	92 100	233 256	
Factor for prout failure	k_8 [-]	2,6	2,8	3,2		3,0	2,6	
Effective embedment depth for calculation	h_{ef} [mm]	-	35 - < 45	40 - < 60	50 - < 70	65 - < 85	-	
Characteristic bending resistance	MAX MAX R/HCR		20	44	92	184		
Factor for prout failure	k_8 [-]		21	45	100	193		
Partial factor for steel failure	$\gamma_{Ms}^{1)}$		2,5	2,6	3,1	3,2		
Factor for ductility	k_7	1,0						
Concrete edge failure								
Effective embedment depth for calculation	$l_f =$ [mm]	h_{ef}						
Outside diameter of a fastener	d_{nom}	6	8	10	12	16	20	
		24						

¹⁾ In absence of other national regulations

Upat Anchor bolt MAX MAX B MAX HCB

Performances

Performances

Annex C 2

Table C3.1: Characteristic values of tension resistance under fire exposure

Size	$h_{ef} \geq [mm]$	MAX, MAX R, MAX HCR						
		M6	M8	M10	M12	M16	M20	M24
Characteristic resistance steel failure	R30	0,6 ¹⁾ / 0,9 ²⁾	1,4	2,8	5,0	9,4	14,7	21,1
	N _{Rk,s,fi} R60	0,4 ¹⁾ / 0,9 ²⁾	1,2	2,3	4,1	7,7	12,0	17,3
	R90	0,3 ¹⁾ / 0,9 ²⁾	0,9	1,9	3,2	6,0	9,4	13,5
	R120	0,2 ¹⁾ / 0,7 ²⁾	0,8	1,6	2,8	5,2	8,1	11,6
Characteristic resistance Concrete cone failure	R30 - N _{Rk,c,fi} R90	$7,7 \cdot h_{ef}^{1,5} \cdot (20)^{0,5} \cdot h_{ef} / 200 / 1000$						
	R120	$7,7 \cdot h_{ef}^{1,5} \cdot (20)^{0,5} \cdot h_{ef} / 200 / 1000 \cdot 0,8$						
	Characteristic resistance pullout failure	R30	0,9 / 2,0					
Characteristic resistance pullout failure	N _{Rk,p,fi} R60	0,4	0,8 / 2,0	2,2 / 3,3	3,0 / 5,0	4,5 / 6,8	8,6	12,0
	R90		0,5 / 2,0					
	R120	0,3	0,3 / 1,6	1,7 / 2,6	2,4 / 4,0	3,6 / 5,4	6,9	9,6

Table C3.2: Characteristic values of shear resistance under fire exposure

Size	MAX, MAX R, MAX HCR	R30		R60	
		V _{Rk,s,fi,30} [kN]	M ⁰ _{Rk,s,fi,30} [Nm]	V _{Rk,s,fi,60} [kN]	M ⁰ _{Rk,s,fi,60} [Nm]
h _{ef} ≥	M6	40	0,6 ¹⁾ / 0,9 ²⁾	0,5 ¹⁾ / 0,2 ²⁾	0,4 ¹⁾ / 0,9 ²⁾
	M8	35	1,8	1,4	1,6
	M10	40	3,6	2,9	3,0
	M12	50	6,3	7,8	4,9
	M16	65	11,7	19,9	9,1
	M20	100	18,2	39,0	14,2
	M24	125	26,3	67,3	20,5
Size	MAX, MAX R, MAX HCR	R90		R120	
		V _{Rk,s,fi,90} [kN]	M ⁰ _{Rk,s,fi,90} [Nm]	V _{Rk,s,fi,120} [kN]	M ⁰ _{Rk,s,fi,120} [Nm]
		40	0,3 ¹⁾ / 0,9 ²⁾	0,2 ¹⁾ / 0,1 ²⁾	0,2 ¹⁾ / 0,7 ²⁾
		35	1,3	1,0	1,2
		40	2,2	2,4	1,9
		50	3,5	5,0	2,8
		65	6,6	12,6	5,3
Concrete prout failure according to EN 1992-4:2018	M20	100	10,3	24,6	8,3
	M24	125	14,8	42,6	11,9

Concrete prout failure according to EN 1992-4:2018

Table C3.3: Minimum spacings and minimum edge distances of anchors under fire exposure for tension and shear load

Size	MAX, MAX R, MAX HCR							
	M6	M8	M10	M12	M16	M20	M24	
Spacing	S _{min}	Annex B3						
Edge distance	c _{min} [mm]	c _{min} = 2 · h _{ef} , for fire exposure from more than one side c _{min} ≥ 300 mm						

¹⁾ MAX

²⁾ MAX R / HCR

Upat Anchor bolt MAX, MAX R, MAX HCR

Performances

Characteristic values of resistance under fire exposure

Annex C 3

Table C4.1: Characteristic values of tension and shear resistance under seismic action category C1

Size	MAX, MAX R, MAX HCR						
	M6	M8	M10	M12	M16	M20	M24
Length of anchor L_{max}	-	167	186	221	285	394	477
Effective embedment depth h_{ef} [mm]		45	40 - 60	50 - 70	65 - 85	100	125
With filling of the annular gap α_{gap} [-]	1,0						
Steel failure							
Characteristic resistance tension load C1 $N_{Rk,s,C1}$ [kN]	-	16,0	27,0	41,0	66,0	111,0	150,0
Partial factor for steel failure $\gamma_{Ms,C1}^{1)}$ [-]		1,5					
Pullout failure							
Characteristic resistance tension load in cracked concrete C1 $N_{Rk,p,C1}$ [kN]	-	4,6	8,0	16,0	28,2	36,0	50,3
Installation factor γ_{inst} [-]		1,0					
Steel failure without lever arm							
Characteristic resistance shear load C1 $V_{Rk,s,C1}$ [kN]	-	11	17	27	47	56	69
Partial factor for steel failure $\gamma_{Ms,C1}^{1)}$ [-]		1,25					

¹⁾ In absence of other national regulations

Table C4.2: Characteristic values of tension and shear resistance under seismic action category C2

Size	MAX, MAX R, MAX HCR ¹⁾						
	M6	M8	M10	M12	M16	M20	M24
Length of anchor L_{max} [mm]	-	186	221	285	394	-	-
With filling of the annular gap α_{gap} [-]		1,0					
Steel failure							
Characteristic resistance tension load C2 $N_{Rk,s,C2}$ [kN]	-	27	41	66	111	-	-
Partial factor for steel failure $\gamma_{Ms,C2}^{2)}$ [-]		1,5					
Pullout failure							
Characteristic resistance tension load in cracked concrete C2 $N_{Rk,p,C2}$ [kN]	-	60	70	85	100	-	-
Characteristic resistance tension load in cracked concrete C2 $N_{Rk,p,C2}$ [kN]		5,1	7,4	21,5	30,7	-	-
Characteristic resistance tension load in cracked concrete C2 $N_{Rk,p,C2}$ [kN]		40-59	50-69	65-84	-	-	-
Installation factor γ_{inst} [-]	1,0						
Steel failure without lever arm							
Characteristic resistance shear load C2 $V_{Rk,s,C2}$ [kN]	-	60	70	85	100	-	-
Characteristic resistance shear load C2 $V_{Rk,s,C2}$ [kN]		10,0	17,4	27,5	39,9	-	-
Characteristic resistance shear load C2 $V_{Rk,s,C2}$ [kN]	-	40-59	50-69	65-84	-	-	-
Characteristic resistance shear load C2 $V_{Rk,s,C2}$ [kN]		7,0	12,7	22,0	-	-	-
Partial factor for steel failure $\gamma_{Ms,C2}^{2)}$ [-]	1,25						

¹⁾ MAX HCR: Only valid for cold-formed version (according to Annex A1)

²⁾ In absence of other national regulations

Upat Anchor bolt MAX, MAX R, MAX HCR

Performances

Characteristic values of resistance under tension and shear loads under seismic action

Annex C 4

Table C5.1: Displacements under static and quasi static **tension** loads

Size	MAX, MAX R, MAX HCR						
	M6	M8	M10	M12	M16	M20	M24
Displacement – factor for tensile load¹⁾							
δ_{N0} - factor	in cracked concrete	0,13	0,22	0,12	0,09	0,08	0,07
$\delta_{N\infty}$ - factor		1,00	0,78	0,40	0,19	0,09	0,07
δ_{N0} - factor	[mm/kN]	0,16	0,07	0,05	0,06	0,05	0,04
$\delta_{N\infty}$ - factor	in uncracked concrete	0,24	0,29	0,21	0,14	0,10	0,06

Table C5.2: Displacements under static and quasi static **shear** loads

Size	MAX						
	M6	M8	M10	M12	M16	M20	M24
Displacement – factor for shear load²⁾							
δ_{V0} - factor		0,6	0,35	0,37	0,27	0,10	0,09
$\delta_{V\infty}$ - factor		0,9	0,52	0,55	0,40	0,14	0,15
δ_{V0} - factor	[mm/kN]	0,6	0,23	0,19	0,18	0,10	0,11
$\delta_{V\infty}$ - factor		0,9	0,27	0,22	0,16	0,11	0,05

1) Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0} - \text{factor} \cdot N_{ED}$$

$$\delta_{N\infty} = \delta_{N\infty} - \text{factor} \cdot N_{ED}$$

(N_{ED} : Design value of the applied tension force)

2) Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0} - \text{factor} \cdot V_{ED}$$

$$\delta_{V\infty} = \delta_{V\infty} - \text{factor} \cdot V_{ED}$$

(V_{ED} : Design value of the applied shear force)

Table C5.3: Displacements under **tension** loads for **category C2** for all embedment depths

Size	MAX, MAX R, MAX HCR						
	M6	M8	M10	M12	M16	M20	M24
Displacement DLS	$\delta_{N,C2(DLS)}$		2,7	4,4	5,6		
Displacement ULS	$\delta_{N,C2(ULS)}$	[mm]	-	11,5	13,0	12,3	14,4

Table C5.4: Displacements under **shear** loads for **category C2** for all embedment depths

Size	MAX, MAX R, MAX HCR						
	M6	M8	M10	M12	M16	M20	M24
Displacement DLS	$\delta_{V,C2(DLS)}$		4,1	4,7	5,5	4,8	
Displacement ULS	$\delta_{V,C2(ULS)}$	[mm]	-	6,2	7,8	10,1	11,2

Upat Anchor bolt MAX, MAX R, MAX HCR

Performances

Displacements under tension and shear loads

Annex C 5