

## **DECLARATION OF PERFORMANCE**

DoP-0618	-CPF-UK	-0019-002

JOP-0618-CPF-UK-0019-002 or fischer Crystal MS			EN
I. Unique identification code of the product-type:	DoP-0618-CPF-UK-0019-002		
2. Intended use/es:	Sealents for façade elements, EN 15651-1:2012: F-EXT-INT (12,5P) Sealents for sanitary joints, EN 15651-3:2012: S (S1)		
3. <u>Manufacturer:</u>	fischerwerke GmbH & Co. KG, Klaus-Fischer-	Str. 1, 72178 Waldacl	ntal, Germany
4. Authorised representative:	-		
5. System/s of AVCP:	System 3, Reaction to fire: System 3		
<ol> <li>Harmonised standard: Notified body/ies:</li> </ol>	EN 15651-1:2012, EN 15651-3:2012 1292 - FUNDACION TECNALIA RESEARCH & INNOVATION		
7. Declared performance/s:			
Conditioning: Substrate:	Procedure A Glass (without primer)		
Essential characteristics*		Performance	Harmonised technical specification
(11) Reaction to fire		Class E	
(12) Release of chemical dangerous to the environment and health		NPD (*)	
Water and air tightness			
(13) Resistance to flow		< 3 mm	EN 15651-1:2012
(14) Loss of volume		< 10 %	EN 15051-1.2012
(15) Tensile properties (i.e. elongation) after immersion in water (at 23 °C)		NPD	
(19) Durability		Pass	1
Conditioning: Substrate:	Procedure B Glass (without primer)		
Essential characteristics*		Performance	Harmonised technical specification
(31) Reaction to fire		Class E	
(32) Release of chemical dangerous to the environm	nent and health	NPD (*)	1
Water and air tightness			1

Water and air tightness (33) Resistance to flow < 3 mm EN 15651-3:2012 (34) Loss of volume < 10 % (35) Tensile properties (i.e. elongation) after immersion in water at 23  $^{\circ}\text{C}$  (class S) NPD (37) Microbiological growth 1 Pass

(38) Durability

\*Numbering system acc. to EN 15651 with FEICA classification (Publication ref.:POP-EX-J12-035).

(\*) See material safety data sheet.

NPD = No Performance Determined

NF = No Failure

NR = Not required



## 8. <u>Appropriate Technical Documentation and/or</u> <u>Specific Technical Documentation:</u>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, under the sole responsibility of the manufacturer identified above.

\_

Signed for and on behalf of the manufacturer by:

(Lik'

Dr.-Ing. Oliver Geibig, Managing Director Business Units & Engineering Turnlingen, 2023-01-10

Jürgen Grün, Managing Director Chemistry & Quality

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.