

**DECLARATION OF PERFORMANCE**

**DoP-Seal-UK-00012-02**  
for fischer Multi AC

EN

- 1. Unique identification code of the product-type: **DoP-Seal-UK-00012-02**
- 2. Intended use/es: **Sealants for façade elements, EN 15651-1:2012: F-EXT-INT (7,5P)**
- 3. Manufacturer: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Germany**
- 4. Authorised representative: **-**
- 5. System/s of AVCP: **System 3, Reaction to fire: System 3**
- 6. Harmonised standard: **EN 15651-1:2012**  
Notified body/ies: **1213 SKZ-TeConA GmbH**
- 7. Declared performance/s:  
  
  - Conditioning: Procedure A (ISO 8339)
  - Substrate: Mortar M2 (without primer)

Essential characteristics*	Performance	Harmonised technical specification
(11) Reaction to fire	Class E	EN 15651-1:2012
(12) Release of chemical dangerous to the environment and health	NPD (*)	
Water and air tightness		
(13) Resistance to flow	≤ 3 mm	
(14) Loss of volume	≤ 25 %	
(15) Tensile properties (i.e. elongation) after immersion in water (at 23 °C)	≥ 25%	
(16) Tensile properties (i.e. elongation) at maintained extension after water immersion	NR	
(17) Tensile properties (i.e. secant modulus) for non-structural low modulus sealants used in joints in areas with cold climates (-30°C)	NR	
(18) Tensile properties (i.e. at maintained extension) for non-structural sealants used in joints in areas with cold climate (-30°C)	NR	
(19) Durability	Pass	

\*Numbering system acc. to EN 15651 with FEICA classification (Publication ref.:POP-EX-J12-035).  
 (\*) See material safety data sheet.  
 NPD = No Performance Determined  
 NF = No Failure  
 NR = Not required

- 8. Appropriate Technical Documentation and/or Specific Technical Documentation: **-**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Dr.-Ing. Oliver Geibig, Managing Director Business Units & Engineering  
Tumlingen, 2023-01-10



Jürgen Grün, Managing Director Chemistry & Quality

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.