

DECLARATION OF PERFORMANCE

DoP-0618-CPF-UK-0015-002

for fischer Multi MS, fischer DKM

EN

- 1. Unique identification code of the product-type: **DoP-0618-CPF-UK-0015-002**
- 2. Intended use/es: **Sealents for façade elements, EN 15651-1:2012: F-EXT-INT-CC (25HM)
Sealents for sanitary joints, EN 15651-3:2012: S (XS3)
Sealants for pedestrian walkways, EN 15651-4:2012: PW-EXT-INT-CC (25HM)**
- 3. Manufacturer: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Germany**
- 4. Authorised representative: **-**
- 5. System/s of AVCP: **System 3, Reaction to fire: System 3**
- 6. Harmonised standard: **EN 15651-1:2012, EN 15651-3:2012, EN 15651-4:2012**
Notified body/ies: **1213 - SKZ – TeConA GmbH**
- 7. Declared performance/s:
Conditioning: Procedure B
Substrate: Mortar M1 (with primer P03) / Glass (without primer) / Anodised aluminium (without primer)

Essential characteristics*	Performance	Harmonised technical specification
(11) Reaction to fire	Class E	EN 15651-1:2012
(12) Release of chemical dangerous to the environment and health	NPD (*)	
Water and air tightness		
(13) Resistance to flow	≤ 3 mm	
(14) Loss of volume	≤ 10 %	
(16) Tensile properties (i.e. elongation) at maintained extension after water immersion	NF	
(17) Tensile properties (i.e. secant modulus) for non-structural low modulus sealants used in joints in areas with cold climates (-30°C)	NR	
(18) Tensile properties (i.e. at maintained extension) for non-structural sealants used in joints in areas with cold climate (-30°C)	NF	
(19) Durability	Pass	

Substrate: Glass (without primer) / Anodised aluminium (without primer)

Essential characteristics*	Performance	Harmonised technical specification
(31) Reaction to fire	Class E	EN 15651-3:2012
(32) Release of chemical dangerous to the environment and health	NPD (*)	
Water and air tightness		
(33) Resistance to flow	≤ 3 mm	
(34) Loss of volume	≤ 20 %	
(36) Tensile properties (i.e. elongation) at maintained extension after water immersion (class XS)	NF	
(37) Microbiological growth	3	
(38) Durability	Pass	

Substrate: Mortar M1 (with primer P03)

Essential characteristics*	Performance	Harmonised technical specification
(41) Reaction to fire	Class E	EN 15651-4:2012
(42) Release of chemical dangerous to the environment and health	NPD (*)	
Water and air tightness		
(43) Tensile properties at maintained extension	NF	
(44) Loss of volume	≤ 10 %	
(45) Tear resistance	NF	
(46) Adhesion- / Cohesion properties at maintained extension after 28 days water immersion	NF / ≤ 50%	
(47) Adhesion- / Cohesion properties at maintained extension after 28 days salt water immersion	NF	
(48) Tensile properties (e.g. secant modulus) for use in cold climate areas (-30 ± 2) °C	NR	
(49) Tensile properties at maintained extension for use in cold climate areas at (-30 ± 2) °C	NF	
(410) Durability	Pass	

*Numbering system acc. to EN 15651 with FEICA classification (Publication ref.:POP-EX-J12-035).

(*) See material safety data sheet.

NPD = No Performance Determined

NF = No Failure

NR = Not required

8. Appropriate Technical Documentation and/or -
Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:




Dr.-Ing. Oliver Geibig, Managing Director Business Units & Engineering
Tumlingen, 2023-01-10

Jürgen Grün, Managing Director Chemistry & Quality