

PROHLÁŠENÍ O VLASTNOSTECH

DoP 0327

pro injektážní kotvu fischer Highbond-Anchor FHB II (lepený rozpěrný upevňovací prvek pro použití v betonu)

CS

1. Jedinečný identifikační kód typu výrobku: **DoP 0327**
2. Zamýšlené/zamyšlená použití: **Dodatečné upevnění v tažené a tlačené zóně betonu, viz. dodatek, obzvláště Přílohy B1 - B11.**
3. Výrobce: **fischerwerke GmbH & Co. KG, Otto-Hahn-Straße 15, 79211 Denzlingen, Německo**
4. Zplnomocněný zástupce: **-**
5. Systém/systémy POSV: **1**
6. Evropský dokument pro posuzování: **EAD 330499-01-0601**
Evropské technické posouzení: **ETA-21/0948; 2022-09-09**
Subjekt pro technické posuzování: **DIBt- Deutsches Institut für Bautechnik**
Oznámený subjekt/oznámené subjekty: **2873 TU Darmstadt**
7. Deklarovaná vlastnost/Deklarované vlastnosti:
Mechanická odolnost a stabilita (BWR 1)
Charakteristická únosnost v tahu (pro statickou a kvazistatickou akci):
Odolnost proti selhání oceli: Příloha C1
Odolnost proti kombinovanému porušení vytažením a selháním betonu: Přílohy C2-C4
Odolnost proti selhání betonu: Příloha C2
Okrajová vzdálenost bránící rozštěpení při zatížení: Příloha C2
Pevnost: Přílohy C2-C4
Utahovací moment při instalaci: Přílohy B3, B4
Minimální vzdálenost od okraje a rozteč: Přílohy B3, B4
Charakteristická únosnost ve smyku (pro statickou a kvazistatickou akci):
Odolnost proti selhání oceli: Příloha C1
Odolnost proti selhání rozštěpením: Příloha C2
Odolnost proti selhání okraje betonu: Příloha C2
posuny při krátkodobém a dlouhodobém zatížení:
Posuny při krátkodobém a dlouhodobém zatížení: Přílohy C5
Charakteristická únosnost a posuny pro seismické kategorie C1 a C2:
Odolnost proti tahovému zatížení, posuny, kategorie C1: NPD
Odolnost proti tahovému zatížení, posuny, kategorie C2: NPD
Odolnost proti smykovému zatížení, posuny, kategorie C1: NPD
Odolnost proti smykovému zatížení, posuny, kategorie C2: NPD
Koefficient prstencové mezery: NPD
Hygiena, zdraví a životní prostředí (BWR 3)
Obsah, emise a / nebo uvolňování nebezpečných látek: NPD

8. Příslušná technická dokumentace a/nebo specifická technická dokumentace: **-**

Vlastnosti výše uvedeného výrobku jsou ve shodě se souborem deklarovaných vlastností. Toto prohlášení o vlastnostech se v souladu s nařízením (EU) č. 305/2011 vydává na výhradní odpovědnost výrobce uvedeného výše.

Podepsáno za výrobce a jeho jménem:



Dr.-Ing. Oliver Geibig, Výkonný ředitel pro obchodní jednotky a inženýrství
Tumlingen, 2022-09-16



Jürgen Grün, Výkonný ředitel pro chemii a kvalitu

Toto PoV bylo připraveno v různých jazykových mutacích. V případě rozporu vždy rozhoduje interpretace verze v anglickém jazyce.
Příloha obsahuje nepovinné a doplňkové informace v anglickém jazyce nad rámec zákonních požadavků.

Translation guidance Essential Characteristics and Performance Parameters for Annexes

Pokyny pro překlad Základní charakteristiky a výkonnostní parametry příloh

Mechanical resistance and stability (BWR 1)				
Mechanická odolnost a stabilita (BWR 1)				
Characteristic resistance to tension load (static and quasi-static loading):				
Charakteristická únosnost v tahu (pro statickou a kvazistatickou akci):				
1 Resistance to steel failure: Odolnost proti selhání oceli:	$N_{Rk,s}$ [kN]			
2 Resistance to combined pull-out and concrete cone failure: Odolnost proti kombinovanému porušení vytážením a selháním betonu:	T_{Rk} and/or $T_{Rk,100}$ [N/mm ²], ψ_{sus}^0 [-] (BF) $N_{Rk,p}$ and/or $N_{Rk,p,100}$ [kN] (BEF)			
3 Resistance to concrete cone failure: Odolnost proti selhání betonu:	$c_{cr,N}$ [mm], $k_{cr,N}$, $k_{ucr,N}$ [-]			
4 Edge distance to prevent splitting under load: Okrajová vzdálenost bránící rozštěpení při zatížení:	$c_{cr,sp}$ [mm]			
5 Robustness: Pevnost:	γ_{inst} [-]			
6 Maximum installation torque:	$\max T_{inst}$ [Nm] (BF)			
Installation torque: Utahovací moment při instalaci:	T_{inst} [Nm] (BEF)			
7 Minimum edge distance and spacing: Minimální vzdálenost od okraje a rozteč:	c_{min} , s_{min} , h_{min} [mm]			
Characteristic resistance to shear load (static and quasi-static loading):				
Charakteristická únosnost ve smyku (pro statickou a kvazistatickou akci):				
8 Resistance to steel failure: Odolnost proti selhání oceli:	$V_{Rk,s}^0$ [kN], $M_{Rk,s}^0$ [Nm], k_7 [-]			
9 Resistance to pry-out failure: Odolnost proti selhání rozštěpením:	k_8 [-]			
10 Resistance to concrete edge failure: Odolnost proti selhání okraje betonu:	d_{nom} , l_f [mm]			
Displacements under short-term and long-term loading: posuny při krátkodobém a dlouhodobém zatížení:				
11 Displacements under short-term and long-term loading: Posuny při krátkodobém a dlouhodobém zatížení:	δ_0 , δ_∞ [mm or mm/(N/mm ²)]			
Characteristic resistance and displacements for seismic performance categories C1 and C2: Charakteristická únosnost a posuny pro seismické kategorie C1 a C2:				
12 Resistance to tension load, displacements: Odolnost proti tahovému zatížení, posuny, kategorie C1:	C1	$N_{Rk,s,C1}$ [kN] (all) $T_{Rk,C1}$ [N/mm ²] (BF) $N_{Rk,p,C1}$ [kN] (BEF)		
Odolnost proti tahovému zatížení, posuny, kategorie C2:	C2	$N_{Rk,s,C2}$ [kN] (all) $T_{Rk,C2}$ [N/mm ²] (BF) $N_{Rk,p,C2}$ [kN] (BEF) $\delta_{N,C2}$ [mm] (all)		
13 Resistance to shear load, displacements: Odolnost proti smykovému zatížení, posuny, kategorie C1:	C1	$V_{Rk,s,C1}$ [kN] (all)		
Odolnost proti smykovému zatížení, posuny, kategorie C2:	C2	$V_{Rk,s,C2}$ [kN] (all) $\delta_{V,C2}$ [mm] (all)		
14 Factor annular gap: Koeficient prstencové mezery:	α_{gap} [-]			
Hygiene, health and the environment (BWR 3)				
Hygiena, zdraví a životní prostředí (BWR 3)				
15 Content, emission and/or release of dangerous substances: Obsah, emise a / nebo uvolňování nebezpečných látek:	-			

Specific Part

1 Technical description of the product

The "fischer Highbond-Anchor FHB II for diamond drilling / extended working life" consisting of a mortar cartridge with mortar fischer FIS HB or fischer mortar capsule FHB II-P(F) and an anchor rod FHB II - A S or FHB II Inject - A S with hexagon nut and washer.

The glass capsule is set into a drilled hole in the concrete. The special formed anchor rod is driven into the glass capsule by machine with simultaneous hammering and turning. For the injection system the anchor rod is placed into a drilled hole filled with injection mortar. The load transfer is realized by mechanical interlock of several cones in the bonding mortar and then via a combination of bonding and friction forces in the anchorage ground (concrete).

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 and/or 100 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi-static loading)	See Annex C 1 to C 4, B 3 to B 4
Characteristic resistance to shear load (static and quasi-static loading)	See Annex C 1 to C 2
Displacements under short-term and long-term loading	See Annex C 5
Characteristic resistance and displacements for seismic performance categories C1 and C2	No performance assessed

3.2 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
Content, emission and/or release of dangerous substances	No performance assessed

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base


In accordance with the European Assessment Document EAD 330499-01-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1


Installation conditions part 1

Highbond - Anchor FHB II - A S


Pre-positioned installation



Push through installation



Pre-positioned or push through installation with subsequently injected fischer filling disc
(annular gap filled with mortar)



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Installation conditions part 1; FHB II - A S


Annex A 1

Appendix 3 / 24


Installation conditions part 2

Highbond - Anchor FHB II Inject - A S (only with injection mortar FIS HB)


Pre-positioned installation



Push through installation



Pre-positioned or push through installation with subsequently injected fischer filling disc
(annular gap filled with mortar)



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Installation conditions part 2; FHB II Inject - A S


Annex A 2

Appendix 4 / 24

Overview system components part 1

Injection cartridge (shuttle cartridge) with sealing cap;


Size: 360 ml, 825 ml



Imprint: fischer FIS HB, processing notes, shelf-life, piston travel scale (optional), curing times and processing times (depending on temperature), hazard code, size, volume

Injection cartridge (coaxial cartridge) with sealing cap;

Size: 150 ml, 300 ml, 380 ml, 400 ml, 410 ml




Imprint: fischer FIS HB, processing notes, shelf-life, piston travel scale (optional), curing times and processing times (depending on temperature), hazard code, size, volume


Resin capsule



Static mixer FIS MR Plus for injection cartridges up to 410 ml



Static mixer FIS JMR for injection cartridge 825 ml




Extension tube Ø 9 for static mixer FIS MR Plus;

Extension tube Ø 9 or Ø 15 for static mixer FIS JMR



Injection adapter



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Overview system components part 1

cartridges / resin capsule / static mixer / accessories


Annex A 3

Appendix 5 / 24


Overview system components part 2

fischer Highbond - Anchor FHB II and FHB II Inject; pre-assembled condition


Highbond - Anchor FHB II - A S




alternative version



Highbond - Anchor FHB II Inject - A S




alternative version




Highbond anchor rod FHB II - A S

Size: M16, M20, M24



Highbond anchor rod FHB II Inject - A S

Size: M16, M20, M24



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Overview system components part 2
anchor rod


Annex A 4

Appendix 6 / 24


Overview system components part 3

fischer filling disc (various versions)


radial




angular




axial




conical washer



washer



hexagon nut



Cleaning brush BS



Compressed-air cleaning tool ABP with
compressed-air nozzle:



or blow-out pump ABG:



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Overview system components part 3
metal parts / cleaning brush / blow-out pump

Annex A 5

Appendix 7 / 24

Table A6.1: Materials

Part	Designation	Material		
1	Injection cartridge	Mortar, hardener, filler		
2	Resin capsule	Mortar, hardener, filler		
Steel grade	Steel	Stainless steel A4	High corrosion resistant steel C	
	zink plated	acc. to EN 10088-1:2014 Corrosion resistance class CRC III acc. to EN 1993-1-4:2006+A1:2015	acc. to EN 10088-1:2014 Corrosion resistance class CRC V acc. to EN 1993-1-4:2006+A1:2015	
3	Highbond-Anchor rod FHB II - A S or FHB II Inject - A S	Property class 8.8 EN ISO 898-1:2013 electroplated $\geq 5 \mu\text{m}$ ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018 $A_5 > 12\%$ fracture elongation	Property class 80 EN ISO 3506-1:2020 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; 1.4062, 1.4662, 1.4462; EN 10088-1:2014 $A_5 > 12\%$ fracture elongation	Property class 80 EN ISO 3506-1:2020 1.4565; 1.4529; EN 10088-1:2014 $A_5 > 12\%$ fracture elongation
4	Washer ISO 7089:2000	electroplated $\geq 5 \mu\text{m}$ ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018	1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; EN 10088-1:2014	1.4565; 1.4529; EN 10088-1:2014
5	Hexagon nut	Property class 8 acc. to EN ISO 898-2:2012 electroplated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018	Property class 70 or 80 EN ISO 3506-2:2020 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; EN 10088-1:2014	Property class 70 or 80 EN ISO 3506-2:2020 1.4565; 1.4529; EN 10088-1:2014
6	Conical washer or fischer filling disc	electroplated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018	1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; EN 10088-1:2014	1.4565; 1.4529; EN 10088-1:2014

fischer Highbond-Anchor FHB II for diamond drilling / extended working life



Product description
Materials

Annex A 6

Appendix 8 / 24

Specifications of intended use part 1

Table B1.1: Overview installation und use

		fischer Highbond-Anchor FHB II with injection mortar FIS HB or resin capsule FHB II-P / FHB II-PF	
		FHB II - A S	FHB II Inject - A S
			
		injection mortar FIS HB or resin capsule FHB II-P / FHB II-PF	
Hammer drilling with standard drill bit		all sizes	
Hammer drilling with hollow drill bit		all sizes (Heller "Duster Expert"; Bosch "Speed Clean"; Hilti "TE-CD, TE-YD")	
Diamond drilling		all sizes (only with resin capsule allowed)	no performance assessed
Static or quasi static load, in	uncracked concrete	all sizes	all sizes
	cracked concrete	Tables: C1.1, C2.1, C3.1, C3.2, C4.1, C5.1, C5.2	Tables: C1.1, C2.1, C4.1, C5.2
Installation and use condition	I1 dry or wet concrete	all sizes	
	I2 water-filled hole	all sizes (only with resin capsule allowed)	no performance assessed
seismic performance category C1 and C2		no performance assessed	
Installation direction		D3 (downwards, horizontal and upwards (overhead) installation)	
Installation	Pre-positioned	all sizes	
	Push through	all sizes	
Installation temperature ¹⁾		FIS HB: $T_{i,min} = -5 \text{ }^{\circ}\text{C}$ to $T_{i,max} = +40 \text{ }^{\circ}\text{C}$ FHB II-P / PF: $T_{i,min} = -5 \text{ }^{\circ}\text{C}$ to $T_{i,max} = +40 \text{ }^{\circ}\text{C}$	
Service temperature	Temperature range T2	-40 °C to +80 °C	(max. short term temperature +80 °C; max. long term temperature +50 °C)
¹⁾ For the standard variation of temperature after installation			
Figures not to scale			
fischer Highbond-Anchor FHB II for diamond drilling / extended working life			Annex B 1
Intended use Specifications part 1			

Specifications of intended use part 2

Base materials:

- Compacted reinforced or unreinforced normal weight concrete without fibres of strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (zinc plated steel, stainless steel or high corrosion resistant steel)
- For all other conditions according to EN1993-1-4: 2006+A1:2015 corresponding to corrosion resistance classes to Annex A 6 table 6.1.

Design:

- Fastenings are designed under the responsibility of an engineer experienced in fastenings and concrete work
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the fastener is indicated on the design drawings (e.g. position of the fastener relative to reinforcement or to supports, etc.)
- Fastenings are designed in accordance with:
EN 1992-4:2018 and EOTA Technical Report TR 055, Edition February 2018

Installation:

- Fastener installation is to be carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Overhead installation is allowed (necessary equipment see installation instruction)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended Use
Specifications part 2

Annex B 2


Appendix 10 / 24

Table B3.1: Installation parameters for Highbond – Anchor rod FHB II - A S

Anchor rod FHB II - A S	Thread	M16x95	M20x170	M24x170
Corresponding resin capsules FHB II-P or FHB II-PF	[-]	16x95	20x170	24x170
Cone diameter d_k	[mm]	14,5	23,0	
Width across flats SW		24	30	36
Nominal drill hole diameter d_0		16	25	
Drill hole depth h_0		110	190	
Effective embedment depth h_{ef}		95	170	
Minimum spacing and minimum edge distance $s_{min} = c_{min}$		50	80	
Diameter of clearance hole of the fixture $d_f \leq$		18	22	26
push through installation $d_f \leq$		18	26	
Min. thickness of concrete member h_{min}		150	240	
Installation torque T_{inst}	[Nm]	50	100	
Thickness of fixture $t_{fix} \leq$	[mm]		1500	
fischer filling disc ¹⁾		38	46	54
$\geq d_a$		7	8	10
t_s				

¹⁾ Using fischer filling disc reduces t_{fix} (usable length of the anchor)

Highbond – Anchor rod FHB II - A S




Marking: work symbol, thread diameter, embedment depth e.g.: M16x95

For stainless steel additional **A4**. For high corrosion resistant steel additional **C**.

For high corrosion resistant steel additional marking “(“ also on the face side

Installation conditions:



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation parameters for Highbond - Anchor FHB II - A S


Annex B 3

Table B4.1: Installation parameters for Highbond - Anchor rod FHB II Inject - A S with injectionmortar FIS HB

Anchor rod FHB II Inject - A S		Thread	M16x95	M20x170	M24x170
Cone diameter	d_k	[mm]	14,5	23,0	
Width across flats	SW		24	30	36
Nominal drill hole diameter	d_0		16	25	
Drill hole depth	h_0		101	176	
Effective embedment depth	h_{ef}		95	170	
Minimum spacing and minimum edge distance	$s_{min} = c_{min}$		50	80	
Diameter of clearance hole of the fixture	pre-positioned installation push through installation		18	22	26
Min. thickness of concrete member	h_{min}		20	26	
Installation torque	T_{inst}		150	240	
Thickness of fixture	$t_{fix} \leq$	[mm]	50		
fischer filling disc ¹⁾	$\geq d_a$		1500	100	
	t_s		38	46	54
			7	8	10


¹⁾ Using fischer filling disc reduces t_{fix} (usable length of the fastener)

Highbond – Anchor rod FHB II Inject - A S



Marking: work symbol, thread diameter, embedment depth e.g.: M16x95
For stainless steel additional "A4". For high corrosion resistant steel additional "C".
For high corrosion resistant steel additional marking "(" also on the face side

Installation conditions:



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life



Intended use
Installation parameters for Highbond - Anchor FHB II Inject - A S

Annex B 4

Appendix 12 / 24

Table B5.1: Dimensions of resin capsule FHB II-P and FHB II-PF

Resin capsule		16x95	20x170	24x170
Capsule length	L_p	120	185	185
Capsule diameter	$\varnothing d_p$	14,5	21,5	

FHB II-P (standard)**FHB II-PF (fast curing)**

Imprint: work symbol, marking, anchor size and effective embedment depth.


e.g.: FHB II-P 16x95 or

FHB II-PF 16x95

Table B5.2: Parameters of the cleaning brush BS (steel brush with steel bristles; only when using injection mortar or resin capsule with diamond drill bit)

The size of the cleaning brush refers to the nominal drill hole diameter

Nominal drill hole diameter	d_0	[mm]	16	25
Steel brush diameter BS	d_b		20	27



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Dimensions resin capsule

Parameters cleaning brush (steel brush)

Annex B 5

Appendix 13 / 24

Table B6.1: Processing time and curing time of the injection mortar FIS HB

Temperature at anchoring base ¹⁾ [°C]	Maximum processing time t_{work}	Minimum curing time ²⁾ t_{cure}
-5 to 0 ³⁾	-	6 h
> 0 to 5 ³⁾	-	3 h
> 5 to 10	15 min	90 min
> 10 to 20	6 min	35 min
> 20 to 30	4 min	20 min
> 30 to 40	2 min	12 min

¹⁾ During the curing time of the mortar the temperature of the anchoring base may not fall below the listed minimum temperature

²⁾ In wet concrete the curing time must be doubled

³⁾ Minimal cartridge temperature +5 °C

Table B6.2: Curing time of the resin capsule FHB II-P and FHB II-PF

Resin capsule FHB II-P (standard)		Resin capsule FHB II-PF (fast curing)	
Temperature at anchoring base ¹⁾ [°C]	Minimum curing time ²⁾ t_{cure}	Temperature at anchoring base ¹⁾ [°C]	Minimum curing time ²⁾ t_{cure}
-5 to 0	4 h	-5 to 0	8 min
> 0 to 10	45 min	> 0 to 10	6 min
> 10 to 20	20 min	> 10 to 20	4 min
> 20	10 min	> 20	2 min

¹⁾ During the curing time of the mortar the temperature of the anchoring base may not fall below the listed minimum temperature.

²⁾ In wet concrete or water-filled holes the curing times must be doubled

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Processing time and curing time


Annex B 6

Appendix 14 / 24

Installation instructions part 1; Installation with resin capsule FHB II-P or FHB II-PF

Drilling the drill hole (hammer drilling with standard drill bit)

1



Drill the hole.

Nominal drill hole diameter d_0 and drill hole depth h_0 see **table B3.1**
Cleaning of the drill hole is not necessary

Go to step 6 (Annex B 8)


Drilling and cleaning the drill hole (hammer drilling with hollow drill bit)

1



Check a suitable hollow drill (see **table B1.1**)
for correct operation of the dust extraction

2




Use a suitable dust extraction system, e.g. fischer FVC 35 M or a comparable dust extraction system with equivalent performance data.
Drill the hole with hollow drill bit. The dust extraction system has to extract the drill dust nonstop during the drilling process and must be adjusted to maximum power.

Nominal drill hole diameter d_0 and drill hole depth h_0 see **table B3.1**


Go to step 6 (Annex B 8)

Drilling and cleaning the drill hole (wet drilling with diamond drill bit)

1




Drill the hole.
Drill hole diameter d_0 and nominal drill hole depth h_0 see **table B3.1**




Break the drill core
and remove it

2




Flush the drill hole, until clear water emerges from the drill hole.

3



Blow out the drill hole twice, using oil-free compressed air ($p \geq 6$ bar)

4



Brush the drill hole twice.
Corresponding cleaning brush BS see **table B5.2**



5



Blow out the drill hole twice, using oil-free compressed air ($p \geq 6$ bar)

Go to step 6 (Annex B 8)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use









Installation instructions part 1

Installation with resin capsule FHB II-P or FHB II-PF

Annex B 7

Installation instructions part 2; Installation with resin capsule FHB II-P or FHB II-PF

Installation Highbond-Anchor rod FHB II - A S

6		Insert the resin capsule FHB II-P or FHB II-PF into the drill hole by hand.
7		<p>Pre-positioned installation: Only use Highbond-Anchor rods FHB II - A S with roof-shaped point. Drive in the Anchor rod using a hammer drill or impact drill. When reaching the setting depth mark stop the drill immediately.</p>
7		<p>Push through installation: Only use Highbond-Anchor rods FHB II - A S with roof-shaped point. Drive in the anchor rod using a hammer drill or impact drill. When reaching the setting depth mark stop the drill immediately.</p>
8		<p>Pre-positioned installation: After inserting the anchor rod, excess mortar must be emerged around the anchor.</p>
8		<p>Push through installation: After inserting the anchor rod, excess mortar must be emerged from the drill hole and must be visible in the fixture.</p>
8a		For overhead installations support the anchor rod with wedges. (e.g. fischer centering wedges)
9		Wait for the specified curing time t_{cure} see table B6.2
10		Installation torque for the hexagon nut T_{inst} see table B3.1, B4.1
Option		<p>The gap between metal parts and fixture (annular gap) may be filled with mortar via the fischer filling disc. Compressive strength $\geq 50 \text{ N/mm}^2$ (e.g. FIS HB, FIS SB, FIS V, FIS V Plus, FIS EM Plus).</p> <p>ATTENTION: Using fischer filling disc reduces t_{fix} (usable length of the anchor)</p>

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation instructions part 2

Installation with resin capsule FHB II-P or FHB II-PF


Annex B 8

Appendix 16 / 24

Installation instructions part 3; Installation with injection mortar FIS HB

Drilling and cleaning the drill hole (hammer drilling with standard drill bit)


1



Drill the hole

Nominal drill hole diameter d_0 and drill hole depth h_0 see **tables B3.1, B4.1**

2




Clean the drill hole.

Blow out the drill hole twice.

If necessary, remove standing water out of the bore hole




3



Brush the bore hole twice. Corresponding cleaning brush BS see **table B5.2**



4



Clean the drill hole.

Blow out the drill hole twice.



For drill hole diameter $d_0 = 16 \text{ mm}$ blow out the hole by hand or oil-free compressed air ($\geq 6 \text{ bar}$).

For drill hole diameter $d_0 = 25 \text{ mm}$ blow out the hole with oil-free compressed air ($\geq 6 \text{ bar}$). Use a compressed-air nozzle.

Go to step 5 (Annex B 10)


Drilling and cleaning the drill hole (hammer drilling with hollow drill bit)

1



Check a suitable hollow drill (see **table B1.1**) for correct operation of the dust extraction

2



Use a suitable dust extraction system, e.g. fischer FVC 35 M or a comparable dust extraction system with equivalent performance data.

Drill the hole with hollow drill bit. The dust extraction system has to extract the drill dust nonstop during the drilling process and must be adjusted to maximum power.

Nominal drill hole diameter d_0 and drill hole depth h_0 see **tables B3.1, B4.1**

Go to step 5 (Annex B 10)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation instructions part 3


Installation with injection mortar FIS HB

Annex B 9



Appendix 17 / 24

Installation instruction part 4; Installation with injection mortar FIS HB

Preparing the cartridge

5		Remove the sealing cap Screw on the static mixer (the spiral in the static mixer must be clearly visible)
6		Place the cartridge into the dispenser
7		Extrude approximately 10 cm of material out until the resin is evenly grey in colour. Do not use mortar that is not uniformly grey

Injection of the mortar

8		Fill approximately 2/3 of the drill hole with mortar. Always begin from the bottom of the hole and avoid bubbles
		For drill hole depth ≥ 170 mm use an extension tube

Go to step 9 (Annex B 11)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation instructions part 4

Installation with injection mortar

Annex B 10

Appendix 18 / 24

Installation instruction part 5; Installation with injection mortar FIS HB

Installation Highbond-Anchor rod FHB II - A S or FHB II Inject - A S






9		<p>Pre-positioned or push through installation: Push the anchor rod down to the bottom of the hole, turning it slightly while doing so. Only use clean and oil-free metal parts.</p>
10		<p>Pre-positioned installation: After inserting the anchor rod, excess mortar must be emerged around the anchor.</p>
10a		<p>Push through installation: After inserting the anchor rod, excess mortar must be emerged from the drill hole and must be visible in the fixture.</p>
11		<p>Wait for the specified curing time t_{cure} see table B6.1</p>
12		<p>Installation torque for the hexagon nut T_{inst} see table B3.1, B4.1</p>
Option		<p>The gap between metal parts and fixture (annular gap) may be filled with mortar via the fischer filling disc. Compressive strength $\geq 50 \text{ N/mm}^2$ (e.g. FIS HB, FIS SB, FIS V, FIS V Plus, FIS EM Plus). ATTENTION: Using fischer filling disc reduces t_{fix} (usable length of the anchor)</p>
<p>fischer Highbond-Anchor FHB II for diamond drilling / extended working life</p>		<p>Annex B 11</p>
<p>Intended use Installation instructions part 5 Installation with injection mortar</p>		<p>Appendix 19 / 24</p>

Table C1.1: Characteristic resistance to steel failure under tension / shear loading of Highbond-Anchor rods FHB II - A S and FHB II Inject - A S

Anchor rod FHB II - A S / FHB II Inject - A S		M16x95	M20x170	M24x170		
Characteristic resistance to steel failure under tension loading						
Characteristic resistance $N_{Rk,s}$	Steel, zinc plated	[kN]	61,6	128,5		
	Stainless steel A4					
	High corrosion resistant steel C		61,6	128,5		
Partial factors¹⁾						
Partial factor $\gamma_{Ms,N}$	Steel, zinc plated	[-]	1,5 ¹⁾			
	Stainless steel A4		1,5 ¹⁾			
	High corrosion resistant steel C		1,5 ¹⁾			
Characteristic resistance to steel failure under shear loading						
without lever arm						
Characteristic resistance $V^0_{Rk,s}$	Steel, zinc plated	[kN]	50,8	80,3		
	Stainless steel A4		62,7	97,9		
	High corrosion resistant steel C		62,7	97,9		
Ductility factor	k_7	[-]	1,0			
with lever arm						
Characteristic resistance $M^0_{Rk,s}$	Steel, zinc plated	[Nm]	266	519		
	Stainless steel A4			896		
	High corrosion resistant steel C		266	519		
Partial factors¹⁾						
Partial factor	$\gamma_{Ms,V}$	[-]	1,25			
1) In absence of other national regulations						
fischer Highbond-Anchor FHB II for diamond drilling / extended working life						
Performance Characteristic resistance to steel failure under tension / shear loading of Highbond-Anchor rods FHB II - A S and FHB II Inject - A S			Annex C 1 Appendix 20 / 24			

Table C2.1: Characteristic resistance to concrete failure under tension / shear loading

Anchor rod FHB II - A S / FHB II Inject - A S		All sizes		
Characteristic resistance to concrete failure under tension loading				
Installation factor	γ_{inst}	[-] See annex C 3 to C 4		
Factors for the compressive strength of concrete > C20/25				
Increasing factor for uncracked or cracked concrete $N_{Rk,p} = \psi_c N_{Rk,p}$ (C20/25)	C25/30	[-]	1,12	
	C30/37		1,22	
	C35/45		1,32	
	C40/50		1,41	
	C45/55		1,50	
	C50/60		1,58	
Splitting failure				
Edge distance	$c_{cr,sp}$	[mm]	2 h_{ef}	
Spacing	$s_{cr,sp}$		4 h_{ef}	
Concrete cone failure				
Uncracked concrete	$k_{ucr,N}$	[-]	11,0 ¹⁾	
Cracked concrete	$k_{cr,N}$		7,7 ¹⁾	
Edge distance	$c_{cr,N}$	[mm]	1,5 h_{ef}	
Spacing	$s_{cr,N}$		3 h_{ef}	
Characteristic resistance to concrete failure under shear loading				
Installation factor	γ_{inst}	[-] 1,0		
Concrete pry-out failure				
Factor for pry-out failure	k_8	[-] 2,0		
Concrete edge failure				
Anchor rod FHB II - A S and FHB II Inject - A S		M16x95	M20x170	
Effective length of fastener in shear loading	l_f	[mm]	95	
Calculation diameter	d_{nom}		16	
1) Related to concrete cylinder compressive strength				
fischer Highbond-Anchor FHB II for diamond drilling / extended working life				
Performance Characteristic resistance to concrete failure under tension / shear loading			Annex C 2	
			Appendix 21 / 24	

Table C3.1: Characteristic resistance to pull-out failure for Highbond-Anchor rods
FHB II - A S with resin capsule FHB II-P or FHB II-PF in diamond drilled
holes; 50 years

Highbond-Anchor rod FHB II - A S ¹⁾	M16x95	M20x170	M24x170
Characteristic resistance to pull-out failure			
Calculation diameter d [mm]	16	25	
Uncracked concrete			
Characteristic resistance in uncracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,ucr} [kN]	51,5	118,5	
Cracked concrete			
Characteristic resistance in cracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,cr} [kN]	42,8	101,4	
Installation factors			
Dry or wet concrete		1,2	
Water-filled hole γ _{inst} [-]		1,2	

¹⁾ Highbond-Anchor rod FHB II - A S with resin capsule FHB II-P / FHB II-PF

Table C3.2: Characteristic resistance to pull-out failure for Highbond-Anchor rods
FHB II - A S with resin capsule FHB II-P or FHB II-PF in diamond drilled
holes; 100 years

Highbond-Anchor rod FHB II - A S ¹⁾	M16x95	M20x170	M24x170
Characteristic resistance to pull-out failure			
Calculation diameter d [mm]	16	25	
Uncracked concrete			
Characteristic resistance in uncracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,ucr,100} [kN]	51,5	118,5	
Cracked concrete			
Characteristic resistance in cracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,cr,100} [kN]	36,0	86,0	
Installation factors			
Dry or wet concrete		1,2	
Water-filled hole γ _{inst} [-]		1,2	

¹⁾ Highbond-Anchor rod FHB II - A S with resin capsule FHB II-P / FHB II-PF

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Performance

Characteristic resistance to pull-out failure for Highbond-Anchor rods FHB II - A S in diamond drilled holes; 50 or 100 years

Annex C 3

Appendix 22 / 24

Table C4.1: Characteristic resistance to pull-out failure for Highbond-Anchor rods
FHB II - A S with resin capsule FHB II-P / FHB II-PF or injection mortar
FIS HB and **FHB II Inject - A S** with injection mortar **FIS HB** in hammer drilled holes; 100 years

Anchor rod FHB II - A S ¹⁾ FHB II Inject - A S ²⁾	M16x95	M20x170	M24x170
Characteristic resistance to pull-out failure			
Calculation diameter d [mm]	16	25	
Uncracked concrete			
Characteristic resistance in uncracked concrete C20/25			
Hammer-drilling with standard or hollow drill bit (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,ucr,100}	[kN]	52,4	118,5
Cracked concrete			
Characteristic resistance in cracked concrete C20/25			
Hammer-drilling with standard or hollow drill bit (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,cr,100}	[kN]	36,0	86,0
Installation factors			
Dry or wet concrete			1,0
Water-filled hole (only with resin capsule)	γ _{inst} [-]		1,0
1) Highbond-Anchor rod FHB II - A S with resin capsule FHB II-P / FHB II-PF or injection mortar FIS HB			
2) Highbond-Anchor rod FHB II Inject - A S with injection mortar FIS HB			
fischer Highbond-Anchor FHB II for diamond drilling / extended working life			
Performance Characteristic resistance to pull-out failure for Highbond-Anchor rods FHB II - A S / FHB II Inject - A S in hammer drilled holes; 100 years		Annex C 4 Appendix 23 / 24	

Table C5.1: Displacements for Highbond-Anchor rod FHB II - A S; 50 years

Anchor rod FHB II – A S		M16x95	M20x170	M24x170	
Displacement-Factors for tension loading ¹⁾					
Uncracked concrete; Temperature range T2					
δ_{N0} -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Cracked concrete; Temperature range T2					
$\delta_{N\infty}$ -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Displacement-Factors for shear loading ²⁾					
Uncracked or cracked concrete; Temperature range T2					
δ_{V0} -Factor	[mm/kN]	0,02	0,02	0,02	
		0,03	0,03	0,03	

¹⁾ Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0}\text{-Factor} \cdot N$$

$$\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot N$$

N = acting tension loading

²⁾ Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V$$

$$\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V$$

V = acting shear loading

Table C5.2: Displacements for Highbond-Anchor rod FHB II - A S and FHB II Inject - A S; 100 years

Anchor rod FHB II – A S / FHB II Inject - A S		M16x95	M20x170	M24x170	
Displacement-Factors for tension loading ¹⁾					
Uncracked concrete; Temperature range T2					
δ_{N0} -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Cracked concrete; Temperature range T2					
$\delta_{N\infty}$ -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Displacement-Factors for shear loading ²⁾					
Uncracked or cracked concrete; Temperature range T2					
δ_{V0} -Factor	[mm/kN]	0,02	0,02	0,02	
		0,03	0,03	0,03	

¹⁾ Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0}\text{-Factor} \cdot N$$

$$\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot N$$

N = acting tension loading

²⁾ Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V$$

$$\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V$$

V = acting shear loading

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Performances

Displacements for Highbond-Anchor rod FHB II - A S and FHB II Inject - A S;
50 or 100 years

Annex C 5