



ΔΗΛΩΣΗ ΕΠΙΔΟΣΕΩΝ



DoP: 0112

για fischer termoz CN 8 / fischer termoz CN 8 R / fischer termoz CNplus 8 (Πλαστικά αγκύρια για χρήση σε μπετόν και τούβλο) – EL

1. Μοναδικός κωδικός ταυτοποίησης του τύπου του προϊόντος: **DoP: 0112**
2. Προβλεπόμενη(-ες) χρήση(-εις): **Για χρήση σε συστήματα εξωτερικής θερμομόνωσης (ETICS) με σοβά για την μετάδοση των ανεμοπιέσεων, δείτε το προσάρτημα, ειδικά τα παραρτήματα B 1 - B 3**
3. Κατασκευαστής: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Straße 1, 72178 Waldachtal, Γερμανία**
4. Εξουσιοδοτημένος αντιπρόσωπος: --
5. Σύστημα/συστήματα AVCP (αξιολόγηση και επαλήθευση της σταθερότητας της επίδοσης): **2+**
6. Ευρωπαϊκό έγγραφο αξιολόγησης: **EAD 330196-01-0604**

Ευρωπαϊκή τεχνική αξιολόγηση: **ETA-09/0394; 2017-12-19**

Οργανισμός τεχνικής αξιολόγησης: **DIBt**

Κοινοποιημένος(-οι) οργανισμός(-οι): **1343 – MPA Darmstadt**

7. Δηλωθείσα(-ες) επίδοση(-εις):

Μηχανική αντιστάση και σταθερότητα (BWR 1),

- Χαρακτηριστική εφελκυστική τιμή: δείτε το προσάρτημα, ειδικά τα παραρτήματα C 1 - C 2
- Αποστάσεις από ακμή και από άξονα: δείτε το προσάρτημα, ειδικά τα παραρτήματα B 2
- Ακαμψία πλάκας έδρασης: δείτε το παράρτημα, συγκεκριμένα τα παραρτήματα C 4
- μετατόπιση: δείτε το παράρτημα, συγκεκριμένα τα παραρτήματα C 4

Εξοικονόμηση ενέργειας και συγκράτηση θερμότητας (BWR 6)

- σημειακή θερμική αγωγιμότητα: δείτε το παράρτημα, συγκεκριμένα τα παραρτήματα C 3

8. Κατάλληλη τεχνική τεκμηρίωση και/ή ειδική τεχνική τεκμηρίωση: ---

Η επίδοση του προϊόντος που ταυτοποιείται ανωτέρω είναι σύμφωνη με τη (τις) δηλωθείσα(-ες) επίδοση(-εις). Αυτή η δήλωση επιδόσεων εκδίδεται σύμφωνα με τον Κανονισμό (ΕΕ) Αρ. 305/2011 με αποκλειστική ευθύνη του κατασκευαστή που προσδιορίζεται παραπάνω.

Υπογραφή για λογαριασμό και εξ ονόματος του κατασκευαστή από:

Andreas Bucher, Dipl.-Ing.

Wolfgang Hengesbach, Dipl.-Ing., Dipl.-Wirtsch.-Ing.

Tumlingen, 2018-01-04

- Αυτή η Δήλωση Απόδοσης μεταφράστηκε σε διάφορες γλώσσες. σε περίπτωση που υπάρχει αμφιβολία για τη μετάφραση η αγγλική έκδοση θα υπερισχύει πάντα.
- Το παράρτημα περιλαμβάνει προαιρετικές και συμπληρωματικές πληροφορίες στα αγγλικά. Αυτές ξεπερνούν τις προβλεπόμενες από το νόμο (γλώσσα ουδέτερη) .

Specific Part

1 Technical description of the product

The fischer nailed-in anchor termoz CN 8 and termoz CNplus 8 consists of an anchor sleeve with an enlarged shaft made of polypropylene (virgin material), an insulation plate made of glass fibre reinforced polyamide (virgin material) (termoz CN 8 / 250-390) and a special compound nail consisting of two parts, one made of glass fibre reinforced polyamide for the shaft element and the other part made of galvanised steel.

The specific nail for the anchor types termoz CN 8 / 250 – 390 and termoz CN 8 R / 250 – 310 is made of galvanized steel which is used together with a separate plastic cylinder made of glass fibre reinforced polyamide.

The serrated expanding part of the anchor sleeve is slotted.

The anchor may in addition be combined with the anchor plates DT 90, DT 110 and DT 140.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verification and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 25 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Safety and accessibility in use (BWR 4)

Essential characteristic	Performance
Characteristic tension resistance	See Annex C 1 and C 2
Edge distances and spacing	See Annex B 2
Plate stiffness	See Annex C 4
Displacements	See Annex C 4

3.2 Energy economy and heat retention (BWR 6)


Essential characteristic	Performance
Point thermal transmittance	See Annex C 3

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base


In accordance with EAD No. 330196-01-0604, the applicable European legal act is: [97/463/EC].

The system to be applied is: 2+

termoz CN 8 / 110 – 230 / termoz CNplus 8 / 110 – 230 – flush mounted



termoz CN 8 / 250 – 390 / termoz CN 8 R / 250 – 310 / termoz CNplus 8 / 250-390 – flush mounted



Legend

- h_{nom} = Overall plastic anchor embedment depth in the base material
- h_1 = Depth of drilled hole to deepest point
- h = Thickness of member (wall)
- h_D = Thickness of insulation material
- t_{tol} = Thickness of equalizing layer or non-load bearing coating


fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description


Installed anchor – flush-mounted

Annex A1

termoz CNplus 8 / 110 – 230 – countersunk mounted



termoz CNplus 8 / 250 – 390 – countersunk mounted



Legend


- h_{nom} = Overall plastic anchor embedment depth in the base material
- h_1 = Depth of drilled hole to deepest point
- h = Thickness of member (wall)
- h_D = Thickness of insulation material
- h_R = Thickness of insulation cap
- t_{tol} = Thickness of equalizing layer or non-load bearing coating

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description

Installed anchor – countersunk mounted

Annex A2

termoz CN 8 / 110-230

¹⁾ Various length of the anchors are possible

e.g. for termoz CN 8 / 110-230:

$$110 \text{ mm} \geq L_a \leq 230 \text{ mm}$$

$$L_a = L_n + 4 \text{ mm}$$

Determination of maximum thickness of insulation: $h_D = L_a - h_{nom} - t_{tol}$

e.g. for termoz CN 8x150:

$$L_a = 148 \text{ mm}, h_{nom} = 35 \text{ mm}, t_{tol} = 10 \text{ mm}$$

$$h_D = 148 - 35 - 10 \approx 100$$

Table A3.1: Dimensions termoz CN 8 / 110-230


Anchor type	Anchor sleeve		Specific compound nail		
	Ø d _d [mm]	h _{nom} [mm]	Ø d _n [mm]	L ₁ [mm]	Ø d ₁ [mm]
termoz CN 8 / 110-230	8	35/55 ²⁾	4,5	40	8

²⁾ Only for use cat. E

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description
Dimensions termoz CN8 / 110-230

Annex A3

termoz CN 8 / 250 – 390


Marking: Brand, name and size of anchor, diameter, categories, optional markings see drawing of anchor plate, example e.g.  termoz CN 8, ABCDE

Various lengths of the anchors are possible:

e.g. for termoz CN 8 / 250 – 390:

$$250 \text{ mm} \geq L_{a1} + L_{a2} \leq 390 \text{ mm}$$

$$L_a = L_{a1} + L_{a2} = L_n + 160,5 \text{ mm}$$

Determination of maximum thickness of insulation:

$$h_D = L_a - h_{nom} - t_{tol}$$

e.g. for termoz CN 8x330:

$$L_a = 328 \text{ mm}, h_{nom} = 35 \text{ mm}, t_{tol} = 10 \text{ mm}$$

$$h_D = 328 - 35 - 10 \approx 280 \text{ mm}$$

Table A4.1: Dimensions termoz CN 8 / 250 – 390


Anchor type	Shaft	Anchor sleeve			Nail		Plastic cylinder	
	L _{a1} [mm]	Ø d _d [mm]	h _{nom} [mm]	L _{a2} [mm]	Ø d _n [mm]	L _n [mm]	L ₁ [mm]	Ø d ₁ [mm]
termoz CN 8 / 250 – 390	161	8	35/55 ¹⁾	87 - 247	4.5	(L _{a1} +L _{a2}) – 160.5	157	8

¹⁾ Only for use cat. E

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description
Dimensions termoz CN8 / 250-390

Annex A4

termoz CN 8 R / 250 – 310

Various lengths of the anchors are possible:

e.g. for termoz CN 8 R / 250 – 310:

$$250 \text{ mm} \geq L_{a1} + L_{a2} \leq 310 \text{ mm}$$

$$L_a = L_{a1} + L_{a2} = L_n + 80,5 \text{ mm}$$

Determination of maximum thickness of insulation:

$$h_D = L_a - h_{nom} - t_{tol}$$

e.g. for termoz CN 8x250 R:

$$L_a = 248 \text{ mm}, h_{nom} = 35 \text{ mm}, t_{tol} = 10 \text{ mm}$$

$$h_D = 248 - 35 - 10 \approx 200 \text{ mm}$$

Table A5.1: Dimensions termoz CN 8 R / 250 – 310


Anchor type	Shaft		Anchor sleeve		Nail		Plastic cylinder	
	L_{a1} [mm]	$\varnothing d_d$ [mm]	h_{nom} [mm]	L_{a2} [mm]	$\varnothing d_n$ [mm]	L_n [mm]	L_1 [mm]	$\varnothing d_1$ [mm]
termoz CN 8 R / 250 – 310	81	8	35/55 ¹⁾	167 - 247	4,5	$(L_{a1} + L_{a2}) - 80,5$	77	8

¹⁾ Only for use cat. E

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description
Dimensions termoz CN8 R / 250-310

Annex A5

termoz CNplus 8 / 110–230


¹⁾Various lengths of the anchors are permissible:

e.g. for termoz CNplus 8 / 110 – 230:

$$110 \text{ mm} \geq L_a \leq 230 \text{ mm}$$

$$L_a = L_n + 1,5 \text{ mm}$$

Determination of maximum thickness of insulation: $h_D = L_a - h_{nom} - t_{tol}$

e.g. for termoz CNplus 8x150:

$$L_a = 148 \text{ mm}, h_{nom} = 35 \text{ mm}, t_{tol} = 10 \text{ mm}$$

$$h_D = 148 - 35 - 10 \approx 100$$

Table A6.1: Dimensions termoz CNplus 8 / 110–230

Anchor type	Anchor sleeve		Specific compound nail			
	Ø d _d [mm]	h _{nom} [mm]	Ø d _n [mm]	L _n [mm]	L ₁ [mm]	Ø d ₁ [mm]
termoz CNplus 8 / 110-230	8	35/55 ¹⁾	4,3	L _a – 1,5	40	8


¹⁾ Only for use cat. D & E

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description

Dimensions termoz CNplus 8 / 110-230

Annex A6

termoz CNplus 8 / 250–310


Marking: Brand, name and size of anchor, diameter, categories, optional markings see drawing of anchor plate, example e.g.  termoz CNplus 8 ABCDE

Various lengths of the anchors are possible:

e.g. for termoz CN plus / 250 – 310:
 $250 \text{ mm} \geq L_{a1} + L_{a2} \leq 310 \text{ mm}$
 $L_a = L_{a1} + L_{a2} = L_n + 79,5 \text{ mm}$

Determination of maximum thickness of insulation:

$$h_D = L_a - h_{nom} - t_{tol}$$

e.g. for termoz CNplus 8 x 250:

$$L_a = 248 \text{ mm}, h_{nom} = 35 \text{ mm}, t_{tol} = 10 \text{ mm}$$

$$h_D = 248 - 35 - 10 \approx 200 \text{ mm}$$

Table A7.1: Dimensions termoz CNplus 8 / 250 – 310

Anchor type	Shaft	Anchor sleeve			Specific compound nail			
	L _{a1} [mm]	Ø d _d [mm]	h _{nom} [mm]	L _{a2} [mm]	Ø d _n [mm]	L _n [mm]	L ₁ [mm]	Ø d ₁ [mm]
termoz CNplus 8 / 250 – 310	81	8	35/55 ¹⁾	167 - 247	4,3	(L _{a1} +L _{a2}) – 79,5	77,5	8


¹⁾ Only for use cat. D & E

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description

Dimensions termoz CNplus 8 / 250-310

Annex A7

termoz CNplus 8 / 330–390

Various lengths of the anchors are possible:

e.g. for termoz CNplus 8 / 330 – 390:

$$330 \text{ mm} \geq L_{a1} + L_{a2} \leq 390 \text{ mm}$$

$$L_a = L_{a1} + L_{a2} = L_n + 159,5 \text{ mm}$$

Determination of maximum thickness of insulation:

$$h_D = L_a - h_{nom} - t_{tol}$$

e.g. for termoz CNplus 8 x 330:

$$L_a = 328 \text{ mm}, h_{nom} = 35 \text{ mm}, t_{tol} = 10 \text{ mm}$$

$$h_D = 328 - 35 - 10 \approx 280 \text{ mm}$$

Marking: Brand, name and size of anchor, diameter, categories, optional markings see drawing of anchor plate example e.g.  termoz CNplus 8 ABCDE

Table A8.1: Dimensions termoz CNplus 8 / 330 – 390

Anchor type	Shaft		Anchor sleeve		Specific compound nail			
	L_{a1} [mm]	$\varnothing d_d$ [mm]	h_{nom} [mm]	L_{a2} [mm]	$\varnothing d_n$ [mm]	L_n [mm]	L_1 [mm]	$\varnothing d_1$ [mm]
termoz CNplus 8/ 330 – 390	161	8	35/55 ¹⁾	167 - 247	4,3	$(L_{a1}+L_{a2}) - 159,5$	157,5	8

¹⁾ Only for use cat. D & E

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8


Product description

Dimensions termoz CNplus 8 / 330-390


Annex A8

Setting tool with SDS adapter or hexagonal adapter available
fischer termoz CNplus 8

Countersunk setting ¹⁾




optional plain surface setting



¹⁾ Alternatively, it is possible to mill the insulation material with a standard, market-available milling tool.

Polystyrene or mineral wool cap



fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8


Product description

Setting tool for fischer termoz CNplus 8

Annex A9

Table A10.1: Material

Designation	Material
Anchor sleeve	PP (virgin material), colour: grey
Shaft termoz CN 8 / 250 – 390 or CN 8 R / 250 – 310 or CNplus 8 / 250 - 390	PA6 (virgin material)GF, colour: grey
Plastic cylinder termoz CN 8 / 250 – 390 or CN 8 R / 250 – 310	PA6 (virgin material) GF
Specific nail termoz CN 8 / 250 – 390 or CN 8 R / 250 – 310	Steel gal Zn A2G or A2F according to EN ISO 4042 : 1999
Specific compound nail termoz CN 8 / 110 – 230 or CNplus 8 / 110 – 230 or CNplus 8 / 250 - 390	PA6 GF (plastic part of compound nail) Steel gal Zn A2G or A2F according to EN ISO 4042 : 1999
Anchor plate	PA6 (virgin material) GF colour: grey, orange, red, green, yellow, blue
Slip-on plate	PA6 (virgin material) GF colour: grey, orange, red, green, yellow, blue

Drawing of the slip-on plates**Table A10.2: Slip-on plate, diameters and material**

Slip-on plate	Ø D [mm]	Ø d _d [mm]	d [mm]	Material
DT 90 / 110 / 140	90 / 110 / 140	22,5	3,9	PA6 GF

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Product description

Material

Slip-on plates combined with termoz CN 8 | termoz CN 8 R | termoz CNplus 8

Annex A10

Specifications of intended use

Anchorage subject to:

- The anchor may only be used for transmission of wind suction loads and shall not be used for the transmission of dead loads of the external thermal insulation composite system (ETICS).

Base materials:

- Normal weight concrete (use category A), according to Annex C1 and C2.
- Solid masonry (use category B), according to Annex C1 and C2.
- Hollow or perforated masonry (use category C), according to Annex C1 and C2.
- Lightweight aggregate concrete (use category D), according to Annex C1 and C2.
- Autoclaved aerated concrete (use category E), according to Annex C1 and C2.
- For other base materials of the use categories A, B, C, D and E the characteristic resistance of the anchor may be determined by job site tests acc. to EOTA Technical Report TR 051 Edition December 2016.

Temperature Range:

- 0°C to +40°C (max. short term temperature +40°C and max. long term temperature +24°C).

Design:

- The anchorages are designed under the responsibility of an engineer experienced in anchorages and masonry work with the partial safety factors $\gamma_M = 2,0$ and $\gamma_F = 1,5$ in absence of other national regulations.
- Verifiable calculation notes and drawings are prepared taking account of the loads to be anchored. The position of the anchors is indicated on the design drawings.
- Fasteners are only to be used for multiple fixings of ETICS.

Installation:

- Hole drilling by the drill modes according to Annex C1 and C2.
- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters on the site.
- Installation temperature from 0°C to +40°C
- Exposure to UV due to solar radiation of the anchor not protected by rendering ≤ 6 weeks.

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Intended use
Specification

Annex B1

Table B2.1: Installation parameters / flush mounted

Anchor type				termoz CN 8 CN8 R termoz CNplus 8
Drill hole diameter	d_0	=	[mm]	8
Cutting diameter of drill bit	d_{cut}	≤	[mm]	8,45
Depth of drilled hole to deepest point	h_1	≥	[mm]	45/55 ¹⁾ /65 ²⁾
Overall plastic anchor embedment depth in the base material	h_{nom}	≥	[mm]	35/45 ¹⁾ /55 ²⁾

¹⁾ Only CNplus 8: for weather shell (thin concrete slabs) : $35 \text{ mm} \leq h_{nom} \leq 45 \text{ mm}$

²⁾ termoz CN 8 | CN8 R : Only for use cat. "E" | termoz CNplus 8: Only for use cat. "D" & "E"

Table B2.2: Installation parameters / countersunk mounted


Anchor type				termoz CNplus 8
Drill hole diameter	d_0	=	[mm]	8
Cutting diameter of drill bit	d_{cut}	≤	[mm]	8,45
Depth of drilled hole to deepest point	h_1	≥	[mm]	60/70 ¹⁾ /80 ²⁾
Overall plastic anchor embedment depth in the base material	h_{nom}	≥	[mm]	35/45 ¹⁾ /55 ²⁾

¹⁾ valid for weather shell (thin concrete slabs): $35 \text{ mm} \leq h_{nom} \leq 45 \text{ mm}$

²⁾ Only for use cat. "D" & "E"

Table B2.3: Minimum distances and spacing

				termoz CN 8 CN8 R termoz CNplus 8
Minimum thickness of member	h_{min}	=	[mm]	100
Minimum spacing	s_{min}	=	[mm]	100
Minimum edge distance	c_{min}	=	[mm]	100

Scheme of distance and spacing

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Intended use


Installation parameters

Minimum distances and spacing

Annex B2

Installation instructions

Setting of anchor (flush mounted) by hammer / fischer termoz CN 8 | termoz CN 8 R | termoz CNplus 8




1. Drill hole by corresponding drilling method

2. Insert anchor manually

3. Set anchor by hammerblows

4. Correctly installed anchor

Setting of anchor (flush mounted) by machine / fischer termoz CNplus 8




1. Drill hole by corresponding drilling method

2. Insert anchor manually

3. Set anchor by machine.

4. Correctly installed anchor

Setting of anchor (flush mounted) by setting tool \ fischer termoz CNplus 8




1. Drill hole by corresponding drilling method

2. Insert anchor manually

3. Set anchor by setting tool.

4. Correctly installed anchor

Setting of anchor (countersunk mounted) by setting tool / fischer termoz CNplus 8



1. Drill hole by corresponding drilling method

2. Insert anchor and set anchor by setting tool.

3. Put on polystyrene or mineral wool cap

4. Correctly installed anchor

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Intended use
Installation instruction

Annex B3

Table C1.1: Characteristic resistance N_{Rk} in [kN] to tension loads for single anchor

Base material	Use cat. ¹⁾	Min. compressive strength f_b [N/mm ²]	Bulk density ρ [kg/dm ³]	Remarks	Drill method ²⁾	Characteristic resistance N_{Rk} [kN] termoz CN 8 termoz CN 8 R
Concrete $\geq$ C12/15 - C50/60 EN 206-1:2000	A	-	-	-	H	0,9
Solid clay bricks Mz acc. to EN 771-1:2011	B	12	$\geq 2,0$	Cross section reduced up to 15% by perforation vertically to the resting area	H	0,9
Calcium silicate solid bricks KS e.g. acc. to EN 771-2:2011	B	12	$\geq 1,8$		H	0,9
Solid concrete blocks Vbn acc. to EN 771-3:2011	B	20	$\geq 2,0$		H	0,75
Lightweight concrete blocks Vbl acc. to EN 771-3:2011	B	8	$\geq 1,4$		H	0,6
Vertically perforated clay bricks Hlz acc. to EN 771-1:2011	C	12	$\geq 1,0$	Cross section reduced between 15% and 50% by perforation vertically to the resting area. Exterior web thickness ≥ 15 mm	R	0,6
Hollow calcium silicate brick KSL acc. to EN 771-2:2011	C	20	$\geq 1,4$	Cross section reduced between 15% and 50% by perforation vertically to the resting area. Exterior web thickness ≥ 23 mm	H	0,75
		12				0,5
Lightweight concrete hollow blocks Hbl , acc. to EN 771-3:2011	C	10	$\geq 1,2$	Cross section reduced between 15% and 50% by perforation vertically to the resting area. Exterior web thickness ≥ 38 mm	H	0,6
Lightweight aggregate concrete LAC , acc. to EN 1520:2011, EN 771-3:2011	D	6	$\geq 0,8$	-	H	0,6
		4				0,4
Autoclaved aerated concrete blocks, AAC acc. to EN 771-4:2011	E	6	$> 0,6$	-	R	0,3³⁾
		4	$> 0,4$			0,3³⁾

¹⁾ See Annex B1²⁾ R = Rotary drilling | H = Hammer drilling³⁾ Only valid for $h_{nom} \geq 55$ mm

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Annex C1

Performance

Characteristic resistance termoz CN 8, termoz CN 8 R

Table C2.1: Characteristic resistance N_{Rk} in [kN] to tension loads for single anchor

Base material	Use cat. ¹⁾	Min. compressive strength f_b [N/mm ²]	Bulk density ρ [kg/dm ³]	Remarks	Drill method ²⁾	Characteristic resistance N_{Rk} [kN] termoz CNplus 8
Concrete $\geq$ C12/15 - C50/60 EN 206-1:2000	A	-	-	-	H	0,9
Weather resistant concrete shell $\geq$ C20/25 EN 206-1:2000	A	-	-	$h \geq 42 \text{ mm}$; $t_{fix} \geq 35 \text{ mm}$	H	0,9
Solid clay bricks Mz acc. to EN 771-1:2011	B	20	$\geq 1,8$	Cross section reduced up to 15% by perforation vertically to the resting area	H	0,9
Calcium silicate solid bricks KS acc. to EN 771-2:2011	B	20	$\geq 1,8$		H	0,9
Solid concrete blocks Vbn acc. to EN 771-3:2011	B	20	$\geq 2,0$		H	0,9
Lightweight concrete blocks Vbl acc. to EN 771-3:2011	B	10	$\geq 1,6$		H	0,75
Vertically perforated clay bricks Hlz acc. to EN 771-1:2011	C	48	$\geq 1,6$	Cross section reduced between 15% and 50% by perforation vertically to the resting area. Exterior web thickness $\geq 17 \text{ mm}$	R	0,75
		12	$\geq 1,0$	Cross section reduced between 15% and 50% by perforation vertically to the resting area. Exterior web thickness $\geq 15 \text{ mm}$		0,5
Hollow calcium silicate brick KSL acc. to EN 771-2:2011	C	16	$\geq 1,4$	Cross section reduced between 15% and 50% by perforation vertically to the resting area. Exterior web thickness $\geq 16 \text{ mm}$	H	0,5
Lightweight concrete hollow blocks Hbl , acc. to EN 771-3:2011	C	10	$\geq 1,2$	Cross section reduced between 15% and 50% by perforation vertically to the resting area. Exterior web thickness $\geq 38 \text{ mm}$	H	0,6
Lightweight aggregate concrete LAC , acc. to EN 1520:2011, EN 771-3:2011	D	6	$\geq 0,9$	-	H	0,4³⁾
Autoclaved aerated concrete blocks, AAC acc. to EN 771-4:2011	E	4	$> 0,4$	-	R	0,3³⁾

¹⁾ See Annex B1²⁾ R = Rotary drilling | H = Hammer drilling³⁾ Only valid for $h_{nom} \geq 55 \text{ mm}$ **fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8****Performance**
Characteristic resistance termoz CNplus 8**Annex C2**

Table C3.1: Point thermal transmittance acc. to EOTA Technical Report TR 025 : 2016 – 05
fischer termoz CN 8 | fischer termoz CN 8 R

Anchor type	Thickness of insulation material h_D [mm]	Point thermal transmittance χ [W/K]
termoz CN 8 / 110-230	60 - 80	0,001
	> 80 - 180	0,000
termoz CN 8 / 250-350	200 - 300	0,000
termoz CN 8 / 370-390	> 300 - 340	0,001
termoz CN 8 R / 250-310	200 - 260	0,001

Table C3.2: Point thermal transmittance acc. to EOTA Technical Report TR 025 : 2016 – 05
fischer termoz CNplus 8 - flush mounted

Thickness of insulation material h _D [mm]	Point thermal transmittance χ [W/K]						
	cat. A	cat. B	cat. C	cat. D	cat. E		
60	0,001	0,001	0,001	0,001	0		
80					0,001		
100	0,002	0,002	0,002	0,001			
120							
140							
160			0,001	0,002			
180				0,001			
200							
220				0	0		
240							
260	0,001	0,001		0,001			
280				0,001			
300							
320				-	-		
340				-	-		

Table C3.3: Point thermal transmittance acc. to EOTA Technical Report TR 025 : 2016 – 05
fischer termoz CNplus 8 - countersunk mounted

Thickness of insulation material h _D [mm]	Point thermal transmittance χ [W/K]				
	cat. A	cat. B	cat. C	cat. D	cat. E
80	0,001	0	0	0	0
100		0,001	0,001	0,001	0,001
120					
140					
160					
180	0,002	0,002	0,001	0,001	0,001
200	0,001	0,001			
220					
240					
260					
280	0	0	0	0	0
300	0,001	0,001			
320					
340					

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Performance
Point thermal transmittance

Annex C3

Table C4.1: Plate stiffness acc. to EOTA Technical Report TR 026 : 2016 – 05

Anchor type	Size of the anchor plate [mm]	Load resistance of the anchor plate [kN]	Plate stiffness [kN/mm]
termoz CN 8 termoz CN 8 R	60	1,7	0,6

Table C4.2: Displacements termoz CN 8 | termoz CN 8 R

Base material		termoz CN 8	termoz CN 8 R
		Tension load F [kN]	Displacements δ [mm]
Concrete $\geq$ C12/15 – C50/60 (EN 206-1:2000)		0,30	< 0,3
Clay brick (EN 771-1:2011), Mz 12		0,30	< 0,5
Calcium silicate solid bricks (EN 771-2:2011), KS 12		0,30	< 0,3
Vertically perforated clay brick (EN 771-1:2011), Hlz 12		0,2	< 0,2
Hollow calcium silicate brick (EN 771-2:2011), KSL 12		0,15	< 0,2
Hollow calcium silicate brick (EN 771-2:2011), KSL 20		0,25	< 0,3
Solid concrete blocks (EN 771-3:2011), Vbn 20		0,25	< 0,3
Hollow brick lightweight concrete (EN 771-3:2011), Hbl 4		0,2	< 0,2
Lightweight concrete solid blocks (EN 771-3:2011), Vbl 8		0,2	< 0,2
Lightweight aggregate concrete (EN 1520:2011, EN 771-3:2011)	LAC 4	0,15	< 0,3
	LAC 6	0,20	
Autoclaved aerated concrete blocks EN 771-4:2011	AAC 4	0,10	< 0,2
	AAC 6	0,13	< 0,3

Table C4.3: Displacements termoz CNplus 8

Base material		termoz CNplus 8	
		Tension load F [kN]	Displacements δ [mm]
Concrete $\geq$ C12/15 – C50/60 (EN 206-1:2000)		0,30	< 0,1
Weather resistant concrete shell $\geq$ C20/25 (EN 206-1:2000)		0,30	< 0,1
Clay brick (EN 771-1:2011), Mz 20		0,30	< 0,2
Calcium silicate solid bricks (EN 771-2:2011), KS 20		0,30	< 0,2
Solid concrete blocks (EN 771-3:2011), Vbn 20		0,30	< 0,2
Lightweight concrete solid blocks (EN 771-3:2011), Vbl 10		0,25	< 0,1
Vertically perforated clay brick (EN 771-1:2011), Hlz 48		0,25	< 0,2
Vertically perforated clay brick (EN 771-1:2011), Hlz 12		0,17	< 0,1
Hollow calcium silicate brick (EN 771-2:2011), KSL 16		0,17	< 0,1
Hollow brick lightweight concrete (EN 771-3:2011), Hbl 10		0,20	< 0,1
Lightweight aggregate concrete (EN 1520:2011, EN 771-3:2011)	LAC 6	0,13	< 0,2
Autoclaved aerated concrete blocks (EN 771-4:2011)	AAC 4	0,10	< 0,1

fischer termoz CN 8 | fischer termoz CN 8 R | fischer termoz CNplus 8

Performance
Plate stiffness
Displacements

Annex C4