



## DECLARATION OF PERFORMANCE

**DoP-0618-CPF-0019-002**

for fischer Crystal MS

EN

1. Unique identification code of the product-type: **DoP-0618-CPF-0019-002**
2. Intended use/es: **Sealents for façade elements, EN 15651-1:2012: F-EXT-INT (12,5P)  
Sealents for sanitary joints, EN 15651-3:2012: S (S1)**
3. Manufacturer: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Germany**
4. Authorised representative: **–**
5. System/s of AVCP: **System 3, Reaction to fire: System 3**
6. Harmonised standard: **EN 15651-1:2012, EN 15651-3:2012**  
Notified body/ies: **1292 - FUNDACION TECNALIA RESEARCH & INNOVATION**
7. Declared performance/s:

Conditioning: Procedure A  
Substrate: Glass (without primer)

| Essential characteristics*  | Performance | Harmonised technical specification |
|---|-------------|------------------------------------|
| (11) Reaction to fire   | Class E     | EN 15651-1:2012                    |
| (12) Release of chemical dangerous to the environment and health              | NPD (*)     |                                    |
| Water and air tightness   |             |                                    |
| (13) Resistance to flow   | < 3 mm      |                                    |
| (14) Loss of volume   | < 10 %      |                                    |
| (15) Tensile properties (i.e. elongation) after immersion in water (at 23 °C) | NPD         |                                    |
| (19) Durability   | Pass        |                                    |

Conditioning: Procedure B  
Substrate: Glass (without primer)

| Essential characteristics*  | Performance | Harmonised technical specification |
|---|-------------|------------------------------------|
| (31) Reaction to fire   | Class E     | EN 15651-3:2012                    |
| (32) Release of chemical dangerous to the environment and health                      | NPD (*)     |                                    |
| Water and air tightness   |             |                                    |
| (33) Resistance to flow   | < 3 mm      |                                    |
| (34) Loss of volume   | < 10 %      |                                    |
| (35) Tensile properties (i.e. elongation) after immersion in water at 23 °C (class S) | NPD         |                                    |
| (37) Microbiological growth   | 1           |                                    |
| (38) Durability   | Pass        |                                    |

\*Numbering system acc. to EN 15651 with FEICA classification (Publication ref.:POP-EX-J12-035).

(\*) See material safety data sheet.

**NPD = No Performance Determined**

**NF = No Failure**

**NR = Not required**



8. Appropriate Technical Documentation and/or  
Specific Technical Documentation:

-

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr.-Ing. Oliver Geibig, Managing Director Business Units & Engineering  
Tumlingen, 2019-10-01

Jürgen Grün, Managing Director Chemistry & Quality

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.