



DECLARATION OF PERFORMANCE

DoP-Seal-00005-03

for fischer DSSI EN

1. <u>Unique identification code of the product-type:</u> **DoP-Seal-00005-03**

2. Intended use/es: Sealents for façade elements, EN 15651-1:2012: F-EXT-INT-CC

Sealents for sanitary joints, EN 15651-3:2012: S (S1)

3. Manufacturer: fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Germany

4. Authorised representative:

5. System/s of AVCP: System 3, Reaction to fire: System 3

6. <u>Harmonised standard:</u> **EN 15651-1:2012, EN 15651-3:2012**

Notified body/ies: 1213 SKZ-Testings GmbH

7. Declared performance/s:

Essential characteristics*	Performance	Harmonised technical specification
(11) Reaction to fire	Class E	
(12) Release of chemical dangerous to the environment and health	evaluated	
Water and air tightness		•
(13) Resistance to flow	≤ 3 mm	EN 15651-1:2012
(14) Loss of volume	≤ 40 %	
(16) Tensile properties (i.e. elongation) at maintained extension after water immersion	NF	
(17) Tensile properties (i.e. secant modulus) for non-structural low modulus sealants used in joints in areas with cold climates (-30°C)	≤ 0,9 MPa	
(18) Tensile properties (i.e. at maintained extension) for non-structural sealants used in joints in areas with cold climate (-30°C)	NF	
(19) Durability	Pass	

Fischer DATA DOP_Sealants_V5.xlsm

1/2





Essential characteristics*	Performance	Harmonised technical specification
(31) Reaction to fire	Class E	
(32) Release of chemical dangerous to the environment and health	evaluated	
Water and air tightness		
(33) Resistance to flow	≤ 3 mm	EN 15651-3:2012
(34) Loss of volume	≤ 55 %	
(35) Tensile properties (i.e. elongation) after immersion in water at 23 °C (class S)	NF	
(37) Microbiological growth	0	
(38) Durability	Pass	

^{*}Numbering system acc. to EN 15651 with FEICA classification (Publication ref.:POP-EX-J12-035).

NPD = No Performance Determined

NF = No Failure

NR = Not required

8. Appropriate Technical Documentation and/or

Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr.-Ing. Oliver Geibig, Managing Director Business Units & Engineering

Tumlingen, 2022-01-11

Jürgen Grün, Managing Director Chemistry & Quality

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.

^(*) See material safety data sheet.