

DECLARATION OF PERFORMANCE

DoP No. 0756-CPD-0303 - EN

1. Unique identification code of the product-type:

Rebar connection with fischer injection mortar FIS V or FIS VS

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-08/0266, Annex 1 – 7

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Post-installed rebar connection
For use in	Normal weight concrete C 12/15 - C 50/60 (EN 206)
Loading	Static and quasi-static
Material	Reinforcing bars:
	Covered sizes: Reinforcing bars 8, 10, 12, 14, 16, 20, 25, 28
	Rebar anchor FRA:
	Internal and external use without particular aggressive conditions Covered sizes: FRA 12, FRA 16, FRA 20
	Rebar anchor FRA C:
	Internal and external use with particular aggressive conditions Covered sizes: FRA 12 C, FRA 16 C, FRA 20 C

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

fischerwerke GmbH & Co. KG, Otto-Hahn-Straße 15, 79211 Denzlingen, Germany

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): ---

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **1**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: ---

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Deutsches Institut für Bautechnik (DIBt) issued ETA-08/0266
on the basis of ETAG 001-1, ETAG 001-5; EOTA TR 023.

MPA Darmstadt 0756-CPD performed

- (i) determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- (ii) initial inspection of the manufacturing plant and of factory production control;
- (iii) continuous surveillance, assessment and evaluation of factory production control.

under system **1** and issued certificate of constancy of performance **0756-CPD-0303**.

9. Declared performance

Essential characteristics	Design Method	Performance	Harmonised technical specification
Characteristic resistance for tension	ETA-08/0266, 4.3	ETA-08/0266, Annex 11	ETAG 001-1
Minimum spacing and minimum edge distance	ETA-08/0266, 4.3	ETA-08/0266, Annex 5	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

i. V. W. Hengesbach *i. V. A. Bucher*

Wolfgang Hengesbach

Andreas Bucher

Dipl.-Ing., Dipl.-Wirtsch.-Ing.

Dipl.-Ing.

Zulassungen & Technische Dokumente

Forschung & Technologietransfer



Waldachtal, 2013-06-19