CE



DECLARATION OF PERFORMANCE

DoP-BS-004

for fischer FRS-CS EN

1. Unique identification code of the product- DoP-BS-004

2. Intended use/es: Anchorage products for the strengthening of concrete using reinforcement in construction and civil

engineering

3. Manufacturer: fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Germany

4. Authorised representative:

5. System of assessment and verification of System 2+ (for uses in buildings and civil engineering works)

constancy of performance: System 3 (for uses subject to reaction to fire regulations)

6. Harmonised standard: EN 1504-6:2006

Notified body/ies: 0921 - Qualitätsgemeinschaft Deutsche Bauchemie e.V. (QDB)

7. Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Pull-Out	≤ 0,6 mm	System 2+	EN 1504-6:2006
Chloride ion content	≤ 0,05 %		
Glass transition temperature	≥ 50 °C		
Reaction to fire	Class E	System 3	
Sustainability/Creep	≤ 0,6 mm	System 2+	
Dangerous substances	NPD (*)		

^(*) See material safety data sheet.

8. <u>Appropriate Technical Documentation</u> <u>and/or Specific Technical Documentation:</u>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr.-Ing. Ronald Mihala, Head of Development and Production Management

Tumlingen, 2024-09-16

Jürgen Grün, Managing Director Chemistry & Quality

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.

Fischer DATA DOP_BS_V5.xlsm 1/1