

## DECLARATION OF PERFORMANCE

**DoP-Seal-00015-03**  
for fischer Multi MS 80 ml

EN

- |   |  |
|---|--|
| 1. <u>Unique identification code of the product-type:</u>   | <b>DoP-Seal-00015-03</b>   |
| 2. <u>Intended use/es:</u>                                  | <b>Sealants for façade elements, EN 15651-1:2012: F-EXT-INT-CC (20HM)<br/>Sealants for sanitary joints, EN 15651-3:2012: XS3<br/>Sealants for pedestrian walkways, EN 15651-4:2012:EXT-INT-CC (20HM)</b> |
| 3. <u>Manufacturer:</u>                                     | <b>fischerwerke GmbH &amp; Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Germany</b>   |
| 4. <u>Authorised representative:</u>                        | –  |
| 5. <u>System/s of AVCP:</u>                                 | <b>System 3, Reaction to fire: System 3</b>  |
| 6. <u>Harmonised standard:</u><br><u>Notified body/ies:</u> | <b>EN 15651-1:2012<br/>1023 - ITC</b>  |
| 7. <u>Declared performance/s:</u>                           |  |
| Conditioning:   | Procedure B  |
| Substrate:  | aluminium  |

Essential characteristics*	Performance	Harmonised technical specification
(11) Reaction to fire	Class E	EN 15651-1:2012
(12) Release of chemical dangerous to the environment and health	NPD	
Water and air tightness		
(13) Resistance to flow	≤ 3 mm	
(14) Loss of volume	≤ 5 %	
(16) Tensile properties (i.e. elongation) at maintained extension after water immersion	NF	
(17) Tensile properties (i.e. secant modulus) for non-structural low modulus sealants used in joints in areas with cold climates (-30°C)	NR	
(18) Tensile properties (i.e. at maintained extension) for non-structural sealants used in joints in areas with cold climate (-30°C)	NF	
(19) Durability	Pass	

Conditioning:  
Substrate:

Procedure B  
aluminium

Essential characteristics*	Performance	Harmonised technical specification
(31) Reaction to fire	Class E	EN 15651-3:2012
(32) Release of chemical dangerous to the environment and health	NPD	
Water and air tightness		
(33) Resistance to flow	≤ 3 mm	
(34) Loss of volume	≤ 5 %	
(36) Tensile properties (i.e. elongation) at maintained extension after water immersion (class XS)	NF	
(37) Microbiological growth	3	
(38) Durability	Pass	

Conditioning:  
Substrate:

Procedure B  
aluminium

Essential characteristics*	Performance	Harmonised technical specification
(41) Reaction to fire	Class E	EN 15651-4:2012
(42) Release of chemical dangerous to the environment and health	NPD	
Water and air tightness		
(43) Tensile properties at maintained extension	NF	
(44) Loss of volume	≤ 5%	
(45) Tear resistance	NF	
(46) Adhesion- / Cohesion properties at maintained extension after 28 days water immersion	NF	
(47) Adhesion- / Cohesion properties at maintained extension after 28 days salt water immersion	NPD	
(48) Tensile properties (e.g. secant modulus) for use in cold climate areas (-30 ± 2) °C	NR	
(49) Tensile properties at maintained extension for use in cold climate areas at (-30 ± 2) °C	NF	
(410) Durability	Pass	

\*Numbering system acc. to EN 15651 with FEICA classification (Publication ref.:POP-EX-J12-035).

NPD = No Performance Determined  
NF = No Failure

NR = Not required

8. Appropriate Technical Documentation and/or  
Specific Technical Documentation: -

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Dr.-Ing. Oliver Geibig, Managing Director Business Units & Engineering  
Tumlingen, 2022-10-24



Jürgen Grün, Managing Director Chemistry & Quality

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.