

## DECLARATION OF PERFORMANCE

### DoP 0362

for fischer injection system fischer RM II (Bonded fastener for use in concrete)

EN

1. Unique identification code of the product-type: **DoP 0362**
2. Intended use/es: **Post-installed fastening in cracked or uncracked concrete, see appendix, especially annexes B1 - B7.**
3. Manufacturer: **fischerwerke GmbH & Co. KG, Otto-Hahn-Straße 15, 79211 Denzlingen, Germany**
4. Authorised representative: **-**
5. System/s of AVCP: **1**
6. European Assessment Document: **EAD 330499-01-0601, Edition 04/2020**  
European Technical Assessment: **ETA-16/0340; 2024-04-16**  
Technical Assessment Body: **DIBt- Deutsches Institut für Bautechnik**  
Notified body/ies: **2873 TU Darmstadt**
7. Declared performance/s:  
**Mechanical resistance and stability (BWR 1)**  
**Characteristic resistance to tension load (static and quasi-static loading):**  
Resistance to steel failure: Annexes C1, C2  
Resistance to combined pull- out and concrete cone failure: Annexes C4, C5  
Resistance to concrete cone failure: Annex C3  
Edge distance to prevent splitting under load: Annex C3  
Robustness: Annexes C3 - C5  
Maximum installation torque: Annexes B3, B4  
Minimum edge distance and spacing: Annexes B3, B4  
**Characteristic resistance to shear load (static and quasi-static loading):**  
Resistance to steel failure: Annexes C1, C2  
Resistance to pry-out failure: Annex C3  
Resistance to concrete edge failure: Annex C3  
**Displacements under short-term and long-term loading:**  
Displacements under short-term and long-term loading: Annex C6  
**Characteristic resistance and displacements for seismic performance categories C1 and C2:**  
Resistance to tension load, displacements, category C1: NPD  
Resistance to tension load, displacements, category C2: NPD  
Resistance to shear load, displacements, category C1: NPD  
Resistance to shear load, displacements, category C2: NPD  
Factor annular gap: NPD  
**Hygiene, health and the environment (BWR 3)**  
Content, emission and/or release of dangerous substances: NPD
8. Appropriate Technical Documentation and/or Specific Technical Documentation: **-**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Dr.-Ing. Oliver Geibig, Managing Director Business Units & Engineering  
Tumlingen, 2024-05-06



Jürgen Grün, Managing Director Chemistry & Quality

This DoP has been prepared in different languages. In case there is a dispute on the interpretation the English version shall always prevail.

The Appendix includes voluntary and complementary information in English language exceeding the (language-neutrally specified) legal requirements.

Translation guidance Essential Characteristics and Performance Parameters for Annexes

| Mechanical resistance and stability (BWR 1)   |   |   |
|---|---|---|
| Characteristic resistance to tension load (static and quasi-static loading):              |   |   |
| 1   | Resistance to steel failure:                                | $N_{Rk,s}$ [kN]   |
| 2   | Resistance to combined pull- out and concrete cone failure: | $T_{Rk}$ and/or $T_{Rk,100}$ [N/mm <sup>2</sup> ], $\psi_{sus}^0$ [-] (BF)<br>$N_{Rk,p}$ and/or $N_{Rk,p,100}$ [kN] (BEF)         |
| 3   | Resistance to concrete cone failure:                        | $c_{cr,N}$ [mm], $k_{cr,N}$ , $k_{ucr,N}$ [-]   |
| 4   | Edge distance to prevent splitting under load:              | $c_{cr,sp}$ [mm]  |
| 5   | Robustness:   | $\gamma_{inst}$ [-]   |
| 6   | Maximum installation torque:                                | max $T_{inst}$ [Nm] (BF)  |
|   | Installation torque:  | $T_{inst}$ [Nm] (BEF)   |
| 7   | Minimum edge distance and spacing:                          | $c_{min}$ , $s_{min}$ , $h_{min}$ [mm]  |
| Characteristic resistance to shear load (static and quasi-static loading):                |   |   |
| 8   | Resistance to steel failure:                                | $V_{Rk,s}^0$ [kN], $M_{Rk,s}^0$ [Nm], $k_7$ [-]   |
| 9   | Resistance to pry-out failure:                              | $k_8$ [-]   |
| 10  | Resistance to concrete edge failure:                        | $d_{nom}$ , $l_f$ [mm]  |
| Displacements under short-term and long-term loading:                                     |   |   |
| 11  | Displacements under short-term and long-term loading:       | $\delta_0$ , $\delta_\infty$ [mm or mm/(N/mm <sup>2</sup> )]  |
| Characteristic resistance and displacements for seismic performance categories C1 and C2: |   |   |
| 12  | Resistance to tension load, displacements:                  | C1<br>$N_{Rk,s,C1}$ [kN] (all)<br>$T_{Rk,C1}$ [N/mm <sup>2</sup> ] (BF)<br>$N_{Rk,p,C1}$ [kN] (BEF)                               |
|   |   | C2<br>$N_{Rk,s,C2}$ [kN] (all)<br>$T_{Rk,C2}$ [N/mm <sup>2</sup> ] (BF)<br>$N_{Rk,p,C2}$ [kN] (BEF)<br>$\delta_{N,C2}$ [mm] (all) |
| 13  | Resistance to shear load, displacements:                    | C1<br>$V_{Rk,s,C1}$ [kN] (all)  |
|   |   | C2<br>$V_{Rk,s,C2}$ [kN] (all)<br>$\delta_{V,C2}$ [mm] (all)  |
| 14  | Factor annular gap:   | $\alpha_{gap}$ [-]  |
| Hygiene, health and the environment (BWR 3)   |   |   |
| 15  | Content, emission and/or release of dangerous substances:   | -   |

## Specific Part

### 1 Technical description of the product

The fischer capsule system RM II is a bonded anchor for use in concrete consisting of a capsule RM II and a steel element according to Annex A2.

The capsule RM II is placed in the hole and the steel element is driven by machine with simultaneous hammering and turning.

The anchor rod is anchored via the bond between steel element, chemical mortar and concrete.

The product description is given in Annex A.

### 2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

### 3 Performance of the product and references to the methods used for its assessment

#### 3.1 Mechanical resistance and stability (BWR 1)

| Essential characteristic   | Performance                       |
|--|-----------------------------------|
| Characteristic resistance to tension load (static and quasi-static loading)              | See Annex B 3 and B 4, C 1 to C 5 |
| Characteristic resistance to shear load (static and quasi-static loading)                | See Annex C 1 to C 4              |
| Displacements under short-term and long-term loading                                     | See Annex C 6                     |
| Characteristic resistance and displacements for seismic performance categories C1 and C2 | No performance assessed           |

#### 3.2 Hygiene, health and the environment (BWR 3)

| Essential characteristic                                 | Performance             |
|--|-------------------------|
| Content, emission and/or release of dangerous substances | No performance assessed |

**4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base**


In accordance with the European Assessment Document EAD 330499-01-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1


## Installation conditions

### fischer anchor rod RG M; installation in concrete

Pre-positioned installation:




Pre-positioned installation with subsequently injected fischer filling disc:




### fischer internal threaded anchor RG M I; installation in concrete

Pre-positioned installation:



Pre-positioned installation with subsequently injected fischer filling disc:



Pictures not to scale

$h_0$  = drill hole depth

$h_{ef}$  = effective anchorage depth

$t_{fix}$  = thickness of fixture

fischer RM II

Product description  
Installation conditions

**Annex A 1**

Appendix 3 / 18

# Overview product components


## Capsule RM II

Size: 8, 10, 12, 16, 16E, 20/22, 24




## fischer anchor rod RG M

Size: M8, M10, M12, M16, M20, M24




## fischer internal threaded anchor RG M I


Size: M8, M10, M12, M16, M20




## Screw / threaded rod / washer / hexagon nut



## fischer filling disc with injection adapter



## fischer RM II – RG M Connector



Size: M8, M10, M12, M16, M20, M24

Pictures not to scale

fischer RM II

**Product description**  
Overview product components

**Annex A 2**

Appendix 4 / 18

**Table A3.1: Materials**

| Part | Designation   | Material   |  |  |
|------|---|--|--|--|
| 1    | Capsule RM II   | Mortar, hardener, filler   |  |  |
|      | Steel grade   | Steel  | Stainless steel<br>R   | High corrosion<br>resistant steel HCR  |
|      |   | zinc plated  | acc. to EN 10088-1:2014<br>Corrosion resistance class<br>CRC III acc. to<br>EN 1993-1-4:2006+A1:2015   | acc. to EN 10088-1:2014<br>Corrosion resistance class<br>CRC V acc. to<br>EN 1993-1-4:2006+A1:2015   |
| 2    | Anchor rod  | Property class<br>4.8, 5.8 or 8.8;<br>EN ISO 898-1:2013<br>zinc plated $\geq 5 \mu\text{m}$ ,<br>ISO 4042:2022<br>or hot dip galvanised<br>$\geq 40 \mu\text{m}$<br>EN ISO 10684:2004<br>$f_{uk} \leq 1000 \text{ N/mm}^2$ | Property class<br>50, 70 or 80<br>EN ISO 3506-1:2020<br>1.4401; 1.4404; 1.4578;<br>1.4571; 1.4439; 1.4362;<br>1.4062, 1.4662, 1.4462<br>EN 10088-1:2014<br>$f_{uk} \leq 1000 \text{ N/mm}^2$ | Property class<br>50 or 80<br>EN ISO 3506-1:2009<br>or property class 70 with<br>$f_{yk} = 560 \text{ N/mm}^2$<br>1.4565; 1.4529<br>EN 10088-1:2014<br>$f_{uk} \leq 1000 \text{ N/mm}^2$ |
|      |   | Fracture elongation $A_5 > 8 \%$ ,   |  |  |
| 3    | Washer<br>ISO 7089:2000   | zinc plated $\geq 5 \mu\text{m}$ ,<br>ISO 4042:2022<br>or hot dip galvanised<br>$\geq 40 \mu\text{m}$<br>EN ISO 10684:2004   | 1.4401; 1.4404;<br>1.4578; 1.4571; 1.4439;<br>1.4362<br>EN 10088-1:2014  | 1.4565; 1.4529<br>EN 10088-1:2014  |
| 4    | Hexagon nut   | Property class<br>4, 5 or 8;<br>EN ISO 898-2:2012<br>zinc plated $\geq 5 \mu\text{m}$ ,<br>ISO 4042:2022<br>or hot dip galvanised<br>$\geq 40 \mu\text{m}$<br>EN ISO 10684:2004  | Property class<br>50, 70 or 80<br>EN ISO 3506-2:2020<br>1.4401; 1.4404; 1.4578;<br>1.4571; 1.4439; 1.4362<br>EN 10088-1:2014   | Property class<br>50, 70 or 80<br>EN ISO 3506-2:2020<br>1.4565; 1.4529<br>EN 10088-1:2014  |
| 5    | fischer<br>internal threaded<br>anchor RG M I   | Property class<br>5.8<br>ISO 898-1:2013<br>zinc plated $\geq 5 \mu\text{m}$ ,<br>ISO 4042:2022   | Property class<br>70<br>EN ISO 3506-1:2020<br>1.4401; 1.4404; 1.4578;<br>1.4571; 1.4439; 1.4362<br>EN 10088-1:2014   | Property class<br>70<br>EN ISO 3506-1:2020<br>1.4565; 1.4529<br>EN 10088-1:2014  |
| 6    | Commercial standard<br>screw or threaded rod<br>for fischer internal<br>threaded anchor<br>RG M I | Property class<br>5.8 or 8.8;<br>EN ISO 898-1:2013<br>zinc plated $\geq 5 \mu\text{m}$ ,<br>ISO 4042:2022<br>fracture elongation<br>$A_5 > 8 \%$   | Property class<br>70<br>EN ISO 3506-1:2020<br>1.4401; 1.4404; 1.4578;<br>1.4571; 1.4439; 1.4362<br>EN 10088-1:2014<br>fracture elongation<br>$A_5 > 8 \%$                                    | Property class<br>70<br>EN ISO 3506-1:2020<br>1.4565; 1.4529<br>EN 10088-1:2014<br>fracture elongation<br>$A_5 > 8 \%$   |
| 7    | fischer filling disc<br>similar to DIN 6319-G   | zinc plated $\geq 5 \mu\text{m}$ ,<br>ISO 4042:2022<br>or hot dip galvanised<br>$\geq 40 \mu\text{m}$<br>EN ISO 10684:2004   | 1.4401; 1.4404;<br>1.4578; 1.4571; 1.4439;<br>1.4362<br>EN 10088-1:2014  | 1.4565; 1.4529<br>EN 10088-1:2014  |





fischer RM II

Product description  
Materials**Annex A 3**

Appendix 5 / 18

# Specifications of intended use part 1

**Table B1.1: Overview use and performance categories**

| Anchorages subject to   |                          | RM II with ...  |   |                     |                                      |
|---|--------------------------|---|---|---------------------|--------------------------------------|
|   |                          | fischer anchor rod<br>RG M<br> | fischer internal threaded anchor<br>RG M I<br> |                     |                                      |
| Hammer drilling with<br>standard drill bit<br>   |                          | Manual or<br>robotic-assisted by<br>fischer BauBot<br>all sizes   |   | Manual<br>all sizes |                                      |
| Hammer drilling<br>with hollow drill bit<br>(fischer „FHD“, Heller<br>"Duster Expert"; Bosch<br>„Speed Clean“; Hilti<br>"TE-CD, TE-YD",<br>DreBo „D-Plus“,<br>DreBo „D-Max“)<br> |                          | Nominal drill bit diameter<br>(d <sub>0</sub> ) 12 mm to 28 mm  |   | all sizes           |                                      |
| Static and quasi static<br>load, in   | uncracked concrete       | all sizes   | Tables:<br>C1.1, C3.1,<br>C4.1, C6.1  | all sizes           | Tables:<br>C2.1, C3.1,<br>C5.1, C6.2 |
|   | cracked concrete         | M10, M12, M16,<br>M20, M24  |   | all sizes           |                                      |
| Use<br>category   | I1 dry or wet concrete   | all sizes   |   | M8, M10, M16        |                                      |
|   | I2 flooded hole          | M12, M16, M20,<br>M24   |   |                     |                                      |
| Installation direction  |                          | D3 (downward and horizontal and upwards (e.g. overhead)<br>installation)  |   |                     |                                      |
| Installation<br>temperature   |                          | T <sub>i,min</sub> = -15 °C to T <sub>i,max</sub> = +40 °C  |   |                     |                                      |
| In-service<br>temperature   | Temperature range<br>I   | -40 °C to +40 °C  | (max. short term temperature +40 °C<br>max. long term temperature +24 °C)   |                     |                                      |
|   | Temperature range<br>II  | -40 °C to +80 °C  | (max. short term temperature +80 °C<br>max. long term temperature +50 °C)   |                     |                                      |
|   | Temperature range<br>III | -40 °C to +120 °C   | (max. short term temperature +120 °C<br>max. long term temperature +72 °C)  |                     |                                      |
| fischer RM II   |                          | <b>Annex B 1</b><br>Appendix 6 / 18   |   |                     |                                      |
| Intended Use<br>Specifications part 1   |                          |   |   |                     |                                      |



## Specifications of intended use part 2

### Base materials:

- Compacted reinforced or unreinforced normal weight concrete without fibres strength classes C20/25 to C50/60 according to EN 206:2013+A2:2021

### Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (zinc coated steel, stainless steel or high corrosion resistant steel)
- For all other conditions according to EN1993-1-4:2006 + A1:2015 corresponding to corrosion resistance classes to Annex A 3 table A3.1.

### Design:

- Anchorages have to be designed by a responsible engineer with experience of concrete anchor design.
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.).
- Anchorages are designed in accordance with: EN 1992-4:2018 and EOTA Technical Report TR 055, Edition February 2018.

### Installation:

- Anchor installation has to be carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site.
- For manual installation the anchorage depth should be marked and adhered to on installation.
- For robot-assisted installation using fischer BauBot, maintain the effective anchoring depth by selecting the appropriate installation program.
- Overhead installation is allowed.

fischer RM II

Intended Use  
Specifications part 2


**Annex B 2**

Appendix 7 / 18

**Table B3.1: Installation parameters for fischer anchor rods RG M**

| Anchor rods RG M   |                     | thread | M8                              | M10 | M12 | M16             | M20 | M24 |
|--|---------------------|--------|---------------------------------|-----|-----|-----------------|-----|-----|
| Nominal drill bit diameter   | $d_0$               | [mm]   | 10                              | 12  | 14  | 18              | 25  | 28  |
| Drill hole depth   | $h_0$               |        | $h_0 = h_{ef}$                  |     |     |                 |     |     |
| Effective embedment depth  | $h_{ef}$            |        | 80                              | 90  | 110 | 125             | 170 | 210 |
| Minimum spacing and minimum edge distance                          | $s_{min} = c_{min}$ |        | 40                              | 45  | 55  | 65              | 85  | 105 |
| Diameter of pre-positioned clearance hole in the fixture anchorage | $d_f$               |        | 9                               | 12  | 14  | 18              | 22  | 26  |
| Minimum thickness of concrete member                               | $h_{min}$           |        | $h_{ef} + 30$<br>( $\geq 100$ ) |     |     | $h_{ef} + 2d_0$ |     |     |
| Maximum installation torque  | $\max T_{inst}$     | [Nm]   | 10                              | 20  | 40  | 60              | 120 | 150 |

**fischer anchor rod RG M**




**Marking (on random place) fischer anchor rod RG M**

|  |        |  |   |
|--|--------|--|---|
| Steel zinc plated PC <sup>1)</sup> 8.8                 | • or + | Steel hot-dip PC <sup>1)</sup> 8.8                     | • |
| High corrosion resistant steel HCR PC <sup>1)</sup> 50 | •      | High corrosion resistant steel HCR PC <sup>1)</sup> 70 | - |
| High corrosion resistant steel HCR PC <sup>1)</sup> 80 | (      | Stainless steel R property class 50                    | ~ |
| Stainless steel R property class 80                    | *      |  |   |

Alternatively: Colour coding according to DIN 976-1:2016 <sup>1)</sup> PC = property class

**Installation conditions:**



Pictures not to scale

fischer RM II

**Intended Use**  
Installation parameters anchor rods RG M



**Annex B 3**

Appendix 8 / 18

**Table B4.1: Installation parameters for fischer internal threaded anchors RG M I**

| Internal threaded anchors RG M I                |                             | thread | M8                   | M10 | M12 | M16 | M20 |
|---|-----------------------------|--------|----------------------|-----|-----|-----|-----|
| Diameter of anchor                              | $d = d_H$                   | [mm]   | 12                   | 16  | 18  | 22  | 28  |
| Nominal drill bit diameter                      | $d_0$                       |        | 14                   | 18  | 20  | 24  | 32  |
| Drill hole depth                                | $h_0$                       |        | $h_0 = h_{ef} = L_H$ |     |     |     |     |
| Effective embedment depth<br>( $h_{ef} = L_H$ ) | $h_{ef}$                    |        | 90                   | 90  | 125 | 160 | 200 |
| Minimum spacing and<br>minimum edge distance    | $s_{min}$<br>=<br>$c_{min}$ |        | 55                   | 65  | 75  | 95  | 125 |
| Diameter of clearance hole in<br>the fixture    | $d_f$                       |        | 9                    | 12  | 14  | 18  | 22  |
| Minimum thickness<br>of concrete member         | $h_{min}$                   |        | 120                  | 125 | 165 | 205 | 260 |
| Maximum screw-in depth                          | $l_{E,max}$                 |        | 18                   | 23  | 26  | 35  | 45  |
| Minimum screw-in depth                          | $l_{E,min}$                 |        | 8                    | 10  | 12  | 16  | 20  |
| Maximum installation torque                     | $\max T_{inst}$             |        | [Nm]                 | 10  | 20  | 40  | 80  |


**fischer internal threaded anchor RG M I**



**Marking:** Anchor size e. g.: **M10**  
 Stainless steel → additional **R**; e.g.: **M10 R**  
 High corrosion resistant steel → additional **HCR**; e.g.: **M10 HCR**

Retaining bolt or threaded rods (including nut and washer) must comply with the appropriate material and strength class of Annex A 3, Table A3.1.

**Installation conditions:**



Pictures not to scale

fischer RM II


**Intended Use**  
 Installation parameters fischer internal threaded anchors RG M I

**Annex B 4**

Appendix 9 / 18

**Table B5.1: Dimensions of resin capsule RM II**

| Capsule RM II    |                | 8   | 10   | 12   | 16   | 16 E | 20/22 | 24  |
|------------------|----------------|-----|------|------|------|------|-------|-----|
| Capsule diameter | d <sub>P</sub> | 9,0 | 10,5 | 12,5 | 16,5 |      | 23,0  |     |
|                  | [mm]           |     |      |      |      |      |       |     |
| Capsule length   | L <sub>P</sub> | 85  | 90   | 97   | 95   | 123  | 160   | 190 |

**Table B5.2: Assignment of resin capsule RM II to fischer anchor rod RG M**

| Anchor rod RG M           |                 |      | M8 | M10 | M12 | M16 | M20   | M24 |
|---------------------------|-----------------|------|----|-----|-----|-----|-------|-----|
| Effective anchorage depth | h <sub>ef</sub> | [mm] | 80 | 90  | 110 | 125 | 170   | 210 |
| Related capsule RM II     |                 | [-]  | 8  | 10  | 12  | 16  | 20/22 | 24  |

**Table B5.3: Assignment of resin capsule RM II to the fischer internal threaded anchor RG M I**

| Internal threaded anchor RG M I |                 |      | M8 | M10 | M12 | M16 | M20 |
|---------------------------------|-----------------|------|----|-----|-----|-----|-----|
| Effective anchorage depth       | h <sub>ef</sub> | [mm] | 90 | 90  | 125 | 160 | 200 |
| Related capsule RM II           |                 | [-]  | 10 | 12  | 16  | 16E | 24  |

**Table B5.4: Minimum curing time**

(During the curing time of the mortar the concrete temperature may not fall below the listed minimum temperature; minimal capsule temperature -15 °C)

| Temperature in the anchoring base [°C] | Minimum curing time t <sub>ure</sub> |
|--|--------------------------------------|
| -15 to -10                             | 30 h                                 |
| > -10 to -5                            | 16 h                                 |
| > -5 to 0                              | 10 h                                 |
| > 0 to +5                              | 45 min                               |
| > +5 to +10                            | 30 min                               |
| > +10 to +20                           | 20 min                               |
| > +20 to +30                           | 5 min                                |
| > +30 to +40                           | 3 min                                |

fischer RM II

**Intended Use**


Dimensions of the capsules, Assignment of the capsule to the anchor rod and internal threaded anchor, Minimum curing time


**Annex B 5**

Appendix 10 / 18

## Installation instructions part 1


Manual or robotic-assisted, (by fischer BauBot), drilling and cleaning the hole (hammer drilling with standard drill bit)


|   |   |  |
|---|---|--|
| 1 |  | <p>Specified drill hole depth <math>h_0</math> should be adhered to (manual e.g. mark on the drill bit, with BauBot by selecting the appropriate drilling program).<br/>Drill the hole.<br/>Drill hole diameter <math>d_0</math> and drill hole depth <math>h_0</math> see <b>Tables B3.1, B4.1</b>.</p> |
|---|---|--|

|   |   |  |
|---|---|--|
| 2 |  | <p>When reaching the drill hole depth <math>h_0</math> pull out the drill bit whilst power drill is switched on. To reduce the drill dust in the drill hole repeat this step minimum <b>three times</b>, beginning from the drill hole bottom (discharging the bore hole).</p> <p>Trickling of the bore dust into the drill hole has to be avoided. (e.g. with exhausting the drill dust) Blowing out or brushing the drill hole is not necessary.</p> |
|---|---|--|

Go to step 3

## Manual drilling and cleaning the hole (hammer drilling with hollow drill bit)

|   |   |  |
|---|---|--|
| 1 |  | <p>Check a suitable hollow drill (see <b>Table B1.1</b>) for correct operation of the dust extraction.</p> |
|---|---|--|

|   |   |   |
|---|---|---|
| 2 |  | <p>Use a suitable dust extraction system, e.g. fischer FVC 35 M or a comparable dust extraction system with equivalent performance data.</p> <p>Drill the hole with hollow drill bit. The dust extraction system has to extract the drill dust nonstop during the drilling process and must be adjusted to maximum power. Diameter of drill hole <math>d_0</math> and drill hole depth <math>h_0</math> see <b>Tables B3.1, B4.1</b>.</p> |
|---|---|---|

Go to step 3

fischer RM II











**Intended use**  
Installation instructions part 1

**Annex B 6**

Appendix 11 / 18

## Installation instructions part 2

Installation of capsule RM II with fischer anchor rods RG M or fischer internal threaded anchors RG M I

|            |   |  |   |  |
|------------|---|--|---|--|
| 3          |    | <p>Push the capsule RM II into the drill hole.</p>   |   | <p>Depending on the anchor being installed, use a suitable setting tool (e.g. RA-SDS).</p> |
| 4          |    |   | <p>Only use clean and oil-free metal parts. Using a suitable adapter, drive the RG M or fischer internal threaded anchor RG M I into the capsule using a hammer drill set on rotary hammer action. Stop when the metal part reaches the bottom of the hole and is set to the correct embedment depth.</p> |  |
| Option 3+4 |    | <p>Combined setting method with fischer BauBot, capsule RM II and fischer anchor rod RG M.</p>   |   |  |
| 5          |   |    | <p>When reaching the correct embedment depth, excess mortar must be emerged from the mouth of the drill hole.</p>   |  |
| 6          |  |   | <p>Wait for the specified curing time, <math>t_{cure}</math> see <b>Table B5.4</b>.</p>   |  |
| Option     |  | <p>After the minimum curing time is reached, the gap between metal part and fixture (annular clearance) may be filled with mortar via the fischer filling disc. compressive strength <math>\geq 50 \text{ N/mm}^2</math> (e.g. fischer injection mortars FIS HB, FIS SB, FIS V Plus, FIS EM Plus).</p> |   |  |

fischer RM II

**Intended use**  
Installation instructions part 2

**Annex B 7**

Appendix 12 / 18

**Table C1.1: Characteristic values for steel failure under tension / shear load of fischer anchor rods RG M**

| Anchor rod RG M  |  | M8                 | M10  | M12                       | M16    | M20 | M24 |     |     |
|--|--|--------------------|------|---------------------------|--------|-----|-----|-----|-----|
| <b>Bearing capacity under tension load, steel failure<sup>3)</sup></b> |  |                    |      |                           |        |     |     |     |     |
| Characteristic resistance $N_{Rk,s}$                                   | Steel zinc plated  | Property class 4.8 | [kN] | 15(13)                    | 23(21) | 33  | 63  | 98  | 141 |
|  |  | 5.8                |      | 19(17)                    | 29(27) | 43  | 79  | 123 | 177 |
|  |  | 8.8                |      | 29(27)                    | 47(43) | 68  | 126 | 196 | 282 |
|  | Stainless steel R and high corrosion resistant steel HCR | 50                 |      | 19                        | 29     | 43  | 79  | 123 | 177 |
|  |  | 70                 |      | 26                        | 41     | 59  | 110 | 172 | 247 |
|  |  | 80                 |      | 30                        | 47     | 68  | 126 | 196 | 282 |
| <b>Partial factors<sup>1)</sup></b>                                    |  |                    |      |                           |        |     |     |     |     |
| Partial factor $\gamma_{Ms,N}$   | Steel zinc plated  | Property class 4.8 | [-]  | 1,50                      |        |     |     |     |     |
|  |  | 5.8                |      | 1,50                      |        |     |     |     |     |
|  |  | 8.8                |      | 1,50                      |        |     |     |     |     |
|  | Stainless steel R and high corrosion resistant steel HCR | 50                 |      | 2,86                      |        |     |     |     |     |
|  |  | 70                 |      | 1,50 <sup>2)</sup> / 1,87 |        |     |     |     |     |
|  |  | 80                 |      | 1,60                      |        |     |     |     |     |
| <b>Bearing capacity under shear load, steel failure<sup>3)</sup></b>   |  |                    |      |                           |        |     |     |     |     |
| <b>without lever arm</b>   |  |                    |      |                           |        |     |     |     |     |
| Characteristic resistance $V^0_{Rk,s}$                                 | Steel zinc plated  | Property class 4.8 | [kN] | 9(8)                      | 14(13) | 20  | 38  | 59  | 85  |
|  |  | 5.8                |      | 11(10)                    | 17(16) | 25  | 47  | 74  | 106 |
|  |  | 8.8                |      | 15(13)                    | 23(21) | 34  | 63  | 98  | 141 |
|  | Stainless steel R and high corrosion resistant steel HCR | 50                 |      | 9                         | 15     | 21  | 39  | 61  | 89  |
|  |  | 70                 |      | 13                        | 20     | 30  | 55  | 86  | 124 |
|  |  | 80                 |      | 15                        | 23     | 34  | 63  | 98  | 141 |
| Ductility factor   | $k_7$  | [-]                | 1,0  |                           |        |     |     |     |     |
| <b>with lever arm</b>  |  |                    |      |                           |        |     |     |     |     |
| Charact. resistance $M^0_{Rk,s}$                                       | Steel zinc plated  | Property class 4.8 | [Nm] | 15(13)                    | 30(27) | 52  | 133 | 259 | 448 |
|  |  | 5.8                |      | 19(16)                    | 37(33) | 65  | 166 | 324 | 560 |
|  |  | 8.8                |      | 30(26)                    | 60(53) | 105 | 266 | 519 | 896 |
|  | Stainless steel R and high corrosion resistant steel HCR | 50                 |      | 19                        | 37     | 65  | 166 | 324 | 560 |
|  |  | 70                 |      | 26                        | 52     | 92  | 232 | 454 | 784 |
|  |  | 80                 |      | 30                        | 60     | 105 | 266 | 519 | 896 |
| <b>Partial factors<sup>1)</sup></b>                                    |  |                    |      |                           |        |     |     |     |     |
| Partial factor $\gamma_{Ms,V}$   | Steel zinc plated  | Property class 4.8 | [-]  | 1,25                      |        |     |     |     |     |
|  |  | 5.8                |      | 1,25                      |        |     |     |     |     |
|  |  | 8.8                |      | 1,25                      |        |     |     |     |     |
|  | Stainless steel R and high corrosion resistant steel HCR | 50                 |      | 2,38                      |        |     |     |     |     |
|  |  | 70                 |      | 1,25 <sup>2)</sup> / 1,56 |        |     |     |     |     |
|  |  | 80                 |      | 1,33                      |        |     |     |     |     |

<sup>1)</sup> In absence of other national regulations

<sup>2)</sup> Only for fischer RG M made of high corrosion-resistant steel HCR

<sup>3)</sup> Values in brackets are valid for undersized fischer anchor rods RG M with smaller stress area  $A_s$  for hot dip galvanised standard threaded rods according to EN ISO 10684:2004+AC:2009

fischer RM II

**Performances**

Characteristic values for steel failure under tension / shear load of fischer anchor rods RG M

**Annex C 1**

Appendix 13 / 18

**Table C2.1: Characteristic values for steel failure under tension / shear load of fischer internal threaded anchors RG M I**

| Internal threaded anchor RG M I                           |                 |                   |     | M8   | M10  | M12  | M16  | M20  |      |
|---|-----------------|-------------------|-----|------|------|------|------|------|------|
| <b>Bearing capacity under tension load, steel failure</b> |                 |                   |     |      |      |      |      |      |      |
| Characteristic bearing capacity with screw                | $N_{Rk,s}$      | Property class    | 5.8 | [kN] | 19   | 29   | 43   | 79   | 123  |
|   |                 |                   | 8.8 |      | 29   | 47   | 68   | 108  | 179  |
|   |                 | Property class 70 | R   |      | 26   | 41   | 59   | 110  | 172  |
|   |                 |                   | HCR |      | 26   | 41   | 59   | 110  | 172  |
| <b>Partial safety factors<sup>1)</sup></b>                |                 |                   |     |      |      |      |      |      |      |
| Partial safety factor                                     | $\gamma_{Ms,N}$ | Property class    | 5.8 | [-]  | 1,50 |      |      |      |      |
|   |                 |                   | 8.8 |      | 1,50 |      |      |      |      |
|   |                 | Property class 70 | R   |      | 1,87 |      |      |      |      |
|   |                 |                   | HCR |      | 1,87 |      |      |      |      |
| <b>Bearing capacity under shear load, steel failure</b>   |                 |                   |     |      |      |      |      |      |      |
| <b>without lever arm</b>                                  |                 |                   |     |      |      |      |      |      |      |
| Characteristic bearing capacity with screw                | $V^0_{Rk,s}$    | Property class    | 5.8 | [kN] | 9,2  | 14,5 | 21,1 | 39,2 | 62,0 |
|   |                 |                   | 8.8 |      | 14,6 | 23,2 | 33,7 | 54,0 | 90,0 |
|   |                 | Property class 70 | R   |      | 12,8 | 20,3 | 29,5 | 54,8 | 86,0 |
|   |                 |                   | HCR |      | 12,8 | 20,3 | 29,5 | 54,8 | 86,0 |
| Ductility factor  |                 | $k_7$             | [-] | 1,0  |      |      |      |      |      |
| <b>with lever arm</b>                                     |                 |                   |     |      |      |      |      |      |      |
| Characteristic bending moment with screw                  | $M^0_{Rk,s}$    | Property class    | 5.8 | [Nm] | 20   | 39   | 68   | 173  | 337  |
|   |                 |                   | 8.8 |      | 30   | 60   | 105  | 266  | 519  |
|   |                 | Property class 70 | R   |      | 26   | 52   | 92   | 232  | 454  |
|   |                 |                   | HCR |      | 26   | 52   | 92   | 232  | 454  |
| <b>Partial safety factors<sup>1)</sup></b>                |                 |                   |     |      |      |      |      |      |      |
| Partial safety factor                                     | $\gamma_{Ms,V}$ | Property class    | 5.8 | [-]  | 1,25 |      |      |      |      |
|   |                 |                   | 8.8 |      | 1,25 |      |      |      |      |
|   |                 | Property class 70 | R   |      | 1,56 |      |      |      |      |
|   |                 |                   | HCR |      | 1,56 |      |      |      |      |

<sup>1)</sup> In absence of other national regulations

fischer RM II

**Performances**

Characteristic values for steel failure under tension / shear load of fischer internal threaded anchor RG M I

**Annex C 2**

Appendix 14 / 18



**Table C3.1: Characteristic values for concrete failure under tension / shear load**

| Size  |                          | All sizes   |   |                      |     |     |                                      |     |
|---|--------------------------|-------------|---|----------------------|-----|-----|--------------------------------------|-----|
| <b>Tension load</b>   |                          |             |   |                      |     |     |                                      |     |
| Installation factor   | $\gamma_{inst}$          | [-]         | See annex C 4 to C 5                                      |                      |     |     |                                      |     |
| <b>Factors for the compressive strength of concrete &gt; C20/25</b>                           |                          |             |   |                      |     |     |                                      |     |
| Increasing factor for $\tau_{RK}$<br>$\tau_{RK}(X/Y) = \Psi_c \cdot \tau_{RK}(C20/25)$        | C25/30                   | $\Psi_c$    | [-]   | 1,02                 |     |     |                                      |     |
|   | C30/37                   |             |   | 1,04                 |     |     |                                      |     |
|   | C35/45                   |             |   | 1,07                 |     |     |                                      |     |
|   | C40/50                   |             |   | 1,08                 |     |     |                                      |     |
|   | C45/55                   |             |   | 1,09                 |     |     |                                      |     |
|   | C50/60                   |             |   | 1,10                 |     |     |                                      |     |
| <b>Splitting failure</b>  |                          |             |   |                      |     |     |                                      |     |
| Edge distance   | $h / h_{ef} \geq 2,0$    | $C_{cr,sp}$ | [mm]  | 1,0 $h_{ef}$         |     |     |                                      |     |
|   | $2,0 > h / h_{ef} > 1,3$ |             |   | 4,6 $h_{ef}$ - 1,8 h |     |     |                                      |     |
|   | $h / h_{ef} \leq 1,3$    |             |   | 2,26 $h_{ef}$        |     |     |                                      |     |
| Spacing   | $S_{cr,sp}$              |             |   | 2 $C_{cr,sp}$        |     |     |                                      |     |
| <b>Concrete cone failure</b>  |                          |             |   |                      |     |     |                                      |     |
| Uncracked concrete  | $k_{ucr,N}$              | [-]         | 11,0  |                      |     |     |                                      |     |
| Cracked concrete  | $k_{cr,N}$               |             | 7,7   |                      |     |     |                                      |     |
| Edge distance   | $C_{cr,N}$               | [mm]        | 1,5 $h_{ef}$  |                      |     |     |                                      |     |
| Spacing   | $S_{cr,N}$               |             | 2 $C_{cr,N}$  |                      |     |     |                                      |     |
| <b>Factors for sustained tension load</b>   |                          |             |   |                      |     |     |                                      |     |
| Factor  | $\Psi_{sus}^0$           | [-]         | -1)   |                      |     |     |                                      |     |
| <b>Shear load</b>   |                          |             |   |                      |     |     |                                      |     |
| All installation conditions   | $\gamma_{inst}$          | [-]         | 1,0   |                      |     |     |                                      |     |
| <b>Concrete pry-out failure</b>   |                          |             |   |                      |     |     |                                      |     |
| Factor for pry-out failure  | $k_8$                    | [-]         | 2,0   |                      |     |     |                                      |     |
| <b>Concrete edge failure</b>  |                          |             |   |                      |     |     |                                      |     |
| Effective length of fastener in shear loading   | $l_f$                    | [mm]        | for $d_{nom} \leq 24$ mm: min ( $h_{ef}$ , 12 $d_{nom}$ ) |                      |     |     |                                      |     |
| <b>Calculation diameters</b>  |                          |             |   |                      |     |     |                                      |     |
| Size  |                          |             | M8  | M10                  | M12 | M16 | M20                                  | M24 |
| fischer anchor rods   | d                        | [mm]        | 8   | 10                   | 12  | 16  | 20                                   | 24  |
| fischer internal threaded anchors RG M I  | $d_{nom}$                |             | 12  | 16                   | 18  | 22  | 28                                   | -2) |
| <sup>1)</sup> No performance assessed<br><sup>2)</sup> Anchor type not part of the assessment |                          |             |   |                      |     |     |                                      |     |
| fischer RM II   |                          |             |   |                      |     |     | <b>Annex C 3</b><br>Appendix 15 / 18 |     |
| <b>Performances</b><br>Characteristic values for concrete failure under tensile / shear load  |                          |             |   |                      |     |     |                                      |     |

**Table C4.1: Characteristic values for combined pull-out and concrete failure for fischer anchor rods RG M in hammer drilled holes; uncracked or cracked concrete**

| Anchor rod RG M   |                     |                 | M8                   | M10             | M12             | M16  | M20  | M24  |      |
|---|---------------------|-----------------|----------------------|-----------------|-----------------|------|------|------|------|
| <b>Combined pullout and concrete cone failure</b>   |                     |                 |                      |                 |                 |      |      |      |      |
| Calculation diameter  | d                   | [mm]            | 8                    | 10              | 12              | 16   | 20   | 24   |      |
| <b>Uncracked concrete</b>   |                     |                 |                      |                 |                 |      |      |      |      |
| <b>Characteristic bond resistance in uncracked concrete C20/25</b>                        |                     |                 |                      |                 |                 |      |      |      |      |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete)</u> |                     |                 |                      |                 |                 |      |      |      |      |
| Tem-<br>perature<br>range   | I: 24 °C / 40 °C    | $\tau_{RK,ucr}$ | [N/mm <sup>2</sup> ] | 12,5            | 12,5            | 12,5 | 12,5 | 12,5 | 12,5 |
|   | II: 50 °C / 80 °C   |                 |                      | 12,0            | 12,0            | 12,0 | 12,0 | 12,0 | 12,0 |
|   | III: 72 °C / 120 °C |                 |                      | 10,5            | 10,5            | 10,5 | 10,5 | 10,5 | 10,5 |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)</u>         |                     |                 |                      |                 |                 |      |      |      |      |
| Tem-<br>perature<br>range   | I: 24 °C / 40 °C    | $\tau_{RK,ucr}$ | [N/mm <sup>2</sup> ] | - <sup>1)</sup> | - <sup>1)</sup> | 12,5 | 12,5 | 12,5 | 12,5 |
|   | II: 50 °C / 80 °C   |                 |                      | - <sup>1)</sup> | - <sup>1)</sup> | 12,0 | 12,0 | 12,0 | 12,0 |
|   | III: 72 °C / 120 °C |                 |                      | - <sup>1)</sup> | - <sup>1)</sup> | 10,5 | 10,5 | 10,5 | 10,5 |
| <b>Installation factors</b>   |                     |                 |                      |                 |                 |      |      |      |      |
| Dry and wet concrete  | $\gamma_{inst}$     | [-]             | 1,2                  |                 |                 |      |      |      |      |
| Flooded hole  |                     |                 | - <sup>1)</sup>      | - <sup>1)</sup> | 1,4             |      |      |      |      |
| <b>Cracked concrete</b>   |                     |                 |                      |                 |                 |      |      |      |      |
| <b>Characteristic bond resistance in cracked concrete C20/25</b>                          |                     |                 |                      |                 |                 |      |      |      |      |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete)</u> |                     |                 |                      |                 |                 |      |      |      |      |
| Tem-<br>perature<br>range   | I: 24 °C / 40 °C    | $\tau_{RK,cr}$  | [N/mm <sup>2</sup> ] | - <sup>1)</sup> | 4,5             | 4,5  | 4,5  | 4,5  | 4,5  |
|   | II: 50 °C / 80 °C   |                 |                      | - <sup>1)</sup> | 4,0             | 4,0  | 4,0  | 4,0  | 4,0  |
|   | III: 72 °C / 120 °C |                 |                      | - <sup>1)</sup> | 3,5             | 3,5  | 3,5  | 3,5  | 3,5  |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)</u>         |                     |                 |                      |                 |                 |      |      |      |      |
| Tem-<br>perature<br>range   | I: 24 °C / 40 °C    | $\tau_{RK,cr}$  | [N/mm <sup>2</sup> ] | - <sup>1)</sup> | - <sup>1)</sup> | 4,5  | 4,5  | 4,5  | 4,5  |
|   | II: 50 °C / 80 °C   |                 |                      | - <sup>1)</sup> | - <sup>1)</sup> | 4,0  | 4,0  | 4,0  | 4,0  |
|   | III: 72 °C / 120 °C |                 |                      | - <sup>1)</sup> | - <sup>1)</sup> | 3,5  | 3,5  | 3,5  | 3,5  |
| <b>Installation factors</b>   |                     |                 |                      |                 |                 |      |      |      |      |
| Dry and wet concrete  | $\gamma_{inst}$     | [-]             | - <sup>1)</sup>      | 1,2             |                 |      |      |      |      |
| Flooded hole  |                     |                 | - <sup>1)</sup>      | - <sup>1)</sup> | 1,4             |      |      |      |      |

<sup>1)</sup> No performance assessed

fischer RM II

**Performances**

Characteristic values for combined pull-out and concrete failure for fischer anchor rod RG M

**Annex C 4**

Appendix 16 / 18

**Table C5.1: Characteristic values for combined pull-out and concrete failure for fischer internal threaded anchors RG M I in hammer drilled holes; uncracked or cracked concrete**

| Internal threaded anchors RG M I   |                     |                 | M8                   | M10             | M12  | M16             | M20  |                 |
|--|---------------------|-----------------|----------------------|-----------------|------|-----------------|------|-----------------|
| <b>Combined pullout and concrete cone failure</b>                                  |                     |                 |                      |                 |      |                 |      |                 |
| Calculation diameter   | d                   | [mm]            | 12                   | 16              | 18   | 22              | 28   |                 |
| <b>Uncracked concrete</b>  |                     |                 |                      |                 |      |                 |      |                 |
| <b>Characteristic bond resistance in uncracked concrete C20/25</b>                 |                     |                 |                      |                 |      |                 |      |                 |
| Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete) |                     |                 |                      |                 |      |                 |      |                 |
| Temperature range  | I: 24 °C / 40 °C    | $\tau_{RK,ucr}$ | [N/mm <sup>2</sup> ] | 11              | 11   | 11              | 11   | 11              |
|  | II: 50 °C / 80 °C   |                 |                      | 10,5            | 10,5 | 10,5            | 10,5 | 10,5            |
|  | III: 72 °C / 120 °C |                 |                      | 9,5             | 9,5  | 9,5             | 9,5  | 9,5             |
| Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)         |                     |                 |                      |                 |      |                 |      |                 |
| Temperature range  | I: 24 °C / 40 °C    | $\tau_{RK,ucr}$ | [N/mm <sup>2</sup> ] | 11              | 11   | - <sup>1)</sup> | 11   | - <sup>1)</sup> |
|  | II: 50 °C / 80 °C   |                 |                      | 10,5            | 10,5 | - <sup>1)</sup> | 10,5 | - <sup>1)</sup> |
|  | III: 72 °C / 120 °C |                 |                      | 9,5             | 9,5  | - <sup>1)</sup> | 9,5  | - <sup>1)</sup> |
| <b>Installation factors</b>  |                     |                 |                      |                 |      |                 |      |                 |
| Dry and wet concrete   | $\gamma_{inst}$     | [-]             | 1,2                  |                 |      |                 |      |                 |
| Flooded hole   |                     |                 | 1,4                  | - <sup>1)</sup> | 1,4  | - <sup>1)</sup> |      |                 |
| <b>Cracked concrete</b>  |                     |                 |                      |                 |      |                 |      |                 |
| <b>Characteristic bond resistance in cracked concrete C20/25</b>                   |                     |                 |                      |                 |      |                 |      |                 |
| Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete) |                     |                 |                      |                 |      |                 |      |                 |
| Temperature range  | I: 24 °C / 40 °C    | $\tau_{RK,cr}$  | [N/mm <sup>2</sup> ] | 4,5             | 4,5  | 4,5             | 4,5  | 4,5             |
|  | II: 50 °C / 80 °C   |                 |                      | 4,0             | 4,0  | 4,0             | 4,0  | 4,0             |
|  | III: 72 °C / 120 °C |                 |                      | 3,5             | 3,5  | 3,5             | 3,5  | 3,5             |
| Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)         |                     |                 |                      |                 |      |                 |      |                 |
| Temperature range  | I: 24 °C / 40 °C    | $\tau_{RK,cr}$  | [N/mm <sup>2</sup> ] | 4,5             | 4,5  | - <sup>1)</sup> | 4,5  | - <sup>1)</sup> |
|  | II: 50 °C / 80 °C   |                 |                      | 4,0             | 4,0  | - <sup>1)</sup> | 4,0  | - <sup>1)</sup> |
|  | III: 72 °C / 120 °C |                 |                      | 3,5             | 3,5  | - <sup>1)</sup> | 3,5  | - <sup>1)</sup> |
| <b>Installation factors</b>  |                     |                 |                      |                 |      |                 |      |                 |
| Dry and wet concrete   | $\gamma_{inst}$     | [-]             | 1,2                  |                 |      |                 |      |                 |
| Flooded hole   |                     |                 | 1,4                  | - <sup>1)</sup> | 1,4  | - <sup>1)</sup> |      |                 |

<sup>1)</sup> No performance assessed

fischer RM II

**Performances**

Characteristic values for combined pull-out and concrete failure for fischer internal threaded anchors RG M I

**Annex C 5**

Appendix 17 / 18

**Table C6.1: Displacements for fischer anchor rods RG M**

| Anchor rod RG M  | M8                        | M10  | M12  | M16  | M20  | M24  |      |
|--|---------------------------|------|------|------|------|------|------|
| <b>Displacement-Factors for tension load<sup>1)</sup></b>          |                           |      |      |      |      |      |      |
| <b>Uncracked or cracked concrete; Temperature range I, II, III</b> |                           |      |      |      |      |      |      |
| $\delta_{N0}$ -Factor  | [mm/(N/mm <sup>2</sup> )] | 0,07 | 0,08 | 0,09 | 0,10 | 0,11 | 0,12 |
| $\delta_{N\infty}$ -Factor   |                           | 0,13 | 0,14 | 0,15 | 0,17 | 0,17 | 0,18 |
| <b>Displacement-Factors for shear load<sup>2)</sup></b>            |                           |      |      |      |      |      |      |
| <b>Uncracked or cracked concrete; Temperature range I, II, III</b> |                           |      |      |      |      |      |      |
| $\delta_{V0}$ -Factor  | [mm/kN]                   | 0,18 | 0,15 | 0,12 | 0,09 | 0,07 | 0,06 |
| $\delta_{V\infty}$ -Factor   |                           | 0,27 | 0,22 | 0,18 | 0,14 | 0,11 | 0,09 |

1) Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0}\text{-Factor} \cdot \tau$$

$$\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot \tau$$

( $\tau$ : acting bond strength under tension load)

2) Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V$$

$$\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V$$

( $V$ : acting shear load)

**Table C6.2: Displacements for fischer internal threaded anchors RG M I**

| Internal threaded anchor RG M I                                    | M8                        | M10  | M12  | M16  | M20  |      |
|--|---------------------------|------|------|------|------|------|
| <b>Displacement-Factors for tension load<sup>1)</sup></b>          |                           |      |      |      |      |      |
| <b>Uncracked or cracked concrete; Temperature range I, II, III</b> |                           |      |      |      |      |      |
| $\delta_{N0}$ -Factor  | [mm/(N/mm <sup>2</sup> )] | 0,09 | 0,10 | 0,10 | 0,11 | 0,19 |
| $\delta_{N\infty}$ -Factor   |                           | 0,13 | 0,15 | 0,15 | 0,17 | 0,19 |
| <b>Displacement-Factors for shear load<sup>2)</sup></b>            |                           |      |      |      |      |      |
| <b>Uncracked or cracked concrete; Temperature range I, II, III</b> |                           |      |      |      |      |      |
| $\delta_{V0}$ -Factor  | [mm/kN]                   | 0,12 | 0,09 | 0,08 | 0,07 | 0,05 |
| $\delta_{V\infty}$ -Factor   |                           | 0,18 | 0,14 | 0,12 | 0,10 | 0,08 |

1) Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0}\text{-Factor} \cdot \tau$$

$$\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot \tau$$

( $\tau$ : acting bond strength under tension load)

2) Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V$$

$$\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V$$

( $V$ : acting shear load)

fischer RM II

**Performances**

Displacements for anchor rods RGM and fischer internal threaded anchors RG M I

**Annex C 6**

Appendix 18 / 18