

DECLARATION OF PERFORMANCE

DoP No. 0756-CPD-0336 - EN

1. Unique identification code of the product-type:

fischer long shaft fixing SXR / SXRL

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-07/0121, Annex 1 – 3

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Plastic anchor for multiple use for non-structural applications
For use in	Normal weight concrete / Masonry walls
Option / category	ETAG 020 - Use category a, b, c, d (SXR 10, SXRL 10)
Loading	Static and quasi-static; Fire (TR020)
Material	Zinc-plated steel: Dry internal conditions only Covered sizes: SXR 8, SXR 10, SXRL 10
	Stainless steel (marking A4): Internal and external use without particular aggressive conditions Covered sizes: SXR 8, SXR 10, SXRL 10
temperature range	+ 30 °C / +50 °C; + 50 °C / +80 °C

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

fischerwerke GmbH & Co. KG, Weinhalde 14 - 18, 72178 Waldachtal, Germany

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): ---

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **2+**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: ---

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Deutsches Institut für Bautechnik (DIBt) issued ETA-07/0121

on the basis of ETAG 020. ETAG 020 - Use category a, b, c, d (SXR 10, SXRL 10)

MPA Darmstadt 0756-CPD performed

- (i) initial inspection of the manufacturing plant and of factory production control;
 - (ii) continuous surveillance, assessment and evaluation of factory production control.
- under system **2+** and issued certificate of constancy of performance **0756-CPD-0336**.


9. Declared performance


Essential characteristics	Design Method	Performance	Harmonised technical specification
Characteristic resistance for tension	ETAG 020 Annex C	ETA-07/0121, Annex 4 - 18, Annex 20 - 21	ETAG 020
Characteristic resistance for shear	ETAG 020 Annex C	ETA-07/0121, Annex 4 - 18, Annex 20 - 22	
Minimum spacing and minimum edge distance	ETAG 020 Annex C	ETA-07/0121, Annex 5, Annex 19, Annex 21	
Displacement for serviceability limit state	ETAG 020 Annex C	ETA-07/0121, Annex 5, Annex 21	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:


Wolfgang Hengesbach
Dipl.-Ing., Dipl.-Wirtsch.-Ing.
Technologietransfer / Zulassungen


Andreas Bucher
Dipl.-Ing.
Technologietransfer / Zulassungen



Waldachtal, 2013-06-28