

TELJESÍTMÉNYNYILATKOZAT

DoP 0196

mert fischer RM II (Ragasztott rögzítés betonban történő felhasználásra)

HU

| | | | |
|---|---|--|---|
| 1. <u>A terméktípus egyedi azonosító kódja:</u> | DoP 0196 | | |
| 2. <u>Felhasználás célja(i):</u> | Repedezett vagy repedésmentes betonba utólag beszerelhető rögzítőelem. | | |
| 3. <u>Gyártó:</u> | Id. a Mellékletet, különösen ezt a mellékletet B1- B7 fischerwerke GmbH & Co. KG, Otto-Hahn-Straße 15, 79211 Denzlingen, Németország | | |
| 4. <u>A meghatalmazott képviselő:</u> | – | | |
| 5. <u>Az AVCP-rendszer(ek):</u> | 1 | | |
| 6. <u>Az európai értékelési dokumentum:</u> | EAD 330499-01-0601 | | |
| Európai műszaki értékelés: | ETA-16/0340; 2020-06-17 | | |
| A műszaki értékelést végző szerv: | DIBt- Deutsches Institut für Bautechnik | | |
| Bejelentett szerv(ek): | 1343 MPA Darmstadt / 2873 TU Darmstadt | | |
| 7. <u>A nyilatkozatban szereplő teljesítmény(ek):</u> | | | |
| Mechanikus szilárdság és stabilitás (BWR 1) | | | |
| Karakterisztikus ellenállás húzásra (statikus és kvázi- statikus terhelések): | Ellenállás acél szakadás tönkremenetel esetén: Mellékletet C1, C2 Ellenállás kombinált beton szakadókúp – kihúzódás tönkremenetel esetén: Mellékletet C4, C5 | | $\tau_{Rk,100} = \text{NPD}$ $\psi_{sus} = \text{NPD}$ |
| | Ellenállás beton szakadókúp tönkremenetel esetén: Mellékletet C3 Peremtávolság hasadási tönkremenetel megelőzésére: Mellékletet C3 | | |
| | Ellenállóképesség: Mellékletet C3- C5 Maximális rögzítési nyomaték: Mellékletet B3, B4 | | |
| | Min. perem- és tengelytávolság: Mellékletet B3, B4 | | |
| Karakterisztikus ellenállás nyírásra (statikus és kvázi- statikus terhelések): | Ellenállás acél szakadás tönkremenetel esetén: Mellékletet C1, C2 Ellenállás pry-out tönkremenetel esetén: Mellékletet C3 Ellenállás beton kitérés tönkremenetel esetén: Mellékletet C3 | | |
| Karakterisztikus ellenállás és elmozdulások a C1 és C2 szeizmikus teljesítménykategóriákhoz: | Ellenállás húzó terhelés esetén, elmozdulások, Kategória C1: NPD Ellenállás húzó terhelés esetén, elmozdulások, Kategória C2: NPD Ellenállás nyíró terhelés esetén, elmozdulások, Kategória C1: NPD Ellenállás nyíró terhelés esetén, elmozdulások, Kategória C2: NPD Faktor Annuláris rés: NPD | | |
| Elmozdulások rövid és hosszú táv terhelés alatt: | Elmozdulások rövid és hosszú táv terhelés alatt: Mellékletet C6 | | |

Higiénia, egészség- és környezetvédelem (BWR 3)

Veszélyes anyagok tartalma, kibocsátása és / vagy kibocsátása: NPA



8. Megfelelő műszaki dokumentáció és/vagy egyedi műszaki dokumentáció: -

A fent azonosított termék teljesítménye megfelel a bejelentett teljesítmény(ek)nek. A 305/2011/EU rendeletnek megfelelően e teljesítménynyilatkozat kiadásáért kizárólag a fent meghatározott gyártó a felelős

A gyártó nevében és részéről aláíró személy:

ppa. Thilo P

Thilo Pregartner, Dr.-Ing.
Tumlingen, 2020-07-01

i.V. P. Sch

Peter Schillinger, Dipl.-Ing.

Ez a Teljesítmény nyilatkozat különböző nyelveken elkészült. Vitás értelmezés esetén az angol verzió az irányadó.

A melléklet a (nyelvsemleges formában megadott) törvényi előírásokon túl önkéntesen megadott, kiegészítő információkat is tartalmaz angolul.

Specific Part

1 Technical description of the product

The fischer capsule system RM II is a bonded anchor for use in concrete consisting of a capsule RM II and a steel element according to Annex A2.

The capsule RM II is placed in the hole and the steel element is driven by machine with simultaneous hammering and turning.

The anchor rod is anchored via the bond between steel element, chemical mortar and concrete.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

| Essential characteristic | Performance |
|--|-----------------------------------|
| Characteristic resistance to tension load (static and quasi-static loading) | See Annex B 3 and B 4, C 1 to C 5 |
| Characteristic resistance to shear load (static and quasi-static loading) | See Annex C 1 to C 4 |
| Displacements under short-term and long-term loading | See Annex C 6 |
| Characteristic resistance and displacements for seismic performance categories C1 and C2 | No performance assessed |

3.2 Hygiene, health and the environment (BWR 3)

| Essential characteristic | Performance |
|--|-------------------------|
| Content, emission and/or release of dangerous substances | No performance assessed |

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base


In accordance with the European Assessment Document EAD 330499-01-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1


Installation conditions

fischer anchor rod RG M; installation in concrete

Pre-positioned installation:




Pre-positioned installation with subsequently injected fischer filling disc:




fischer internal threaded anchor RG M I; installation in concrete

Pre-positioned installation:



Pre-positioned installation with subsequently injected fischer filling disc:



Pictures not to scale

h_0 = drill hole depth

h_{ef} = effective anchorage depth

t_{fix} = thickness of fixture

fischer RM II

Product description
Installation conditions

Annex A 1

Appendix 3/ 18

Overview product components


Capsule RM II

Size: 8, 10, 12, 16, 16E, 20/22, 24




fischer anchor rod RG M

Size: M8, M10, M12, M16, M20, M24




fischer internal threaded anchor RG M I


Size: M8, M10, M12, M16, M20



Screw / threaded rod / washer / hexagon nut



fischer filling disc with injection adapter



Pictures not to scale

fischer RM II

Product description
Overview product components

Annex A 2

Appendix 4/ 18





Table A3.1: Materials

| Part | Designation | Material | | |
|------|---|--|---|---|
| 1 | Capsule RM II | Mortar, hardener, filler | | |
| | Steel grade | Steel | Stainless steel R | High corrosion resistant steel HCR |
| | | zinc plated | acc. to EN 10088-1:2014 Corrosion resistance class CRC III acc. to EN 1993-1-4:2015 | acc. to EN 10088-1:2014 Corrosion resistance class CRC V acc. to EN 1993-1-4:2015 |
| 2 | Anchor rod | Property class 4.8, 5.8 or 8.8; EN ISO 898-1:2013 zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) or hot dip galvanised $\geq 40 \mu\text{m}$ EN ISO 10684:2004 $f_{uk} \leq 1000 \text{ N/mm}^2$ | Property class 50, 70 or 80 EN ISO 3506-1:2009 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; 1.4062, 1.4662, 1.4462 EN 10088-1:2014 $f_{uk} \leq 1000 \text{ N/mm}^2$ | Property class 50 or 80 EN ISO 3506-1:2009 or property class 70 with $f_{yk} = 560 \text{ N/mm}^2$ 1.4565; 1.4529 EN 10088-1:2014 $f_{uk} \leq 1000 \text{ N/mm}^2$ |
| | | Fracture elongation $A_5 > 8 \%$, | | |
| 3 | Washer ISO 7089:2000 | zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) or hot dip galvanised $\geq 40 \mu\text{m}$ EN ISO 10684:2004 | 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362 EN 10088-1:2014 | 1.4565; 1.4529 EN 10088-1:2014 |
| 4 | Hexagon nut | Property class 4, 5 or 8; EN ISO 898-2:2012 zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) or hot dip galvanised $\geq 40 \mu\text{m}$ EN ISO 10684:2004 | Property class 50, 70 or 80 EN ISO 3506-1:2009 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362 EN 10088-1:2014 | Property class 50, 70 or 80 EN ISO 3506-1:2009 1.4565; 1.4529 EN 10088-1:2014 |
| 5 | fischer internal threaded anchor RG M I | Property class 5.8 ISO 898-1:2013 zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) | Property class 70 EN ISO 3506-1:2009 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362 EN 10088-1:2014 | Property class 70 EN ISO 3506-1:2009 1.4565; 1.4529 EN 10088-1:2014 |
| 6 | Commercial standard screw or threaded rod for fischer internal threaded anchor RG M I | Property class 5.8 or 8.8; EN ISO 898-1:2013 zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) fracture elongation $A_5 > 8 \%$ | Property class 70 EN ISO 3506-1:2009 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362 EN 10088-1:2014 fracture elongation $A_5 > 8 \%$ | Property class 70 EN ISO 3506-1:2009 1.4565; 1.4529 EN 10088-1:2014 fracture elongation $A_5 > 8 \%$ |
| 7 | fischer filling disc similar to DIN 6319-G | zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) or hot dip galvanised $\geq 40 \mu\text{m}$ EN ISO 10684:2004 | 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362 EN 10088-1:2014 | 1.4565; 1.4529 EN 10088-1:2014 |

| | |
|---|------------------------------------|
| fischer RM II | Annex A 3 Appendix 5/ 18 |
| Product description Materials | |

Specifications of intended use (part 1)

Table B1.1: Overview use and performance categories

| Anchorages subject to | | RM II with ... | | | |
|--|------------------------|---|---|--------------|--------------------------------------|
| | | fischer anchor rod RG M  | fischer internal threaded anchor RG M I  | | |
| Hammer drilling with standard drill bit  | | all sizes | all sizes | | |
| Hammer drilling with hollow drill bit (fischer „FHD“, Heller "Duster Expert"; Bosch „Speed Clean“; Hilti "TE-CD, TE-YD", DreBo „D-Plus“, DreBo „D-Max“)  | | Nominal drill bit diameter (d ₀) 12 mm to 28 mm | | all sizes | |
| Static and quasi static load, in | uncracked concrete | all sizes | Tables: C1.1, C3.1, C4.1, C6.1 | all sizes | Tables: C2.1, C3.1, C5.1, C6.2 |
| | cracked concrete | M10, M12, M16, M20, M24 | | | |
| Use category | I1 dry or wet concrete | all sizes | | all sizes | |
| | I2 flooded hole | M12, M16, M20, M24 | | M8, M10, M16 | |
| Installation direction | | D3 (downward and horizontal and upwards (e.g. overhead) installation) | | | |
| Installation temperature | | $T_{i,min} = -15\text{ °C}$ to $T_{i,max} = +40\text{ °C}$ | | | |
| In-service temperature | Temperature range I | -40 °C to +40 °C | (max. short term temperature +40 °C and max. long term temperature +24 °C) | | |
| | Temperature range II | -40 °C to +80 °C | (max. short term temperature +80 °C and max. long term temperature +50 °C) | | |
| | Temperature range III | -40 °C to +120 °C | (max. short term temperature +120 °C and max. long term temperature +72 °C) | | |
| fischer RM II | | Annex B 1 Appendix 6/ 18 | | | |
| Intended Use Specifications (part 1) | | | | | |

Specifications of intended use (part 2)

Base materials:

- Compacted reinforced or unreinforced normal weight concrete without fibres strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (zinc coated steel, stainless steel or high corrosion resistant steel)
- For all other conditions according to EN1993-1-4:2015 corresponding to corrosion resistance classes to Annex A 3 table A3.1.

Design:

- Anchorages have to be designed by a responsible engineer with experience of concrete anchor design.
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.)
- Anchorages are designed in accordance with:
EN 1992-4:2018 and EOTA Technical Report TR 055, Edition February 2018.

Installation:

- Anchor installation has to be carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- In case of aborted hole: The hole shall be filled with mortar
- Anchorage depth should be marked and adhered to on installation
- Overhead installation is allowed

fischer RM II


Intended Use
Specifications (part 2)

Annex B 2

Appendix 7/ 18

Table B3.1: Installation parameters for fischer anchor rods RG M


| Anchor rods RG M | | thread | M8 | M10 | M12 | M16 | M20 | M24 |
|--|---------------------|--------|---------------------------------|-----|-----|-----------------|-----|-----|
| Width across flats | SW | [mm] | 13 | 17 | 19 | 24 | 30 | 36 |
| Nominal drill bit diameter | d_0 | | 10 | 12 | 14 | 18 | 25 | 28 |
| Drill hole depth | h_0 | | $h_0 = h_{ef}$ | | | | | |
| Effective embedment depth | h_{ef} | | 80 | 90 | 110 | 125 | 170 | 210 |
| Minimum spacing and minimum edge distance | $s_{min} = c_{min}$ | | 40 | 45 | 55 | 65 | 85 | 105 |
| Diameter of clearance hole in the pre-positioned anchorage fixture ¹⁾ | d_f | | 9 | 12 | 14 | 18 | 22 | 26 |
| Minimum thickness of concrete member | h_{min} | | $h_{ef} + 30$ (≥ 100) | | | $h_{ef} + 2d_0$ | | |
| Maximum installation torque | $\max T_{inst}$ | [Nm] | 10 | 20 | 40 | 60 | 120 | 150 |



Marking (on random place) fischer anchor rod RG M

| | | | |
|--|--------|--|---|
| Steel zinc plated PC ¹⁾ 8.8 | • or + | Steel hot-dip PC ¹⁾ 8.8 | • |
| High corrosion resistant steel HCR PC ¹⁾ 50 | • | High corrosion resistant steel HCR PC ¹⁾ 70 | - |
| High corrosion resistant steel HCR PC ¹⁾ 80 | (| Stainless steel R property class 50 | ~ |
| Stainless steel R property class 80 | * | | |

Alternatively: Colour coding according to DIN 976-1:2016 ¹⁾ PC = property class





| | |
|---|------------------------------------|
| fischer RM II | Annex B 3 Appendix 8/ 18 |
| Intended Use Installation parameters anchor rods RG M | |

Table B4.1: Installation parameters for **fischer internal threaded anchors RG M I**

| Internal threaded anchors RG M I | | thread | M8 | M10 | M12 | M16 | M20 |
|--|-----------------------------|--------|----------------------|-----|-----|-----|-----|
| Diameter of anchor | $d = d_H$ | [mm] | 12 | 16 | 18 | 22 | 28 |
| Nominal drill bit diameter | d_0 | | 14 | 18 | 20 | 24 | 32 |
| Drill hole depth | h_0 | | $h_0 = h_{ef} = L_H$ | | | | |
| Effective embedment depth ($h_{ef} = L_H$) | h_{ef} | | 90 | 90 | 125 | 160 | 200 |
| Minimum spacing and minimum edge distance | s_{min} = c_{min} | | 55 | 65 | 75 | 95 | 125 |
| Diameter of clearance hole in the fixture ¹⁾ | d_f | | 9 | 12 | 14 | 18 | 22 |
| Minimum thickness of concrete member | h_{min} | | 120 | 125 | 165 | 205 | 260 |
| Maximum screw-in depth | $l_{E,max}$ | | 18 | 23 | 26 | 35 | 45 |
| Minimum screw-in depth | $l_{E,min}$ | | 8 | 10 | 12 | 16 | 20 |
| Maximum installation torque | $\max T_{inst}$ | [Nm] | 10 | 20 | 40 | 80 | 120 |


fischer internal threaded anchor RG M I



Marking: Anchor size e. g.: **M10**
 Stainless steel → additional **R**; e.g.: **M10 R**
 High corrosion resistant steel → additional **HCR**; e.g.: **M10 HCR**

Retaining bolt or threaded rods (including nut and washer) must comply with the appropriate material and strength class of Annex A 3, Table A3.1.

Installation conditions:



Pictures not to scale

fischer RM II

Intended Use
 Installation parameters fischer internal threaded anchors RG M I

Annex B 4

Appendix 9/ 18

| Table B5.1: Dimensions of resin capsule RM II | | | | | | | | |
|--|-------|----------|-----------|-----------|-----------|-------------|--------------|-----------|
| Capsule RM II | | 8 | 10 | 12 | 16 | 16 E | 20/22 | 24 |
| Capsule diameter | d_P | [mm] | 9,0 | 10,5 | 12,5 | 16,5 | | 23,0 |
| Capsule length | L_P | | 85 | 90 | 97 | 95 | 123 | 160 |




Table B5.2: Assignment of resin capsule RM II to fischer anchor rod RG M

| Anchor rod RG M | | | M8 | M10 | M12 | M16 | M20 | M24 |
|---------------------------|----------|------|-----------|------------|------------|------------|------------|------------|
| Effective anchorage depth | h_{ef} | [mm] | 80 | 90 | 110 | 125 | 170 | 210 |
| Related capsule RM II | | [-] | 8 | 10 | 12 | 16 | 20/22 | 24 |

Table B5.3: Assignment of resin capsule RM II to the fischer internal threaded anchor RG M I

| Internal threaded anchor RG M I | | | M8 | M10 | M12 | M16 | M20 |
|--|----------|------|-----------|------------|------------|------------|------------|
| Effective anchorage depth | h_{ef} | [mm] | 90 | 90 | 125 | 160 | 200 |
| Related capsule RM II | | [-] | 10 | 12 | 16 | 16E | 24 |

Table B5.4: Minimum curing time



(During the curing time of the mortar the concrete temperature may not fall below the listed minimum temperature; minimal capsule temperature -15 °C)

| Concrete temperature [°C] | Minimum curing time t_{cure} |
|---------------------------|--------------------------------|
| -15 to -10 | 30 h |
| > -10 to -5 | 16 h |
| > -5 to 0 | 10 h |
| > 0 to 5 | 45 min |
| > 5 to 10 | 30 min |
| > 10 to 20 | 20 min |
| > 20 to 30 | 5 min |
| > 30 to 40 | 3 min |

| | |
|--|-------------------------------------|
| fischer RM II | Annex B 5 Appendix 10/ 18 |
| Intended Use Dimensions of the capsules, Assignment of the capsule to the anchor rod and internal threaded anchor, Minimum curing time | |



Installation instructions part 1

Drilling and cleaning the hole (hammer drilling with standard drill bit)

| | | |
|---|---|--|
| 1 |  | <p>Specified drill hole depth h_0 should be adhered to (e.g. mark on the drill bit). Drill the hole. Drill hole diameter d_0 and drill hole depth h_0 see Tables B3.1, B4.1</p> |
| 2 |  | <p>When reaching the drill hole depth h_0 pull out the drill bit whilst power drill is switched on. To reduce the drill dust in the drill hole repeat this step minimum three times, beginning from the drill hole bottom (discharging the bore hole)</p> <p>Trickling of the bore dust into the drill hole has to be avoided. (e.g. with exhausting the drill dust) Blowing out or brushing the drill hole is not necessary</p> |

Go to step 3

Drilling and cleaning the hole (hammer drilling with hollow drill bit)

| | | |
|---|---|---|
| 1 |  | <p>Check a suitable hollow drill (see Table B1.1) for correct operation of the dust extraction</p> |
| 2 |  | <p>Use a suitable dust extraction system, e.g. fischer FVC 35 M or a comparable dust extraction system with equivalent performance data</p> <p>Drill the hole with hollow drill bit. The dust extraction system has to extract the drill dust nonstop during the drilling process and must be adjusted to maximum power. Diameter of drill hole d_0 and drill hole depth h_0 see Tables B3.1, B4.1</p> |

Go to step 3

fischer RM II










Intended use
Installation instructions part 1

Annex B 6

Appendix 11/ 18

Installation instructions part 2

Installation of capsule RM II with fischer anchor rods RG M or fischer internal threaded anchors RG M I

| | | | |
|--------|---|--|--|
| 3 |  | <p>Push the capsule RM II into the drill hole</p> |  <p>Depending on the anchor being installed, use a suitable setting tool (e.g. RA-SDS)</p> |
| 4 |  |  | <p>Only use clean and oil-free metal parts. Using a suitable adapter, drive the RG M or fischer internal threaded anchor RG M I into the capsule using a hammer drill set on rotary hammer action. Stop when the metal part reaches the bottom of the hole and is set to the correct embedment depth</p> |
| 5 |  |  | <p>When reaching the correct embedment depth, excess mortar must be emerged from the mouth of the drill hole</p> |
| 6 |  |  | <p>Wait for the specified curing time, t_{cure} see Table B5.4</p> <p>Mounting the fixture max T_{inst} see Table B3.1, B4.1</p> |
| Option |  | <p>After the minimum curing time is reached, the gap between metal part and fixture (annular clearance) may be filled with mortar via the fischer filling disc. compressive strength $\geq 50 \text{ N/mm}^2$ (e.g. fischer injection mortars FIS HB, FIS SB, FIS V, FIS EM Plus)</p> | |

fischer RM II

Intended use
Installation instructions part 2

Annex B 7

Appendix 12/ 18

Table C1.1: Characteristic values for **steel failure** under tension / shear load of **fischer anchor rods RG M**

| Anchor rod RG M | | M8 | M10 | M12 | M16 | M20 | M24 | | | |
|--|--|----------------|------|--------|---------------------------|--------|-----|-----|-----|-----|
| Bearing capacity under tension load, steel failure³⁾ | | | | | | | | | | |
| Characteristic resistance $N_{Rk,s}$ | Steel zinc plated | Property class | [kN] | 4.8 | 15(13) | 23(21) | 33 | 63 | 98 | 141 |
| | | | | 5.8 | 19(17) | 29(27) | 43 | 79 | 123 | 177 |
| | 8.8 | | | 29(27) | 47(43) | 68 | 126 | 196 | 282 | |
| | Stainless steel R and high corrosion resistant steel HCR | | | 50 | 19 | 29 | 43 | 79 | 123 | 177 |
| | | | | 70 | 26 | 41 | 59 | 110 | 172 | 247 |
| | | | | 80 | 30 | 47 | 68 | 126 | 196 | 282 |
| Partial factors¹⁾ | | | | | | | | | | |
| Partial factor $\gamma_{Ms,N}$ | Steel zinc plated | Property class | [-] | 4.8 | 1,50 | | | | | |
| | | | | 5.8 | 1,50 | | | | | |
| | 8.8 | | | 1,50 | | | | | | |
| | Stainless steel R and high corrosion resistant steel HCR | | | 50 | 2,86 | | | | | |
| | | | | 70 | 1,50 ²⁾ / 1,87 | | | | | |
| | | | | 80 | 1,60 | | | | | |
| Bearing capacity under shear load, steel failure³⁾ | | | | | | | | | | |
| without lever arm | | | | | | | | | | |
| Characteristic resistance $V_{Rk,s}^0$ | Steel zinc plated | Property class | [kN] | 4.8 | 9(8) | 14(13) | 20 | 38 | 59 | 85 |
| | | | | 5.8 | 11(10) | 17(16) | 25 | 47 | 74 | 106 |
| | 8.8 | | | 15(13) | 23(21) | 34 | 63 | 98 | 141 | |
| | Stainless steel R and high corrosion resistant steel HCR | | | 50 | 9 | 15 | 21 | 39 | 61 | 89 |
| | | | | 70 | 13 | 20 | 30 | 55 | 86 | 124 |
| | | | | 80 | 15 | 23 | 34 | 63 | 98 | 141 |
| Ductility factor | k_7 | [-] | 1,0 | | | | | | | |
| with lever arm | | | | | | | | | | |
| Charact. resistance $M_{Rk,s}^0$ | Steel zinc plated | Property class | [Nm] | 4.8 | 15(13) | 30(27) | 52 | 133 | 259 | 448 |
| | | | | 5.8 | 19(16) | 37(33) | 65 | 166 | 324 | 560 |
| | 8.8 | | | 30(26) | 60(53) | 105 | 266 | 519 | 896 | |
| | Stainless steel R and high corrosion resistant steel HCR | | | 50 | 19 | 37 | 65 | 166 | 324 | 560 |
| | | | | 70 | 26 | 52 | 92 | 232 | 454 | 784 |
| | | | | 80 | 30 | 60 | 105 | 266 | 519 | 896 |
| Partial factors¹⁾ | | | | | | | | | | |
| Partial factor $\gamma_{Ms,V}$ | Steel zinc plated | Property class | [-] | 4.8 | 1,25 | | | | | |
| | | | | 5.8 | 1,25 | | | | | |
| | 8.8 | | | 1,25 | | | | | | |
| | Stainless steel R and high corrosion resistant steel HCR | | | 50 | 2,38 | | | | | |
| | | | | 70 | 1,25 ²⁾ / 1,56 | | | | | |
| | | | | 80 | 1,33 | | | | | |

¹⁾ In absence of other national regulations

²⁾ Only for fischer RG M made of high corrosion-resistant steel HCR

³⁾ Values in brackets are valid for undersized fischer anchor rods RG M with smaller stress area A_s for hot dip galvanised standard threaded rods according to EN ISO 10684:2004+AC:2009

fischer RM II

Performances

Characteristic values for steel failure under tension / shear load of fischer anchor rods RG M

Annex C 1

Appendix 13/ 18

Table C2.1: Characteristic values for **steel failure** under tension / shear load of **fischer internal threaded anchors RG M I**

| Internal threaded anchor RG M I | | | | M8 | M10 | M12 | M16 | M20 |
|---|----------------|----------------|------|------|------|------|------|------|
| Bearing capacity under tension load, steel failure | | | | | | | | |
| Characteristic bearing capacity with screw | Property class | 5.8 | [kN] | 19 | 29 | 43 | 79 | 123 |
| | | 8.8 | | 29 | 47 | 68 | 108 | 179 |
| | | R | | 26 | 41 | 59 | 110 | 172 |
| | | HCR | | 26 | 41 | 59 | 110 | 172 |
| Partial factors¹⁾ | | | | | | | | |
| Partial factor | Property class | 5.8 | [-] | 1,50 | | | | |
| | | 8.8 | | 1,50 | | | | |
| | | R | | 1,87 | | | | |
| | | HCR | | 1,87 | | | | |
| Bearing capacity under shear load, steel failure | | | | | | | | |
| without lever arm | | | | | | | | |
| Characteristic bearing capacity with screw | Property class | 5.8 | [kN] | 9,2 | 14,5 | 21,1 | 39,2 | 62,0 |
| | | 8.8 | | 14,6 | 23,2 | 33,7 | 54,0 | 90,0 |
| | | R | | 12,8 | 20,3 | 29,5 | 54,8 | 86,0 |
| | | HCR | | 12,8 | 20,3 | 29,5 | 54,8 | 86,0 |
| Ductility factor | | K ₇ | [-] | 1,0 | | | | |
| with lever arm | | | | | | | | |
| Characteristic bending moment with screw | Property class | 5.8 | [Nm] | 20 | 39 | 68 | 173 | 337 |
| | | 8.8 | | 30 | 60 | 105 | 266 | 519 |
| | | R | | 26 | 52 | 92 | 232 | 454 |
| | | HCR | | 26 | 52 | 92 | 232 | 454 |
| Partial factors¹⁾ | | | | | | | | |
| Partial factor | Property class | 5.8 | [-] | 1,25 | | | | |
| | | 8.8 | | 1,25 | | | | |
| | | R | | 1,56 | | | | |
| | | HCR | | 1,56 | | | | |

¹⁾ In absence of other national regulations

fischer RM II

Performances

Characteristic values for steel failure under tension / shear load of fischer internal threaded anchor RG M I

Annex C 2

Appendix 14/ 18

| Table C3.1: Characteristic values for concrete failure under tension / shear load | | | | | | | | | |
|---|--------------------------|-----------------|------------------|---|----------------------|-----|-------------------------------------|-----|-----------------|
| Size | | | All sizes | | | | | | |
| Tension load | | | | | | | | | |
| Installation factor | | γ_{inst} | [-] | See annex C 4 to C 5 | | | | | |
| Factors for the compressive strength of concrete > C20/25 | | | | | | | | | |
| Increasing factor for τ_{RK} | C25/30 | | Ψ_c | [-] | 1,02 | | | | |
| | C30/37 | | | | 1,04 | | | | |
| | C35/45 | | | | 1,07 | | | | |
| | C40/50 | | | | 1,08 | | | | |
| | C45/55 | | | | 1,09 | | | | |
| | C50/60 | | | | 1,10 | | | | |
| Splitting failure | | | | | | | | | |
| Edge distance | $h / h_{ef} \geq 2,0$ | | $C_{cr,sp}$ | [mm] | 1,0 h_{ef} | | | | |
| | $2,0 > h / h_{ef} > 1,3$ | | | | 4,6 h_{ef} - 1,8 h | | | | |
| | $h / h_{ef} \leq 1,3$ | | | | 2,26 h_{ef} | | | | |
| Spacing | | $S_{cr,sp}$ | | | 2 $C_{cr,sp}$ | | | | |
| Concrete cone failure | | | | | | | | | |
| Uncracked concrete | | $k_{ucr,N}$ | [-] | 11,0 | | | | | |
| Cracked concrete | | $k_{cr,N}$ | | 7,7 | | | | | |
| Edge distance | | $C_{cr,N}$ | [mm] | 1,5 h_{ef} | | | | | |
| Spacing | | $S_{cr,N}$ | | 2 $C_{cr,N}$ | | | | | |
| Factors for sustained tension load | | | | | | | | | |
| Factor | | Ψ_{sus}^0 | [-] | - ¹⁾ | | | | | |
| Shear load | | | | | | | | | |
| Installation factor | | γ_{inst} | [-] | 1,0 | | | | | |
| Concrete pry-out failure | | | | | | | | | |
| Factor for pry-out failure | | k_8 | [-] | 2,0 | | | | | |
| Concrete edge failure | | | | | | | | | |
| Effective length of fastener in shear loading | | l_f | [mm] | for $d_{nom} \leq 24$ mm: min (h_{ef} ; 12 d_{nom}) | | | | | |
| Calculation diameters | | | | | | | | | |
| Size | | | M8 | M10 | M12 | M16 | M20 | M24 | |
| fischer anchor rods | | d | [mm] | 8 | 10 | 12 | 16 | 20 | 24 |
| fischer internal threaded anchors RG M I | | d_{nom} | | 12 | 16 | 18 | 22 | 28 | - ²⁾ |
| ¹⁾ No performance assessed ²⁾ Anchor type not part of the assessment | | | | | | | | | |
| fischer RM II | | | | | | | Annex C 3 Appendix 15/ 18 | | |
| Performances Characteristic values for concrete failure under tensile / shear load | | | | | | | | | |

| Table C4.1: Characteristic values for combined pull-out and concrete failure for fischer anchor rods RG M in hammer drilled holes; uncracked or cracked concrete | | | | | | | | | |
|--|---------------------|-----------------|--------------------------------------|-----------------|-----------------|------------|-------------------------------------|------------|------|
| Anchor rod RG M | | | M8 | M10 | M12 | M16 | M20 | M24 | |
| Combined pullout and concrete cone failure | | | | | | | | | |
| Calculation diameter | | d | [mm] | 8 | 10 | 12 | 16 | 20 | 24 |
| Uncracked concrete | | | | | | | | | |
| Characteristic bond resistance in uncracked concrete C20/25 | | | | | | | | | |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete)</u> | | | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | | $\tau_{Rk,ucr}$ [N/mm ²] | 12,5 | 12,5 | 12,5 | 12,5 | 12,5 | 12,5 |
| | II: 80 °C / 50 °C | | | 12,0 | 12,0 | 12,0 | 12,0 | 12,0 | 12,0 |
| | III: 120 °C / 72 °C | | | 10,5 | 10,5 | 10,5 | 10,5 | 10,5 | 10,5 |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)</u> | | | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | | $\tau_{Rk,ucr}$ [N/mm ²] | - ¹⁾ | - ¹⁾ | 12,5 | 12,5 | 12,5 | 12,5 |
| | II: 80 °C / 50 °C | | | - ¹⁾ | - ¹⁾ | 12,0 | 12,0 | 12,0 | 12,0 |
| | III: 120 °C / 72 °C | | | - ¹⁾ | - ¹⁾ | 10,5 | 10,5 | 10,5 | 10,5 |
| Installation factors | | | | | | | | | |
| Dry and wet concrete | | γ_{inst} | [-] | 1,2 | | | | | |
| Flooded hole | | | | - ¹⁾ | - ¹⁾ | 1,4 | | | |
| Cracked concrete | | | | | | | | | |
| Characteristic bond resistance in cracked concrete C20/25 | | | | | | | | | |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete)</u> | | | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | | $\tau_{Rk,cr}$ [N/mm ²] | - ¹⁾ | 4,5 | 4,5 | 4,5 | 4,5 | 4,5 |
| | II: 80 °C / 50 °C | | | - ¹⁾ | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 |
| | III: 120 °C / 72 °C | | | - ¹⁾ | 3,5 | 3,5 | 3,5 | 3,5 | 3,5 |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)</u> | | | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | | $\tau_{Rk,cr}$ [N/mm ²] | - ¹⁾ | - ¹⁾ | 4,5 | 4,5 | 4,5 | 4,5 |
| | II: 80 °C / 50 °C | | | - ¹⁾ | - ¹⁾ | 4,0 | 4,0 | 4,0 | 4,0 |
| | III: 120 °C / 72 °C | | | - ¹⁾ | - ¹⁾ | 3,5 | 3,5 | 3,5 | 3,5 |
| Installation factors | | | | | | | | | |
| Dry and wet concrete | | γ_{inst} | [-] | - ¹⁾ | 1,2 | | | | |
| Flooded hole | | | | - ¹⁾ | - ¹⁾ | 1,4 | | | |
| ¹⁾ No performance assessed | | | | | | | | | |
| fischer RM II | | | | | | | Annex C 4 Appendix 16/ 18 | | |
| Performances Characteristic values for combined pull-out and concrete failure for fischer anchor rod RG M | | | | | | | | | |

Table C5.1: Characteristic values for **combined pull-out** and concrete failure for **fischer internal threaded anchors RG M I** in hammer drilled holes; **uncracked or cracked concrete**

| Internal threaded anchors RG M I | | | M8 | M10 | M12 | M16 | M20 |
|---|---------------------|--------------------------------------|------|------|-----------------|------|-----------------|
| Combined pullout and concrete cone failure | | | | | | | |
| Calculation diameter | d | [mm] | 12 | 16 | 18 | 22 | 28 |
| Uncracked concrete | | | | | | | |
| Characteristic bond resistance in uncracked concrete C20/25 | | | | | | | |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete)</u> | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | $\tau_{Rk,ucr}$ [N/mm ²] | 11 | 11 | 11 | 11 | 11 |
| | II: 80 °C / 50 °C | | 10,5 | 10,5 | 10,5 | 10,5 | 10,5 |
| | III: 120 °C / 72 °C | | 9,5 | 9,5 | 9,5 | 9,5 | 9,5 |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)</u> | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | $\tau_{Rk,ucr}$ [N/mm ²] | 11 | 11 | - ¹⁾ | 11 | - ¹⁾ |
| | II: 80 °C / 50 °C | | 10,5 | 10,5 | - ¹⁾ | 10,5 | - ¹⁾ |
| | III: 120 °C / 72 °C | | 9,5 | 9,5 | - ¹⁾ | 9,5 | - ¹⁾ |
| Installation factors | | | | | | | |
| Dry and wet concrete | γ_{inst} | [-] | 1,2 | | | | |
| Flooded hole | | | 1,4 | | - ¹⁾ | 1,4 | - ¹⁾ |
| Cracked concrete | | | | | | | |
| Characteristic bond resistance in cracked concrete C20/25 | | | | | | | |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (dry and wet concrete)</u> | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | $\tau_{Rk,cr}$ [N/mm ²] | 4,5 | 4,5 | 4,5 | 4,5 | 4,5 |
| | II: 80 °C / 50 °C | | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 |
| | III: 120 °C / 72 °C | | 3,5 | 3,5 | 3,5 | 3,5 | 3,5 |
| <u>Hammer-drilling with standard drill bit or hollow drill bit (flooded hole)</u> | | | | | | | |
| Tem- perature range | I: 40 °C / 24 °C | $\tau_{Rk,cr}$ [N/mm ²] | 4,5 | 4,5 | - ¹⁾ | 4,5 | - ¹⁾ |
| | II: 80 °C / 50 °C | | 4,0 | 4,0 | - ¹⁾ | 4,0 | - ¹⁾ |
| | III: 120 °C / 72 °C | | 3,5 | 3,5 | - ¹⁾ | 3,5 | - ¹⁾ |
| Installation factors | | | | | | | |
| Dry and wet concrete | γ_{inst} | [-] | 1,2 | | | | |
| Flooded hole | | | 1,4 | | - ¹⁾ | 1,4 | - ¹⁾ |

¹⁾ No performance assessed

fischer RM II

Performances

Characteristic values for combined pull-out and concrete failure for fischer internal threaded anchors RG M I

Annex C 5

Appendix 17/ 18

Table C6.1: Displacements for fischer anchor rods RG M

| Anchor rod RG M | M8 | M10 | M12 | M16 | M20 | M24 | |
|--|---------------------------|------|------|--|------|------|------|
| Displacement-Factors for tension load¹⁾ | | | | | | | |
| Uncracked or cracked concrete; Temperature range I, II, III | | | | | | | |
| δ_{N0} -Factor | [mm/(N/mm ²)] | 0,07 | 0,08 | 0,09 | 0,10 | 0,11 | 0,12 |
| $\delta_{N\infty}$ -Factor | | 0,13 | 0,14 | 0,15 | 0,17 | 0,17 | 0,18 |
| Displacement-Factors for shear load²⁾ | | | | | | | |
| Uncracked or cracked concrete; Temperature range I, II, III | | | | | | | |
| δ_{V0} -Factor | [mm/kN] | 0,18 | 0,15 | 0,12 | 0,09 | 0,07 | 0,06 |
| $\delta_{V\infty}$ -Factor | | 0,27 | 0,22 | 0,18 | 0,14 | 0,11 | 0,09 |
| 1) Calculation of effective displacement: $\delta_{N0} = \delta_{N0}\text{-Factor} \cdot \tau_{Ed}$ $\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot \tau_{Ed}$ (τ_{Ed} : Design value of the applied tensile stress) | | | | 2) Calculation of effective displacement: $\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V_{Ed}$ $\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V_{Ed}$ (V_{Ed} : Design value of the applied shear force) | | | |

Table C6.2: Displacements for fischer internal threaded anchors RG M I

| Internal threaded anchor RG M I | M8 | M10 | M12 | M16 | M20 | |
|--|---------------------------|------|--|------|------|------|
| Displacement-Factors for tension load¹⁾ | | | | | | |
| Uncracked or cracked concrete; Temperature range I, II, III | | | | | | |
| δ_{N0} -Factor | [mm/(N/mm ²)] | 0,09 | 0,10 | 0,10 | 0,11 | 0,19 |
| $\delta_{N\infty}$ -Factor | | 0,13 | 0,15 | 0,15 | 0,17 | 0,19 |
| Displacement-Factors for shear load²⁾ | | | | | | |
| Uncracked or cracked concrete; Temperature range I, II, III | | | | | | |
| δ_{V0} -Factor | [mm/kN] | 0,12 | 0,09 | 0,08 | 0,07 | 0,05 |
| $\delta_{V\infty}$ -Factor | | 0,18 | 0,14 | 0,12 | 0,10 | 0,08 |
| 1) Calculation of effective displacement: $\delta_{N0} = \delta_{N0}\text{-Factor} \cdot \tau_{Ed}$ $\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot \tau_{Ed}$ (τ_{Ed} : Design value of the applied tensile stress) | | | 2) Calculation of effective displacement: $\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V_{Ed}$ $\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V_{Ed}$ (V_{Ed} : Design value of the applied shear force) | | | |