



DICHIARAZIONE DI PRESTAZIONE



DoP: 00121

per ancorante con fascetta espandente fischer FAZ II (Tassello a espansione a coppia controllata) – IT

1. Codice di identificazione unico del prodotto-tipo: **DoP: 00121**

2. Usi previsti:

Fissaggio post-installato in calcestruzzo fessurato o non fessurato, vedere l'appendice, specialmente gli Annessi B 1 a B 6

3. Fabbricante: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Straße 1, 72178 Waldachtal, Germania**

4. Mandatario: --

5. Sistemi di VVCP: **1**

6. Documento per la valutazione europea: **EAD 330232-00-0601**

Valutazione tecnica europea: **ETA-05/0069; 2017-07-03**

Organismo di valutazione tecnica: **DIBt**

Organismi notificati: **1343 – MPA Darmstadt**

7. Prestazioni dichiarate:

Resistenza meccanica e stabilità (BWR 1),

- **Resistenza caratteristica per l'azione statica e quasi statica: Vedere appendice, specialmente Annessi C 1 a C 2**
- **Resistenza caratteristica per le categorie di prestazione sismica C1 e C2: Vedere l'appendice, specialmente l'Annesso C 4**
- **Spostamenti: Vedere l'appendice, specialmente l'Annesso C 5**

Sicurezza in caso di incendio (BWR 2)

- **Reazione al fuoco: Gli ancoraggi soddisfano i requisiti per la Classe A1**
- **Resistenza caratteristica sotto l'esposizione al fuoco: Vedere appendice, specialmente Annesso C 3**

8. Documentazione tecnica appropriata e/o documentazione tecnica specifica: ---

La prestazione del prodotto sopra identificato è conforme all'insieme delle prestazioni dichiarate. La presente dichiarazione di responsabilità viene emessa, in conformità al regolamento (UE) n. 305/2011, sotto la sola responsabilità del fabbricante sopra identificato.

Firmato a nome e per conto del fabbricante da:

Andreas Bucher, Dipl.-Ing.

Wolfgang Hengesbach, Dipl.-Ing., Dipl.-Wirtsch.-Ing.

Tumlingen, 2017-07-10

- Questa Dichiarazione di Prestazione (DoP) è stata preparata in diverse lingue. In caso di divergenza d'interpretazione avrà sempre prevalenza la versione inglese.
- L'appendice include informazioni volontarie e complementari in lingua inglese (lingua specificata neutrale) eccetto i requisiti di legge

Specific Part**1 Technical description of the product**

The fischer Bolt Anchor FAZ II is an anchor made of galvanised steel (FAZ II) or made of stainless steel (FAZ II A4) or high corrosion resistant steel (FAZ II C) which is placed into a drilled hole and anchored by torque-controlled expansion.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment**3.1 Mechanical resistance and stability (BWR 1)**

Essential characteristic	Performance
Characteristic resistance for static and quasi static action	See Annex C 1 and C 2
Characteristic resistance for seismic performance categories C1 and C2	See Annex C 4
Displacements	See Annex C 5

3.2 Safety in case of fire (BWR 2)


Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for Class A1
Characteristic resistance under fire exposure	See Annex C 3

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base


In accordance with EAD 330232-00-0601, the applicable European legal act is: [96/582/EC].

The system to be applied is: 1



Cone bolt manufactured by cold - forming:



Cone bolt manufactured by turning:



- ① Expansion sleeve
- ② Cone bolt (cold – formed or turned)
- ③ Washer
- ④ Hexagon nut
- ⑤ fischer FAZ II dome nut




(Fig. not to scaled)

fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Product description
Installed condition

Annex A 1

Product label and letter-code:



Product label, example:

FAZ II 12/30 A4

Brand | type of fastener
placed at marking area 2 or marking area 3

Thread size / max. thickness of the fixture (t_{fix})
identification A4 or C placed at marking area 2

FAZ II: carbon steel, galvanized

FAZ II A4: stainless steel

FAZ II C: high corrosion resistant steel

Table A2.1: Letter - code at marking area 1:

Marking		(a)	(b)	(c)	(d)	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(K)
Max. t _{fix}		5	10	15	20	5	10	15	20	25	30	35	40	45	50
B ≥ [mm]	M6	-				45	50	55	60	65	70	75	80	85	90
	M8	40	45	-		50	55	60	65	70	75	80	85	90	95
	M10	45	50	55	60	65	70	75	80	85	90	95	100	105	110
	M12	55	60	65	70	75	80	85	90	95	100	105	110	115	120
	M16	70	75	80	85	90	95	100	105	110	115	120	125	130	135
	M20	-				105	110	115	120	125	130	135	140	145	150
	M24					130	135	140	145	150	155	160	165	170	175
Marking		(L)	(M)	(N)	(O)	(P)	(R)	(S)	(T)	(U)	(V)	(W)	(X)	(Y)	(Z)
Max. t _{fix}		60	70	80	90	100	120	140	160	180	200	250	300	350	400
B ≥ [mm]	M6	100	110	120	130	140	160	180	200	220	240	290	340	390	440
	M8	105	115	125	135	145	165	185	205	225	245	295	345	395	445
	M10	120	130	140	150	160	180	200	220	240	260	310	360	410	460
	M12	130	140	150	160	170	190	210	230	250	270	320	370	420	470
	M16	145	155	165	175	185	205	225	245	265	285	335	385	435	485
	M20	160	170	180	190	200	220	240	260	280	300	350	400	450	500
	M24	185	195	205	215	225	245	265	285	305	325	375	425	475	525

Calculation existing h_{ef} for installed fasteners:

$$\text{existing } h_{ef} = B_{(\text{according to table A2.1})} - \text{existing } t_{fix}$$

Thickness of the fixture t_{fix} including thickness of fastener plate t and e.g. thickness of grout layer t_{grout}
or other non-structural layers

(Fig. not to scaled)

fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Product description

Product label and letter code

Annex A 2

Product dimensions




Table A3.1: Dimensions [mm]

Part	Designation			FAZ II, FAZ II A4, FAZ II C						
				M6	M8	M10	M12	M16	M20	M24
1	Expansion sleeve	Sheet thickness		0,8	1,3	1,4	1,6	2,4		3,0
2	Cone bolt	Thread size M		6	8	10	12	16	20	24
		L _G		10	19	26	31	40	50	57
3	Washer	t _s	≥	1,4		1,8	2,3	2,7		3,7
		Ø d _s		11	15	19	23	29	36	43
4 & 5	Hexagon nut / fischer FAZ II dome nut	Wrench size		10	13	17	19	24	30	36
5		L _D	≥	-		22	27	33	-	
6	fischer filling disc FFD	t	=	6				7	8	10

(Fig. not to scaled)

fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Product description
Dimensions


Annex A 3

Specifications of intended use							
Anchorages subject to:							
Size	FAZ II, FAZ II A4, FAZ II C						
	M6	M8	M10	M12	M16	M20	M24
Static and quasi-static loads	✓						
Cracked and uncracked concrete							
Fire exposure							
Seismic performance category	C1	-	✓				
	C2 ¹⁾	-	✓			-	
¹⁾ FAZ II C: Only valid for cold-formed version (according to Annex A1)							
Base materials: - Reinforced and unreinforced normal weight concrete (cracked and uncracked) according to EN 206-1: 2000 - Strength classes C20/25 to C50/60 according to EN 206-1: 2000							
Use conditions (Environmental conditions): - Structures subject to dry internal conditions (FAZ II, FAZ II A4, FAZ II C) - Structures subject to external atmospheric exposure (including industrial and marine environment) and to permanently damp internal condition, if no particular aggressive conditions exist (FAZ II A4, FAZ II C) - Structures subject to external atmospheric exposure and permanently damp internal condition, if other particular aggressive conditions exist (FAZ II C)							
Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where deicing materials are used)							
Design: - Anchorages are to be designed under the responsibility of an engineer experienced in anchorages and concrete work - Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.) - Design of fastenings according to FprEN 1992-4: 2016 and EOTA Technical Report TR 055 - For effective embedment depth $h_{ef} < 40$ mm and $h_{min} \geq 80$ mm and < 100 mm only statically indeterminate fixings (e.g. light-weight suspended ceilings with internal exposure) are covered by the ETA							
fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C						Annex B 1	
Intended Use Specifications							

Table B2.1: Installation parameters

Size	FAZ II, FAZ II A4, FAZ II C						
	M6	M8	M10	M12	M16	M20	M24
Nominal drill hole diameter $d_0 =$	6	8	10	12	16	20	24
Maximum bit diameter with hammer or hollow drilling $d_{cut,max}$ [mm]	6,40	8,45	10,45	12,5	16,5	20,55	24,55
Maximum bit diameter with diamond drilling	-	8,15		12,25	16,45	20,50	24,40
Overall fastener embedment depth in the concrete $h_{nom} \geq (L)$ [mm]	46,5 (6,5)	44,5 (9,5)	52,0 (12)	63,5 (13,5)	82,5 (17,5)	120 (20)	148,5 (23,5)
Depth of drill hole to deepest point $h_1 \geq$	Existing $h_{ef} + L = h_{nom}$ $h_{nom} + 5$					$h_{nom} + 10$	
Diameter of clearance hole in the fixture $d_f \leq$ [mm]	7	9	12	14	18	22	26
Required setting torque $T_{inst} =$ [Nm]	8	20	45	60	110	200	270
Excess length after hammering-in the cone bolt (for fischer dome nut applications according to Annex B6) $O =$ [mm]	-		12	16	20	-	

Setting gauge FAZ II SL-H
for anchor with fischer FAZ II dome nut:



- h_{ef} = Effective embedment depth
 t_{fix} = Thickness of the fixture
 h_1 = Depth of drill hole to deepest point
 h = Thickness of the concrete member
 h_{min} = Minimum thickness of concrete member
 h_{nom} = Overall fastener embedment depth in the concrete
 T_{inst} = Required setting torque

(Fig. not to scaled)


fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Intended Use
Installation parameters


Annex B 2

Table B3.1: Minimum thickness of concrete members, minimum spacing and minimum edge distance

Size		FAZ II, FAZ II A4, FAZ II C						
		M6	M8	M10	M12	M16	M20	M24
Minimum edge distance								
Uncracked concrete	c_{min}	45	40	45	55	65	95	135
Cracked concrete							85	100
Minimum spacing	s_{min} [mm]	according to Annex B4						
Minimum thickness of concrete member	h_{min}	80			100	140	160	200
Thickness of concrete member	$h \geq$	max. $\{h_{min}; h_1^{(1)} + 30\}$				max. $\{h_{min}; h_1^{(1)} + 2 \cdot d_o\}$		
Minimum spacing								
Uncracked concrete	s_{min}	35	40	40	50	65	95	100
Cracked concrete			35					
Minimum edge distance	c_{min} [mm]	according to Annex B4						
Minimum thickness of concrete member	h_{min}	80			100	140	160	200
Thickness of concrete member	$h \geq$	max. $\{h_{min}; h_1^{(1)} + 30\}$				max. $\{h_{min}; h_1^{(1)} + 2 \cdot d_o\}$		
Minimal splitting area								
Uncracked concrete	$A_{sp,req}$ [$\cdot 1000$ mm ²]	5,1	18	37	54	67	100	117,5
Cracked concrete		1,5	12	27	40	50	77	87,5
¹⁾ h_1 according to Annex B2 Splitting failure applied for minimum edge distance and spacing in dependence of the h_{ef} For the calculation of minimum spacing and minimum edge distance of anchors in combination with different embedment depths and thicknesses of concrete members the following equation shall be fulfilled: $A_{sp,req} < A_{sp,ef}$ $A_{sp,req}$ = required splitting area $A_{sp,ef}$ = effective splitting area (according to Annex B4)								
fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C						Annex B 3		
Intended Use Minimum thickness of member, minimum spacing and edge distance								

Table B4.1: Effective splitting area $A_{sp,ef}$ with member thickness $h > h_{ef} + 1,5 \cdot c$ and $h \geq h_{min}$


Single anchor and group of anchors with $s > 3 \cdot c$	$A_{sp,ef} = (6 \cdot c) \cdot (h_{ef} + 1,5 \cdot c)$	[mm ²]	with $c \geq c_{min}$
Group of anchors with $s \leq 3 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot (h_{ef} + 1,5 \cdot c)$	[mm ²]	with $c \geq c_{min}$ and $s \geq s_{min}$

Table B4.2: Effective splitting area $A_{sp,ef}$ with member thickness $h \leq h_{ef} + 1,5 \cdot c$ and $h \geq h_{min}$


Single anchor and group of anchors with $s > 3 \cdot c$	$A_{sp,ef} = 6 \cdot c \cdot \text{existing } h$	[mm ²]	with $c \geq c_{min}$
Group of anchors with $s \leq 3 \cdot c$	$A_{sp,ef} = (3 \cdot c + s) \cdot \text{existing } h$	[mm ²]	with $c \geq c_{min}$ and $s \geq s_{min}$

Edge distance and axial spacing shall be rounded to at least 5 mm

(Fig. not to scaled)

fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Annex B 4

Intended Use






Minimum thickness of member, minimum spacings and edge distances

Installation instructions:

- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Use of the anchor only as supplied by the manufacturer without exchanging the components of the anchor
Exception: fischer FAZ II dome nut.
- Checking before placing the anchor to ensure that the strength class of the concrete in which the anchor is to be placed is in the range given and is not lower than that of the concrete to which the characteristic loads apply
- Check of concrete being well compacted, e.g. without significant voids
- Hammer, hollow or diamond drilling according to Annex B5
- Drill hole created perpendicular $\pm 5^\circ$ to concrete surface, positioning without damaging the reinforcement
- In case of aborted hole: new drilling at a minimum distance twice the depth of the aborted drill hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application
- It must be ensured that in case of fire local spalling of the concrete cover does not occur
- Fastenings in stand-off installation or with a grout layer under seismic action are not covered
- In case of seismic applications the fastener shall be positioned outside of critical regions (e.g. plastic hinges) of the concrete structure

Installation instructions: Drilling and cleaning the hole

Types of drills and cleaning

Hammer drill			
		1: Drill the hole	2: Clean the hole
Hollow drill			-
		1: Drill the hole with automatic cleaning	
Diamond drill, for non seismic applications only and $\geq$ drill $\varnothing 8$			
		1: Drill the hole	2: Clean the hole


fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Annex B 5



Intended Use
Installation instructions

Installation instructions: Installation of the anchor

HEXAGON NUT:




3: Set the fastener

4: Apply T_{inst} 


5: Installed fastener

fischer FAZ II DOME NUT:


Option 1: Push through installation with setting gauge SL-H:





3: Set the fastener using setting gauge



4: Check offset




5: Turn on the washer and fischer FAZ II dome nut


6: Apply T_{inst} 

7: Installed fastener


Option 2: Push through installation with hexagon nut:



3: Set the fastener



4: check setting position: Visible one turn of a thread





4.1: Remove nut

fischer FILLING DISC FFD optional for seismic C2 application or minimizing the annular gap:

Optional

The gap between bolt and fixture may be filled with mortar (compressive strength $\geq 50 \text{ N/mm}^2$ e.g. FIS SB) after step 7 (for eliminating the annular gap).
The filling disc is additional to the standard washer.
The thickness of the filling disc must be considered for definition of t_{fix} .
Countersunk of the filling disc in direction to the anchor plate.



fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Intended Use
Installation instructions

Annex B 6

Table C1.1: Characteristic **tension** resistance under static and quasi-static action

Size				FAZ II, FAZ II A4, FAZ II C								
				M6	M8		M10	M12	M16	M20	M24	
Steel failure												
Characteristic resistance	FAZ II	$N_{Rk,s}$	[kN]	7,6	16,6		28,3	43,2	67,0	123,3	176,7	
	FAZ II A4/C			11,4	17,0		29,0	44,3	70,6	124,9	183,6	
Partial factor for steel failure			γ_{Ms} ¹⁾	1,5								
Pullout failure												
Effective embedment depth for calculation			h_{ef}	[mm]	40	35 - < 45	45	40 - 60	50 - 70	65 - 85	100	125
Characteristic resistance in cracked concrete C20/25			$N_{Rk,p}$	[kN]	1,5	5,5	8	13	20	- ²⁾		
Characteristic resistance in uncracked concrete C20/25					10,5	14		20	22			
Increasing factors for $N_{Rk,p}$ for cracked and uncracked concrete			ψ_c	C25/30	1,12							
				C30/37	1,22							
				C35/45	1,32							
				C40/50	1,41							
				C45/55	1,50							
				C50/60	1,58							
Installation sensitivity factor			γ_{inst}	1,0								
Concrete cone and splitting failure												
Factor for uncracked concrete			$k_1 = k_{ucr,N}$	[-]	11,0 ³⁾							
Factor for cracked concrete			$k_1 = k_{cr,N}$		7,7 ³⁾							
Characteristic spacing			$s_{cr,N}$	[mm]	$3 \cdot h_{ef}$							
Characteristic edge distance			$c_{cr,N}$		$1,5 \cdot h_{ef}$							
Spacing			$s_{cr,sp}$	$2 \cdot c_{cr,sp}$								
Edge distance for h = 80			$c_{cr,sp}$	[mm]	40	$2,4 \cdot h_{ef}$	$2 \cdot h_{ef}$	-	-			
Edge distance for h = 100							$2,4 \cdot h_{ef}$	$2 \cdot h_{ef}$				
Edge distance for h = 120							$1,9 \cdot h_{ef}$	$2,1 \cdot h_{ef}$				
Edge distance for h = 140								$1,5 \cdot h_{ef}$				$2 \cdot h_{ef}$
Edge distance for h = 160							$2,4 \cdot h_{ef}$	-				
Edge distance for h = 200								$2,2 \cdot h_{ef}$				
¹⁾ In absence of other national regulations ²⁾ Pullout failure not relevant ³⁾ Based on concrete strength as cylinder strength												
fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C										Annex C 1		
Performances Characteristic values of resistance under tension loads												

Table C2.1: Characteristic values of **shear** resistance under static and quasi-static action

Size			FAZ II, FAZ II A4, FAZ II C						
			M6	M8	M10	M12	M16	M20	M24
Steel failure without lever arm									
Characteristic resistance	FAZ II	$V_{Rk,s}$ [kN]	5,9	13,6	21,4	30,6	55,0	81,4	110,1
	FAZ II A4/C		8,8	16,8	26,5	38,3	69,8	106,3	148,5
Partial factor for steel failure	$\gamma_{Ms}^{1)}$	[-]	1,25						
Factor for ductility	k_7		1,0						
Steel failure with lever arm and Concrete pryout failure									
Effective embedment depth for calculation	h_{ef} [mm]		40	45	60	70	85	100	125
Characteristic bending resistance	FAZ II	$M_{Rk,s}^0$ [Nm]	11,4	26	52	92	233	513	865
	FAZ II A4/C		10,7	29	59	100	256	519	898
Factor for pryout failure	k_8 [-]		2,6	2,8	3,2	3,0	2,6	2,4	
Effective embedment depth for calculation	h_{ef} [mm]	-		35 - < 45	40 - < 60	50 - < 70	65 - < 85		-
Characteristic bending resistance	FAZ II			20	44	92	184		
	FAZ II A4/C			21	45	100	193		
Factor for pryout failure	k_8 [-]			2,5	2,6	3,1	3,2		
Partial factor for steel failure	$\gamma_{Ms}^{1)}$	[-]	1,25						
Factor for ductility	k_7		1,0						
Concrete edge failure									
Effective embedment depth for calculation	$l_f =$ [mm]	h_{ef}							
Outside diameter of a fastener	d_{nom}		6	8	10	12	16	20	24
¹⁾ In absence of other national regulations									
fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C							Annex C 2		
Performances									
Characteristic values of resistance under shear loads									

Table C3.1: Characteristic values of tension resistance under fire exposure

Size		FAZ II, FAZ II A4, FAZ II C						
		M6	M8	M10	M12	M16	M20	M24
	$h_{ef} \geq$ [mm]	40	35 / 45	40 / 60	50 / 70	65 / 85	100	125
Characteristic resistance steel failure	$N_{Rk,s,fi}$ R30	0,6 ¹⁾ / 0,9 ²⁾	1,4	2,8	5,0	9,4	14,7	21,1
	R60	0,4 ¹⁾ / 0,9 ²⁾	1,2	2,3	4,1	7,7	12,0	17,3
	R90	0,3 ¹⁾ / 0,9 ²⁾	0,9	1,9	3,2	6,0	9,4	13,5
	R120	0,2 ¹⁾ / 0,7 ²⁾	0,8	1,6	2,8	5,2	8,1	11,6
Characteristic resistance Concrete cone failure	$N_{Rk,c,fi}$ R30 - R90	$7,7 \cdot h_{ef}^{1,5} \cdot (20)^{0,5} \cdot h_{ef} / 200 / 1000$						
	R120	$7,7 \cdot h_{ef}^{1,5} \cdot (20)^{0,5} \cdot h_{ef} / 200 / 1000 \cdot 0,8$						
Characteristic resistance pullout failure	$N_{Rk,p,fi}$ R30	0,4	0,9 / 2,0	2,2 / 3,3	3,0 / 5,0	4,5 / 6,8	8,6	12,0
	R60		0,8 / 2,0					
	R90		0,5 / 2,0					
	R120	0,3	0,3 / 1,6	1,7 / 2,6	2,4 / 4,0	3,6 / 5,4	6,9	9,6

Table C3.2: Characteristic values of shear resistance under fire exposure

Size FAZ II, FAZ II A4, FAZ II C		R30		R60	
		$V_{Rk,s,fi,30}$ [kN]	$M^0_{Rk,s,fi,30}$ [Nm]	$V_{Rk,s,fi,60}$ [kN]	$M^0_{Rk,s,fi,60}$ [Nm]
M6	$h_{ef} \geq$	40	0,6 ¹⁾ / 0,9 ²⁾	0,5 ¹⁾ / 0,2 ²⁾	0,4 ¹⁾ / 0,9 ²⁾
M8		35	1,8	1,4	1,2
M10		40	3,6	2,9	3,0
M12		50	6,3	7,8	6,4
M16		65	11,7	19,9	16,3
M20		100	18,2	39,0	31,8
M24		125	26,3	67,3	55,0
M24		125	26,3	67,3	55,0

Size FAZ II, FAZ II A4, FAZ II C		R90		R120	
		$V_{Rk,s,fi,90}$ [kN]	$M^0_{Rk,s,fi,90}$ [Nm]	$V_{Rk,s,fi,120}$ [kN]	$M^0_{Rk,s,fi,120}$ [Nm]
M6	$h_{ef} \geq$	40	0,3 ¹⁾ / 0,9 ²⁾	0,2 ¹⁾ / 0,1 ²⁾	0,2 ¹⁾ / 0,1 ²⁾
M8		35	1,3	1,0	0,8
M10		40	2,2	2,4	2,1
M12		50	3,5	5,0	4,3
M16		65	6,6	12,6	11,0
M20		100	10,3	24,6	21,4
M24		125	14,8	42,6	37,0
M24		125	14,8	42,6	37,0

Concrete pryout failure according to EN 1992-4

Table C3.3: Minimum spacings and minimum edge distances of anchors under fire exposure for tension and shear load

Size		FAZ II, FAZ II A4, FAZ II C						
		M6	M8	M10	M12	M16	M20	M24
Spacing	s_{min}	Annex B3						
Edge distance	c_{min} [mm]	$c_{min} = 2 \cdot h_{ef}$ for fire exposure from more than one side $c_{min} \geq 300$ mm						

¹⁾ FAZ II gvz²⁾ FAZ II A4 / C

fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Performances
Characteristic values of resistance under fire exposure

Annex C 3

Table C4.1: Characteristic values of tension and shear resistance under seismic action category C1

Size	FAZ II, FAZ II A4, FAZ II C						
	M6	M8	M10	M12	M16	M20	M24
Length of anchor $L_{\max}$	-	167	186	221	285	394	477
Effective embedment depth h_{ef} [mm]		45	40 - 60	50 - 70	65 - 85	100	125
Steel failure							
Characteristic resistance tension load C1 $N_{Rk,s,C1}$ [kN]	-	16,0	27,0	41,0	66,0	111,0	150,0
Partial factor for steel failure $\gamma_{Ms,C1}^{1)}$ [-]		1,5					
Pullout failure							
Characteristic resistance tension load in cracked concrete C1 $N_{Rk,p,C1}$ [kN]	-	4,6	8,0	16,0	28,2	36,0	50,3
Installation sensitivity factor γ_{inst} [-]		1,0					
Steel failure without lever arm							
Characteristic resistance shear load C1 $V_{Rk,s,C1}$ [kN]	-	11	17	27	47	56	69
Partial factor for steel failure $\gamma_{Ms,C1}^{1)}$ [-]		1,25					

¹⁾ In absence of other national regulations

$N_{Rk,eq} = N_{Rk,C1}$ for all failures

Table C4.2: Characteristic values of tension and shear resistance under seismic action category C2

Size		FAZ II, FAZ II A4, FAZ II C ¹⁾						
		M6	M8	M10	M12	M16	M20	M24
Length of anchor L _{max} [mm]		-		186	221	285	394	-
Steel failure								
Characteristic resistance tension load C2 N _{Rk,s,C2} [kN]		-		27	41	66	111	-
Partial factor for steel failure γ _{Ms,C2} ²⁾ [-]				1,5				
Pullout failure								
Characteristic resistance tension load in cracked concrete C2	h _{ef} [mm]	-		60	70	85	100	-
	N _{Rk,p,C2} [kN]			5,1	7,4	21,5	30,7	
	h _{ef} [mm]			40-59	50-69	65-84	-	
	N _{Rk,p,C2} [kN]			2,7	4,4	16,4		
Installation sensitivity factor γ _{inst} [-]		1,0						
Steel failure without lever arm								
Characteristic resistance shear load C2	h _{ef} [mm]	-		60	70	85	100	-
	V _{Rk,s,C2} [kN]			10,0	17,4	27,5	39,9	
	h _{ef} [mm]			40-59	50-69	65-84	-	
	V _{Rk,s,C2} [kN]			7,0	12,7	22,0		
Partial factor for steel failure γ _{Ms,C2} ²⁾ [-]		1,25						

¹⁾ FAZ II C: Only valid for cold-formed version (according to Annex A1)

²⁾ In absence of other national regulations

$N_{Rk,eq} = N_{Rk,C1}$ for all failures

fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Performances
Characteristic values of resistance under tension and shear loads under seismic action

Annex C 4

Table C5.1: Displacements under static and quasi static **tension** loads

Size	FAZ II, FAZ II A4, FAZ II C						
	M6	M8	M10	M12	M16	M20	M24
Displacement – factor for tensile load¹⁾							
δ_{N0} - factor	0,13	0,22	0,12	0,09	0,08	0,07	0,05
	1,00	0,78	0,40	0,19	0,09		0,07
$\delta_{N\infty}$ - factor	0,16	0,07	0,05	0,06		0,05	0,04
	0,24	0,29	0,21	0,14	0,10	0,06	0,05

Table C5.2: Displacements under static and quasi static **shear** loads

Size	FAZ II						
	M6	M8	M10	M12	M16	M20	M24
Displacement – factor for shear load²⁾							
δ_{V0} - factor	0,6	0,35	0,37	0,27	0,10	0,09	0,07
	0,9	0,52	0,55	0,40	0,14	0,15	0,11
$\delta_{V\infty}$ - factor	FAZ II A4, FAZ II C						
	0,6	0,23	0,19	0,18	0,10	0,11	0,07
	0,9	0,27	0,22	0,16	0,11	0,05	0,09

¹⁾ Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0} - \text{factor} \cdot N_{ED}$$

$$\delta_{N\infty} = \delta_{N\infty} - \text{factor} \cdot N_{ED}$$

(N_{ED} : Design value of the applied tension force)

²⁾ Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0} - \text{factor} \cdot V_{ED}$$

$$\delta_{V\infty} = \delta_{V\infty} - \text{factor} \cdot V_{ED}$$

(V_{ED} : Design value of the applied shear force)

Table C5.3: Displacements under **tension** loads for **category C2** for all embedment depths

Size	FAZ II, FAZ II A4, FAZ II C						
	M6	M8	M10	M12	M16	M20	M24
Displacement DLS $\delta_{N,C2(DLS)}$	-		2,7	4,4	5,6	-	
Displacement ULS $\delta_{N,C2(ULS)}$			11,5	13,0	12,3		

Table C5.4: Displacements under **shear** loads for **category C2** for all embedment depths

Size	FAZ II, FAZ II A4, FAZ II C						
	M6	M8	M10	M12	M16	M20	M24
Displacement DLS $\delta_{V,C2(DLS)}$ [mm]	-		4,1	4,7	5,5	4,8	-
Displacement ULS $\delta_{V,C2(ULS)}$			6,2	7,8	10,1	11,2	

fischer Bolt Anchor FAZ II, FAZ II A4, FAZ II C

Performances

Displacements under tension and shear loads

Annex C 5