



DICHIARAZIONE DI PRESTAZIONE

DoP 0293

per Sistema fischer Highbond-Anchor FHB II (Ancorante chimico a espansione per utilizzo in calcestruzzo)

IT

1. Codice di identificazione unico del prodotto-tipo: **DoP 0293**
2. Uso previsti: **Fissaggio post-installato in calcestruzzo fessurato o non fessurato, vedi appendice, in particolare gli allegati da B1 - B11.**
3. Fabbricante: **fischerwerke GmbH & Co. KG, Otto-Hahn-Straße 15, 79211 Denzlingen, Germany**
4. Mandatario: **-**
5. Sistemi di VVCP: **1**
6. Documento per la valutazione europea: **EAD 330499-01-0601**
Valutazione tecnica europea: **ETA-21/0948; 2021-12-21**
Organismo di valutazione tecnica: **DIBt- Deutsches Institut für Bautechnik**
Organismi notificati: **2873 TU Darmstadt**
7. Prestazioni dichiarate:
Resistenza meccanica e stabilità (BWR 1)
Resistenza caratteristica al carico di tensione (carico statico e quasi-statico):
Resistenza alla rottura dell'acciaio: Allegato C1
Resistenza alla rottura del calcestruzzo combinata con sfilamento: Allegati C2-C4
Resistenza alla rottura del cono di calcestruzzo: Allegato C2
Distanza dal bordo per evitare lo splitting sotto carico: Allegato C2
Robustezza: Allegati C2-C4
Coppia di installazione: Allegati B3, B4
Distanza dal bordo e interassi minimi: Allegati B3, B4

Resistenza caratteristica al carico di taglio (carico statico e quasi statico):
Resistenza alla rottura dell'acciaio: Allegato C1
Resistenza alla rottura per pry-out: Allegato C2
Resistenza alla rottura del bordo di calcestruzzo: Allegato C2

Spostamenti con carichi a breve e a lungo termine:
Spostamenti con carichi a breve e a lungo termine: Allegati C5

Resistenza e spostamenti caratteristici per le categorie di prestazione sismica C1 e C2:
Resistenza al carico di trazione, spostamenti, categoria C1: NPD
Resistenza al carico di trazione, spostamenti, categoria C2: NPD
Resistenza al carico di taglio, spostamenti, categoria C1: NPD
Resistenza al carico di taglio, spostamenti, categoria C2: NPD
Fattore spazio anulare: NPD
8. Documentazione tecnica appropriata e/o documentazione tecnica specifica: **-**

La prestazione del prodotto sopra identificato è conforme all'insieme delle prestazioni dichiarate. La presente dichiarazione di prestazione è emessa, in conformità al regolamento (UE) n. 305/2011, sotto la sola responsabilità del fabbricante sopra identificato.

Firmato a nome e per conto del fabbricante da:

Dr.-Ing. Oliver Geibig, Direttore Generale Unità di Business & Engineering
Tumlingen, 2022-01-03

Jürgen Grün, Direttore Generale Chimica & Qualità

Questa Dichiarazione di Prestazione (DoP) è stata preparata in varie lingue. In caso di contestazioni sull'interpretazione, prevarrà sempre la versione inglese.
L'Appendice include informazioni volontarie e complementari in lingua inglese che superano i requisiti di legge (lingua specificata in modo neutrale).

Specific Part

1 Technical description of the product

The "fischer Highbond-Anchor FHB II for diamond drilling / extended working life" consisting of a mortar cartridge with mortar fischer FIS HB or fischer mortar capsule FHB II-P(F) and an anchor rod FHB II - A S or FHB II Inject - A S with hexagon nut and washer.

The glass capsule is set into a drilled hole in the concrete. The special formed anchor rod is driven into the glass capsule by machine with simultaneous hammering and turning. For the injection system the anchor rod is placed into a drilled hole filled with injection mortar. The load transfer is realized by mechanical interlock of several cones in the bonding mortar and then via a combination of bonding and friction forces in the anchorage ground (concrete).

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 and/or 100 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi-static loading)	See Annex C1 to C4, B3 to B4
Characteristic resistance to shear load (static and quasi-static loading)	See Annex C1 to C2
Displacements under short-term and long-term loading	See Annex C5
Characteristic resistance and displacements for seismic performance categories C1 and C2	No performance assessed

3.2 Hygiene, health and the environment (BWR 3)

Essential characteristic	Performance
Content, emission and/or release of dangerous substances	No performance assessed

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base


In accordance with the European Assessment Document EAD 330499-01-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1


Installation conditions part 1

Highbond - Anchor FHB II - A S


Pre-positioned installation



Push through installation



Pre-positioned or push through installation with subsequently injected fischer filling disc
(annular gap filled with mortar)



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description


Installation conditions part 1; FHB II - A S

Annex A 1
Appendix 3 / 24


Installation conditions part 2

Highbond - Anchor FHB II Inject - A S (only with injection cartridge system FIS HB)


Pre-positioned installation



Push through installation



Pre-positioned or push through installation with subsequently injected fischer filling disc
(annular gap filled with mortar)



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Installation conditions part 2; FHB II Inject - A S



Annex A 2

Appendix 4 / 24

Overview system components part 1

Injection cartridge (shuttle cartridge) with sealing cap;



Size: 360 ml, 825 ml



Imprint: fischer FIS HB, processing notes, shelf-life, piston travel scale (optional), curing times and processing times (depending on temperature), hazard code, size, volume

Injection cartridge (coaxial cartridge) with sealing cap;

Size: 150 ml, 300 ml, 380 ml, 400 ml, 410 ml




Imprint: fischer FIS HB, processing notes, shelf-life, piston travel scale (optional), curing times and processing times (depending on temperature), hazard code, size, volume


Resin capsule



Static mixer FIS MR Plus for injection cartridges up to 410 ml




Static mixer FIS JMR for injection cartridge 825 ml



Extension tube Ø 9 for static mixer FIS MR Plus;
Extension tube Ø 9 or Ø 15 for static mixer FIS JMR



Injection adapter



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description


Overview system components part 1
cartridges / resin capsule / static mixer / accessories

Annex A 3
Appendix 5 / 24


Overview system components part 2

fischer Highbond - Anchor FHB II and FHB II Inject; pre-assembled condition


Highbond - Anchor FHB II - A S




alternative version



Highbond - Anchor FHB II Inject - A S




alternative version




Highbond anchor rod FHB II - A S

Size: M16, M20, M24



Highbond anchor rod FHB II Inject - A S

Size: M16, M20, M24



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Overview system components part 2
anchor rod


Annex A 4

Appendix 6 / 24


Overview system components part 3

fischer filling disc (various versions)


radial




angular




axial




conical washer



washer



hexagon nut



Cleaning brush BS



Compressed-air cleaning tool ABP with compressed-air nozzle:



or blow-out pump ABG:



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Product description

Overview system components part 3
metal parts / cleaning brush / blow-out pump



Annex A 5
Appendix 7 / 24

Table A6.1: Materials

Part	Designation	Material		
1	Injection cartridge	Mortar, hardener, filler		
2	Resin capsule	Mortar, hardener, filler		
Steel grade	Steel	Stainless steel R	High corrosion resistant steel HCR	
	zink plated	acc. to EN 10088-1:2014 Corrosion resistance class CRC III acc. to EN 1993-1-4:2006+A1:2015	acc. to EN 10088-1:2014 Corrosion resistance class CRC V acc. to EN 1993-1-4:2006+A1:2015	
3	Highbond-Anchor rod FHB II - A S or FHB II Inject - A S	Property class 8.8 EN ISO 898-1:2013 electroplated $\geq 5 \mu\text{m}$ ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018 $A_5 > 12\%$ fracture elongation	Property class 80 EN ISO 3506-1:2020 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; 1.4062, 1.4662, 1.4462; EN 10088-1:2014 $A_5 > 12\%$ fracture elongation	Property class 80 EN ISO 3506-1:2020 1.4565; 1.4529; EN 10088-1:2014 $A_5 > 12\%$ fracture elongation
4	Washer ISO 7089:2000	electroplated $\geq 5 \mu\text{m}$ ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018	1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; EN 10088-1:2014	1.4565; 1.4529; EN 10088-1:2014
5	Hexagon nut	Property class 8 acc. to EN ISO 898-2:2012 electroplated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018	Property class 70 or 80 EN ISO 3506-2:2020 1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; EN 10088-1:2014	Property class 70 or 80 EN ISO 3506-2:2020 1.4565; 1.4529; EN 10088-1:2014
6	Conical washer or fischer filling disc	electroplated $\geq 5 \mu\text{m}$, ISO 4042:2018/Zn5/An(A2K) acc. to EN ISO 4042:2018	1.4401; 1.4404; 1.4578; 1.4571; 1.4439; 1.4362; EN 10088-1:2014	1.4565; 1.4529; EN 10088-1:2014
fischer Highbond-Anchor FHB II for diamond drilling / extended working life				
Product description Materials				Annex A 6 Appendix 8 / 24

Specifications of intended use part 1

Table B1.1: Overview installation und use

		fischer Highbond-Anchor FHB II with injection mortar FIS HB or resin capsule FHB II-P / FHB II-PF			
		FHB II - A S	FHB II Inject - A S		
					
Hammer drilling with standard drill bit		injection mortar FIS HB or resin capsule FHB II-P / FHB II-PF			
Hammer drilling with hollow drill bit		injection mortar FIS HB			
Diamond drilling		all sizes (only with resin capsule allowed)	no performance assessed		
Static or quasi static load, in	uncracked concrete	all sizes	all sizes		
	cracked concrete	Tables: C1.1, C2.1, C3.1, C3.2, C4.1, C5.1, C5.2	Tables: C1.1, C2.1, C4.1, C5.2		
Installation and use condition	I1 dry or wet concrete	all sizes			
	I2 water-filled hole	all sizes (only with resin capsule allowed)	no performance assessed		
seismic performance category C1 and C2		no performance assessed			
Installation direction		D3 (downwards, horizontal and upwards (overhead) installation)			
Installation	Pre-positioned	all sizes			
	Push through	all sizes			
Installation temperature ¹⁾	FIS HB: $T_{i,min} = -5 \text{ }^{\circ}\text{C}$ to $T_{i,max} = +40 \text{ }^{\circ}\text{C}$				
	FHB II-P / PF: $T_{i,min} = -5 \text{ }^{\circ}\text{C}$ to $T_{i,max} = +40 \text{ }^{\circ}\text{C}$				
Service temperature	Temperature range T2	-40 $\text{ }^{\circ}\text{C}$ to +80 $\text{ }^{\circ}\text{C}$ (max. short term temperature +80 $\text{ }^{\circ}\text{C}$; max. long term temperature +50 $\text{ }^{\circ}\text{C}$)			
¹⁾ For the standard variation of temperature after installation					
Figures not to scale					
fischer Highbond-Anchor FHB II for diamond drilling / extended working life			Annex B 1 Appendix 9 / 24		
Intended use Specifications part 1					

Specifications of intended use part 2

Base materials:

- Compacted reinforced or unreinforced normal weight concrete without fibres of strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (zinc plated steel, stainless steel or high corrosion resistant steel)
- For all other conditions according to EN1993-1-4: 2006+A1:2015 corresponding to corrosion resistance classes to Annex A 6 table 6.1.

Design:

- Fastenings are designed under the responsibility of an engineer experienced in fastenings and concrete work
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the fastener is indicated on the design drawings (e.g. position of the fastener relative to reinforcement or to supports, etc.)
- Fastenings are designed in accordance with:
EN 1992-4:2018 and EOTA Technical Report TR 055, Edition February 2018

Installation:

- Fastener installation is to be carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Overhead installation is allowed (necessary equipment see installation instruction)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended Use
Specifications part 2


Annex B 2
Appendix 10 / 24

Table B3.1: Installation parameters for Highbond – Anchor rod FHB II - A S

Anchor rod FHB II - A S	Thread	M16x95	M20x170	M24x170
Corresponding resin capsules FHB II-P or FHB II-PF	[-]	16x95	20x170	24x170
Cone diameter d_k	[mm]	14,5	23,0	
Width across flats SW		24	30	36
Nominal drill hole diameter d_0		16	25	
Drill hole depth h_0		110	190	
Effective embedment depth h_{ef}		95	170	
Minimum spacing and minimum edge distance $s_{min} = c_{min}$		50	80	
Diameter of clearance hole of the fixture $d_f \leq$		18	22	26
push through installation $d_f \leq$		18	26	
Min. thickness of concrete member h_{min}		150	240	
Installation torque T_{inst}	[Nm]	50	100	
Thickness of fixture $t_{fix} \leq$	[mm]		1500	
fischer filling disc ¹⁾ $\geq d_a$		38	46	54
t_s		7	8	10

¹⁾ Using fischer filling disc reduces t_{fix} (usable length of the anchor)

Highbond – Anchor rod FHB II - A S




Marking: work symbol, thread diameter, embedment depth e.g.: M16x95

For stainless steel additional **R**. For high corrosion resistant steel additional **HCR**.

For high corrosion resistant steel additional marking “(“ also on the face side

Installation conditions:



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation parameters for Highbond - Anchor FHB II - A S

Annex B 3


Appendix 11 / 24

Table B4.1: Installation parameters for Highbond - Anchor rod FHB II Inject - A S with injectionmortar FIS HB

Anchor rod FHB II Inject - A S		Thread	M16x95	M20x170	M24x170
Cone diameter	d_k	[mm]	14,5	23,0	
Width across flats	SW		24	30	36
Nominal drill hole diameter	d_0		16	25	
Drill hole depth	h_0		101	176	
Effective embedment depth	h_{ef}		95	170	
Minimum spacing and minimum edge distance	$s_{min} = c_{min}$		50	80	
Diameter of clearance hole of the fixture	pre-positioned installation		18	22	26
	push through installation		20	26	
Min. thickness of concrete member	h_{min}		150	240	
Installation torque	T_{inst}	[Nm]	50	100	
Thickness of fixture	$t_{fix} \leq$	[mm]	1500		
fischer filling disc ¹⁾	$\geq d_a$		38	46	54
	t_s		7	8	10

¹⁾ Using fischer filling disc reduces t_{fix} (usable length of the fastener)

Highbond – Anchor rod FHB II Inject - A S




Marking: work symbol, thread diameter, embedment depth e.g.:  M16x95

For stainless steel additional **R**. For high corrosion resistant steel additional **HCR**.

For high corrosion resistant steel additional marking ““ also on the face side

Installation conditions:



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use



Installation parameters for Highbond - Anchor FHB II Inject - A S

Annex B 4

Appendix 12 / 24

Table B5.1: Dimensions of resin capsule FHB II-P and FHB II-PF

Resin capsule		16x95	20x170	24x170
Capsule length	L_p	120	185	185
Capsule diameter	$\emptyset d_p$	[mm]	14,5	21,5

FHB II-P (standard)**FHB II-PF (fast curing)**

Imprint: work symbol, marking, anchor size and effective embedment depth.

e.g.: FHB II-P 16x95 or

FHB II-PF 16x95

Table B5.2: Parameters of the cleaning brush BS (steel brush with steel bristles; only when using injection mortar or resin capsule with diamond drill bit)

The size of the cleaning brush refers to the nominal drill hole diameter

Nominal drill hole diameter	d_0		16	25
Steel brush diameter BS	d_b	[mm]	20	27



Figures not to scale

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Dimensions resin capsule

Parameters cleaning brush (steel brush)

Annex B 5
Appendix 13 / 24

Table B6.1: Processing time and curing time of the injection mortar FIS HB

Temperature at anchoring base ¹⁾ [°C]	Maximum processing time t_{work}	Minimum curing time ²⁾ t_{cure}
-5 to 0 ³⁾	-	6 h
> 0 to 5 ³⁾	-	3 h
> 5 to 10	15 min	90 min
> 10 to 20	6 min	35 min
> 20 to 30	4 min	20 min
> 30 to 40	2 min	12 min

¹⁾ During the curing time of the mortar the temperature of the anchoring base may not fall below the listed minimum temperature

²⁾ In wet concrete the curing time must be doubled

³⁾ Minimal cartridge temperature +5 °C

Table B6.2: Curing time of the resin capsule FHB II-P and FHB II-PF

Resin capsule FHB II-P (standard)		Resin capsule FHB II-PF (fast curing)	
Temperature at anchoring base ¹⁾ [°C]	Minimum curing time ²⁾ t_{cure}	Temperature at anchoring base ¹⁾ [°C]	Minimum curing time ²⁾ t_{cure}
-5 to 0	4 h	-5 to 0	8 min
> 0 to 10	45 min	> 0 to 10	6 min
> 10 to 20	20 min	> 10 to 20	4 min
> 20	10 min	> 20	2 min

¹⁾ During the curing time of the mortar the temperature of the anchoring base may not fall below the listed minimum temperature.

²⁾ In wet concrete or water-filled holes the curing times must be doubled

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Processing time and curing time


Annex B 6

Appendix 14 / 24

Installation instructions part 1; Installation with resin capsule FHB II-P or FHB II-PF

Drilling the drill hole (hammer drilling with standard drill bit)

1



Drill the hole.

Nominal drill hole diameter d_0 and drill hole depth h_0 see **table B3.1**
Cleaning of the drill hole is not necessary

Go to step 6 (Annex B 8)


Drilling and cleaning the drill hole (hammer drilling with hollow drill bit)

1



Check a suitable hollow drill (see **table B1.1**)
for correct operation of the dust extraction

2



Use a suitable dust extraction system, e.g. fischer FVC 35 M or a comparable
dust extraction system with equivalent performance data.
Drill the hole with hollow drill bit. The dust extraction system has to extract the
drill dust nonstop during the drilling process and must be adjusted to
maximum power.

Nominal drill hole diameter d_0 and drill hole depth h_0 see **table B3.1**


Go to step 6 (Annex B 8)

Drilling and cleaning the drill hole (wet drilling with diamond drill bit)

1




Drill the hole.
Drill hole diameter d_0 and
nominal drill hole depth h_0
see **table B3.1**




Break the drill core
and remove it

2




Flush the drill hole, until clear water emerges from the drill hole.

3



Blow out the drill hole twice, using oil-free compressed air ($p \geq 6$ bar)


4



Brush the drill hole twice.
Corresponding cleaning brush BS see
table B5.2



5



Blow out the drill hole twice, using oil-free compressed air ($p \geq 6$ bar)

Go to step 6 (Annex B 8)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation instructions part 1








Installation with resin capsule FHB II-P or FHB II-PF

Annex B 7

Appendix 15 / 24

Installation instructions part 2; Installation with resin capsule FHB II-P or FHB II-PF

Installation Highbond-Anchor rod FHB II - A S

6		Insert the resin capsule FHB II-P or FHB II-PF into the drill hole by hand.
7		Pre-positioned installation: Only use Highbond-Anchor rods FHB II - A S with roof-shaped point . Drive in the Anchor rod using a hammer drill or impact drill. When reaching the setting depth mark stop the drill immediately.
7		Push through installation: Only use Highbond-Anchor rods FHB II - A S with roof-shaped point . Drive in the anchor rod using a hammer drill or impact drill. When reaching the setting depth mark stop the drill immediately.
8		Pre-positioned installation: After inserting the anchor rod, excess mortar must be emerged around the anchor.
8		Push through installation: After inserting the anchor rod, excess mortar must be emerged from the drill hole and must be visible in the fixture.
8a		For overhead installations support the anchor rod with wedges. (e.g. fischer centering wedges)
9		Wait for the specified curing time t_{cure} see table B6.2
10		Installation torque for the hexagon nut T_{inst} see table B3.1, B4.1
Option		The gap between metal parts and fixture (annular gap) may be filled with mortar via the fischer filling disc. Compressive strength $\geq 50 \text{ N/mm}^2$ (e.g. FIS HB, FIS SB, FIS V, FIS V Plus, FIS EM Plus). ATTENTION: Using fischer filling disc reduces t_{fix} (usable length of the anchor)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation instructions part 2





Installation with resin capsule FHB II-P or FHB II-PF

Annex B 8

Appendix 16 / 24


Installation instructions part 3; Installation with injection mortar FIS HB

Drilling and cleaning the drill hole (hammer drilling with standard drill bit)

1	 <p>Drill the hole Nominal drill hole diameter d_0 and drill hole depth h_0 see tables B3.1, B4.1</p>
2	 <p>Clean the drill hole. Blow out the drill hole twice. If necessary, remove standing water out of the bore hole For drill hole diameter $d_0 = 16 \text{ mm}$ blow out the hole by hand or oil-free compressed air ($\geq 6 \text{ bar}$). For drill hole diameter $d_0 = 25 \text{ mm}$ blow out the hole with oil-free compressed air ($\geq 6 \text{ bar}$). Use a compressed-air nozzle.</p>
3	 <p>Brush the bore hole twice. Corresponding cleaning brush BS see table B5.2</p>
4	 <p>Clean the drill hole. Blow out the drill hole twice. For drill hole diameter $d_0 = 16 \text{ mm}$ blow out the hole by hand or oil-free compressed air ($\geq 6 \text{ bar}$). For drill hole diameter $d_0 = 25 \text{ mm}$ blow out the hole with oil-free compressed air ($\geq 6 \text{ bar}$). Use a compressed-air nozzle.</p>

Go to step 5 (Annex B 10)

Drilling and cleaning the drill hole (hammer drilling with hollow drill bit)

1	 <p>Check a suitable hollow drill (see table B1.1) for correct operation of the dust extraction</p>
2	 <p>Use a suitable dust extraction system, e.g. fischer FVC 35 M or a comparable dust extraction system with equivalent performance data. Drill the hole with hollow drill bit. The dust extraction system has to extract the drill dust nonstop during the drilling process and must be adjusted to maximum power. Nominal drill hole diameter d_0 and drill hole depth h_0 see tables B3.1, B4.1</p>

Go to step 5 (Annex B 10)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation instructions part 3


Installation with injection mortar FIS HB

Annex B 9



Appendix 17 / 24

Installation instruction part 4; Installation with injection mortar FIS HB

Preparing the cartridge

5		Remove the sealing cap Screw on the static mixer (the spiral in the static mixer must be clearly visible)
6		Place the cartridge into the dispenser
7		Extrude approximately 10 cm of material out until the resin is evenly grey in colour. Do not use mortar that is not uniformly grey

Injection of the mortar

8		Fill approximately 2/3 of the drill hole with mortar. Always begin from the bottom of the hole and avoid bubbles
		For drill hole depth ≥ 170 mm use an extension tube

Go to step 9 (Annex B 11)

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Intended use

Installation instructions part 4

Installation with injection mortar

Annex B 10

Appendix 18 / 24

Installation instruction part 5; Installation with injection mortar FIS HB

Installation Highbond-Anchor rod FHB II - A S or FHB II Inject - A S







9		<p>Pre-positioned or push through installation: Push the anchor rod down to the bottom of the hole, turning it slightly while doing so. Only use clean and oil-free metal parts.</p>
10		<p>Pre-positioned installation: After inserting the anchor rod, excess mortar must be emerged around the anchor.</p>
10a		<p>For overhead installations support the anchor rod with wedges. (e.g. fischer centering wedges)</p>
11		<p>Wait for the specified curing time t_{cure} see table B6.1</p>
12		<p>Installation torque for the hexagon nut T_{inst} see table B3.1, B4.1</p>
Option		<p>The gap between metal parts and fixture (annular gap) may be filled with mortar via the fischer filling disc. Compressive strength $\geq 50 \text{ N/mm}^2$ (e.g. FIS HB, FIS SB, FIS V, FIS V Plus, FIS EM Plus). ATTENTION: Using fischer filling disc reduces t_{fix} (usable length of the anchor)</p>
fischer Highbond-Anchor FHB II for diamond drilling / extended working life		
Intended use Installation instructions part 5 Installation with injection mortar		Annex B 11 Appendix 19 / 24

Table C1.1: Characteristic resistance to **steel failure** under **tension / shear loading** of **Highbond-Anchor rods FHB II - A S and FHB II Inject - A S**

Ancher rod FHB II - A S / FHB II Inject - A S		M16x95	M20x170	M24x170		
Characteristic resistance to steel failure under tension loading						
Characteristic resistance $N_{Rk,s}$	Steel, zinc plated	[kN]	61,6	128,5		
	Stainless steel R					
	High corrosion resistant steel HCR		61,6	128,5		
Partial factors ¹⁾						
$\gamma_{Ms,N}$	Steel, zinc plated	[-]	1,5 ¹⁾			
	Stainless steel R		1,5 ¹⁾			
	High corrosion resistant steel HCR		1,5 ¹⁾			
Characteristic resistance to steel failure under shear loading						
without lever arm						
Characteristic resistance $V^0_{Rk,s}$	Steel, zinc plated	[kN]	50,8	80,3		
	Stainless steel R		62,7	97,9		
	High corrosion resistant steel HCR		62,7	97,9		
Ductility factor	k_7	[-]	1,0			
with lever arm						
Characteristic resistance $M^0_{Rk,s}$	Steel, zinc plated	[Nm]	266	519		
	Stainless steel R					
	High corrosion resistant steel HCR		266	519		
Partial factors ¹⁾						
Partial factor	$\gamma_{Ms,V}$	[-]	1,25			
¹⁾ In absence of other national regulations						
fischer Highbond-Anchor FHB II for diamond drilling / extended working life						
Performance Characteristic resistance to steel failure under tension / shear loading of Highbond-Anchor rods FHB II - A S and FHB II Inject - A S				Annex C 1 Appendix 20 / 24		

Table C2.1: Characteristic resistance to concrete failure under tension / shear loading

Anchor rod FHB II - A S / FHB II Inject - A S			All sizes	
Characteristic resistance to concrete failure under tension loading				
Installation factor	γ_{inst}	[-]	See annex C 3 to C 4	
Factors for the compressive strength of concrete > C20/25				
Increasing factor for uncracked or cracked concrete $N_{Rk,p} = \psi_c N_{Rk,p}$ (C20/25)	C25/30	[-]	1,12	
	C30/37		1,22	
	C35/45		1,32	
	C40/50		1,41	
	C45/55		1,50	
	C50/60		1,58	
Splitting failure				
Edge distance	$c_{cr,sp}$	[mm]	2 h_{ef}	
Spacing	$s_{cr,sp}$		4 h_{ef}	
Concrete cone failure				
Uncracked concrete	$k_{ucr,N}$	[-]	11,0 ¹⁾	
Cracked concrete	$k_{cr,N}$		7,7 ¹⁾	
Edge distance	$c_{cr,N}$	[mm]	1,5 h_{ef}	
Spacing	$s_{cr,N}$		3 h_{ef}	
Characteristic resistance to concrete failure under shear loading				
Installation factor	γ_{inst}	[-]	1,0	
Concrete pry-out failure				
Factor for pry-out failure	k_8	[-]	2,0	
Concrete edge failure				
Anchor rod FHB II - A S and FHB II Inject - A S		M16x95	M20x170	
Effective length of fastener in shear loading	l_f	[mm]	95	
Calculation diameter	d_{nom}		16	
1) Related to concrete cylinder compressive strength				
fischer Highbond-Anchor FHB II for diamond drilling / extended working life				
Performance Characteristic resistance to concrete failure under tension / shear loading			Annex C 2 Appendix 21 / 24	

Table C3.1: Characteristic resistance to pull-out failure for **Highbond-Anchor rods FHB II - A S** with **resin capsule FHB II-P or FHB II-PF** in diamond drilled holes; **50 years**

Highbond-Anchor rod FHB II - A S ¹⁾	M16x95	M20x170	M24x170
Characteristic resistance to pull-out failure			
Calculation diameter d [mm]	16	25	
Uncracked concrete			
Characteristic resistance in uncracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,ucr} [kN]	51,5	118,5	
Cracked concrete			
Characteristic resistance in cracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,cr} [kN]	42,8	101,4	
Installation factors			
Dry or wet concrete		1,2	
Water-filled hole γ _{inst} [-]		1,2	

¹⁾ Highbond-Anchor rod FHB II - A S with resin capsule FHB II-P / FHB II-PF

Table C3.2: Characteristic resistance to pull-out failure for **Highbond-Anchor rods FHB II - A S** with **resin capsule FHB II-P or FHB II-PF** in diamond drilled holes; **100 years**

Highbond-Anchor rod FHB II - A S ¹⁾	M16x95	M20x170	M24x170
Characteristic resistance to pull-out failure			
Calculation diameter d [mm]	16	25	
Uncracked concrete			
Characteristic resistance in uncracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,ucr,100} [kN]	51,5	118,5	
Cracked concrete			
Characteristic resistance in cracked concrete C20/25			
Diamond-drilling (dry or wet concrete / water-filled hole)			
Temperature range T2 50 °C / 80 °C N _{Rk,p,cr,100} [kN]	36,0	86,0	
Installation factors			
Dry or wet concrete		1,2	
Water-filled hole γ _{inst} [-]		1,2	

¹⁾ Highbond-Anchor rod FHB II - A S with resin capsule FHB II-P / FHB II-PF

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Performance

Characteristic resistance to pull-out failure for Highbond-Anchor rods FHB II - A S in diamond drilled holes; 50 or 100 years

Annex C 3
Appendix 22 / 24

Table C4.1: Characteristic resistance to pull-out failure for **Highbond-Anchor rods FHB II - A S** with **resin capsule FHB II-P / FHB II-PF** or **injection mortar FIS HB** and **FHB II Inject - A S** with **injection mortar FIS HB** in hammer drilled holes; **100 years**

Anchor rod FHB II - A S ¹⁾ FHB II Inject - A S ²⁾	M16x95	M20x170	M24x170
Characteristic resistance to pull-out failure			
Calculation diameter d [mm]	16	25	
Uncracked concrete			
Characteristic resistance in uncracked concrete C20/25			
Hammer-drilling with standard or hollow drill bit (dry or wet concrete / water-filled hole)			
Temperature range T2	50 °C / 80 °C	N _{Rk,p,ucr,100} [kN]	52,4
			118,5
Cracked concrete			
Characteristic resistance in cracked concrete C20/25			
Hammer-drilling with standard or hollow drill bit (dry or wet concrete / water-filled hole)			
Temperature range T2	50 °C / 80 °C	N _{Rk,p,cr,100} [kN]	36,0
			86,0
Installation factors			
Dry or wet concrete			1,0
Water-filled hole (only with resin capsule)	γ _{inst}	[·]	1,0

¹⁾ Highbond-Anchor rod FHB II - A S with resin capsule FHB II-P / FHB II-PF or injection mortar FIS HB

²⁾ Highbond-Anchor rod FHB II Inject - A S with injection mortar FIS HB

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Performance

Characteristic resistance to pull-out failure for Highbond-Anchor rods FHB II - A S / FHB II Inject - A S in hammer drilled holes; 100 years

Annex C 4
Appendix 23 / 24

Table C5.1: Displacements for Highbond-Anchor rod FHB II - A S; 50 years

Anchor rod FHB II – A S		M16x95	M20x170	M24x170	
Displacement-Factors for tension loading ¹⁾					
Uncracked concrete; Temperature range T2					
δ_{N0} -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Cracked concrete; Temperature range T2					
$\delta_{N\infty}$ -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Displacement-Factors for shear loading ²⁾					
Uncracked or cracked concrete; Temperature range T2					
δ_{V0} -Factor	[mm/kN]	0,02	0,02	0,02	
		0,03	0,03	0,03	

¹⁾ Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0}\text{-Factor} \cdot N$$

$$\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot N$$

N = acting tension loading

²⁾ Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V$$

$$\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V$$

V = acting shear loading

Table C5.2: Displacements for Highbond-Anchor rod FHB II - A S and FHB II Inject - A S; 100 years

Anchor rod FHB II – A S / FHB II Inject - A S		M16x95	M20x170	M24x170	
Displacement-Factors for tension loading ¹⁾					
Uncracked concrete; Temperature range T2					
δ_{N0} -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Cracked concrete; Temperature range T2					
$\delta_{N\infty}$ -Factor	[mm/kN]	0,030	0,020	0,016	
		0,120	0,045	0,045	
Displacement-Factors for shear loading ²⁾					
Uncracked or cracked concrete; Temperature range T2					
δ_{V0} -Factor	[mm/kN]	0,02	0,02	0,02	
		0,03	0,03	0,03	

¹⁾ Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0}\text{-Factor} \cdot N$$

$$\delta_{N\infty} = \delta_{N\infty}\text{-Factor} \cdot N$$

N = acting tension loading

²⁾ Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0}\text{-Factor} \cdot V$$

$$\delta_{V\infty} = \delta_{V\infty}\text{-Factor} \cdot V$$

V = acting shear loading

fischer Highbond-Anchor FHB II for diamond drilling / extended working life

Performances

Displacements for Highbond-Anchor rod FHB II - A S and FHB II Inject - A S;
50 or 100 years

Annex C 5

Appendix 24 / 24