EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA

DoP 0416

fischer HybridPower (mehāniskais enkurs betonam)

LV

1. Unikāls izstrādājuma tipa identifikācijas numurs: **DoP 0416**

2. Paredzētais izmantojums: **Pēcapstrādes mehāniskais enkurs neplaisājušam betonam , Skatīt papildinājumu, īpaši pielikumus B1 - B3.**

3. Ražotājs: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Vācija**

4. Pilnvarotais pārstāvis: **–**

5. Ekspluatācijas īpašību noturības novērtējuma un pārbaudes (AVCP) sistēma(-as): **1**

6. Eiropas novērtējuma dokuments: **EAD 330232-02-0601**
   Eiropas tehniskais novērtējums: **ETA-26/0167; 2026-06-23**
   Tehniskā novērtējuma iestāde: **ETA-Danmark A/S**
   Paziņotā(-ās) iestāde(-es): **2873 TU Darmstadt**

7. Deklarētā(-ās) ekspluatācijas īpašība(-as):
   Mehāniskā izturība un stabilitāte (BWR 1)
   Raksturīgā izturība pret vilkmi (statiskā un kvazistatiskā slodze) metode A:
   1 Izturība pret tērauda bojājumiem: Pielikums C1
   2 Izturība pret izraušanas bojājumu: Pielikums C1
   3 Izturība pret betona konusa bojājumu: Pielikums C2
   4 Robustums: Pielikums C1
   5 Minimālais malas attālums un atstatums: Pielikums B2
   6 Malu attālums, lai novērstu plaisāšanu zem slodzes: Pielikums C2
   Raksturīgā izturība pret bīdes slodzi (statiskā un kvazistatiskā slodze):
   7 Izturība pret tērauda bojājumiem (bīdes slodze): Pielikums C3
   8 Izturība pret izraušanas bojājumu no malas: Pielikums C3
   Raksturīgā izturība vienkāršotam projektējumam:
   9 Metode B: NPD
   10 Metode C: NPD
   Pārvietojumi:
   11 Pārvietojumi statiskās un kvazistatiskās slodzes apstākļos: Pielikums C5
   Stingrība
   12 Stingrība elastīgajā diapazonā pie stiepes slodzes NPD
   13 Stingrības raksturlielumi nelineāriem atsperu modeļiem pie stiepes slodzes NPD
   Raksturīgā izturība un pārvietojumi seismiskās veiktspējas kategorijām C1:
   14 Stiepes slodzes nestspēja: NPD
   15 Bīdes slodzes nestspēja, Gredzenveida spraugas koeficients: NPD
   Seismiskās veiktspējas kategorijas C2 raksturīgā nestspēja un pārvietojumi:
   16 Stiepes slodzes nestspēja, pārvietojumi: NPD
   17 Bīdes slodzes nestspēja un pārvietojumi, gredzenveida spraugas koeficients: NPD
   Drošība ugunsgrēka gadījumā (BWR 2)
   18 Reakcija uz uguni: Klase (A1)
   Izturība pret uguni:
   19 Ugunsizturība pret tērauda bojājumiem (vilces slodze): Pielikums C4
   20 Ugunsizturība pret izraušanas bojājumu (vilces slodze): Pielikums C4
   21 Ugunsizturība pret tērauda bojājumiem (bīdes slodze): Pielikums C4
   Izturība:
   22 Izturība: Pielikumi B1

8. Atbilstīgā tehniskā dokumentācija un/vai īpašā tehniskā dokumentācija: **–**

Iepriekš norādītā izstrādājuma ekspluatācijas īpašības atbilst deklarēto ekspluatācijas īpašību kopumam. Šī ekspluatācijas īpašību deklarācija izdota saskaņā ar Regulu (ES) Nr. 305/2011, un par to ir atbildīgs vienīgi iepriekš norādītais ražotājs.

Parakstīts ražotāja vārdā:

i.V.

Dr. Christian Weber, Attīstības vadītājs

Tumlingen, 2026-08-01

Dieter Pfaff, Starptautiskās ražošanas federācijas un kvalitātes vadības vadītājs

Šī deklarācija par tehniskajiem raksturojumiem ir sagatavota dažādās valodās. Gadījumos, ja rodas strīdi attiecībā uz skaidrojumu, prioritāte vienmēr ir angļu versijai. Pielikums satur brīvprātīgi sniegtu papildu informāciju angļu valodā, kas pārsniedz (norādīts neatkarīgi no valodas) likumā noteiktās prasības.

Translation guidance Essential Characteristics and Performance Parameters for Annexes

Tulkošanas norādījumi Pielikumu būtiskie raksturlielumi un darbības parametri

Mechanical resistance and stability (BWR 1) **Mehāniskā izturība un stabilitāte (BWR 1)**		
Characteristic resistance under static and quasi-static loading, Method A **Raksturīgā izturība pret vilkmi (statiskā un kvazistatiskā slodze) metode A:**		
1	Resistance to steel failure: **Izturība pret tērauda bojājumiem:**	$N_{Rk,s}$ [kN], E_s [N/mm^2]
2	Resistance to pull- out failure: **Izturība pret izraušanas bojājumu:**	$N_{Rk,p}$ [kN], ψ_c
3	Resistance to concrete cone failure: **Izturība pret betona konusa bojājumu:**	$k_{cr,N}$, $k_{ucr,N}$ [-], h_{ef}, $c_{cr,N}$ [mm]
4	Robustness: **Robustums:**	γ_{inst} [-]
5	Minimum edge distance and spacing: **Minimālais malas attālums un atstatums:**	c_{min}, s_{min}, h_{min} [mm]
6	Edge distance to prevent splitting under load: **Malu attālums, lai novērstu plaisāšanu zem slodzes:**	$N^0_{Rk,sp}$ [kN], $c_{cr,sp}$ [mm]
Characteristic resistance to shear load (static and quasi-static loading), Method A **Raksturīgā izturība pret bīdes slodzi (statiskā un kvazistatiskā slodze):**		
7	Resistance to steel failure under shear load: **Izturība pret tērauda bojājumiem (bīdes slodze):**	$V^0_{Rk,s}$ [kN], $M^0_{Rk,s}$ [Nm], k_7 [-]
8	Resistance to pry-out failure: **Izturība pret izraušanas bojājumu no malas:**	k_8 [-]
Characteristic Resistance for simplified design: **Raksturīgā izturība vienkāršotam projektējumam:**		
9	Method B: **Metode B:**	F^0_{Rk} [kN], $M^0_{Rk,s}$ [Nm] ψ_c [-], c_{cr}, s_{cr}, c_{min}, s_{min}, h_{min} [mm]
10	Method C: **Metode C:**	F_{Rk} [kN], $M^0_{Rk,s}$ [Nm], c_{cr}, s_{cr}, h_{min} [mm]
Displacements **Pārvietojumi:**		
11	Displacements under static and quasi-static loading: **Pārvietojumi statiskās un kvazistatiskās slodzes apstākļos:**	δ_{N0}, $\delta N_{50years}$, $\delta N_{100years}$, δ_{V0}, $\delta_{V\infty}$ [mm]
12	Stiffness characteristics for tension loading for non-linear spring models:	$k_{1,cr}$, $k_{2,cr}$, $k_{3,cr}$, $k_{4,cr}$ [kN/mm]
Stingrība		
12	Stiffness in the elastic range under tension loading **Stingrība elastīgajā diapazonā pie stiepes slodzes**	$k_{A,ucr}$, $k_{A,cr}$ [N/mm]
13	Stiffness characteristics for tension loading for non-linear spring models **Stingrības raksturlielumi nelineāriem atsperu modeļiem pie stiepes slodzes**	$k_{A,ucr}$, $k_{B,ucr}$, $k_{C,ucr}$, $k_{D,ucr}$ [N/mm] $k_{A,cr}$, $k_{B,cr}$, $k_{C,cr}$, $k_{D,cr}$ [N/mm]
Characteristic resistance for seismic performance category C1: **Raksturīgā izturība un pārvietojumi seismiskās veiktspējas kategorijām C1:**		
14	Resistance to tension load: **Stiepes slodzes nestspēja:**	$N_{Rk,s,C1}$ [kN], $N_{Rk,p,C1}$ [kN]
15	Resistance to shear load:, Factor annular gap: **Bīdes slodzes nestspēja, Gredzenveida spraugas koeficients:**	$V_{Rk,s,C1}$ [kN]
Characteristic resistance and displacements for seismic performance categorie C2: **Seismiskās veiktspējas kategorijas C2 raksturīgā nestspēja un pārvietojumi:**		
16	Resistance to tension load, displacements: **Stiepes slodzes nestspēja, pārvietojumi:**	$N_{Rk,s,C2}$ [kN], $N_{Rk,p,C2}$ [kN] $\delta_{N,C2(0,5)}$, $\delta_{N,C2(0,8)}$ [mm]
17	Resistance to shear load and displacements, factor annular gap: **Bīdes slodzes nestspēja un pārvietojumi, gredzenveida spraugas koeficients:**	$V_{Rk,s,C2}$ [kN], $\delta_{V,C2(0,5)}$, $\delta_{V,C2(0,8)}$ [mm]
Safety in case of fire (BWR 2) **Drošība ugunsgrēka gadījumā (BWR 2)**		
18	Reaction to fire: **Reakcija uz uguni:**	Class
Resistance to fire: **Izturība pret uguni:**		
19	Fire resistance to steel failure (tension load): **Ugunsizturība pret tērauda bojājumiem (vilces slodze):**	$N_{Rk,s,fi}$ [kN]
20	Fire resistance to pull-out failure (tension load): **Ugunsizturība pret izraušanas bojājumu (vilces slodze):**	$N_{Rk,p,fi}$ [kN]
21	Fire resistance to steel failure (shear load): **Ugunsizturība pret tērauda bojājumiem (bīdes slodze):**	$V_{Rk,s,fi}$ [kN], $M^0_{Rk,s,fi}$ [Nm]
Aspects of durability **Izturība:**		
22	Durability: **Izturība:**	Class

II SPECIFIC PART OF THE EUROPEAN TECHNICAL ASSESSMENT

1 Technical description of product

The fischer HybridPower is a plastic anchor consisting of a plug sleeve made of polyamide combined with a metal sceleton (power wedge), and a special screw made of either galvanized steel with an additional organic coating or stainless steel according to Annex A3. The anchor is available with two different head types; a hexagon head (type FUS) and a countersunk head (type T).

The anchors are intended for use in both cracked and uncracked concrete of strength classes ranging from C20/25 to C50/60.

The anchor is screwed into a predrilled cylindrical drill hole, and the power wedges interlock with the base material ensuring a secure anchorage.

The product description is given in Annex A and the intended use specifications of the product are detailed in Annex B.

2 Specification of the intended use(s) in accordance with the applicable European Assessment Document (hereinafter EAD)

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The provisions made in this European Technical Assessment are based on an assumed intended working life of the anchor of 50 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer or Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

Characteristic	Assessment of characteristic
3.1 Mechanical resistance and stability (BWR1)	
Characteristic resistance to tension load (static and quasi-static loading) Method A	
Resistance to steel failure under tension load	Annex C1
Resistance to pull-out failure	Annex C1
Resistance to concrete cone failure	Annex C2
Robustness	Annex C1
Minimum edge distance and spacing	Annex B2
Edge distance to prevent splitting under load	Annex C2
Characteristic resistance to shear load (static and quasi-static loading)	
Resistance to steel failure under shear load	Annex C3
Resistance to pry-out failure	Annex C3
Characteristic resistance for simplified methods	
Method B	Not relevant
Method C	Not relevant
Displacements	
Displacements under static and quasi-static loading	Annex C5
Stiffness	
Stiffness in the elastic range under tension loading	No performance assessed
Stiffness characteristics for tension loading for non-linear spring models	No performance assessed
Characteristic resistance for seismic performance category C1	
Resistance to tension load	No performance assessed
Resistance to shear load	No performance assessed
Characteristic resistance and displacements for seismic performance category C2	
Resistance to tension load and displacements	No performance assessed

Characteristic	Assessment of characteristic
Resistance to shear load and displacements	No performance assessed
3.2 Safety in case of fire (BWR2)	
Reaction to fire	Class A1
Resistance to fire	
Fire resistance to steel failure under tension load	Annex C4
Fire resistance to pull-out failure	Annex C4
Fire resistance to steel failure under shear load	Annex C4
3.3 Aspects of durability	
Durability	Annex B1

See additional information in section 3.9

3.9 General aspects related to the performance of the product

The European Technical Assessment is issued for the product on the basis of agreed data/information, deposited with ETA-Danmark, which identifies the product that has been assessed and judged. Changes to the product or production process, which could result in this deposited data/information being incorrect, should be notified to ETA-Danmark before the changes are introduced. ETA-Danmark will decide whether or not such changes affect the ETA and consequently the validity of the CE marking on the basis of the ETA and if so whether further assessment or alterations to the ETA, shall be necessary.

4 Assessment and verification of constancy of performance (AVCP) (hereinafter AVCP) system applied, with reference to its legal base.

4.1 AVCP system

According to the decision 1996/582/EC of the European Commission, the system(s) of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No. 305/2011) is 1.

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at ETA-Danmark prior to CE marking.

The following standards and documents are referred to in this European Technical Assesment:

− EOTA European Assessment Document EAD 330232-02-0601: Mechanical fasteners for use in concrete
− EN 206:2013+A2:2021: Concrete – Specification, performance, production and conformity
− EN 1992-4:2019-04: Eurocode 2 - Design of concrete structures - Part 4: Design of fastenings for use in concrete; German version EN 1992-4:2018
− EN 1993-1-4:2006 + A1:2015: Eurocode 3: Design of steel structures - Part 1-4: General rules - Supplementary rules for stainless steels
− EN ISO 4042:2018: Fasteners – Electroplated coating systems

fischer HybridPower



Legend

d_0	=	Nominal drill hole diameter
h_{nom}	=	Overall plastic anchor embedment depth in the base material
h_1	=	Depth of drill hole to deepest point
h	=	Thickness of concrete member
t_{fix}	=	Thickness of fixture and / or non-load bearing layer

Figure not to scale

Anchor sleeve – HybridPower



Special screws

Countersunk screw





Hexagonal screw with washer





1) Additional marking for the special screw, stainless steel version: e.g. "A4" or "R" or “A2”.
2) Internal driving feature for Torx bit is optional for hexagonal head.
3) Optional additional version with underhead ribs.

Table A2.1: Dimensions

Anchor type	Anchor sleeve					Special screw		
	h_{nom} [mm]	d_{nom} [mm]	l_D [mm]	l_{Sf} [mm]	d_{Sf} [mm]	d_S [mm]	l_G [mm]	l_S [mm]
HybridPower FUS	80	10	90-230	2,5	15	7,0	77	l_D
HybridPower T	80	10	90-230	2,5	15	7,0	77	l_D

Legend

h_{nom}	=	Overall plastic anchor embedment depth in the base material
d_{nom}	=	Nominal diameter of the anchor sleeve
l_D	=	Length of the anchor sleeve
l_{Sf}	=	Thickness of the anchor sleeve collar
d_{Sf}	=	Diameter of the anchor sleeve collar
d_S	=	Diameter of the screw
l_G	=	Thread length of the screw
l_S	=	Length of the screw

Figures not to scale

Table A3.1: Materials

Name	Material
HybridPower anchor sleeve	- Polyamide, PA6, colour: red
HybridPower sceleton	- Ferritic stainless steel
Special screw	- Galvanised steel gvz with Zn5/Ag or Zn5/An in accordance with EN ISO 4042 with additional organic layer (Zn5/Ag/T7 or Zn5/An/T7, resp., total layer thickness ≥ 6 µm) **or** - Stainless steel “A2” of corrosion resistance class CRC II in accordance with EN 1993-1-4 **or** - Stainless steel “A4” or “R” of corrosion resistance class CRC III in accordance with EN 1993-1-4

Specifications of intended use

Anchorages subject to:

- Static and quasi-static loads.
- Fire exposure.

Base materials:

- Reinforced or unreinforced compacted normal weight concrete without fibres (cracked or uncracked) in accordance with EN 206-1.
- Strength classes C20/25 to C50/60 in accordance with EN 206-1.

Use conditions (Environmental conditions):

- Temperature Range: - 20 °C to + 50 °C.
- Structures subject to dry internal conditions (HybridPower, HybridPower A2, HybridPower A4, HybridPower R).
- For all other conditions according to EN 1993-1-4 corresponding to corrosion resistance class (CRC):
  - for CRC II: for HybridPower A2
  - for CRC III: for HybridPower A4 or HybridPower R

Design:

- The structural design is conducted under responsibility of a designer experienced in the field of anchorages and concrete works.
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the fastener is indicated on the design drawings (e.g. position of the fastener relative to reinforcement or to supports, etc.).
- Design of fastenings according to EN 1992-4.

Installation:

- Fastener installation is to be carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters on the site.
- Use of the fastener only as supplied by the manufacturer without exchanging the components of the fastener.
- Hammer drilling.
- Drill hole created perpendicular +/- 5° to concrete surface, positioning without damaging the reinforcement.
- In case of aborted hole: new drilling at a minimum distance twice the depth of the aborted drill hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application.
- Installation temperature: - 20 °C to + 40 °C.
- Exposure to UV due to solar radiation of the anchor not protected by rendering ≤ 6 weeks.
- No ingress of water in the borehole at temperatures < 0°C.

Table B2.1: Installation parameters

Anchor type				HybridPower, HybridPower A2, HybridPower A4, HybridPower R
Nominal drill hole diameter	d_0	=	[mm]	10
Cutting diameter of drill bit	d_{cut}	≤	[mm]	10,45
Overall plastic anchor embedment depth in the base material	h_{nom}	≥	[mm]	80
Depth of drill hole to deepest point	h_1	≥	[mm]	90
Diameter of clearance hole in the fixture	d_f	≤	[mm]	10,50[1)]
Thickness of fixture and / or non-load bearing layer	t_{fix}	≥	[mm]	1

[1)] In combination of hexagon screw with washer and anchor sleeve, use in elongated hole under tensile load is allowed.



Table B2.2: Minimum thickness of concrete members, minimum edge distances and minimum spacing

Anchor type			HybridPower, HybridPower A2, HybridPower A4, HybridPower R
			10
Minimum edge distance and spacing			
Uncracked concrete Cracked concrete	c_{min}	[mm]	50
Uncracked concrete Cracked concrete	s_{min}	[mm]	50
Minimum thickness of concrete member	h_{min}	[mm]	100

Figure not to scale

fischer HybridPower

Intended use
Installation parameters
Minimum thickness of member, edge distances and spacing

Annex B2

Installation instructions

The following pictures show fixing through timber in concrete.



1. Drill the bore hole as per Table B2.1 using hammer drilling.
2. Remove dust from borehole.



3. Insert anchor (screw and sleeve) by using a hammer until the collar of the plastic sleeve is flush with the surface of the fixture.



4. The screw is screwed-in until the head of the screw touches the sleeve. The anchor is correctly installed, if the head of the screw fits tight on the surface and nor the anchor sleeve neither the screw cannot be turned-in any further.



5. Correctly installed anchor.

Figures not to scale

Table C1.1: Characteristic values of tension resistance under static and quasi-static action

Anchor type				HybridPower, HybridPower A2, HybridPower A4, HybridPower R
				10
Overall plastic anchor embedment depth in the base material		h_{nom} ≥	[mm]	80
Steel failure				
Characteristic tension resistance	HybridPower	$N_{Rk,s}$	[kN]	21,70
	HybridPower A2			
	HybridPower A4			
	HybridPower R			
Partial factor for steel failure	HybridPower	γ_{Ms} 1)	[-]	1,55
	HybridPower A2			
	HybridPower A4			
	HybridPower R			
Pullout failure				
Characteristic resistance in cracked concrete C20/25		$N_{Rk,p,cr}$	[kN]	2,00 2)
Increasing factor ψ_c for cracked concrete $N_{Rk,p,cr} = \psi_c \times N_{Rk,p,cr}$ (C20/25)	C25/30		[-]	1,00
	C30/37			
	C35/45			
	C40/50			
	C45/55			
	C50/60			
Installation sensitivity factor for cracked concrete		$\gamma_{inst,cr}$	[-]	1,00
Characteristic resistance in uncracked concrete C20/25		$N_{Rk,p,ucr}$	[kN]	10,50
Increasing factor ψ_c for uncracked concrete $N_{Rk,p,ucr} = \psi_c \times N_{Rk,p,ucr}$ (C20/25)	C25/30		[-]	1,05
	C30/37			1,08
	C35/45			1,12
	C40/50			1,15
	C45/55			1,18
	C50/60			1,20
Installation sensitivity factor for uncracked concrete		$\gamma_{inst,ucr}$	[-]	1,00

1) In absence of other national regulations.
2) If it is ensured that the temperature during working life does not exceed + 30°C, the values may be increased by 1,08.

Table C2.1: Characteristic values of tension resistance under static and quasi-static action

Anchor type					HybridPower, HybridPower A2, HybridPower A4, HybridPower R
					10
Overall plastic anchor embedment depth in the base material		h_{nom}	≥	[mm]	80
Concrete cone and splitting failure					
Effective embedment depth for calculation	cracked concrete	$h_{ef,cr}$	≥	[mm]	35
	uncracked concrete	$h_{ef,ucr}$	≥		53
Factor for cracked concrete		$k_{cr,N}$		[-]	7,7
Factor for uncracked concrete		$k_{ucr,N}$			11,0
Characteristic spacing	cracked concrete	$s_{cr,N,cr}$		[mm]	105
	unracked concrete	$s_{cr,N,ucr}$			159
Characteristic edge distance	cracked concrete	$c_{cr,N,cr}$		[mm]	53
	unracked concrete	$c_{cr,N,ucr}$			80
Characteristic spacing for splitting failure	cracked concrete	$s_{cr,sp,cr}$		[mm]	2 x $c_{cr,sp}$
	unracked concrete	$s_{cr,sp,ucr}$			
Characteristic edge distance for splitting failure	cracked concrete	$c_{cr,sp,cr}$		[mm]	49
	unracked concrete	$c_{cr,sp,ucr}$			53
Characteristic resistance to splitting		$N^0_{Rk,sp}$		[kN]	min {$N^0_{Rk,c}$; $N_{Rk,p}$}[1)]

[1)] $N^0_{Rk,c}$ according to EN 1992-4.

Table C3.1: Characteristic values of shear resistance under static and quasi-static action

Anchor type				HybridPower, HybridPower A2, HybridPower A4, HybridPower R
				10
Steel failure without lever arm				
Characteristic resistance	HybridPower HybridPower A2 HybridPower A4 HybridPower R	$V^0_{Rk,s}$	[kN]	10,80
Partial factor for steel failure		γ_{Ms} 1)	[-]	1,29
Factor for ductility	HybridPower	k_7	[-]	0,80
	HybridPower A2 HybridPower A4 HybridPower R			1,00
Steel failure with lever arm and Concrete pryout failure				
Characteristic bending resistance	HybridPower HybridPower A2 HybridPower A4 HybridPower R	$M^0_{Rk,s}$	[Nm]	20,60
Factor for pryout failure		k_8	[-]	1,00
Partial factor for steel failure		γ_{Ms} 1)	[-]	1,25
Concrete edge failure				
Effective embedment depth for calculation in cracked concrete		$l_{f,cr}$	[mm]	35
Effective embedment depth for calculation in uncracked concrete		$l_{f,ucr}$	[mm]	53
Nominal diameter of a fastener		d_{nom}	[mm]	10

1) In absence of other national regulations.

Table C4.1: Characteristic values of tension and shear resistance under fire exposure

Anchor type				HybridPower, HybridPower A2, HybridPower A4, HybridPower R
				10
Overall plastic anchor embedment depth in the base material	h_{nom}		≥ [mm]	80
Tension loading				
Characteristic resistance **steel failure**	$N_{Rk,s,fi}$	R30	[kN]	0,45
		R60		0,35
		R90		0,25
		R120		0,20
Characteristic resistance **Concrete cone failure**	$N_{Rk,c,fi}$	R30 - R90	[kN]	1,20
		R120		1,00
Characteristic resistance **pullout failure**	$N_{Rk,p,fi}$	R30	[kN]	0,45
		R60		0,35
		R90		0,25
		R120		0,20
Shear loading				
Characteristic resistance **steel failure**	$V_{Rk,s,fi}$	R30	[kN]	2,00
		R60		1,50
		R90		1,00
		R120		0,80
Characteristic resistance **pryout failure**	$V_{Rk,cp,fi}$	R30 - R90	[kN]	1,20
		R120		1,00
Characteristic resistance **concrete edge failure**	$V_{Rk,c,fi}$	R30 - R90	[kN]	5,60
		R120		4,50
Characteristic resistance **steel failure**	$M^0_{Rk,s,fi}$	R30	[Nm]	2,09
		R60		1,62
		R90		1,07
		R120		0,80

Table C4.2: Characteristic spacings and characteristic edge distances of fasteners under fire exposure for tension and shear load

Anchor type			HybridPower, HybridPower A2, HybridPower A4, HybridPower R
			10
Spacing	$s_{cr,fi}$	[mm]	140
Edge distance	$c_{cr,fi}$	[mm]	70 for fire exposure from more than one side c_{min} ≥ 300 mm.

Table C5.1: Displacements under static and quasi static tension loads

Anchor type			HybridPower, HybridPower A2, HybridPower A4, HybridPower R
			10
Displacement – factor for tensile load[1)]			
δ_{N0} - factor	in cracked concrete	[mm/kN]	0,20
$\delta_{N\infty}$ - factor			0,30
δ_{N0} - factor	in uncracked concrete		0,60
$\delta_{N\infty}$ - factor			1,10

[1)] Calculation of effective displacement:
$\delta_{N0} = \delta_{N0}$ - factor x N
$\delta_{N\infty} = \delta_{N\infty}$ - factor x N

N = Action tension loading

Table C5.2: Displacements under static and quasi static shear loads

Anchor type			HybridPower, HybridPower A2, HybridPower A4, HybridPower R
			10
Displacement – factor for shear load[2)]			
δ_{V0} - factor	in cracked and uncracked concrete	[mm/kN]	6,50
$\delta_{V\infty}$ - factor			9,80

[2)] Calculation of effective displacement:
$\delta_{V0} = \delta_{V0}$ - factor x V
$\delta_{V\infty} = \delta_{V\infty}$ - factor x V

V = Action shear loading