

PRESTATIEVERKLARING

DoP 0416

voor fischer HybridPower (mechanisch anker voor gebruik in beton)

NL

- | | |
|--|--|
| 1. <u>Unieke identificatiecode van het producttype:</u> | DoP 0416 |
| 2. <u>Beoogd(e) gebruik(en):</u> | Bevestigingen in ongescheurd beton., zie bijlage, met name de bijlagen B1 - B3. |
| 3. <u>Fabrikant:</u> | fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Duitsland |
| 4. <u>Gemachtigde:</u> | – |
| 5. <u>Het systeem of de systemen voor de beoordeling en verificatie van de prestatiebestendigheid:</u> | 1 |
| 6. <u>Europees beoordelingsdocument:</u> | EAD 330232-02-0601 |
| Europese technische beoordeling: | ETA-26/0167; 2026-06-23 |
| Technische beoordelingsinstantie: | ETA-Danmark A/S |
| Aangemelde instantie(s): | 2873 TU Darmstadt |

7. Aangegeven prestatie(s):

Mechanische weerstand en stabiliteit (BWR 1)

Kenmerkende weerstand tegen spanningsbelasting (statische en quasi-statische belasting) Methode A:

- 1 Weerstand tegen staalbreuk: Bijlage C1
- 2 Weerstand tegen uittrekken: Bijlage C1
- 3 Weerstand tegen betonnen kegelbreuk: Bijlage C2
- 4 Robuustheid Bijlage C1
- 5 Minimale rand- en hartafstand: Bijlage B2
- 6 Randafstand om spleetbreuk onder belasting te voorkomen: Bijlage C2

Kenmerkende weerstand tegen schuifbelasting (statische en quasi-statische belasting):

- 7 Weerstand tegen staalbreuk (afschuifbelasting): Bijlage C3
- 8 Weerstand tegen uitbreken (pryout): Bijlage C3

Kenmerkende weerstand voor een vereenvoudigd ontwerp:

- 9 Methode B: NPD
- 10 Methode C: NPD

Verplaatsingen:

- 11 Verplaatsingen onder statische en quasi-statische belasting: Bijlage C5

Stijfheid:

- 12 Stijfheid in het elastische bereik bij trekbelasting: NPD
- 13 Stijfheidseigenschappen voor trekbelasting voor niet-lineaire veermodellen: NPD

Kenmerkende weerstand voor seismische prestatiecategorie C1:

- 14 Trekkraftweerstand: NPD
- 15 Weerstand afschuifbelasting, Factor ringvormige opening: NPD

Kenmerkende weerstand en verplaatsingen voor de seismische prestatiecategorieën C2:

- 16 Trekkraftweerstand, verplaatsingen: NPD
- 17 Weerstand afschuifbelasting, verplaatsingen, Factor ringvormige opening: NPD

Veiligheid in geval van brand (BWR 2)

- 18 Reactie op brand: Klasse (A1)

Weerstand tegen vuur:

- 19 Weerstand bij brand, staalbreuk (trekbelasting): Bijlage C4
- 20 Weerstand bij brand, uittrekken, (trekbelasting): Bijlage C4
- 21 Weerstand bij brand, staalbreuk (afschuifbelasting): Bijlage C4


Duurzaamheid:

- 22 Duurzaamheid: Bijlages B1

8. Geëigende technische documentatie en/of specifieke technische documentatie: **–**

De prestaties van het hierboven omschreven product zijn conform de aangegeven prestaties. Deze prestatieverklaring wordt in overeenstemming met Verordening (EU) nr. 305/2011 onder de exclusieve verantwoordelijkheid van de hierboven vermelde fabrikant verstrekt.

Ondertekend voor en namens de fabrikant door:



Dr. Christian Weber, Hoofd Ontwikkeling
Tumlingen, 2026-08-01



Dieter Pfaff, Hoofd van de Internationale Productiefederatie en Kwaliteitsbeheer

Deze DoP is opgesteld in meerdere talen. In het geval van geschillen over de interpretatie zal de Engelse tekst altijd prevaleren.
Het aanhangsel bevat vrijwillige en aanvullende informatie in het Engels die de (taal-neutraal gespecificeerde) wettelijke vereisten overschrijdt.

Translation guidance Essential Characteristics and Performance Parameters for Annexes

Vertaal assistent van de essentiële kenmerken en eigenschappen voor bijlagen

Mechanical resistance and stability (BWR 1)

Mechanische weerstand en stabiliteit (BWR 1)

Characteristic resistance under static and quasi-static loading, Method A

Kenmerkende weerstand tegen spanningsbelasting (statische en quasi-statische belasting) Methode A:

1	Resistance to steel failure: Weerstand tegen staalbreuk:	$N_{Rk,s}$ [kN], E_s [N/mm ²]
2	Resistance to pull- out failure: Weerstand tegen uittrekken:	$N_{Rk,p}$ [kN], ψ_c
3	Resistance to concrete cone failure: Weerstand tegen betonnen kegelbreuk:	$k_{cr,N}$, $k_{ucr,N}$ [-], h_{ef} , $c_{cr,N}$ [mm]
4	Robustness: Robuustheid	γ_{inst} [-]
5	Minimum edge distance and spacing: Minimale rand- en hartafstand:	c_{min} , s_{min} , h_{min} [mm]
6	Edge distance to prevent splitting under load: Randafstand om spleetbreuk onder belasting te voorkomen:	$N^0_{Rk,sp}$ [kN], $c_{cr,sp}$ [mm]

Characteristic resistance to shear load (static and quasi-static loading), Method A

Kenmerkende weerstand tegen schuifbelasting (statische en quasi-statische belasting):

7	Resistance to steel failure under shear load: Weerstand tegen staalbreuk (afschuifbelasting):	$V^0_{Rk,s}$ [kN], $M^0_{Rk,s}$ [Nm], k_7 [-]
8	Resistance to pry-out failure: Weerstand tegen uitbreken (pryout):	k_8 [-]

Characteristic Resistance for simplified design:

Kenmerkende weerstand voor een vereenvoudigd ontwerp:

9	Method B: Methode B:	F^0_{Rk} [kN], $M^0_{Rk,s}$ [Nm] ψ_c [-], c_{cr} , s_{cr} , c_{min} , s_{min} , h_{min} [mm]
10	Method C: Methode C:	F_{Rk} [kN], $M^0_{Rk,s}$ [Nm], c_{cr} , s_{cr} , h_{min} [mm]

Displacements

Verplaatsingen:

11	Displacements under static and quasi-static loading: Verplaatsingen onder statische en quasi-statische belasting:	δ_{N0} , $\delta_{N50years}$, $\delta_{N100years}$, δ_{V0} , $\delta_{V\infty}$ [mm]
----	---	--

12	Stiffness characteristics for tension loading for non-linear spring models: Stijfheid:	$k_{1,cr}$, $k_{2,cr}$, $k_{3,cr}$, $k_{4,cr}$ [kN/mm]
----	--	---

12	Stiffness in the elastic range under tension loading Stijfheid in het elastische bereik bij trekbelasting:	$k_{A,ucr}$, $k_{A,cr}$ [N/mm]
13	Stiffness characteristics for tension loading for non-linear spring models Stijfheidseigenschappen voor trekbelasting voor niet-lineaire veermodellen:	$k_{A,ucr}$, $k_{B,ucr}$, $k_{C,ucr}$, $k_{D,ucr}$ [N/mm] $k_{A,cr}$, $k_{B,cr}$, $k_{C,cr}$, $k_{D,cr}$ [N/mm]

Characteristic resistance for seismic performance category C1:

Kenmerkende weerstand voor seismische prestatiecategorie C1:

14	Resistance to tension load: Trekkrachtweerstand:	$N_{Rk,s,C1}$ [kN], $N_{Rk,p,C1}$ [kN]
15	Resistance to shear load:, Factor annular gap: Weerstand afschuifbelasting:, Factor ringvormige opening:	$V_{Rk,s,C1}$ [kN]

Characteristic resistance and displacements for seismic performance categorie C2:

Kenmerkende weerstand en verplaatsingen voor de seismische prestatiecategorieën C2:

16	Resistance to tension load, displacements: Trekkrachtweerstand, verplaatsingen:	$N_{Rk,s,C2}$ [kN], $N_{Rk,p,C2}$ [kN] $\delta_{N,C2(0,5)}$, $\delta_{N,C2(0,8)}$ [mm]
17	Resistance to shear load and displacements, factor annular gap: Weerstand afschuifbelasting, verplaatsingen, Factor ringvormige opening:	$V_{Rk,s,C2}$ [kN], $\delta_{V,C2(0,5)}$, $\delta_{V,C2(0,8)}$ [mm]

Safety in case of fire (BWR 2)

Veiligheid in geval van brand (BWR 2)

18	Reaction to fire: Reactie op brand:	Class
----	---	-------

Resistance to fire:

Weerstand tegen vuur:

19	Fire resistance to steel failure (tension load): Weerstand bij brand, staalbreuk (trekbelasting):	$N_{Rk,s,fi}$ [kN]
20	Fire resistance to pull-out failure (tension load): Weerstand bij brand, uittrekken, (trekbelasting):	$N_{Rk,p,fi}$ [kN]
21	Fire resistance to steel failure (shear load): Weerstand bij brand, staalbreuk (afschuifbelasting):	$V_{Rk,s,fi}$ [kN], $M^0_{Rk,s,fi}$ [Nm]

Aspects of durability

Duurzaamheid:

22	Durability: Duurzaamheid:	Class
----	-------------------------------------	-------

II SPECIFIC PART OF THE EUROPEAN TECHNICAL ASSESSMENT

1 Technical description of product

The fischer HybridPower is a plastic anchor consisting of a plug sleeve made of polyamide combined with a metal skeleton (power wedge), and a special screw made of either galvanized steel with an additional organic coating or stainless steel according to Annex A3. The anchor is available with two different head types; a hexagon head (type FUS) and a countersunk head (type T).

The anchors are intended for use in both cracked and uncracked concrete of strength classes ranging from C20/25 to C50/60.

The anchor is screwed into a predrilled cylindrical drill hole, and the power wedges interlock with the base material ensuring a secure anchorage.

The product description is given in Annex A and the intended use specifications of the product are detailed in Annex B.

2 Specification of the intended use(s) in accordance with the applicable European Assessment Document (hereinafter EAD)

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The provisions made in this European Technical Assessment are based on an assumed intended working life of the anchor of 50 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer or Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

Characteristic	Assessment of characteristic
----------------	------------------------------

3.1 Mechanical resistance and stability (BWR1)

Characteristic resistance to tension load (static and quasi-static loading) Method A

Resistance to steel failure under tension load	Annex C1
Resistance to pull-out failure	Annex C1
Resistance to concrete cone failure	Annex C2
Robustness	Annex C1
Minimum edge distance and spacing	Annex B2
Edge distance to prevent splitting under load	Annex C2

Characteristic resistance to shear load (static and quasi-static loading)

Resistance to steel failure under shear load	Annex C3
Resistance to pry-out failure	Annex C3

Characteristic resistance for simplified methods

Method B	Not relevant
Method C	Not relevant

Displacements

Displacements under static and quasi-static loading	Annex C5
---	----------

Stiffness

Stiffness in the elastic range under tension loading	No performance assessed
Stiffness characteristics for tension loading for non-linear spring models	No performance assessed

Characteristic resistance for seismic performance category C1

Resistance to tension load	No performance assessed
Resistance to shear load	No performance assessed

Characteristic resistance and displacements for seismic performance category C2

Resistance to tension load and displacements	No performance assessed
--	-------------------------

Characteristic	Assessment of characteristic
Resistance to shear load and displacements	No performance assessed

3.2 Safety in case of fire (BWR2)

Reaction to fire	Class A1
------------------	----------

Resistance to fire

Fire resistance to steel failure under tension load	Annex C4
Fire resistance to pull-out failure	Annex C4
Fire resistance to steel failure under shear load	Annex C4

3.3 Aspects of durability

Durability	Annex B1
------------	----------

See additional information in section 3.9

3.9 General aspects related to the performance of the product

The European Technical Assessment is issued for the product on the basis of agreed data/information, deposited with ETA-Danmark, which identifies the product that has been assessed and judged. Changes to the product or production process, which could result in this deposited data/information being incorrect, should be notified to ETA-Danmark before the changes are introduced. ETA-Danmark will decide whether or not such changes affect the ETA and consequently the validity of the CE marking on the basis of the ETA and if so whether further assessment or alterations to the ETA, shall be necessary.

4 Assessment and verification of constancy of performance (AVCP) (hereinafter AVCP) system applied, with reference to its legal base.

4.1 AVCP system

According to the decision 1996/582/EC of the European Commission, the system(s) of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No. 305/2011) is 1.


5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at ETA-Danmark prior to CE marking.

The following standards and documents are referred to in this European Technical Assessment:

- EOTA European Assessment Document EAD 330232-02-0601: Mechanical fasteners for use in concrete
- EN 206:2013+A2:2021: Concrete – Specification, performance, production and conformity
- EN 1992-4:2019-04: Eurocode 2 - Design of concrete structures - Part 4: Design of fastenings for use in concrete; German version EN 1992-4:2018
- EN 1993-1-4:2006 + A1:2015: Eurocode 3: Design of steel structures - Part 1-4: General rules - Supplementary rules for stainless steels
- EN ISO 4042:2018: Fasteners – Electroplated coating systems

fischer HybridPower



Legend

- d_0 = Nominal drill hole diameter
- h_{nom} = Overall plastic anchor embedment depth in the base material
- h_1 = Depth of drill hole to deepest point
- h = Thickness of concrete member
- t_{fix} = Thickness of fixture and / or non-load bearing layer

Figure not to scale


fischer HybridPower

Product description
Installed anchor

Annex A1



Appendix 6 / 16

Anchor sleeve – HybridPower





Special screws

Countersunk screw



Hexagonal screw with washer



- 1) Additional marking for the special screw, stainless steel version: e.g. "A4" or "R" or "A2".
2) Internal driving feature for Torx bit is optional for hexagonal head.
3) Optional additional version with underhead ribs.

Table A2.1: Dimensions

Anchor type	Anchor sleeve					Special screw		
	h_{nom} [mm]	d_{nom} [mm]	l_D [mm]	l_{sf} [mm]	d_{sf} [mm]	d_s [mm]	l_G [mm]	l_s [mm]
HybridPower FUS	80	10	90-230	2,5	15	7,0	77	l_D
HybridPower T	80	10	90-230	2,5	15	7,0	77	l_D

Legend

h_{nom}	=	Overall plastic anchor embedment depth in the base material
d_{nom}	=	Nominal diameter of the anchor sleeve
l_D	=	Length of the anchor sleeve
l_{sf}	=	Thickness of the anchor sleeve collar
d_{sf}	=	Diameter of the anchor sleeve collar
d_s	=	Diameter of the screw
l_G	=	Thread length of the screw
l_s	=	Length of the screw

Figures not to scale

fischer HybridPower

Product description

Anchor type and special screws
Marking and dimensions

Annex A2

Appendix 7 / 16

Table A3.1: Materials

Name	Material
HybridPower anchor sleeve	- Polyamide, PA6, colour: red
HybridPower skeleton	- Ferritic stainless steel
Special screw	- Galvanised steel gvz with Zn5/Ag or Zn5/An in accordance with EN ISO 4042 with additional organic layer (Zn5/Ag/T7 or Zn5/An/T7, resp., total layer thickness $\geq 6 \mu\text{m}$) <u>or</u> - Stainless steel "A2" of corrosion resistance class CRC II in accordance with EN 1993-1-4 <u>or</u> - Stainless steel "A4" or "R" of corrosion resistance class CRC III in accordance with EN 1993-1-4

fischer HybridPower**Product description**
Materials**Annex A3**

Appendix 8 / 16

Specifications of intended use

Anchorage subject to:

- Static and quasi-static loads.
- Fire exposure.

Base materials:

- Reinforced or unreinforced compacted normal weight concrete without fibres (cracked or uncracked) in accordance with EN 206-1.
- Strength classes C20/25 to C50/60 in accordance with EN 206-1.

Use conditions (Environmental conditions):

- Temperature Range: - 20 °C to + 50 °C.
- Structures subject to dry internal conditions (HybridPower, HybridPower A2, HybridPower A4, HybridPower R).
- For all other conditions according to EN 1993-1-4 corresponding to corrosion resistance class (CRC):
 - for CRC II: for HybridPower A2
 - for CRC III: for HybridPower A4 or HybridPower R

Design:

- The structural design is conducted under responsibility of a designer experienced in the field of anchorages and concrete works.
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the fastener is indicated on the design drawings (e.g. position of the fastener relative to reinforcement or to supports, etc.).
- Design of fastenings according to EN 1992-4.

Installation:

- Fastener installation is to be carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters on the site.
- Use of the fastener only as supplied by the manufacturer without exchanging the components of the fastener.
- Hammer drilling.
- Drill hole created perpendicular +/- 5° to concrete surface, positioning without damaging the reinforcement.
- In case of aborted hole: new drilling at a minimum distance twice the depth of the aborted drill hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application.
- Installation temperature: - 20 °C to + 40 °C.
- Exposure to UV due to solar radiation of the anchor not protected by rendering ≤ 6 weeks.
- No ingress of water in the borehole at temperatures < 0°C.

fischer HybridPower

Intended use
Specifications

Annex B1

Appendix 9 / 16

Table B2.1: Installation parameters

Anchor type			HybridPower, HybridPower A2, HybridPower A4, HybridPower R
Nominal drill hole diameter	d_0	= [mm]	10
Cutting diameter of drill bit	d_{cut}	≤ [mm]	10,45
Overall plastic anchor embedment depth in the base material	h_{nom}	≥ [mm]	80
Depth of drill hole to deepest point	h_1	≥ [mm]	90
Diameter of clearance hole in the fixture	d_f	≤ [mm]	10,50 ¹⁾
Thickness of fixture and / or non-load bearing layer	t_{fix}	≥ [mm]	1

¹⁾ In combination of hexagon screw with washer and anchor sleeve, use in elongated hole under tensile load is allowed.




Table B2.2: Minimum thickness of concrete members, minimum edge distances and minimum spacing

Anchor type		HybridPower, HybridPower A2, HybridPower A4, HybridPower R
		10
Minimum edge distance and spacing		
Uncracked concrete	c_{min}	50
Cracked concrete		
Uncracked concrete	s_{min} [mm]	50
Cracked concrete		
Minimum thickness of concrete member	h_{min}	100

Figure not to scale

fischer HybridPower

Intended use


Installation parameters
Minimum thickness of member, edge distances and spacing

Annex B2


Appendix 10 / 16

Installation instructions


The following pictures show fixing through timber in concrete.




1. Drill the bore hole as per Table B2.1 using hammer drilling.
2. Remove dust from borehole.



3. Insert anchor (screw and sleeve) by using a hammer until the collar of the plastic sleeve is flush with the surface of the fixture.



4. The screw is screwed-in until the head of the screw touches the sleeve. The anchor is correctly installed, if the head of the screw fits tight on the surface and nor the anchor sleeve neither the screw cannot be turned-in any further.



5. Correctly installed anchor.

Figures not to scale

fischer HybridPower

Intended use
Installation instructions

Annex B3

Appendix 11 / 16

Table C1.1: Characteristic values of tension resistance under static and quasi-static action

Anchor type		HybridPower, HybridPower A2, HybridPower A4, HybridPower R	
		10	
Overall plastic anchor embedment depth in the base material	$h_{nom} \geq$ [mm]	80	
Steel failure			
Characteristic tension resistance	HybridPower	$N_{Rk,s}$ [kN]	21,70
	HybridPower A2		
	HybridPower A4		
	HybridPower R		
Partial factor for steel failure	HybridPower	$\gamma_{Ms}^{1)}$ [-]	1,55
	HybridPower A2		
	HybridPower A4		
	HybridPower R		
Pullout failure			
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p,cr}$ [kN]	2,00 ²⁾	
Increasing factor ψ_c for cracked concrete $N_{Rk,p,cr} = \psi_c \times N_{Rk,p,cr}$ (C20/25)	C25/30	[-]	1,00
	C30/37		
	C35/45		
	C40/50		
	C45/55		
	C50/60		
Installation sensitivity factor for cracked concrete	$\gamma_{inst,cr}$ [-]	1,00	
Characteristic resistance in uncracked concrete C20/25	$N_{Rk,p,ucr}$ [kN]	10,50	
Increasing factor ψ_c for uncracked concrete $N_{Rk,p,ucr} = \psi_c \times N_{Rk,p,ucr}$ (C20/25)	C25/30	[-]	1,05
	C30/37		1,08
	C35/45		1,12
	C40/50		1,15
	C45/55		1,18
	C50/60		1,20
Installation sensitivity factor for uncracked concrete	$\gamma_{inst,ucr}$ [-]	1,00	

¹⁾ In absence of other national regulations.

²⁾ If it is ensured that the temperature during working life does not exceed + 30°C, the values may be increased by 1,08.

fischer HybridPower

Performances

Characteristic values of tension resistance under static and quasi-static action

Annex C1

Appendix 12 / 16

Table C2.1: Characteristic values of tension resistance under static and quasi-static action

Anchor type				HybridPower, HybridPower A2, HybridPower A4, HybridPower R
				10
Overall plastic anchor embedment depth in the base material				80
Concrete cone and splitting failure				
Effective embedment depth for calculation	cracked concrete	$h_{ef,cr} \geq$	[mm]	35
	uncracked concrete	$h_{ef,ucr} \geq$	[mm]	53
Factor for cracked concrete		$k_{cr,N}$	[-]	7,7
Factor for uncracked concrete		$k_{ucr,N}$		11,0
Characteristic spacing	cracked concrete	$s_{cr,N,cr}$	[mm]	105
	unracked concrete	$s_{cr,N,ucr}$		159
Characteristic edge distance	cracked concrete	$c_{cr,N,cr}$	[mm]	53
	unracked concrete	$c_{cr,N,ucr}$		80
Characteristic spacing for splitting failure	cracked concrete	$s_{cr,sp,cr}$	[mm]	2 x $c_{cr,sp}$
	unracked concrete	$s_{cr,sp,ucr}$		
Characteristic edge distance for splitting failure	cracked concrete	$c_{cr,sp,cr}$	[mm]	49
	unracked concrete	$c_{cr,sp,ucr}$		53
Characteristic resistance to splitting		$N_{Rk,sp}^0$	[kN]	$\min \{N_{Rk,c}^0; N_{Rk,p}\}^{1)}$

¹⁾ $N_{Rk,c}^0$ according to EN 1992-4.

fischer HybridPower

Performances

Characteristic values of tension resistance under static and quasi-static action

Annex C2

Appendix 13 / 16

Table C3.1: Characteristic values of shear resistance under static and quasi-static action

Anchor type		HybridPower, HybridPower A2, HybridPower A4, HybridPower R	
		10	
Steel failure without lever arm			
Characteristic resistance	HybridPower	$V_{Rk,s}^0$ [kN]	10,80
	HybridPower A2		
	HybridPower A4		
	HybridPower R		
Partial factor for steel failure		$\gamma_{Ms}^{1)}$	1,29
Factor for ductility	HybridPower	k_7 [-]	0,80
	HybridPower A2		1,00
	HybridPower A4		
	HybridPower R		
Steel failure with lever arm and Concrete pryout failure			
Characteristic bending resistance	HybridPower	$M_{Rk,s}^0$ [Nm]	20,60
	HybridPower A2		
	HybridPower A4		
	HybridPower R		
Factor for pryout failure		k_8	1,00
Partial factor for steel failure		$\gamma_{Ms}^{1)}$ [-]	1,25
Concrete edge failure			
Effective embedment depth for calculation in cracked concrete		$l_{f,cr}$	35
Effective embedment depth for calculation in uncracked concrete		$l_{f,ucr}$ [mm]	53
Nominal diameter of a fastener		d_{nom}	10

¹⁾ In absence of other national regulations.

fischer HybridPower

Performances

Characteristic values of shear resistance under static and quasi-static action

Annex C3

Appendix 14 / 16

Table C4.1: Characteristic values of tension and shear resistance under fire exposure				
Anchor type			HybridPower, HybridPower A2, HybridPower A4, HybridPower R	
			10	
Overall plastic anchor embedment depth in the base material	h_{nom}	$\geq$ [mm]	80	
Tension loading				
Characteristic resistance steel failure	$N_{Rk,s,fi}$	R30	0,45	
		R60	0,35	
		R90	0,25	
		R120	0,20	
Characteristic resistance Concrete cone failure	$N_{Rk,c,fi}$	R30 [kN]	1,20	
		- R90		
		R120	1,00	
Characteristic resistance pullout failure	$N_{Rk,p,fi}$	R30	0,45	
		R60	0,35	
		R90	0,25	
		R120	0,20	
Shear loading				
Characteristic resistance steel failure	$V_{Rk,s,fi}$	R30	2,00	
		R60	1,50	
		R90	1,00	
		R120	0,80	
Characteristic resistance pryout failure	$V_{Rk,cp,fi}$	R30 [kN]	1,20	
		- R90		
		R120	1,00	
Characteristic resistance concrete edge failure	$V_{Rk,c,fi}$	R30	5,60	
		- R90		
		R120	4,50	
Characteristic resistance steel failure	$M^0_{Rk,s,fi}$	R30 [Nm]	2,09	
		R60	1,62	
		R90	1,07	
		R120	0,80	

Table C4.2: Characteristic spacings and characteristic edge distances of fasteners under fire exposure for tension and shear load			
Anchor type		HybridPower, HybridPower A2, HybridPower A4, HybridPower R	
		10	
Spacing	$S_{cr,fi}$	140	
	[mm]		
Edge distance	$C_{cr,fi}$	70	
		for fire exposure from more than one side $c_{min} \geq 300$ mm.	

fischer HybridPower	Annex C4
Performances Characteristic values of resistance under fire exposure	
Appendix 15 / 16	

Table C5.1: Displacements under static and quasi static tension loads

Anchor type	HybridPower, HybridPower A2, HybridPower A4, HybridPower R
	10
Displacement – factor for tensile load¹⁾	
δ_{N0} - factor in cracked concrete	0,20
$\delta_{N\infty}$ - factor [mm/kN]	0,30
δ_{N0} - factor in uncracked concrete	0,60
$\delta_{N\infty}$ - factor	1,10

1) Calculation of effective displacement:

$$\delta_{N0} = \delta_{N0} - \text{factor} \times N$$

$$\delta_{N\infty} = \delta_{N\infty} - \text{factor} \times N$$

N = Action tension loading

Table C5.2: Displacements under static and quasi static shear loads

Anchor type	HybridPower, HybridPower A2, HybridPower A4, HybridPower R
	10
Displacement – factor for shear load²⁾	
δ_{V0} - factor in cracked and uncracked concrete [mm/kN]	6,50
$\delta_{V\infty}$ - factor	9,80

2) Calculation of effective displacement:

$$\delta_{V0} = \delta_{V0} - \text{factor} \times V$$

$$\delta_{V\infty} = \delta_{V\infty} - \text{factor} \times V$$

V = Action shear loading

fischer HybridPower

Performances

Displacements under tension and shear loads

Annex C5

Appendix 16 / 16