

## DEKLARACJA WŁAŚCIWOŚCI UŻYTKOWYCH

### DoP 0322

dla kotwy panelowej fischer-Zykon FZP II (for Mirage)

PL

1. Niepowtarzalny kod identyfikacyjny typu wyrobu: **DoP 0322**
2. Zamierzone zastosowanie: **Kotwa do mocowania od tylnej strony płyt fasadowych z płytek ceramicznych "Mirage", zobacz załącznik, w szczególności aneksy B1 - B6.**
3. Producent: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Niemcy**
4. Upoważniony przedstawiciel: **-**
5. System(-y) oceny i weryfikacji stałości właściwości użytkowych: **2+**
6. Europejski dokument oceny: **EAD 330030-00-0601**  
Europejska ocena techniczna: **ETA-22/0400; 2022-08-25**  
Jednostka ds. oceny technicznej: **ETA-DANMARK A/S**  
Jednostka lub jednostki notyfikowane: **2873 TU Darmstadt**
7. Deklarowane właściwości użytkowe:  
**Wytrzymałość mechaniczna i stabilność osadzenia (BWR 1)**  
Charakterystyczna nośność na wyrwanie lub wyrwanie pod wpływem obciążenia rozciągającego: Aneks C1  
Charakterystyczna nośność na wyrwanie lub wyrwanie pod wpływem obciążenia ścinającego: Aneks C1  
Charakterystyczna nośność na wyrwanie lub wyrwanie pod wpływem połączonego obciążenia rozciągającego i ścinającego: Aneks C1 **Y=NPD; F<sub>Rk</sub>=NPD**  
  
Odległości osiowe i od krawędzi: Aneksy B3, C1  
Trwałość: Aneks A3, B1  
Charakterystyczna nośność na zniszczenie stali przy obciążeniu rozciągającym i ścinającym: NPD  
  
**Ochrona przeciwpożarowa (BWR 2)**  
Reakcja na ogień: Klasy (A1)
8. Odpowiednia dokumentacja techniczna lub specjalna dokumentacja techniczna: **-**

Właściwości użytkowe określonego powyżej wyrobu są zgodne z zestawem deklarowanych właściwości użytkowych. Niniejsza deklaracja właściwości użytkowych wydana zostaje zgodnie z rozporządzeniem (UE) nr 305/2011 na wyłączną odpowiedzialność producenta określonego powyżej.

W imieniu producenta podpisał(-a):



Dr.-Ing. Oliver Geibig, Dyrektor Zarządzający ds. Jednostek Biznesowych i Inżynierii  
Tumlingen, 2022-10-12



Jürgen Grün, Dyrektor Zarządzający ds. Chemii i Jakości

Niniejsza Deklaracja Właściwości Użytkowych została przygotowana w różnych językach. W razie wątpliwości w interpretacji, wersja angielska jest zawsze miarodajna.

Załącznik zawiera dobrowolne i uzupełniające informacje w języku angielskim (neutralne językowo), a wykraczające poza wymagania prawne.

## II SPECIFIC PART OF THE EUROPEAN TECHNICAL ASSESSMENT

### 1 Technical description of product

The fischer ZYKON FZP II for fixing Mirage facade panels is a special anchor made of stainless steel, consisting of an anchor with M6 external thread, an expansion part, a shim washer and a hexagonal nut. The anchor is put into an undercut drill hole and by driving-in the screw it is placed form-fitted and deformation-controlled.

The Mirage facade panels are made from ceramic tiles in accordance with EN 14411 and have the following characteristics:

	Values
E-Module [N/mm <sup>2</sup> ], mean	30000
Thermal Expansion (µm/mK)	6,6 m/mK
5% Fractile bending resistance, characteristic	45 N/mm <sup>2</sup>
Density [g/cm <sup>3</sup> ], nominal	2,55
Frost resistance	Yes

For the installed anchor see figure in Annex A1.

### 2 Specification of the intended use in accordance with the applicable European Assessment Document (hereinafter EAD)

The fischer ZYKON FZP II are intended for fixing Mirage facade panels for which requirements for mechanical resistance and stability in the sense of the Basic Works Requirements 1 of Regulation 305/2011 shall be fulfilled. The façade panels shall correspond to the drawings and specifications of this European Technical Assessment. The intended use specifications of the product are detailed in the Annex B1.

The façade panels with rear fixing by the anchor may only be used for rear ventilated front curtain walls. Each façade panel shall be fixed technically strain-free with at least four anchors in a rectangular arrangement via single agraffes on a capable substructure (for small panels or small fitted pieces, differential or fill-in pieces the number and position of the anchors shall be chosen constructively).

The anchor may be used in structures subject to dry internal conditions and also in structures subject to

external atmospheric exposure (including industrial and marine environment), if no particular aggressive conditions exist. Such particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurisation plants or road tunnels where de-icing materials are used).

The provisions made in this European Technical Assessment are based on an assumed working life of the anchor of 50 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer or Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

### 3 Performance of the product and references to the methods used for its assessment

---

Characteristic	Assessment of characteristic
<b>3.1 Mechanical resistance and stability (BWR1)</b>	
Characteristic load bearing capacity and displacements	The anchor corresponds to the drawings and specifications given in Annex A2-A3. The characteristic material values, dimensions and tolerances of the anchor not indicated in Annex A2-A3 shall correspond to the respective values laid down in the technical documentation of this European Technical Assessment.
Characteristic resistance to breakout or pull-out failure under tension load	The characteristic values for the design of the façade panels with rear fixing by the anchor are given in Annex C1.
Characteristic resistance to breakout or pull-out failure under shear load	
Edge distance and spacing	
Characteristic resistance to steel failure under tension and shear load	
Characteristic resistance to breakout or pull-out failure under combined tension and shear load	No performance assessed
Durability	The anchors are made from stainless steel (material no. 1.4401, 1.4571 or 1.4404) corresponding to corrosion resistance class (CRC) III in EN 1993-1-4 table A.3.
<b>3.2 Safety in case of fire (BWR2)</b>	
Reaction to fire	The anchors are made from steel classified as Euroclass A1 in accordance with EN 13501-1 and Commission Delegated Regulation 2016/364

---


## **4 Attestation and verification of constancy of performance (AVCP)**

### **4.1 AVCP system**

According to the decision 97/161/EC the European Commission, the system(s) of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No 305/2011) is 2+.


**Installed fastener**

**Figure A1:**



**Example of façade panel on substructure**

**Figure A2:**



**fischer Zykon panel anchor FZP II - T**

**Product description**  
Installed anchoring and fixing example


**Annex A 1**

Appendix 4 / 13

**Type of anchor**


**Anchor with external thread M6**

**Figure A3:**




**Type of mounting**

**Figure A4:**



**Identification system**




<b>fischer Zykon panel anchor FZP II - T</b>		<b>Annex A 2</b> Appendix 5 / 13
<b>Product description</b> Type of anchor, built-in state and identification system		

**Parts of anchor and materials**

**Cone bolt external thread M6** (Option: UNC thread)

**Figure A5:**



**Expansion part**

For cone bolts with external thread M6


**Figure A6:**



**Shim washer**

For cone bolts with external thread M6


**Figure A7:**



**Hexagonal nut**

For cone bolts with external thread M6

**Figure A8:**



**Table A1: Material of anchor parts**

Anchor parts	Material
Cone bolt	Stainless steel, EN 10088 :2014
Expansion part	Stainless steel, EN 10088 :2014
Shim washer	Polyamide 6.6
Hexagonal nut	Aluminum, EN 755:2016 Stainless steel, EN 10088 :2014

**fischer Zykon panel anchor FZP II - T**

**Product description**  
Parts of anchor and material

**Annex A 3**

Appendix 6 / 13

## Specifications of intended use

### Anchorage subject to:

- Static and quasi-static loads.

### Use conditions (Environmental conditions):

- According to the corrosion resistance class (CRC) according to EN 1993-1-4:2015 (ETA Section 3.1)

### Anchorage ground:

- The Mirage façade panels shall be in accordance with EN 144112016 "Ceramic tiles – definition, classification, characteristics, assessment and verification of constancy of performance and marking". The Mirage façade panels have to meet the requirements of group BI<sub>a</sub> according to EN 14411:2016.
- The characteristic values of the façade panels correspond to Table B1.

### Design:

- The design of anchorages under static and quasistatic load is carried out in accordance with the specifications of the façade panel manufacturer.
- The façade panels, their fixings as well as the substructure including its connection to wall brackets and their connection to the construction works are designed for the respective case of application under the responsibility of an engineer skilled in the field of façade construction.
- Verifiable calculation notes and drawings shall be prepared taking account of the loads to be anchored, the nature and strength of the base materials and the dimensions of the anchorage members as well as of the relevant tolerances. The position of the anchor is indicated on the design drawings.
- Each façade panel is fixed with at least four anchors in a rectangular arrangement via single clasps or panel support profiles on the substructure. For small panels or small fitted pieces, differential or fill- in pieces the number and position of the anchors shall be chosen constructively.
- Edge distance and spacing shall be observed. For small panels, differential and fitted pieces, the edge and axial spacing shall be chosen constructively.
- The substructure is constructed such that the façade panels are fixed technically strain-free via skids (loose bearings) and one fixed point (fixed bearing). The fixed point may be placed at the panel edge or in the panel field.
- Two fixing points of the façade panel are designed such that they are able to carry the dead load of the façade panel.
- If constraining forces are present, these must be considered for the design.
- When using clasps on horizontal support profiles, the horizontal fixing points of a facade panel at the same height must each be fixed to the same support profile.

**fischer Zykon panel anchor FZP II - T**

**Intended use**  
Specifications

**Annex B 1**

Appendix 7 / 13



**Table B1: Characteristic values of façade panels – geometrical and physical properties**

Trade name			Mirage
Country of origin			Italy
Maximum panel size	L x H or H x L	[mm]	1198 x 2398
Nominal panel thickness	$h_{nom} =$	[mm]	9
Panel thickness (minimum)	$h_{min} =$	[mm]	9,5
Panel thickness (maximum)	$h_{max} =$	[mm]	8,5
Dead load	$g_k =$	[kN/m <sup>2</sup> ]	0,225
Specific weight	$\gamma =$	[kN/m <sup>3</sup> ]	25,0
Density - dry	$\rho \geq$	[g/cm <sup>3</sup> ]	2,55
Modulus of elastic	$E_{mean} =$	[N/mm <sup>2</sup> ]	30000
Poisson ratio	$\nu =$	[-]	0,2
Coefficient of thermal expansion	$\alpha_T =$	[10 <sup>-6</sup> K <sup>-1</sup> ]	6,6
Characteristic bending strength	$\sigma_{Rk} =$	[N/mm <sup>2</sup> ]	45

**fischer Zykon panel anchor FZP II - T**

**Intended use**  
Specifications

**Annex B 2**


Appendix 8 / 13

## Installation:

- The drillings are done at the factory or on site under workshop conditions; when making the drillings on site the execution is supervised by the responsible project supervisor or a skilled representative of the project supervisor.
- Making of the undercut drilling is done with a special drill bit or a special CNC drill bit according to Annex B 4 and a special drilling device in accordance with the information deposited with Deutsches Institut für Bautechnik.
- The drilling residues are removed from the drill hole.
- In case of aborted hole: new drilling at a minimum distance away of twice the depth of the aborted hole.
- The geometry of the drill hole is checked on 1 % of all drillings. The following dimensions shall be checked and documented according to manufacturer's information and testing instructions by means of a control aids according to Annex B 7, Figure B5, B6 and B7.
  - Diameter of the cylindrical drill hole.
  - Diameter of the undercut.
  - Remaining wall thickness (drill hole depth and panel thickness respectively).
- If the tolerance given in Annex B 4, Table B2 is exceeded, the geometry of the drill hole shall be checked on 25 % of the drillings performed. No further drill hole may exceed the tolerances otherwise all the drill holes shall be controlled. Drilling holes falling below or exceeding the tolerances shall be rejected.
 

Note: Checking the geometry of the drill hole on 1 % of all drillings means that on one of the 25 panels (this corresponds to 100 drillings for panels with 4 undercut anchors) one drilling shall be checked. If the tolerances given in Annex B 4 Table B2 are exceeded the extent of the control shall be increase to 25 % of the drillings, i.e. one drilling each shall be checked on all the 25 panels.
- In addition, every 500<sup>th</sup> drill hole and drill change the diameter of the undercut must be checked with the internal quick test.
- The anchors are installed in a deformation controlled manner. For this purpose suitable installation tools per Annex B 5, Figure B4 shall be used. The anchor is set correctly if, in the state, the spacer the bolt projection "b" as per Annex A 2, Figure B4 or Annex B 6, Illustration 5.1 is observed.
- During transport and storage on site the façade panels are protected from damages; the façade panels are not to be hung up jerkily (if need be lifters shall be used for hanging up the façade panels); façade panels and reveal panels respectively with incipient cracks are not be installed.
- The façade panels are arranged in a "reclined" or "upright" position.
- Overhead mounting is permitted (e.g. mounting of ceiling cladding)
- The façade are installed by skilled specialists and the laying instructions of the manufacturer shall be paid attention to.
- The façade panels must not be used for the transmission of impact loads and for the protection against falling.

**Figure B1: Definition of edge and centre distance**



fischer Zykon panel anchor FZP II - T


Intended use  
Installation

**Annex B 3**

Appendix 9 / 13

## Geometry of the drill hole

Figure B2:



## Special drills

Figure B3:

Examples:




Table B2: Drill hole dimensions [mm]

$\varnothing d_0$	$\varnothing d_1$	$h_r^*$	$n$	$h_v$	$h_{nom}$
11,2 ± 0,2	13,5 ± 0,3	≈ 4,0	≈ 4	5 $\begin{matrix} +0,4 \\ -0 \end{matrix}$	≥ 9

\* Is to be complied with in case of deviations from  $h_{nom}$

fischer Zykon panel anchor FZP II - T

### Intended use

Drill bit, geometry of the drill hole and installation parameters

Annex B 4


Appendix 10 / 13

**Setting tools**


**Figure B4:**



Manual setting tool SGT




Cordless screwdriver with setting tool e.g. SGA or screw socket



Battery-setting tool SGB

**Means for undercut control  $\varnothing d_1$**

**Figure B5:**



Internal quick test


**Volume gauge**



HVL-T (Undercut minimum volume gauge)

**Figure B6:**


**Go / noGo gauge for checking cylindrical drill hole diameter  $d_0$**



DPL-T (Diameter gauge)

**Means for measuring drill hole depth  $h_1$  and drill hole diameter  $d_0$**

**Figure B7:**



Calliper with depth gauge

**fischer Zykon panel anchor FZP II - T**

**Intended use**

Setting devices and testing equipment

**Annex B 5**

Appendix 11 / 13


# Installation instructions

Example: Set with SGA


1.)




2.)




3.)




4.)



5.1.)



5.2.)



fischer Zykon panel anchor FZP II - T

Intended use  
Installation instructions

Annex B 6

Appendix 12 / 13

**Table C1: Characteristic values of anchors and panels**

Anchor type			FZP II 11x5 M6/T
Façade panel <sup>3)</sup>			<b>Mirage</b>
Nominal panel thickness	$h_{nom} \geq$	[mm]	9
Embedment depth <sup>2)</sup>	$h_v =$	[mm]	5
Characteristic resistance	Tension load <sup>1)</sup>	$N_{Rk} =$	[kN]
	Shear load <sup>1)</sup>	$V_{Rk} =$	[kN]
Trilinear limit	Interaction	$X =$	[-]
Minimum edge distance		$a_r =$	[mm]
Spacing		$a \leq$	[mm]

1) In case of coincident stress of an anchor due to tension and shear load following equation shall be observed:

$$\frac{N_{Ed}}{N_{Rd}} + \frac{V_{Ed}}{V_{Rd}} \leq 1.0$$

2) For FZP II: anchoring depth  $h_v =$  drill hole depth  $h_1 =$  embedment depth  $h_s$

3) See annex B1 for additional characteristics of the façade

**fischer Zykon panel anchor FZP II - T**

**Performances**

Characteristic values of anchors and panels

**Annex C 1**

Appendix 13 / 13