



DECLARAÇÃO DE DESEMPENHO



N.o 0069 – PT

1. Código de identificação único do produto-tipo: **Âncora suspensa EA II**

2. Utilização(ões) prevista(s):

Produto	Utilização/ões pretendida/s
Âncoras metálicas para utilização em betão (tipo pesado)	Fixação pós-instalada em betão não fissurado, Ver anexo, especialmente anexos B 1 - B 4

3. Fabricante: **fischerwerke GmbH & Co. KG, Klaus-Fischer-Straße 1, 72178 Waldachtal, Alemanha**

4. Mandatário: --

5. Sistema(s) de avaliação e verificação da regularidade do desempenho (AVCP): **1**

6a. Norma harmonizada: ---

Organismo(s) notificado(s): ---

6b. Documento de Avaliação Europeu **ETAG 001; 2013-04**

Avaliação Técnica Europeia **ETA-07/0135; 2016-12-09**

Organismo de Avaliação Técnica: **DIBt**

Organismo(s) notificado(s): **1343 – MPA Darmstadt**

7. Desempenho(s) declarado(s):

Resistência mecânica e estabilidade (BWR 1)

Característica essencial	Desempenho
Resistência característica para ação estática e quase estática, deslocamentos	Ver anexo, especialmente anexos C 1 - C 4

Segurança em caso de incêndio (BWR 2)

Característica essencial	Desempenho
Reacção ao fogo	As fixações satisfazem os requisitos da Classe A 1
Resistência ao fogo	NPD

8. Documentação Técnica Adequada e/ou Documentação Técnica Específica: ---

O desempenho do produto identificado acima está em conformidade com o conjunto de desempenhos declarados. A presente declaração de desempenho é emitida, em conformidade com o Regulamento (UE) n.o 305/2011, sob a exclusiva responsabilidade do fabricante identificado acima.

Assinado por e em nome do fabricante por:

Andreas Bucher, Dipl.-Ing.

Wolfgang Hengesbach, Dipl.-Ing., Dipl.-Wirtsch.-Ing.

i.V. A. Bucher

i.V. W. Hengesbach

Tumlingen, 2016-12-15

- Este DoP foi preparado em diferentes línguas. Em caso de litígio sobre a interpretação, a versão em inglês prevalecerá sempre.

- O Anexo inclui informações voluntárias e complementares em inglês que excedem os requisitos legais (linguisticamente especificados).

Specific Part

1 Technical description of the product

The fischer drop-in anchor EA II is an anchor made of galvanized or stainless steel which is placed into a drilled hole and anchored by deformation-controlled expansion.

The fixture shall be anchored with a fastening screw or threaded rod.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the anchor of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance for static and quasi-static loading, displacements	See Annex C 1 to C 4

3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Anchorage satisfy requirements for Class A1
Resistance to fire	No performance assessed


3.4 Safety in use (BWR 4)

The essential characteristics regarding Safety in use are included under the Basic Works Requirement Mechanical resistance and stability.


4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with guideline for European technical approval ETAG 001, April 2013 used as European Assessment Document (EAD) according to Article 66 Paragraph 3 of Regulation (EU) No 305/2011 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1



Intended use in concrete




fischer drop-in anchor EA II

Product description


Anchor types
Installed condition

Annex A 1




Anchor size EA II	M6x30	M8x30	M8x40	M10x30	M10x40	M12x50	M12x50 D	M16x65	M20x80
h_{ef} [mm]	30	30	40	30	40	50		65	80
$\varnothing d_{nom}$ [mm]	8	10		12		15	16	20	25
$\varnothing d_{rim}$ [mm]	9,5	11,5		13,5		16,5	17,5	21,5	27,0
$\varnothing d_1$ [mm]	5	6,5		8		10		13,5	17,5
l_1 [mm]	14	13,5		13	18	18		25	26

Distinctive feature



0× groove for:

- EA II M6x30..
- EA II M8x30..
- EA II M10x40..
- EA II M12x50..
- EA II M16x65..
- EA II M20x80..



2× groove for:

- EA II M8x40..
- EA II M10x30..

Marking on anchor body


galvanized steel (gvz)		stainless steel (A4)	
with rim	rimless	with rim	rimless
EA II M6x30	EA II M6x30 RL	EA II M6x30 A4	EA II M6x30 RL A4
EA II M8x30	EA II M8x30 RL	EA II M8x30 A4	EA II M8x30 RL A4
EA II M8x40	EA II M8x40 RL	EA II M8x40 A4	EA II M8x40 RL A4
EA II M10x30	EA II M10x30 RL	EA II M10x30 A4	EA II M10x30 RL A4
EA II M10x40	EA II M10x40 RL	EA II M10x40 A4	EA II M10x40 RL A4
EA II M12x50	EA II M12x50 RL	EA II M12x50 A4	EA II M12x50 RL A4
EA II M12x50 D	EA II M12x50 RLD	EA II M12x50 DA4	EA II M12x50 RL DA4
EA II M16x65	EA II M16x65 RL	EA II M16x65 A4	EA II M16x65 RL A4
EA II M20x80	EA II M20x80 RL	EA II M20x80 A4	EA II M20x80 RL A4

fischer drop-in anchor EA II


Product description
Anchor types

Annex A 2

Expansion sleeve



Expansion pin

**Table A1: Materials**

Designation	Material	
	galvanised steel ($\geq 5 \mu\text{m}$)	stainless steel
Expansion sleeve	EN 10277:2008 or EN 10084:2008 or EN 10111:2008 or EN 10263:2001 or EN 10087:1998 or ASTM A29/A29M	EN 10088:2005
Expansion pin		
Fastening screw or threaded rod	steel, property class 4.6, 5.6, 5.8 or 8.8 according to EN ISO 898-1:2012	property class 50, 70 or 80 according to EN ISO 3506:2009

fischer drop-in anchor EA II

Product description
 Material
Annex A 3

Intended use

Anchorage subject to:

- Static and quasi-static loads

Base materials:

- Reinforced or unreinforced normal weight concrete according to EN 206-1:2000
- Strength classes C20/25 to C50/60 according to EN 206-1:2000
- Non-cracked concrete: all sizes

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (zinc coated steel or stainless steel)
- Structures subject to external atmospheric exposure (including industrial and marine environment) and to permanently damp internal condition, if no particular aggressive conditions exist (stainless steel)

Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where de-icing materials are used)

Design:

- Anchorages are designed under the responsibility of an engineer experienced in anchorages and concrete work
- Verifiable calculation notes and drawings are prepared taking into account the loads to be anchored. The position of the anchor is indicated on the design drawings (e. g. position of the anchor relative to reinforcement or to supports, etc.)
- Anchorages under static or quasi-static actions are to be designed in accordance with:
 - ETAG 001, Annex C, design method A, Edition August 2010 or
 - CEN/TS 1992-4:2009, design method A
- Fasteners can be used as a single fixing for use in structural application, according to: ETAG 001 Part 4, Edition August 2010

Installation:

- Anchor installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Create drill hole with hammer drill or with hollow drill and vacuum cleaner
- The anchor may only be used once
- In case of aborted hole: New hole must be drilled at a minimum distance of twice the depth of the aborted hole or closer, if the hole is filled with a high strength mortar and only if the hole is not in the direction of the oblique tensile or shear load
- Anchor expansion by impact using the setting tools given in Annex B 3. The anchor is properly set if the stop of the setting tool reaches the expansion sleeve. The manual setting tool with installation control leaves a visible mark on the sleeve, as illustrated in Annex B 3 and B 4



fischer drop-in anchor EA II

Intended Use
Specifications

Annex B 1

Table B2: Installation parameters for concrete C20/25 to C50/60

Anchor size			M6x30	M8x30	M8x40	M10x30	M10x40	M12x50	M12x50 D	M16x65	M20x80
Nominal drill hole diameter	d ₀	[mm]	8	10		12		15	16	20	25
Effective anchorage depth	h _{ef}	[mm]	30	30	40	30	40	50		65	80
Maximum installation torque	max. T _{inst}	[Nm]	4	8		15		35		60	120
Minimum drill hole depth	h ₁	[mm]	32	33	43	33	43	54		70	85
Minimum screw-in depth	l _{s,min}	[mm]	6	8		10		12		16	20
Maximum screw-in depth	l _{s,max}	[mm]	14	14		14	17	22		28	34
Clearance of hole diameter	Ø d _f ≤	[mm]	7	9		12		14		18	22
h _{min} = 80 mm											
Minimum spacing	s _{min}	[mm]	70	110	200	200		-	-	-	-
Minimum edge distance	c _{min}	[mm]	150	150		150		-	-	-	-
h _{min} = 100 mm											
Minimum spacing	s _{min}	[mm]	65	70		90	150	200		-	-
Minimum edge distance	c _{min}	[mm]	115	115		160	180			-	-
h _{min} = 120 mm											
Minimum spacing	s _{min}	[mm]	65	70		85	95	145		-	-
Minimum edge distance	c _{min}	[mm]	115	115		140	150	200		-	-
h _{min} = 160 mm											
Minimum spacing	s _{min}	[mm]	65	70		85	95	145		180	-
Minimum edge distance	c _{min}	[mm]	115	115		140	150	200		240	-
h _{min} = 200 mm											
Minimum spacing	s _{min}	[mm]	65	70		85	95	145		180	190
Minimum edge distance	c _{min}	[mm]	115	115		140	150	200		240	280



Fastening screw or threaded rod:

- Minimum property class and materials according to table A1
- The length of the fastening screw or threaded rod shall be determined depending on thickness of fixture t_{fix} , admissible tolerances and maximum screw length $l_{s,max}$ as well as minimum screw-in depth $l_{s,min}$




fischer drop-in anchor EA II

Intended Use
Installation parameters


Annex B 2

Setting & drilling tools

Setting tools

Setting tools	Marking	Description	Marking on EA II with rim and rimless
	EHS Plus M..x h _{ef}	Manual setting tool with hand guard	
	EHS M..x h _{ef}	Manual setting tool basic format	
	EMS M..x h _{ef}	Machine setting tool with SDS Plus	No marking

Drilling tools

	EBB ØD x l	Stop drill
Or other usual drill		




Table B3: Parameters of setting tools


Manual setting tool	Machine setting tool	Stop drill	For anchor size EA II	Ø D1	Ø D2	L
EHS M6x25/30	EMS M6x25/30	EBB 8x30	EA II M6x30	4,8	9,0	17,0
EHS M8x25/30	EMS M8x25/30	EBB 10x30	EA II M8x30	6,4	11,0	18,0
EHS M8x40	EMS M8x40	EBB 10x40	EA II M8x40			28,0
EHS M10x25/30	EMS M10x25/30	EBB 12x30	EA II M10x30	7,9	13,0	18,0
EHS M10x40	EMS M10x40	EBB 12x40	EA II M10x40			24,0
EHS M12x50	EMS M12x50	EBB 15x50	EA II M12x50	10,2	16,5	30,0
EHS M12x50	EMS M12x50	EBB 16x50	EA II M12x50 D			
EHS M16x65	EMS M16x65	EBB 20x65	EA II M16x65	13,5	22	36,0
EHS M20x80	EMS M20x80	EBB 25x80	EA II M20x80	16,4	27	50,0

fischer drop-in anchor EA II

Intended Use
Setting & Drilling tools

Annex B 3

Installation instructions



No.	Description
1	Create drill hole with hammer drill or with hollow drill and vacuum cleaner
2	Clean from drill-dust
3	Set anchor till anchor is flush with surface of concrete
4	Expand the sleeve by driving the pin into the sleeve and control the correct setting
5	Fixation of fixture. Maximum installation torque max. T_{inst} must not be crossed

fischer drop-in anchor EA II

Intended Use
Installation instructions

Annex B 4

Table C1: Characteristic values for tension loads due to design method A according to ETAG 001, Annex C or CEN TS 1992-4: 2009

EA II			property class	M6x30 ¹⁾	M8x30 ¹⁾	M8x40	M10x30 ¹⁾	M10x40	M12x50	M12x50 D	M16x65	M20x80
Installation safety factor		$\gamma_2 = \gamma_{inst}$	[-]	1,0								
Steel failure												
Characteristic resistance	$N_{Rk,s}$ [kN]	A4-50		10,1	18,3		29,0		42,1		78,3	122,4
Partial safety factor	γ_{Ms}			2,86								
Characteristic resistance	$N_{Rk,s}$ [kN]	A4-70		14,1	19,6		24,9		45,1	59,0	73,8	117,2
Partial safety factor	γ_{Ms}			1,87			1,5			1,87		1,5
Characteristic resistance	$N_{Rk,s}$ [kN]	A4-80		16,1	19,6		24,9		45,1	59,0	73,8	117,2
Partial safety factor	γ_{Ms}			1,6			1,5					
Characteristic resistance	$N_{Rk,s}$ [kN]	steel 4.6		8,0	14,6		23,2		33,7		62,7	97,9
Partial safety factor	γ_{Ms}			2,0								
Characteristic resistance	$N_{Rk,s}$ [kN]	steel 5.6		10,1	18,3		29,0		42,1		78,3	122,4
Partial safety factor	γ_{Ms}			2,0								
Characteristic resistance	$N_{Rk,s}$ [kN]	steel 5.8		10,1	17,2		21,8		39,6	42,1	64,7	102,8
Partial safety factor	γ_{Ms}			1,5								
Characteristic resistance	$N_{Rk,s}$ [kN]	steel 8.8		13,5	17,2		21,8		39,6	53,3	64,7	102,8
Partial safety factor	γ_{Ms}			1,5								
Pull-out failure not decisive												
Concrete cone failure												
Effective anchorage depth	h_{ef}	[mm]		30	40	30	40		50		65	80
Characteristic spacing	$s_{cr,N}$	[mm]		90	120	90	120		150		195	240
Characteristic edge distance	$c_{cr,N}$	[mm]		45	60	45	60		75		97	120
Factor according CEN/TS	k_{ucr}	[-]		10,1								
Splitting failure												
Characteristic spacing	$s_{cr,sp}$	[mm]		210	280	210	320		350		455	560
Characteristic edge distance	$c_{cr,sp}$	[mm]		105	140	105	160		175		227	280

¹⁾ Only for application with statically indeterminate structural components.

fischer drop-in anchor EA II

Performances
Design method A
Characteristic resistance to tension loads

Annex C 1

Table C2: Characteristic values for shear loads due to design method A according to ETAG 001, Annex C or CEN TS 1992-4: 2009

EA II			property class	M6x30 ¹⁾	M8x30 ¹⁾	M8x40	M10x30 ¹⁾	M10x40	M12x50	M12x50 D	M16x65	M20x80
Factor for ductility k ₂ [-]				1,0								
Steel failure without lever arm												
Characteristic resistance	V _{Rk,s} [kN]	A4-50	5,0	9,2	14,5	21,1	39,2	61,2				
Partial safety factor	γ _{Ms}		2,38									
Characteristic resistance	V _{Rk,s} [kN]	A4-70	7,0	9,8	12,4	22,6	29,5	37	59			
Partial safety factor	γ _{Ms}		1,56	1,25				1,56	1,25			
Characteristic resistance	V _{Rk,s} [kN]	A4-80	8,0	9,8	12,4	22,6	30,4	36,9	58,6			
Partial safety factor	γ _{Ms}		1,33	1,25								
Characteristic resistance	V _{Rk,s} [kN]	steel 4.6	4,0	7,3	11,6	16,9	31	49				
Partial safety factor	γ _{Ms}		1,67									
Characteristic resistance	V _{Rk,s} [kN]	steel 5.6	5,0	9,2	14,5	21,1	39	61				
Partial safety factor	γ _{Ms}		1,67									
Characteristic resistance	V _{Rk,s} [kN]	steel 5.8	5,0	8,6	10,9	19,8	21,1	32	51			
Partial safety factor	γ _{Ms}		1,25									
Characteristic resistance	V _{Rk,s} [kN]	steel 8.8	6,8	8,6	10,9	19,8	27	32	51			
Partial safety factor	γ _{Ms}		1,25									
Steel failure with lever arm												
Characteristic resistance	M ⁰ _{Rk,s} [Nm]	A4-50	8	19	37	66	166	324				
Partial safety factor	γ _{Ms}		2,38									
Characteristic resistance	M ⁰ _{Rk,s} [Nm]	A4-70	11	26	52	92	232	454				
Partial safety factor	γ _{Ms}		1,56									
Characteristic resistance	M ⁰ _{Rk,s} [Nm]	A4-80	12	30	60	105	266	519				
Partial safety factor	γ _{Ms}		1,33									
Characteristic resistance	M ⁰ _{Rk,s} [Nm]	Stahl 4.6	6,1	15	30	52	133	259				
Partial safety factor	γ _{Ms}		1,67									
Characteristic resistance	M ⁰ _{Rk,s} [Nm]	Stahl 5.6	7,6	19	37	66	166	324				
Partial safety factor	γ _{Ms}		1,67									
Characteristic resistance	M ⁰ _{Rk,s} [Nm]	Stahl 5.8	7,6	19	37	66	166	324				
Partial safety factor	γ _{Ms}		1,25									
Characteristic resistance	M ⁰ _{Rk,s} [Nm]	Stahl 8.8	12	30	60	105	266	517				
Partial safety factor	γ _{Ms}		1,25									

¹⁾ Only for application with statically indeterminate structural components.

fischer drop-in anchor EA II

Performances
Design method A
Characteristic resistance to shear loads

Annex C 2

Table C3: Characteristic values for shear loads due to design method A according to ETAG 001, Annex C or CEN TS 1992-4: 2009

EA II	M6x30	M8x30	M8x40	M10x30	M10x40	M12x50	M12x50 D	M16x65	M20x80		
Concrete pry out failure											
Factor in equation (5.6) of ETAG 001 Annex C, 5.2.3.3	k = k ₃		1,74	1,88	1,74	1,88	2,0				
Installation safety factor ¹⁾	γ ₂ = γ _{inst}		1,0								
Concrete edge failure											
Effective length of anchor in shear loading	l _f = h _{ef} [mm]		30	40	30	40	50		65	80	
Effective diameter of anchor	Ø d _{nom} [mm]		8	10		12		15	16	20	25

fischer drop-in anchor EA II

Performances
Design method A
Characteristic resistance to shear loads

Annex C 3

Table C4.1: Displacements under tension and shear loads for EA II in galvanised steel

EA II			M6x30	M8x30	M8x40	M10x30	M10x40	M12x50	M12x50 D	M16x65	M20x80
Tension load in C20/25 to C50/60	N	[kN]	4,0		6,1	4,0	6,1	8,5		12,6	17,2
Displacement	δ_{No}	[mm]	0,1								
	$\delta_{No\infty}$	[mm]	0,2								
Shear load in C20/25 to C50/60	V	[kN]	3,9	4,9		6,2		11,3	15,2	18,5	29,4
Displacement	δ_{Vo}	[mm]	0,95	1,00		1,05		1,10		1,40	1,80
	$\delta_{Vo\infty}$	[mm]	1,40	1,50		1,60		1,70		2,10	2,70

Table C4.2: Displacements under tension and shear loads for EA II in stainless steel

EA II A4			M6x30	M8x30	M8x40	M10x30	M10x40	M12x50	M12x50 D	M16x65	M20x80
Tension load in C20/25 to C50/60	N	[kN]	4,0		6,1	4,0	6,1	8,5		12,6	17,2
Displacement	δ_{No}	[mm]	0,1								
	$\delta_{No\infty}$	[mm]	0,2								
Shear load in C20/25 to C50/60	V	[kN]	3,2	5,6		7,1		12,9	13,5	21,1	33,5
Displacement	δ_{Vo}	[mm]	0,95	1,00		1,05		1,10		1,40	1,80
	$\delta_{Vo\infty}$	[mm]	1,40	1,50		1,60		1,70		2,10	2,70

fischer drop-in anchor EA II

Performances
 Displacements
Annex C 4