

**DECLARAȚIA DE PERFORMANȚĂ****DoP 0197**

pentru bulonul de ancore Fischer FH II, FH II-I (Ancore din metal pentru utilizare în beton)

RO

1. <u>Cod unic de identificare al produsului-tip:</u>	DoP 0197		
2. <u>Utilizare (utilizări) preconizată (preconizate):</u>	Prindere cu instalare ulterioară în beton fisurat sau nefisurat. Consultați suplimentul, în special anexele B1- B6		
3. <u>Fabricant:</u>	fischerwerke GmbH & Co. KG, Klaus-Fischer-Str. 1, 72178 Waldachtal, Germany		
4. <u>Reprezentant autorizat:</u>	-		
5. <u>Sistemul (sistemele) de evaluare și de verificare a constantei performantei:</u>	1		
6. <u>Documentul de evaluare european:</u> Rezistență mecanică și stabilitate (BWR 1) Rezistență caracteristică la întindere (pentru încărcări statice și cvasistatiche):	EAD 330232-00-0601 (Edition 10/ 2016) ETA-07/0025; 2020-09-23 DIBt- Deutsches Institut für Bautechnik Organism (organisme) notificat(e):	Rezistență la cedarea oțelului: Rezistență la smulgere:	Anexe C1, C2 Anexe C1, C2
		Rezistență la cedarea conului de beton:	Anexe C1, C2
		Robustețe:	Anexe C1, C2
		Distanță minimă față de margine și între ancore:	Anexe C7
		Distanță față de margine pentru a preveni fisuri sub încărcare:	Anexe C1, C2
		Deplasări sub încărcări statice și cvasistatiche:	Anexe C10, C11
Rezistență caracteristică la forfecare (pentru încărcări statice și cvasistatiche):	Rezistență la cedarea oțelului (rezistență la forfecare) Rezistență la cedarea cu brăț de levier: Rezistență la cedarea muchiei betonului: Deplasări sub încărcări statice și cvasistatiche:	Anexe C3, C4 Anexe C3, C4 Anexe C3, C4 Anexe C10, C11	
	Durabilitate:	Anexe A4, B1	
Rezistență caracteristică și Deplasări pentru performanță seismică de categoriile C1 și C2:	Rezistență la cedarea oțelului: Rezistență la smulgere:	Anexe C8, C9 Anexe C8, C9	
	Alungirea la rupere:	>8%	
	Factor gol circular:	Anexe C8, C9	
	Deplasări:	Anexe C11	

Siguranță în caz de incendiu (BWR 2)

Reacție la foc:

Clasa (A1)

Rezistență la incendiu:

Rezistență la foc în ipoteza cedării oțelului

Anexe C5

Rezistență la foc în ipoteza cedării prin smulgere

Anexe C5

Rezistență la foc în ipoteza cedării oțelului

Anexe C6

8. Documentatie tehnica adevarata si/sau documentatie tehnica specifica: -

Performanța produsului identificat mai sus este în conformitate cu setul de performanțe declarate. Această declarație de performanță este eliberată în conformitate cu Regulamentul (UE) nr. 305/2011, pe răspunderea exclusivă a fabricantului identificat mai sus.

Semnată pentru și în numele fabricantului de către:

ppu. Thilo Pregartner

Thilo Pregartner, Dr.-Ing.
Tumlingen, 2020-10-06

i.V. P. Schillinger

Peter Schillinger, Dipl.-Ing.

Această declarație de performanță a fost întocmită în mai multe limbi. În cazul unei divergențe de interpretare, versiunea în limba engleză prevalează întotdeauna.

Suplimentul include informații voluntare și complementare în limba engleză, în afara cerințelor legale (specificate neutru din punct de vedere al limbii).

Specific Part

1 Technical description of the product

The fischer High-Performance Anchor FH II, FH II-I is an anchor made of galvanised steel (sizes with external diameter 10, 12, 15, 18, 24, 28 and 32, sizes with internal thread 12/M6 I, 12/M8 I, 15/M10 I and 15/M12 I) or stainless steel (sizes with external diameter 10, 12, 15, 18 and 24, sizes with internal thread 12/M6 I, 12/M8 I, 15/M10 I and 15/M12 I) which is placed into a drilled hole and anchored by torque-controlled expansion.

The product description is given in Annex A.

2 Specification of the intended use in accordance with the applicable European Assessment Document

The performances given in Section 3 are only valid if the fastener is used in compliance with the specifications and conditions given in Annex B.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the fastener of at least 50 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

3.1 Mechanical resistance and stability (BWR 1)

Essential characteristic	Performance
Characteristic resistance to tension load (static and quasi-static loading)	See Annex C 1, C 2, C 7
Characteristic resistance to shear load (static and quasi-static loading)	See Annex C 3 and C4
Displacements (static and quasi-static loading)	See Annex C 10, C 11
Characteristic resistance and displacements for seismic performance categories C1 and C2	See Annex C 8, C 9, C 11
Durability	See Annex B 1


3.2 Safety in case of fire (BWR 2)

Essential characteristic	Performance
Reaction to fire	Class A1
Resistance to fire	See Annex C 5, C 6

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with the European Assessment Document EAD 330232-01-0601 the applicable European legal act is: [96/582/EC].

The system to be applied is: 1



Type hexagon screw **S**

FH II 10 - 32 S

FH II 10 - 24 S R




Product label, example:

Brand _____

Type of fastener _____

Identification R

Nominal drill hole diameter/max. thickness of fixture (t_{fix})



Type countersunk screw **SK**

FH II 10 - 18 SK

FH II 10 - 18 SK R

Type hexagon nut **B**

FH II 10 - 32 B

FH II 10 - 24 B R

Type cap nut **H**

FH II 10 - 24 H

FH II 10 - 24 H R

Hexagon screw

Threaded rod

Plastic sleeve

Countersunk screw

Cone nut

Washer

Cap nut


Distance sleeve

Conical washer

Hexagon nut

Expansion sleeve

Internal thread socket



Type internal threaded anchor I

FH II 12 M6-I or M8-I

FH II 15 M10-I or M12-I

Product label, example:

Brand _____

Type of fastener _____

Identification R

Nominal drill hole diameter / size of internal thread
(Fig. not to scale)

fischer High-Performance Anchor FH II, FH II-I

Product description

Anchor types FH II, FH II R, FH II-I, FH II-I R

Annex A 1




Table A2.1: Dimensions [mm] FH II and FH II R

Anchor type	FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Thread	M	6	8	10	12	16	20
Diameter cone nut	d _c	10	12	14,8	17,8	23,7	27,5
	FH II-S, -B	10	13	17	19	24	30
	FH II-SK ¹⁾	4	5	6	8		³⁾
Wrench size SW	FH II-H	13	17	17	19	24	³⁾
	FH II-S R, -B R, -H R	10	13	17	19	24	³⁾
	FH II-SK R ¹⁾	4	5	6	8		³⁾
t _{fix} FH II-S, -B, -H + FH II-S R, -B R, -H R	min	0	0	0	0	0	0
t _{fix} FH II-SK + FH II-SK R ²⁾	min	5	6	6	8		³⁾
Length of screw / bolt	L _s , L _h , L _b (- t _{fix})	≥ 49	74	89	99	124	149
Length of countersunk screw	L _{sk} (- t _{fix})	≥ 54	79	95	107		³⁾

¹⁾ Internal hexagon

²⁾ The influence of the thickness of fixture to the characteristic resistance for shear loads, steel failure without lever arm is taken into account, see tables C3.1, C8.1 and C9.1

³⁾ Anchor type not part of assessment

(Fig. not to scale)

fischer High-Performance Anchor FH II, FH II-I

Product description

Anchor types and dimensions FH II, FH II R

Annex A 2

Table A3.1: Material FH II and FH II R

No.	Designation	Material	
		FH II	FH II R
Steel grade	Steel	Steel	Stainless steel R
	Zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018		Acc. to EN 10088:2014
1	Hexagon screw	Steel class 8.8; EN ISO 898-1:2013	Class 80 EN ISO 3506:2020
2	Countersunk screw		
3	Cap nut		
4	Hexagon nut	Steel class 8	
5	Threaded rod	Steel $f_{uk} \geq 800 \text{ N/mm}^2$; $f_{yk} \geq 640 \text{ N/mm}^2$	Stainless steel EN 10088:2014 $f_{uk} \geq 800 \text{ N/mm}^2$; $f_{yk} \geq 640 \text{ N/mm}^2$
6	Cone nut	Steel EN 10277:2018	Stainless steel EN 10088:2014
7	Distance sleeve	Steel EN 10305:2016	
8	Expansion sleeve	Steel EN 10139:2020/ EN 10277:2018	
9	Plastic sleeve	ABS (plastic)	
10	Washer	Steel EN 10139:2020	Stainless steel EN 10088:2014
11	Conical washer	Steel EN 10277:2018	

fischer High-Performance Anchor FH II, FH II-I

Product description
Materials FH II and FH II R
Annex A 3




Table A4.1: Anchor Dimensions [mm] FH II-I and FH II-I R

Anchor type FH II-I, FH II-I R	FH II 12/M6 I	FH II 12/M8 I	FH II 15/M10 I	FH II 15/M12 I
Thread M	6	8	10	12
Diameter cone nut d_c	12	12	14,8	14,8
Wrench size internal hexagon SW	6	8	6	8
Anchor length L	77,5	77,5	90	90

Table A4.2: Material FH II-I and FH II-I R

No.	Designation	Material	
		FH II-I	FH II-I R
Steel grade	Steel	Steel	Stainless steel R
	Zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018	Zinc plated $\geq 5 \mu\text{m}$, ISO 4042:2018	Acc. to EN 10088:2014
6	Cone nut	Steel EN 10277:2018	Stainless steel EN 10088:2014
8	Expansion sleeve	Steel EN 10139:2020 / EN 10277:2018	
9	Plastic sleeve	ABS (plastic)	
12	Internal thread bolt	Steel EN 10277:2018 $f_{uk} \geq 750 \text{ N/mm}^2$, $f_{yk} \geq 600 \text{ N/mm}^2$	Stainless steel EN 10088:2014 $f_{uk} \geq 750 \text{ N/mm}^2$, $f_{yk} \geq 600 \text{ N/mm}^2$
Requirements for fixing elements		Steel strength class 5.8, 6.8 or 8.8 EN ISO 898-1:2013	Steel strength class A50, A70 or A80 EN ISO 3506:2010 1.4362, 1.4401, 1.4404, 1.4571, 1.4529

(Fig. not to scale)

fischer High-Performance Anchor FH II, FH II-I

Product description

Anchor types, dimensions and materials FH II-I, FH II I-R

Annex A 4

Specifications of intended use

Anchorages subject to:

Size		10	12	15	18	24	28	32
High Performance Anchor	FH II-S, -B				✓			
	FH II-H, -S R, -B R, -H R			✓				1)
	FH II-SK, FH II-SK R		✓				1)	
High Performance Anchor FH II-I, FH II-I R		1)		✓			1)	
Hammer drilling with standard drill bit								
Hammer drilling with hollow drill bit with automatic cleaning					✓			
Static and quasi-static loads								
Cracked and uncracked concrete					✓			
Fire exposure								
Seismic performance category	C1 FH II	2)			✓			
	C1 FH II R			✓			1)	
	C2 FH II	1)			✓			
	C2 FH II R			✓			1)	
	C1 FH II-I, FH II-I R	2)						
	C2 FH II-I, FH II-I R		2)				1)	

¹⁾ Anchor type not part of the assessment

²⁾ No performance assessed

Base materials:

- Compacted reinforced or unreinforced normal weight concrete without fibres (cracked and uncracked) of strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016

Use conditions (Environmental conditions):

- Structures subject to dry internal conditions (FH II, FH II R, FH II-I, FH II-I R)
- Structures subject to external atmospheric exposure (including industrial and marine environment) and to permanently damp internal conditions, if no particular aggressive conditions exist (FH II R, FH II-I R)

Note: Particular aggressive conditions are e.g. permanent, alternating immersion in seawater or the splash zone of seawater, chloride atmosphere of indoor swimming pools or atmosphere with extreme chemical pollution (e.g. in desulphurization plants or road tunnels where deicing materials are used)


Design:

- Anchorages are to be designed under the responsibility of an engineer experienced in anchorages and concrete work
- Verifiable calculation notes and drawings are to be prepared taking account of the loads to be anchored. The position of the anchor is indicated on the design drawings (e.g. position of the anchor relative to reinforcement or to supports, etc.)
- Design of fastenings according to EN 1992-4:2018 and EOTA Technical Report TR 055, Edition February 2018

fischer High-Performance Anchor FH II, FH II-I

Intended use
Specifications

Annex B 1



h_{ef} = Effective embedment depth

t_{fix} = Thickness of the fixture

h_1 = Depth of drill hole to deepest point

h_{min} = Minimum thickness of concrete member

T_{inst} = Required setting torque

Table B2.1: Installation parameters FH II and FH II R

Anchor type FH II S, -SK, -B, -H and FH II S R, -SK R, -B R, -H R	FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32	
Nominal drill hole diameter d_0	10	12	15	18	24	28	32	
Maximum diameter of drill bit $d_{cut} \leq$	10,45	12,50	15,50	18,50	24,55	28,55	32,70	
Depth of drill hole to deepest $h_1 \geq$	[mm] 55	80	90	105	125	155	180	
Diameter of clearance hole $d_f \leq$	12	14	17	20	26	31	35	
Diameter of counter sunk FH II SK	18	22	25	32	1)			
Depth of counter sunk, 90° FH II SK R	[mm] 5,0	5,8	5,8	8,0	1)			
Required setting torque	FH II S	10	22,5	40	80	160	180	200
	FH II B		17,5	38		120	180	200
	FH II H		22,5	40		90	1)	
	FH II SK					1)		
	FH II S R, FH II B R	15			100	160	1)	
	FH II H R		25	40			1)	
	FH II SK R		10				1)	


¹⁾ Anchor type not part of assessment

(Fig. not to scale)

fischer High-Performance Anchor FH II, FH II-I

Intended use
Installation parameters FH II, FH II R

Annex B 2



- h_{ef} = Effective embedment depth
 h_1 = Depth of drill hole to deepest point
 h_{min} = Minimum thickness of concrete member
 T_{inst} = Required setting torque
 U = Required gap after torqueing
 l_s = Screw-in depth

Table B3.1: Installation parameters FH II-I and FH II-I R

Anchor type FH II-I and FH II-I R	FH II 12/M6 I	FH II 12/M8 I	FH II 15/M10 I	FH II 15/M12 I
Nominal drill hole diameter d_0	12		15	
Maximum bit diameter $d_{\text{cut}} \leq$		12,50		15,50
Depth of drill hole $h_1 \geq$ [mm]		85		95
Diameter of clearance hole $d_f \leq$	7	9	12	14
Required gap after torquing ¹⁾ U			3 - 5	
Required setting torque ¹⁾ T_{inst} [Nm]		15		25
Minimum screw-in depth $l_s \geq$ [mm]	11 + U	13 + U	10 + U	12 + U
Maximum screw-in depth $l_s \leq$ [mm]			20 + U	
Maximum torque on fixture in combination with screws and threaded rods strength class ≥ 5.8 resp. $\geq A50$ $\max T_{\text{fix}}$ [Nm]	3	8	15	20

¹⁾ At least one of the requirements concerning the gap U or the required setting torque T_{inst} have to be fulfilled

(Fig. not to scale)

fischer High-Performance Anchor FH II, FH II-I

Intended use
Installation parameters FH II-I, FH II-I R

Annex B 3

Installation instructions:

- Fastener installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site
- Use of the fastener only as supplied by the manufacturer without exchanging the components of the fastener
- Checking before placing the fastener to ensure that the strength class of the concrete in which the fastener is to be placed is in the range given and is not lower than that of the concrete to which the characteristic loads apply
- Check of concrete being well compacted, e.g. without significant voids
- Hammer or hollow drilling according to Annex B5 and B6
- Drill hole created perpendicular +/- 5° to concrete surface, positioning without damaging the reinforcement
- In case of aborted hole: new drilling at a minimum distance twice the depth of the aborted drill hole or smaller distance if the aborted drill hole is filled with high strength mortar and if under shear or oblique tension load it is not in the direction of load application

fischer High-Performance Anchor FH II, FH II-I


Intended Use
Installation instructions

Annex B 4


Appendix 9/ 22

Installation instruction for the fischer High-Performance anchor
FH II 10 - FH II 32 and FH II 10 R - FH II 24 R


**Hollow
drilling**




Continue with step 3, 4 and 5




Installation instruction FH II 10 - 32 S and FH II 10 - 24 S R



Installation instruction FH II 10 - 18 SK and FH II 10 - 18 SK R



Installation instruction FH II 10 - 32 B and FH II 10 - 24 B R



Installation instruction FH II 10 - 24 H and FH II 10 - 24 H R

Step	1	2	3	4	5
Step	Description				
1	Create drill hole with hammer drill			Create drill hole with hollow drill and vacuum cleaner	
2	Clean the hole			-	
3	Set the fastener				
4	Apply T_{inst}				
5	Installed fastener				

Types of drill bits

Hammer drill



Hollow drill









fischer High-Performance Anchor FH II, FH II-I

Intended use

Installation instructions FH II, FH II R

Annex B 5

Installation instruction for the fischer High-Performance anchor internal thread
FH II-I and FH II-I R

Hollow drilling		Continue with step 2, 3, and 4				
Hammer drilling						4
Step	1	2	3			4

Step	Description	
1	Create drill hole with hammer drill, clean drill hole	Create drill hole with hollow drill and vacuum cleaner
2	Hammering in the anchor flushed with the surface of the concrete	
3	Tighten the anchor. The included hexagon bit in the package should be used. Other tightening methods are allowed. Tighten the anchor in the concrete until the gap U is 3 - 5 mm or the required setting torque T_{inst} is reached. Only one of the above requirements has to be fulfilled.	
4	Attach the fixture and use a suitable screw or anchor rod. The length of the screw or anchor rod should be determined depending on the thickness of fixture t_{fix} , admissible tolerances, and available thread length $l_{s,max}$ and $l_{s,min}$ including the gap U. Tighten the screw with the torque $\leq \max T_{fix}$ ($\max T_{fix}$ see table B3.1)	

Types of drill bits

Hammer drill



Hollow drill



fischer High-Performance Anchor FH II, FH II-I

Intended use

Installation instructions FH II-I, FH II-I R

Annex B 6

Table C1.1: Performance characteristics of **tension resistance under static and quasi-static loads for FH II and FH II R**

Anchor type FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R	FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Steel failure							
FH II-S, -B, FH II-H, FH II-H R, -B R	N _{Rk,s} [kN]	16,1	29,3	46,4	67,4	125,3	195,8
FH II-S R		16,1	29,3	46,4	67,4	125,3	2) ²⁾
FH II-SK		16,1	29,3	46,4	67,4		2)
Partial factor	γ _{Ms} ¹⁾ [-]				1,5		
FH II-S R	N _{Rk,s} [kN]	16,1	29,3	46,4	67,4	125,3	2) ²⁾
FH II-SK R		16,1	29,3	46,4	67,4		2)
Partial factor	γ _{Ms} ¹⁾ [-]				1,6		
Pullout failure							
Characteristic resistance in cracked concrete C20/25 FH II and FH II R	N _{Rk,p} [kN]	7,5	12,0	16,0	25,0	34,4	48,1
Characteristic resistance in uncracked concrete C20/25 FH II		12,5	22,9	28,8	35,2	49,2	68,8
Characteristic resistance in uncracked concrete C20/25 FH II R		12,5	20,0	28,8	35,2	49,2	2)
Increasing factors for N _{Rk,p} for cracked and uncracked concrete	ψ ^c	C25/30			1,12		
		C30/37			1,22		
		C35/45			1,32		
		C40/50			1,41		
		C45/55			1,50		
		C50/60			1,58		
Installation factor	γ _{inst} [-]				1,0		
Concrete cone failure and splitting failure							
Effective embedment depth	h _{ef} [mm]	40	60	70	80	100	125
Factor for cracked concrete	k _{cr,N} [-]				7,7 ³⁾		
Factor for uncracked concrete	k _{ucr,N} [-]				11,0 ³⁾		
Spacing	s _{cr,N}	120	180	210	240	300	375
Edge distance	c _{cr,N} [mm]	60	90	105	120	150	187,5
Spacing (splitting)	s _{cr,sp}	190	300	320	340	380	480
Edge distance (splitting)	c _{cr,sp}	95	150	160	170	190	240
Characteristic resistance (splitting)	N ⁰ _{Rk,sp} [kN]					min {N ⁰ _{Rk,c} , N ⁰ _{Rk,p} } ⁴⁾	

¹⁾ In absence of other national regulations

²⁾ Anchor type no performance assessed

³⁾ Based on concrete strength as cylinder strength

⁴⁾ N⁰_{Rk,c} acc. EN 1992-4:2018

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of tension resistance for FH II and FH II R

Annex C 1

Table C2.1: Performance characteristics of **tension resistance** under static and quasi-static loads for FH II-I and FH II-I R

Anchor type FH II-I and FH II-I R	FH II 12/M6 I	FH II 12/M8 I	FH II 15/M10 I	FH II 15/M12 I
Steel failure				
Anchor in combination with screw / threaded rod of galvanised steel complying with DIN EN ISO 898				
Strength class 5.8	10	19	29	43
Strength class 6.8	N _{Rk,s} [kN]	12	23	35
Strength class 8.8		16	27	44
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,5	
Anchor in combination with screw / threaded rod of stainless steel complying with DIN EN ISO 3506				
Screw/thread strength class A50	N _{Rk,s} [kN]	10	19	29
Partial factor $\gamma_{Ms}^{1)}$ [-]			2,86	
Screw/thread strength class A70	N _{Rk,s} [kN]	14	26	41
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,87	
Screw/thread strength class A80	N _{Rk,s} [kN]	16	29	46
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,60	
Pullout failure				
Characteristic resistance in cracked concrete C20/25	N _{Rk,p} [kN]	9,0		12,0
Characteristic resistance in uncracked concrete C20/25		20,0		28,8
Increasing factors for N _{Rk,p} for cracked and uncracked concrete	C25/30	1,12		
	C30/37	1,22		
	C35/45	1,32		
	C40/50	1,41		
	C45/55	1,50		
	C50/60	1,58		
Installation factor γ_{inst} [-]			1,0	
Concrete cone failure and splitting failure				
Effective embedment depth h _{ef} [mm]		60		70
Factor for cracked concrete k _{cr,N}			7,7 ²⁾	
Factor for uncracked concrete k _{ucr,N}	[-]		11,0 ²⁾	
Spacing S _{cr,N}		180		210
Edge distance C _{cr,N}		90		105
Spacing (splitting) S _{cr,sp}	[mm]	300		320
Edge distance (splitting) C _{cr,sp}		150		160
Characteristic resistance (splitting) N ⁰ _{Rk,sp} [kN]			min {N ⁰ _{Rk,C} , N ⁰ _{Rk,p} } ³⁾	

¹⁾ In absence of other national regulations

²⁾ Based on concrete strength as cylinder strength

³⁾ N⁰_{Rk,C} acc. EN 1992-4:2018

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of tension resistance for FH II-I and FH II-I R

Annex C 2

Table C3.1: Performance characteristics of **shear resistance** for **FH II** and **FH II R** under static and quasi-static loads

Anchor type FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R		FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Installation factor γ_{inst} [-]							1,0	
Steel failure without lever arm								
FH II-S	$V^0_{Rk,s}$ [kN]	18,0	33,0	59,0	76,0	146,0	176,4	217,0
FH II-B		16,0	27,2	42,8	61,9	119,0	148,8	169,0
FH II-H		16,0	27,2	42,8	61,9	119,0		3)
FH II-SK	$t_{\text{fix}}^{2)}$ [mm]		≥ 10		≥ 15			
	$V^0_{Rk,s}$ [kN]	18,0	33,0	59,0	76,0			3)
	$t_{\text{fix}}^{2)}$ [mm]		< 10		< 15			
	$V^0_{Rk,s}$ [kN]	8,0	14,0	23,0	34,0			
Partial factor $\gamma_{Ms}^{1)}$ [-]						1,25		
Factor for ductility k_7 [-]						1,0		
FH II-S R	$V^0_{Rk,s}$ [kN]	18,0	33,0	59,0	76,0	146,0		3)
Partial factor $\gamma_{Ms}^{1)}$ [-]						1,33		
FH II-B R, -H R	$V^0_{Rk,s}$ [kN]	16,0	27,2	42,8	61,9	119,0		3)
Partial factor $\gamma_{Ms}^{1)}$ [-]						1,25		
FH II-SK R	$t_{\text{fix}}^{2)}$ [mm]		≥ 10		≥ 15			
	$V^0_{Rk,s}$ [kN]	18,0	33,0	59,0	76,0			3)
	$t_{\text{fix}}^{2)}$ [mm]		< 10		< 15			
	$V^0_{Rk,s}$ [kN]	8,0	14,0	23,0	34,0			
Partial factor $\gamma_{Ms}^{1)}$ [-]						1,33		
Factor for ductility k_7 [-]						1,0		
Steel failure with lever arm and concrete prout failure								
Characteristic bending resistance FH II-S, -SK, -B, -H	$M^0_{Rk,s}$ [Nm]	12	30	60	105	266	518	896
Partial factor $\gamma_{Ms}^{1)}$ [-]						1,25		
Characteristic bending resistance FH II R	$M^0_{Rk,s}$ [Nm]	12	30	60	105	266		3)
Partial factor $\gamma_{Ms}^{1)}$ [-]						1,25		
Partial factor $\gamma_{Ms}^{1)}$ [-]						1,33		
Factor for prout failure k_8 [-]		1,0					2,0	
Concrete edge failure								
Effective embedment depth for calculation	$l_f =$ [mm]						h_{ef}	
Outside diameter of a fastener d_{nom}		10	12	15	18	24	28	32

¹⁾ In absence of other national regulations

²⁾ The thickness of the fixture has influence to the characteristic resistance for shear loads, steel failure without lever arm

³⁾ No performance assessed

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of shear resistance for FH II and FH II R

Annex C 3

Table C4.1: Performance characteristics of shear resistance for FH II-I and FH II-I R under static and quasi-static loads

Anchor type FH II-I and FH II-I R	FH II 12/M6 I	FH II 12/M8 I	FH II 15/M10 I	FH II 15/M12 I
Installation factor γ_{inst} [-]		1,0		
Steel failure without lever arm				
Anchor in combination with screw / threaded rod of galvanised steel complying with DIN EN ISO 898:2013				
Strength class 5.8	5	9	15	21
Strength class 6.8	$V^0_{Rk,s}$ [kN]	6	11	18
Strength class 8.8		8	14	23
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,25	
Factor for ductility k_7 [-]			1,0	
Anchor in combination with screw / threaded rod of stainless steel complying with DIN EN ISO 3506:2010				
Strength class A50	$V^0_{Rk,s}$ [kN]	5	9	15
Partial factor $\gamma_{Ms}^{1)}$ [-]			2,38	
Strength class A70	$V^0_{Rk,s}$ [kN]	7	13	20
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,56	
Strength class A80	$V^0_{Rk,s}$ [kN]	8	15	23
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,33	
Factor for ductility k_7 [-]			1,0	
Steel failure with lever arm and concrete prout failure				
Anchor in combination with screw / threaded rod of galvanised steel complying with DIN EN ISO 898:2013				
Strength class 5.8	8	19	37	65
Strength class 6.8	$M^0_{Rk,s}$ [Nm]	9	23	44
Strength class 8.8		12	30	60
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,25	
Factor for ductility k_7 [-]			1,0	
Anchor in combination with screw / threaded rod of stainless steel complying with DIN EN ISO 3506:2010				
Strength class A50	$M^0_{Rk,s}$ [Nm]	8	19	37
P Partial factor $\gamma_{Ms}^{1)}$ [-]			2,38	
Strength class A70	$M^0_{Rk,s}$ [Nm]	11	26	52
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,56	
Strength class A80	$M^0_{Rk,s}$ [Nm]	12	30	60
Partial factor $\gamma_{Ms}^{1)}$ [-]			1,33	
Factor for ductility k_7 [-]			1,0	
Factor for prout failure k_8			2,0	
Concrete edge failure				
Effective embedment depth for calculation	$l_f =$ [mm]		h_{ef}	
Outside diameter of fastener	d_{nom}	12		15

¹⁾ In absence of other national regulations

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of shear resistance for FH II-I and FH II-I R

Annex C 4

Table C5.1: Performance characteristics of **tension resistance** under **fire exposure**

Anchor type	R30			R60		
	$N_{Rk,s,fi,30}$ [kN]	$N_{Rk,p,fi,30}$ [kN]	$N^0_{Rk,c,fi,30}$ [kN]	$N_{Rk,s,fi,60}$ [kN]	$N_{Rk,p,fi,60}$ [kN]	$N^0_{Rk,c,fi,60}$ [kN]
FH II 10, FH II 10 R	0,2	1,8	1,8	0,2	1,8	1,8
FH II 12, FH II 12 R	2,0	3,0	5,0	1,3	3,0	5,0
FH II 15, FH II 15 R	3,2	4,0	7,4	2,3	4,0	7,4
FH II 18, FH II 18 R	4,8	6,3	10,3	3,9	6,3	10,3
FH II 24, FH II 24 R	8,9	9,0	18,0	7,3	9,0	18,0
FH II 28	13,9	12,6	31,4	11,3	12,6	31,4
FH II 32	20,0	16,5	49,6	16,3	16,5	49,6
FH II 12/M6-I, 5.8, A50 ¹⁾	0,1	2,3	5,0	0,1	2,3	5,0
FH II 12/M6-I R 8.8, A70, A80 ^{1) 2)}	0,2			0,2		
FH II 12/M8-I, 5.8, A50 ¹⁾	1,3			0,8		
FH II 12/M8-I R 8.8, A70, A80 ^{1) 2)}	2,0			1,3		
FH II 15/M10-I, 5.8, A50 ¹⁾	2,0	3,0	7,4	1,4	3,0	7,4
FH II 15/M10-I R 8.8, A70, A80 ^{1) 2)}	3,2			2,3		
FH II 15/M12-I, 5.8/A50 ¹⁾	3,0			2,4		
FH II 15/M12-I R 8.8, A70, A80 ^{1) 2)}	4,8			3,9		
Anchor type	R90			R120		
	$N_{Rk,s,fi,90}$ [kN]	$N_{Rk,p,fi,90}$ [kN]	$N^0_{Rk,c,fi,90}$ [kN]	$N_{Rk,s,fi,120}$ [kN]	$N_{Rk,p,fi,120}$ [kN]	$N^0_{Rk,c,fi,120}$ [kN]
FH II 10, FH II 10 R	0,1	1,8	1,8	0,1	1,5	1,5
FH II 12, FH II 12 R	0,6	3,0	5,0	0,2	2,4	4,0
FH II 15, FH II 15 R	1,4	4,0	7,4	1,0	3,2	5,9
FH II 18, FH II 18 R	3,0	6,3	10,3	2,6	5,0	8,2
FH II 24, FH II 24 R	5,6	9,0	18,0	4,8	7,2	14,4
FH II 28	8,8	12,6	31,4	7,5	10,1	25,2
FH II 32	12,6	16,5	49,6	10,8	13,2	39,7
FH II 12/M6-I, 5.8, A50 ¹⁾	0,1	2,3	5,0	0,1	1,8	4,0
FH II 12/M6-I R 8.8, A70, A80 ^{1) 2)}	0,1			0,1		
FH II 12/M8-I, 5.8, A50 ¹⁾	0,4			0,1		
FH II 12/M8-I R 8.8, A70, A80 ^{1) 2)}	0,6			0,2		
FH II 15/M10-I, 5.8, A50 ¹⁾	0,9	3,0	7,4	0,6	2,4	5,9
FH II 15/M10-I R 8.8, A70, A80 ^{1) 2)}	1,4			1,0		
FH II 15/M12-I, 5.8/A50 ¹⁾	1,9			1,6		
FH II 15/M12-I R 8.8, A70, A80 ^{1) 2)}	3,0			2,6		

¹⁾ Intermediate values by linear interpolation

²⁾ In combination with screw / threaded rod strength class 8.8, A70, A80

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of tension resistance under fire exposure

Annex C 5

Table C6.1: Performance characteristics of shear resistance under fire exposure

Anchor type	R30		R60	
	$V_{Rk,s,fi,30}$ [kN]	$M_{Rk,s,fi,30}^0$ [Nm]	$V_{Rk,s,fi,60}$ [kN]	$M_{Rk,s,fi,60}^0$ [Nm]
FH II 10, FH II 10 R	0,3	0	0,3	0
FH II 12, FH II 12 R	2,0	2	1,3	1
FH II 15, FH II 15 R	3,2	4	2,3	3
FH II 18, FH II 18 R	4,8	7	3,9	6
FH II 24, FH II 24 R	8,9	19	7,3	15
FH II 28	13,9	37	11,3	30
FH II 32	20,0	64	16,3	52
FH II 12/M6 I, FH II 12/M6 I R	5,8, A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	0,2 0,3	0 0	0 0
FH II 12/M8 I, FH II 12/M8-I R	5,8, A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	1,3 2,0	1 2	0,8 1,3
FH II 15/M10 I, FH II 15/M10-I R	5,8, A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	2,0 3,2	3 4	1,4 2,3
FH II 15/M12-I, FH II 15/M12-I R	5,8/A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	3,0 4,8	4 7	2,4 3,9
Anchor type	R90		R120	
	$V_{Rk,s,fi,90}$ [kN]	$M_{Rk,s,fi,90}^0$ [Nm]	$V_{Rk,s,fi,120}$ [kN]	$M_{Rk,s,fi,120}^0$ [Nm]
FH II 10, FH II 10 R	0,2	0	0,1	0
FH II 12, FH II 12 R	0,6	1	0,2	0
FH II 15, FH II 15 R	1,4	2	1,0	1
FH II 18, FH II 18 R	3,0	5	2,6	4
FH II 24, FH II 24 R	5,6	12	4,8	10
FH II 28	8,8	23	7,5	20
FH II 32	12,6	40	10,8	34
FH II 12/M6-I, FH II 12/M6-I R	5,8, A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	0,1 0,2	0 0	0,1 0
FH II 12/M8-I, FH II 12/M8-I R	5,8, A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	0,4 0,6	1 1	0,1 0,2
FH II 15/M10 I, FH II 15/M10-I R	5,8, A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	0,9 1,4	2 3	0,6 1,0
FH II 15/M12 I, FH II 15/M12-I R	5,8/A50 ¹⁾ 8,8, A70, A80 ^{1) 2)}	1,9 3,0	4 6	1,6 2,6

¹⁾ Intermediate values by linear interpolation²⁾ In combination with screw / threaded rod strength class 8,8, A70, A80**Table C6.2:** Minimum spacings and minimum edge distances of anchors under fire exposure for tension and shear loads

Anchor type	FH II 10	FH II 12 FH II 12-I	FH II 15 FH II 15-I	FH II 18	FH II 24	FH II 28	FH II 32
Spacing	$\frac{S_{cr,N,fi}}{S_{min,fi}}$	$4x h_{ef}$					
	40	50	60	70	80	100	120
Edge distance	$\frac{C_{cr,N,fi}}{C_{min,fi}}$ [mm]	$2 \times h_{ef}$					

$$C_{min,fi} = 2 \times h_{ef}, \\ \text{for fire exposure from more than one side } c_{min,fi} \geq 300 \text{ mm}$$

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of shear resistance under fire exposure

Minimum spacings and minimum edge distances of anchors under fire exposure

Annex C 6

Table C7.1: Minimum thickness of concrete member, minimum spacing and minimum edge distances
FH II, FH II R

Anchor type FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R	FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32		
Minimum thickness of concrete member	h_{min}	[mm]	80	120	140	160	200	250	300
Minimum spacing, cracked concrete	s_{min}	[mm]	40	50	60	70	80	100	120
	for $c \geq$		40	80	120	140	180	200	260
Minimum edge distance, cracked concrete	c_{min}	[mm]	40	50	60	70	80	100	120
	for $s \geq$		40	80	120	160	200	220	280
Minimum spacing, uncracked concrete	s_{min}	[mm]	40	60	70	80	100	120	160
	for $c \geq$		70	100	100	160	200	220	360
Minimum edge distance, uncracked concrete	c_{min}	[mm]	40	60	70	80	100	120	180
	for $s \geq$		70	100	140	200	220	240	380

Intermediate values may be calculated by linear interpolation

Table C7.2: Minimum thickness of concrete member, minimum spacing and minimum edge distances
FH II-I, FH II-I R

Anchor type FH II-I and FH II-I R	FH II 12/M6 I	FH II 15/M10 I	FH II 15/M12 I	
Minimum thickness of concrete member	h_{min}	[mm]	125	150
Minimum spacing, cracked concrete	s_{min}	[mm]	50	60
	for $c \geq$		80	120
Minimum edge distance, cracked concrete	c_{min}	[mm]	50	60
	for $s \geq$		80	120
Minimum spacing, uncracked concrete	s_{min}	[mm]	60	70
	for $c \geq$		100	100
Minimum edge distance, uncracked concrete	c_{min}	[mm]	60	70
	for $s \geq$		100	140

Intermediate values may be calculated by linear interpolation.

fischer High-Performance Anchor FH II, FH II-I

Performances

Minimum thickness of concrete member, minimum spacing and minimum edge distances

Annex C 7

Table C8.1: Performance characteristics of **tension and shear resistance** for **seismic performance category C1** for FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R

Anchor type FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R		FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Steel failure							
Characteristic resistance of tension load C1	FH II-S, -B	29,3	46,4	67,4	125,3	195,8	282,0
	FH II-H, -H R, -B R	N _{Rk,s,C1} [kN]	29,3	46,4	67,4	125,3	3)
	FH II-SK		29,3	46,4	67,4		3)
	Partial factor	γ _{Ms,C1} ¹⁾ [-]			1,5		
	FH II-S R	N _{Rk,s,C1} [kN]	29,3	46,4	67,4	125,3	3)
	FH II-SK R		29,3	46,4	67,4		3)
	Partial factor	γ _{Ms,C1} ¹⁾ [-]			1,6		
Pullout failure							
Characteristic resistance of tension load in cracked concrete C1	N _{Rk,p,C1} [kN]	12,0	16,0	25,0	36,0	50,3	66,1
	γ _{Mp,C1} ¹⁾ [-]				1,5		
Steel failure without lever arm							
Characteristic resistance of shear load C1							
FH II-S	V _{Rk,s,C1} [kN]	25,0	41,0	60,0	123,0	141,0	200,0
		17,0	30,0	46,0	103,0	117,0	169,0
		17,0	30,0	46,0	103,0		
FH II-B	t _{fix} ²⁾ [mm]	≥ 10		≥ 15			
	V _{Rk,s,C} [kN]	25,0	41,0	60,0			
	t _{fix} ²⁾ [mm]	< 10		< 15			
	V _{Rk,s,C} [kN]	11,0	16,0	27,0			
Partial factor	γ _{Ms,C1} ¹⁾ [-]			1,25			
FH II-S R	V _{Rk,s,C1} [kN]	25,0	41,0	60,0	123,0		-
Partial factor	γ _{Ms,C1} ¹⁾ [-]			1,33			
FH II-B R, -H R	V _{Rk,s,C1} [kN]	17,0	30,0	46,0	103,0		-
Partial factor	γ _{Ms,C1} ¹⁾ [-]			1,25			
FH II-SK	t _{fix} ²⁾ [mm]	≥ 10		≥ 15			
	V _{Rk,s,C1} [kN]	25,0	41,0	60,0			
	t _{fix} ²⁾ [mm]	< 10		< 15			
	V _{Rk,s,C1} [kN]	11,0	16,0	27,0			
Partial factor	γ _{Ms,C1} ¹⁾ [-]			1,33			
Factor for annular gap	α _{gap}			0,50			

¹⁾ In absence of other national regulations

²⁾ The thickness of the fixture has influence to the characteristic resistance for shear loads, steel failure without lever arm

³⁾ No performance assessed

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of tension and shear resistance for seismic performance category C1

Annex C 8

Table C9.1: Performance characteristics of **tension and shear resistance** for **seismic performance category C2** for FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R

Anchor type FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R		FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Steel failure							
Characteristic resistance of tension load C2	FH II-S, -B		29,3	46,4	67,4	125,3	195,8
	FH II-H, -H R, -B R	N _{Rk,s,C2} [kN]	29,3	46,4	67,4	125,3	3)
	FH II-SK		29,3	46,4	67,4		3)
	Partial factor $\gamma_{Ms,C2}^{1)}$ [-]				1,5		
	FH II-S R	N _{Rk,s,C2} [kN]	29,3	46,4	67,4	125,3	3)
	FH II-SK R		29,3	46,4	67,4		3)
	Partial factor $\gamma_{Ms,C2}^{1)}$ [-]				1,6		
Pullout failure							
Characteristic resistance of tension load in cracked concrete C2	N _{Rk,p,C2} [kN]		6,2	11,3	21,8	43,0	65,9
	$\gamma_{Mp,C2}^{1)}$ [-]				1,5		
Steel failure without lever arm							
Characteristic resistance of shear load C2							
FH II-S			14,7	28,9	41,0		100,7
	V _{Rk,s,C2} [kN]		9,8	20,9	34,1	61,9	67,2
			9,8	20,9	34,1	61,9	3)
FH II-SK	t _{fix} ²⁾ [mm]		≥ 10	≥ 15			
	V _{Rk,s,C2} [kN]		14,8	23,3	33,8		3)
	t _{fix} ²⁾ [mm]		< 10	< 15			
	V _{Rk,s,C2} [kN]		6,3	9,1	15,1		
Partial factor $\gamma_{Ms,C2}^{1)}$ [-]					1,25		
FH II-S R	V _{Rk,s,C2} [kN]		14,7	28,9	41,0	100,7	3)
Partial factor $\gamma_{Ms,C2}^{1)}$ [-]					1,33		
FH II-B R, -H R	V _{Rk,s,C2} [kN]		9,8	20,9	34,1	61,9	3)
Partial factor $\gamma_{Ms,C2}^{1)}$ [-]					1,25		
FH II-SK R	t _{fix} ²⁾ [mm]		≥ 10	≥ 15			
	V _{Rk,s,C2} [kN]		14,8	23,3	33,8		3)
	t _{fix} ²⁾ [mm]		< 10	< 15			
	V _{Rk,s,C2} [kN]		6,3	9,1	15,1		
Partial factor $\gamma_{Ms,C2}^{1)}$ [-]					1,33		
Factor for annular gap	α_{gap}				0,50		

¹⁾ In absence of other national regulations

²⁾ The thickness of the fixture has influence to the characteristic resistance for shear loads, steel failure without lever arm

3) No performance assessed

fischer High-Performance Anchor FH II, FH II-I

Performances

Performance characteristics of tension and shear resistance for seismic performance category C2

Annex C 9

Table C10.1: Displacements under static and quasi static **tension loads** for FH II and FH II R

Anchor type FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R		FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Tension load cracked concrete	N [kN]	3,6	5,7	7,6	11,9	17,1	24,0	31,5
Corresponding displacements	$\frac{\delta_{N0}}{\delta_{N\infty}}$ [mm]	1,0	1,0	1,0	1,0	1,0	0,7	0,7
		1,7	1,6	1,6	1,6	1,8	1,3	1,1
Tension load uncracked concrete	N [kN]	6,0	11,2	14,1	17,2	24,0	33,6	44,2
Corresponding displacements	$\frac{\delta_{N0}}{\delta_{N\infty}}$ [mm]	0,6	1,0	1,0	1,0	1,0	0,3	0,3
		1,7	1,6	1,6	1,6	1,8	1,3	1,1

Table C10.2: Displacements under static and quasi static **tension loads** for FH II-I and FH II-I R

Anchor type FH II-I and FH II-I R		FH II 12/M6 I	FH II 15/M10 I
Tension load cracked concrete	N [kN]	4,3	5,7
Tension load uncracked concrete	N [kN]	9,5	14,1
Corresponding displacements	$\frac{\delta_{N0}}{\delta_{N\infty}}$ [mm]	1,7	1,9
		2,2	2,9

Table C10.3: Displacements under static and quasi static **shear loads** for FH II-S and FH II-SK

Anchor type FH II-S and FH II-SK		FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Shear load in cracked and uncracked concrete	V [kN]	10,3	18,9	33,7	43,4	83,4	99,4	124,0
Corresponding displacements	$\frac{\delta_{v0}}{\delta_{v\infty}}$ [mm]	2,4	2,7	4,4	5,0	7,0	6,0	8,0
		3,6	4,1	6,6	7,5	10,5	9,0	12,0

Table C10.4: Displacements under static and quasi static **shear loads** for FH II-B and FH II-H

Anchor type FH II-B and FH II-H		FH II 10	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Shear load in cracked and uncracked concrete	V [kN]	8,9	15,4	23,4	35,4	68,0	83,4	96,6
Corresponding displacements	$\frac{\delta_{v0}}{\delta_{v\infty}}$ [mm]	2,2	2,3	3,0	5,0	7,0	5,0	5,0
		3,3	3,5	4,5	7,5	10,5	7,5	7,5

fischer High-Performance Anchor FH II, FH II-I

Performances
Displacements under tension and shear loads

Annex C 10

Table C11.1: Displacements under static and quasi static **shear loads** for FH II-S R, FH II-SK R, FH II-B R and FH II-H R

Anchor type FH II-S R, -SK R, -B R, -H R	FH II 10	FH II 12	FH II 15	FH II 18	FH II 24
Shear load in cracked and uncracked concrete V [kN]	10,3	16,0	24,6	37,7	68,0
Corresponding displacements $\frac{\delta v_0}{\delta v_\infty}$ [mm]	3,5 5,3	3,5 5,3	3,7 5,6	5,7 8,6	9,0 13,5

Table C11.2: Displacements under static and quasi static **shear loads** for FH II-I and FH II-I R

Anchor type: FH II-I and FH II-I R	FH II 12/M6 I	FH II 12/M8 I	FH II 15/M10 I	FH II 15/M12 I
Shear load in cracked and uncracked concrete V [kN]	4,6	8,3	13,3	13,7
Corresponding displacements $\frac{\delta v_0}{\delta v_\infty}$ [mm]	2,6 3,9	2,6 3,9	2,2 3,3	2,2 3,3

Table C11.3: Displacements under **tension loads** for **seismic performance category C2** for FH II and FH II R

Anchor type FH II-S, -SK, -B, -H and FH II-S R, -SK R, -B R, -H R	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Displacement DLS $\delta_{N,C2}(\text{DLS})$ [mm]	1,55	2,63	2,04	4,26		3,06
Displacement ULS $\delta_{N,C2}(\text{ULS})$ [mm]	8,71	11,07	7,30	11,70		11,44

Table C11.4: Displacements under **shear loads** for **seismic performance category C2** for FH II and FH II R

Anchor type FH II-S, -SK and FH II-S R, -SK R	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Displacement DLS $\delta_{v,C2}(\text{DLS})$ [mm]	3,53	4,18	4,67	5,59		4,79
Displacement ULS $\delta_{v,C2}(\text{ULS})$ [mm]	6,62	7,38	9,03	14,09		9,95
Anchor type FH II-B, -H and FH II-B R, -H R	FH II 12	FH II 15	FH II 18	FH II 24	FH II 28	FH II 32
Displacement DLS $\delta_{v,C2}(\text{DLS})$ [mm]	3,42	4,26	4,29		4,79	
Displacement ULS $\delta_{v,C2}(\text{ULS})$ [mm]	5,26	6,66	7,95	7,69		9,95

fischer High-Performance Anchor FH II, FH II-I

Performances
Displacements under tension and shear loads

Annex C 11