

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 22/08/2024 Revision date: 29/11/2024 Supersedes version of: 22/08/2024 Version: 1.1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture Trade name : FireStop Foam

UFI VV30-X0TX-U00V-KQN8

00043712 Article number Vaporizer Aerosol

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

: Industrial use, Professional use Main use category

Industrial/Professional use spec As from 24 August 2023 adequate training is required before industrial or professional use

Use of the substance/mixture : Polyurethane, polyurethane foam

### 1.3. Details of the supplier of the safety data sheet

Manufacturer Distributor fischerwerke GmbH & Co. KG fischer fixings UK Ltd. Klaus-Fischer-Straße 1 Whitely Road

72178 Waldachtal Oxon OX10 9AT Wallingford

United Kingdom of Great Britain and Northern Ireland Germany T +49(0)7443 12-0, F +49(0)7443 12-4222 T +44 14 91 82 79 00, F +44 14 91 82 79 53 info-sdb@fischer.de, www.fischer.de info@fischer.co.uk, www.fischer.co.uk

#### 1.4. Emergency telephone number

Emergency number : +49(0)6132-84463 (24h)

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1	H222;H229
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373
Full text of hazard classes, H- and EUH-statements: see section	on 16

#### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### 2.2. Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02



GHS07

GHS08

Signal word (CLP)

Contains : Isocyanic acid, polymethylenepolyphenylene ester

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

29/11/2024 (Revision date) GB - en 1/12 01/04/2025 (Printing date)

# Safety Data Sheet

Precautionary statements (CLP)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

P102 - Keep out of reach of children.

P260 - Do not breathe gas.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection/face protection, protective clothing, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local,

regional, national and/or international regulation.

**EUH-statements** : EUH204 - Contains isocyanates. May produce an allergic reaction. Extra phrases

: Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Without adequate ventilation formation of explosive mixtures may be possible.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

As from 24 August 2023 adequate training is required before industrial or professional use.

Supplementary information: www.feica.eu/PUinfo.

#### 2.3. Other hazards

PBT: not relevant - no registration required vPvB: not relevant - no registration required

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isocyanic acid, polymethylenepolyphenylene ester	CAS-No.: 9016-87-9 EC-No.: 618-498-9	≥ 30 - < 80	Acute Tox. 4 (Inhalation:vapour), H332 (ATE=0.31 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 EUH204
Reaction products of phosphoryl trichloride and 2-methyloxirane	CAS-No.: 1244733-77-4 EC-No.: 807-935-0 REACH-no: 01-2119486772-26	< 25	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight)
halogenated polyetherpolyol	CAS-No.: 86675-46-9 EC-No.: 617-903-6 REACH-no: 01-2119972940-30	< 15	Acute Tox. 4 (Oral), H302 (ATE=632 mg/kg bodyweight)
dimethyl ether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128-37	< 10	Flam. Gas 1, H220 Press. Gas (Liq.), H280

29/11/2024 (Revision date) GB - en 2/12 01/04/2025 (Printing date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. First-aid measures after skin contact : Wash skin with plenty of water and soap. Take off contaminated clothing. If skin irritation or rash occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Wash out mouth with water and afterwards drink plenty of water. Do NOT induce vomiting. Call a poison center or

a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete

protective clothing.

Other information : Do not allow water used to extinguish fire to enter drains, ground or waterways.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe Avoid breathing

dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8:

"Exposure controls/personal protection".

# 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site

# 6.4. Reference to other sections

For further information refer to section 13.

29/11/2024 (Revision date) GB - en 3/12 01/04/2025 (Printing date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

#### 7.3. Specific end use(s)

PU installation foams.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

National occupational exposure and biological limit values

#### dimethyl ether (115-10-6)

#### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Dimethylether
IOEL TWA	1920 mg/m³
	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Dimethyl ether
WEL TWA (OEL TWA)	766 mg/m³
	400 ppm
WEL STEL (OEL STEL)	958 mg/m³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# 8.2. Exposure controls

# Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

# Personal protection equipment

Personal protective equipment symbol(s):







### Eye and face protection

Eye protection:

Safety glasses

#### Skin protection

Skin and body protection:

Wear suitable protective clothing

29/11/2024 (Revision date) GB - en 4/12 01/04/2025 (Printing date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Butyl rubber	6 (> 480 minutes)	> 0,7		EN 374-2, EN 374-3
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,7		EN 374-2, EN 374-3

#### Respiratory protection

#### Respiratory protection:

In the event of insufficient ventilation: Use self-contained breathing apparatus

Respiratory protection			
Device	Filter type	Condition	Standard
	Type A - High-boiling (>65 °C) organic compounds		EN 140
	Filter AX (brown)		EN 14387

#### **Environmental exposure controls**

#### **Environmental exposure controls:**

Avoid release to the environment.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: LiquidColour: Various colours.Appearance: Aerosol.Odour: Not availableOdour threshold: Not availableMelting point: Not availableFreezing point: Not availableBoiling point: Aerosol Not applicable

Flammability : Aerosol Not applicable : Aerosol Not applicable

Explosive properties : Pressurised container: May burst if heated.

Flash point : Aerosol Not applicable

Solubility : Not miscible. Reacts with water.

Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : > 500 kPa Vapour pressure at 50°C : Not available Density : 1.3 g/cm³ Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

# 9.2. Other information

# Information with regard to physical hazard classes

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

29/11/2024 (Revision date) GB - en 5/12

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong acids. Oxidizing agent. Strong bases. Water. alcohols. Amines.

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

FireStop	Foam
----------	------

ATE CLP (dust,mist) 2.5 mg/l/4h

ш	[ a a a v. a m i a	aaid	malv.maath.		** m h a m ** l a m a		(0016 07 0)
ш	isocvanic	aciu.	DOIV MELI	vieneboi	vbnenviene	ester	(9016 - 87 - 9)

LD50 oral rat	> 10000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 9400 mg/kg (OECD 402 method)
LC50 Inhalation - Rat (Vapours)	0.31 mg/l/4h (OECD 403 method)

Reaction products of	nhosphoryl	trichloride and	2-methyloxirane	(1244733-77-4)

LD50 oral rat	632 mg/kg
T	2000 A (0707 402 A D

LD50 dermal rat > 2000 mg/kg (OECD 402 method)

# $dimethyl\ ether\ (115-10-6)$

LC50 Inhalation - Rat [ppm] 164000 ppm

#### halogenated polyetherpolyol (86675-46-9)

LD50 oral rat		917 mg/kg bodyweight
Skin corrosion/irritation	:	Causes skin irritation.
Serious eye damage/irritation	:	Causes serious eye irritation.

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

# $Is o cyanic\ a cid,\ polymethylene polyphenylene\ ester\ (9016-87-9)$

IARC group 3 - Not classifiable
Reproductive toxicity: Not classified

STOT-single exposure : May cause respiratory irritation.

# Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

#### Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

### halogenated polyetherpolyol (86675-46-9)

LOAEL (oral, rat, 90 days)
417 mg/kg bodyweight Animal: rat, Guideline: other:

Aspiration hazard : Not classified

29/11/2024 (Revision date) GB - en 6/12 01/04/2025 (Printing date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

FireStop Foam		
Vaporizer	Aerosol	
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)		
Viscosity, kinematic	> 161.551 mm²/s	

# 11.2. Information on other hazards

No additional information available

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Isocyanic acid nalymathylananalynh	envlene ester (9016-87-9)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Hazardous to the aquatic environment, short-term (acute)	: Not classified
	environment.
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
LC50 - Fish [1] > 1000 mg/l Brachydanio rerio (zebra-fish)	
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna (Water flea)
ErC50 algae	> 1640 mg/l Scenedesmus subspicatus
NOEC chronic crustacea	> 10 mg/l Daphnia magna (Water flea)
Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)	

LC50 - Fish [1] EC50 - Crustacea [1]	56.2 mg/l Brachydanio rerio (zebra-fish) 131 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	82 mg/l Pseudokirchneriella subcapitata
NOEC (chronic)	32 mg/l Daphnia magna (Water flea)

dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l Poecilia reticulata (Guppy)
EC50 - Crustacea [1]	> 4.4 g/l Daphnia magna (Water flea)
EC50 96h - Algae [1]	154917 mg/l

zero your right [1]	
halogenated polyetherpolyol (86675-46-9)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

# 12.2. Persistence and degradability

FireStop Foam		
Persistence and degradability	Not rapidly degradable	
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)		
Persistence and degradability	Not rapidly degradable	
Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)		
Persistence and degradability	Rapidly degradable	
dimethyl ether (115-10-6)		
Persistence and degradability Not rapidly degradable		
halogenated polyetherpolyol (86675-46-9)		
Persistence and degradability	Not rapidly degradable	

29/11/2024 (Revision date) GB - en 7/12 01/04/2025 (Printing date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# 12.3. Bioaccumulative potential

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)			
Bioconcentration factor (BCF REACH) < 14 Cyprinus carpio (Common carp)			
Partition coefficient n-octanol/water (Log Pow) 10.46			
dimethyl ether (115-10-6)			
Partition coefficient n-octanol/water (Log Pow) 0.1			

# 12.4. Mobility in soil

dimethyl ether (115-10-6)	
Mobility in soil	27

# 12.5. Results of PBT and vPvB assessment

FireStop F	o i	a	m
------------	-----	---	---

PBT: not relevant - no registration required

vPvB: not relevant - no registration required

# 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Regional waste regulation

: Disposal must be done according to official regulations.

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations

: Discharging into rivers and drains is forbidden.

Additional information

: Special waste.

European List of Waste (LoW, EC 2000/532)

: 08 05 01\* - waste isocyanates

16 05 04\* - gases in pressure containers (including halons) containing dangerous substances 17 06 04 - insulation materials other than those mentioned in 17 06 01 and 17 06 03

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA			
14.1. UN number or ID number					
UN 1950	UN 1950	UN 1950			
14.2. UN proper shipping name					
AEROSOLS	AEROSOLS	Aerosols, flammable			
Transport document description					
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1			
14.3. Transport hazard class(es)					
2.1	2.1	2.1			
2	2	2			
14.4. Packing group					
Not applicable	Not applicable	Not applicable			

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No
No supplementary information available		

#### 14.6. Special precautions for user

# Overland transport

Classification code (ADR) : 5F

: 190, 327, 344, 625 Special provisions (ADR)

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0 Packing instructions (ADR) : P207, LP200

Special packing provisions (ADR) : PP87, RR6, L2 Mixed packing provisions (ADR) : MP9 Transport category (ADR) : V14 Special provisions for carriage - Packages (ADR)

#### Transport by sea

Tunnel restriction code (ADR)

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

#### Air transport

PCA packing instructions (IATA) : 203 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) 150kg Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

: D

### **EU-Regulations**

### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

# **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

# Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

29/11/2024 (Revision date) GB - en 9/12

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

# Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	

29/11/2024 (Revision date) 01/04/2025 (Printing date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ED Endocrine disruptor

Full text of H- and EUH-statements:			
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4		
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aerosol 1	Aerosol, Category 1		
Carc. 2	Carcinogenicity, Category 2		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1	Flammable gases, Category 1		
Press. Gas (Liq.)	Gases under pressure : Liquefied gas		
Resp. Sens. 1	Respiratory sensitisation, Category 1		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
Skin Sens. 1	Skin sensitisation, Category 1		
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H229	Pressurised container: May burst if heated.		
H280	Contains gas under pressure; may explode if heated.		
H302	Harmful if swallowed.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
H335	May cause respiratory irritation.		
H351	Suspected of causing cancer.		
H373	May cause damage to organs through prolonged or repeated exposure.		
EUH204	Contains isocyanates. May produce an allergic reaction.		

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	On basis of test data
Acute Tox. 4 (Inhalation:dust,mist)	Н332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

29/11/2024 (Revision date) 01/04/2025 (Printing date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.