Fill&Fix

Kit Safety Information Sheet (SIS)

Issue date: 06/03/2025 Version: 1.0

SECTION 1: Kit identification

1.1 Kit identifier

Trade name : Fill&Fix
Article number : 00505084

1.2 Details of the supplier of the Kit safety information sheet

fischerwerke GmbH & Co. KG
Klaus-Fischer-Straße 1
72178 Waldachtal - Germany
T +49(0)7443 12-0 - F +49(0)7443 12-4222
info-sdb@fischer.de - www.fischer.de

SECTION 2: General information

Restrictions on use : As from 24 August 2023 adequate training is required before industrial or professional use
Storage : 5 - 25°C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page This product is a Kit which consists of several independently packaged components

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Name	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Fill&Fix Component A	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Fill&Fix Component B	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 2, H411



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Trade name	:	Fill&Fix Component A
UFI	:	AU20-V0J6-500X-NMNG
Article number	:	M154

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category	:	Industrial use,Professional use,Consumer use
Use of the substance/mixture	:	composite mortar

1.2.2. Uses advised against

Restrictions on use	:	Observe technical data sheet

1.3. Details of the supplier of the safety data sheet

Manufacturer
fischerwerke GmbH & Co. KG
Klaus-Fischer-Straße 1
72178 Waldachtal
Germany
T +49(0)7443 12-0, F +49(0)7443 12-4222
info-sdb@fischer.de, www.fischer.de

Distributor
fischer fixings UK Ltd.
Whitely Road
Oxon OX10 9AT Wallingford
United Kingdom of Great Britain and Northern Ireland
T +44 14 91 82 79 00, F +44 14 91 82 79 53
info@fischer.co.uk, www.fischer.co.uk

1.4. Emergency telephone number

Emergency number	:	+49(0)6132-84463 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Oral)	H302
Eye Irrit. 2	H319

Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07

Signal word (CLP)	:	Warning
Contains	:	butane-1,4-diol; triethylenediamine; polypropylene glycol
Hazard statements (CLP)	:	H302 - Harmful if swallowed. H319 - Causes serious eye irritation.
Precautionary statements (CLP)	:	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Labelling according to: exemption for packages of a capacity of 125ml or less

Hazard pictograms (CLP) :

GHS07

Signal word (CLP) : Warning
Hazardous ingredients : butane-1,4-diol; triethylenediamine; polypropylene glycol
Hazard statements (CLP) : H302 - Harmful if swallowed.
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
polypropylene glycol	CAS-No.: 25322-69-4 EC-No.: 500-039-8	≥ 30 – < 40	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight)
butane-1,4-diol	CAS-No.: 110-63-4 EC-No.: 203-786-5 REACH-no: 01-2119471849-20	≥ 5 – < 10	Acute Tox. 4 (Oral), H302 (ATE=1500 mg/kg bodyweight) Acute Tox. 3 (Inhalation:vapour), H331 (ATE=3 mg/l/4h) STOT SE 3, H336
triethylenediamine	CAS-No.: 280-57-9 EC-No.: 205-999-9 REACH-no: 01-2119980944-22	≥ 1 – < 2.5	Flam. Sol. 1, H228 Acute Tox. 4 (Oral), H302 (ATE=700 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	:	Do not allow water used to extinguish fire to enter drains, ground or waterways. Avoid direct discharge into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	:	Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	:	Mechanically recover the product.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	:	Not expected to present a significant hazard under anticipated conditions of normal use. In the event that dust and/or fine particles are generated with this product, it is prudent to minimize prolonged inhalation exposure to these forms not to exceed the occupational exposure limit.
Precautions for safe handling	:	Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing vapours.
Hygiene measures	:	Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	:	Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves. Breakthrough time : refer to the recommendations of the supplier. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves	Nitrile rubber (NBR), Butyl rubber	2 (> 30 minutes)			

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Solid
Appearance	:	Paste.
Colour	:	white.
Odour	:	slight.
Odour threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	> 100 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable
Vapour pressure	:	No data available
Relative vapour density at 20°C	:	No data available

Relative density	:	No data available
Density	:	0.73 – 0.77 g/cm³
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	77922.078 – 123287.671 mm²/s
Viscosity, dynamic	:	60 – 90 Pa·s
Explosive properties	:	No data available
Oxidising properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	:	Harmful if swallowed.
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Fill&Fix Component A	
ATE CLP (oral)	1186.36 mg/kg bodyweight
butane-1,4-diol (110-63-4)	
LD50 oral rat	1500 mg/kg
LD50 dermal rat	> 2000 mg/kg bw/day
LC50 Inhalation - Rat	> 5.1 mg/l (OECD 403 method)
triethylenediamine (280-57-9)	
LD50 oral rat	700 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
polypropylene glycol (25322-69-4)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 5010 mg/kg bodyweight Animal: rabbit, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.34 mg/l Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)

Skin corrosion/irritation	:	Not classified pH: No data available
Serious eye damage/irritation	:	Causes serious eye irritation. pH: No data available

Respiratory or skin sensitisation	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified

butane-1,4-diol (110-63-4)	
NOAEL (chronic, oral, animal/male, 2 years)	225 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:, Remarks on results: other:
NOAEL (chronic, oral, animal/female, 2 years)	450 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:, Remarks on results: other:

Reproductive toxicity	:	Not classified
STOT-single exposure	:	Not classified

butane-1,4-diol (110-63-4)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	:	Not classified

triethylenediamine (280-57-9)	
LOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

polypropylene glycol (25322-69-4)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (subchronic, oral, animal/male, 90 days)	443 mg/kg bodyweight Animal: cat, Animal sex: male

Aspiration hazard	:	Not classified

Fill&Fix Component A	
Viscosity, kinematic	77922.078 – 123287.671 mm²/s

butane-1,4-diol (110-63-4)	
Viscosity, kinematic	83.2 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)' Remarks on result: 'other:'

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	:	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short–term (acute)	:	Not classified
Hazardous to the aquatic environment, long–term (chronic)	:	Not classified

butane-1,4-diol (110-63-4)	
LC50 - Fish [1]	> 30000 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	813 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 500 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	> 85 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

triethylenediamine (280-57-9)	
LC50 - Fish [1]	681 mg/l Leuciscus idus (golden orfe)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	110 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

polypropylene glycol (25322-69-4)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	> 109 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

polypropylene glycol (25322-69-4)	
LOEC (chronic)	> 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Fill&Fix Component A	
Persistence and degradability	Not rapidly degradable
butane-1,4-diol (110-63-4)	
Persistence and degradability	Not rapidly degradable
triethylenediamine (280-57-9)	
Persistence and degradability	Not rapidly degradable
polypropylene glycol (25322-69-4)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Only pass on empty containers/packaging for recycling.
Additional information : Not classified as hazardous waste when part A and part B are mixed and are fully cured.
European List of Waste (LoW, EC 2000/532) : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* - paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number		
Not regulated for transport		
14.2. UN proper shipping name		
Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)		
Not regulated	Not regulated	Not regulated
14.4. Packing group		
Not regulated	Not regulated	Not regulated
14.5. Environmental hazards		
Not regulated	Not regulated	Not regulated

No supplementary information available

14.6. Special precautions for user

Overland transport
Not regulated

Transport by sea
Not regulated

Air transport
Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value

Abbreviations and acronyms:	
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Sol. 1	Flammable solids, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H228	Flammable solid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.

Full text of H- and EUH-statements:	
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Oral)	H302	Calculation method
Eye Irrit. 2	H319	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Trade name	:	Fill&Fix Component B
UFI	:	GX20-D07K-G00E-AY7J
Article number	:	M156

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Intended for general public

Main use category	:	Industrial use,Professional use,Consumer use
Industrial/Professional use spec	:	As from 24 August 2023 adequate training is required before industrial or professional use
Use of the substance/mixture	:	composite mortar

Uses advised against

Restrictions on use	:	Observe technical data sheet

1.3. Details of the supplier of the safety data sheet

Manufacturer
fischerwerke GmbH & Co. KG
Klaus-Fischer-Straße 1
72178 Waldachtal
Germany
T +49(0)7443 12-0, F +49(0)7443 12-4222
info-sdb@fischer.de, www.fischer.de

Distributor
fischer fixings UK Ltd.
Whitely Road
Oxon OX10 9AT Wallingford
United Kingdom of Great Britain and Northern Ireland
T +44 14 91 82 79 00, F +44 14 91 82 79 53
info@fischer.co.uk, www.fischer.co.uk

1.4. Emergency telephone number

Emergency number	:	+49(0)6132-84463 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 2	H411

Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07 GHS08 GHS09

Signal word (CLP)	:	Danger
Contains	:	Isocyanic acid, polymethylenepolyphenylene ester; aromatic polyisocyanate prepolymer; o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate
Hazard statements (CLP)	:	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction.

		H319 - Causes serious eye irritation. H332 - Harmful if inhaled. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 - May cause respiratory irritation. H351 - Suspected of causing cancer. H373 - May cause damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	:	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P280 - Wear eye protection, protective gloves. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342+P311 - If experiencing respiratory symptoms: Call doctor.
EUH-statements	:	EUH204 - Contains isocyanates. May produce an allergic reaction.
Extra phrases	:	Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

Labelling according to: exemption for packages of a capacity of 125ml or less

Hazard pictograms (CLP)	:	 GHS07 GHS08 GHS09
Signal word (CLP)	:	Danger
Hazardous ingredients	:	Isocyanic acid, polymethylenepolyphenylene ester; aromatic polyisocyanate prepolymer; o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate
Hazard statements (CLP)	:	H317 - May cause an allergic skin reaction. H332 - Harmful if inhaled. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 - May cause respiratory irritation. H351 - Suspected of causing cancer. H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	:	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P280 - Wear eye protection, protective gloves. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342+P311 - If experiencing respiratory symptoms: Call doctor.
EUH-statements	:	EUH204 - Contains isocyanates. May produce an allergic reaction.
Extra phrases	:	Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isocyanic acid, polymethylenepolyphenylene ester	CAS-No.: 9016-87-9 EC-No.: 618-498-9	≥ 40 – < 50	Acute Tox. 4 (Inhalation:vapour), H332 (ATE=0.31 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 EUH204
aromatic polyisocyanate prepolymer	CAS-No.: 99784-49-3	≥ 25 – < 30	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 2, H411
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate	CAS-No.: 5873-54-1 EC-No.: 227-534-9 EC Index-No.: 615-005-00-9 REACH-no: 01-2119480143-45	≥ 5 – < 10	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate substance with national workplace exposure limit(s) (IE)	CAS-No.: 101-68-8 EC-No.: 202-966-0 EC Index-No.: 615-005-00-9 REACH-no: 01-2119457014-47	≥ 5 – < 10	Acute Tox. 4 (Inhalation), H332 (ATE=0.49 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

Specific concentration limits:		
Name	**Product identifier**	**Specific concentration limits (%)**
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate	CAS-No.: 5873-54-1 EC-No.: 227-534-9 EC Index-No.: 615-005-00-9 REACH-no: 01-2119480143-45	(0.1 ≤ C ≤ 100) Resp. Sens. 1; H334 (5 ≤ C ≤ 100) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) Skin Irrit. 2; H315 (5 ≤ C ≤ 100) STOT SE 3; H335
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	CAS-No.: 101-68-8 EC-No.: 202-966-0 EC Index-No.: 615-005-00-9 REACH-no: 01-2119457014-47	(0.1 ≤ C ≤ 100) Resp. Sens. 1; H334 (5 ≤ C ≤ 100) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) Skin Irrit. 2; H315 (5 ≤ C ≤ 100) STOT SE 3; H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Other information : Do not allow water used to extinguish fire to enter drains, ground or waterways. Avoid direct discharge into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use. In the event that dust and/or fine particles are generated with this product, it is prudent to minimize prolonged inhalation exposure to these forms not to exceed the occupational exposure limit.

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing vapours.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
Ireland - Occupational Exposure Limits	
Local name	4,4'-Methylene-diphenyl diisocyanate (as —NCO) [MDI]
OEL TWA	0.005 ppm
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values), Sens (In the workplace, respiratory or dermal exposures to sensitising agents may occur. Sensitisers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The “sens” notation alone does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitisers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2024

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment symbol(s):

Eye and face protection

Eye protection:
Safety glasses

Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves. Breakthrough time : refer to the recommendations of the supplier. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves	Nitrile rubber (NBR), Butyl rubber	2 (> 30 minutes)			

Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Solid
Colour	:	light brown.
Appearance	:	Paste.
Odour	:	slight.
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not available
Lower explosion limit	:	Not applicable
Upper explosion limit	:	Not applicable
Flash point	:	> 100 °C
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	Not available
pH	:	Not available
pH solution	:	Not available
Viscosity, kinematic	:	23076.923 – 54545.455 mm^2/s
Viscosity, dynamic	:	30 – 60 Pa·s
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	1.1 – 1.3 g/cm^3
Relative density	:	Not available
Relative vapour density at 20°C	:	Not applicable
Particle size	:	Not available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Inhalation:dust,mist: Harmful if inhaled.

Fill&Fix Component B	
ATE CLP (dust,mist)	1.308 mg/l/4h

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
LD50 oral rat	> 10000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 9400 mg/kg (OECD 402 method)
LC50 Inhalation - Rat (Vapours)	0.31 mg/l/4h (OECD 403 method)

aromatic polyisocyanate prepolymer (99784-49-3)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 9400 mg/kg (OECD 402 method)

o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: other:
LD50 dermal rabbit	> 9400 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
LD50 oral rat	> 2000 mg/kg bodyweight
LD50 dermal rabbit	> 9400 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	0.49 mg/l

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
IARC group	3 - Not classifiable

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
STOT-single exposure	May cause respiratory irritation.

aromatic polyisocyanate prepolymer (99784-49-3)	
STOT-single exposure	May cause respiratory irritation.

o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)	
STOT-single exposure	May cause respiratory irritation.

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

aromatic polyisocyanate prepolymer (99784-49-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Fill&Fix Component B	
Viscosity, kinematic	23076.923 – 54545.455 mm²/s

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
Viscosity, kinematic	> 161.551 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Toxic to aquatic life with long lasting effects.

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
LC50 - Fish [1]	> 1000 mg/l Brachydanio rerio (zebra-fish)
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna (Water flea)
ErC50 algae	> 1640 mg/l Scenedesmus subspicatus
NOEC chronic crustacea	> 10 mg/l Daphnia magna (Water flea)
aromatic polyisocyanate prepolymer (99784-49-3)	
NOEC chronic crustacea	> 10 mg/l (OECD 202 method)
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
LC50 - Fish [1]	> 1000 mg/l Brachydanio rerio (zebra-fish)
NOEC (chronic)	≥ 10 mg/l

12.2. Persistence and degradability

Fill&Fix Component B	
Persistence and degradability	Not rapidly degradable
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
Persistence and degradability	Not rapidly degradable
aromatic polyisocyanate prepolymer (99784-49-3)	
Persistence and degradability	Not rapidly degradable
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)	
Persistence and degradability	Not rapidly degradable
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	
Bioconcentration factor (BCF REACH)	< 14 Cyprinus carpio (Common carp)
Partition coefficient n-octanol/water (Log Pow)	10.46
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)	
Partition coefficient n-octanol/water (Log Pow)	4.51

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	:	Only pass on empty containers/packaging for recycling.
Additional information	:	Not classified as hazardous waste when part A and part B are mixed and are fully cured.
European List of Waste (LoW, EC 2000/532)	:	08 05 01* - waste isocyanates

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
Special provision(s) applied : 375	Special provision(s) applied : 969	Special provision(s) applied : A197
These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of the transport regulations provided the packagings meet the general provisions.		
14.1. UN number or ID number		
UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (aromatic polyisocyanate prepolymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (aromatic polyisocyanate prepolymer)	Environmentally hazardous substance, solid, n.o.s. (aromatic polyisocyanate prepolymer)
Transport document description		
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (aromatic polyisocyanate prepolymer), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (aromatic polyisocyanate prepolymer), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (aromatic polyisocyanate prepolymer), 9, III
14.3. Transport hazard class(es)		
9	9	9
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	M7
Special provisions (ADR)	:	274, 335, 375, 601
Limited quantities (ADR)	:	5kg

Excepted quantities (ADR)	:	E1
Packing instructions (ADR)	:	P002, IBC08, LP02, R001
Special packing provisions (ADR)	:	PP12, B3
Mixed packing provisions (ADR)	:	MP10
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V13
Orange plates	:	
Tunnel restriction code (ADR)	:	-

Transport by sea

Special provisions (IMDG)	:	274, 335, 966, 967, 969
Limited quantities (IMDG)	:	5 kg
Packing instructions (IMDG)	:	LP02, P002
Special packing provisions (IMDG)	:	PP12

Air transport

PCA packing instructions (IATA)	:	956
PCA max net quantity (IATA)	:	400kg
CAO packing instructions (IATA)	:	956
CAO max net quantity (IATA)	:	400kg
Special provisions (IATA)	:	A97, A158, A179, A197, A215
ERG code (IATA)	:	9L

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

Full text of H- and EUH-statements:	
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH204	Contains isocyanates. May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.