

## FURNITURE SAVIOR

Properties	Value	Unit	Method / Remarks
	System		
Chemical Base	polyurethane		
Consistency	non-sag		
Color	beige		
Storage temperature	+5 to +25	°C	
Shelf life	12	months	in the unopened original packaging, in a dry place
Skin formation time	1 - 2	min	at 22 °C

### Application

Fast repair compound for repairing broken out hinges.

2-component, solvent-free injection compound for the quick repair of torn out cabinet doors, door hinges, handles in wood and panel building materials. Wood screws can be screwed in directly and unscrewed out again. This enables simple and quick installation. After approx. 2 minutes any material, that can be used in wood, can be added to the cured compound without pre-drilling.

Screws, hooks, eyelets or similar up to Ø 6 mm can be screwed in and out again.

### Properties / Features

- screwable
- paintable
- grindable
- final strength after 5 minutes
- for indoor and outdoor applications

### Directions for use

Extrude at least 4 cm and reject. The compound swells during curing. Remove excess material after curing.

After use, leave the mixing nozzle on the syringe. When using the syringe again, turn off the mixing nozzle and remove any encrusted material at the syringe opening, turn on a new mixing nozzle.

**Storage**

Store at +5 to +25 °C.

For further safe handling information on this product, consult the Safety Data Sheet (SDS).

The information in this technical data sheet and our application-technology consulting, verbally and in writing, is given to the best of our knowledge, but is non-binding and is not a guarantee in the sense of § 443 BGB. We recommend that, before using our products, you check the suitability for the intended application. As the individual product can be used for a wide range of applications and the conditions on site that cannot be estimated, we also recommend testing the bonding before using the product.