

Bolt anchor MAX

Load table

Permissible loads of a single anchor¹⁾ in normal concrete of strength class C20/25

For the design the complete current assessment ETA-10/0170 has to be considered.

Type	Material / surface ²⁾	Effective an- chorage depth h_{ef} [mm]	Minimum mem- ber thickness h_{min} [mm]	Installation- torque T_{inst} [Nm]	Cracked concrete				Non-cracked concrete			
					Permissible Tension (N_{perm}), Shear loads (V_{perm}), minimum spacing (s_{min}) and edge distances (c_{min})				Permissible Tension (N_{perm}), Shear loads (V_{perm}), minimum spacing (s_{min}) and edge distances (c_{min})			
					$N_{perm}^{3)}$ [kN]	$V_{perm}^{3)}$ [kN]	$s_{min}^{3)}$ [mm]	$c_{min}^{3)}$ [mm]	$N_{perm}^{3)}$ [kN]	$V_{perm}^{3)}$ [kN]	$s_{min}^{3)}$ [mm]	$c_{min}^{3)}$ [mm]
MAX 8	zp	35	80	20	2.6	7.8	35	40	4.9	7.8	40	40
	zp	45	90	20	3.8	7.8	35	40	6.7	7.8	40	40
	R	35	80	20	2.6	9.5	35	40	4.9	9.6	40	40
	R	45	90	20	3.8	9.6	35	40	6.7	9.6	40	40
MAX 10	zp	40	90	45	4.1	12.2	40	45	5.9	12.2	40	45
	zp	60	110	45	6.2	12.2	40	45	9.5	12.2	40	45
	R	40	90	45	4.1	13.3	40	45	5.9	15.1	40	45
	R	60	110	45	6.2	15.1	40	45	9.5	15.1	40	45
MAX 12	zp	50	100	60	5.8	17.5	50	55	8.3	17.5	50	55
	zp	70	120	60	9.5	17.5	50	55	10.5	17.5	50	55
	R	50	100	60	5.8	18.6	50	55	8.3	21.9	50	55
	R	70	120	60	9.5	21.9	50	55	10.5	21.9	50	55
MAX 16	zp	65	140	110	8.6	31.4	60	65	12.3	31.4	65	65
	zp	85	140	110	12.9	31.4	60	65	18.4	31.4	65	65
	R	65	140	110	8.6	25.8	60	65	12.3	36.8	65	65
	R	85	140	110	12.9	38.6	60	65	18.4	39.9	65	65
MAX 20	zp	100	170	200	16.4	42.6	95	85	23.4	46.5	95	95
	R	100	170	200	16.4	42.6	95	85	23.4	60.7	95	95

¹⁾ Design according to EN 1992-4:2018 (for static resp. quasi-static loads). The partial safety factors for material resistance as regulated in the ETA as well as a partial safety factor for load actions of $\gamma_L = 1.4$ are considered. As a single anchor counts e.g. an anchor with a spacing $s \geq 3 \times h_{ef}$ and an edge distance $c \geq 1.5 \times h_{ef}$. Accurate data see ETA.

²⁾ Further steel grades, versions and technical data see ETA, e.g. for dry internal conditions, galvanised steel zp; for damp interior stainless steel R and exterior conditions, e.g. material 1.4362, 1.4401.

³⁾ In the case of combinations of tensile and shear loads, bending moments and reduced edge and axial spacings (anchor groups), the design must be carried out in accordance with the provisions of the complete ETA and the provisions of the EN 1992-4:2018. We recommend to use our anchor design software DesignFix.