


Loads



FCN Clix P and FCN Clix M

Item	Item No.	Max. recom- mended tension load for FUS 1,5 mm	Max. recom- mended tension load for FUS 2,0 mm	Max. recom- mended tension load for FUS 2,5 mm	Max. recom- mended shear load for FUS 1,5 mm	Max. recom- mended shear load for FUS 2,0/2,5 mm	Tightening torque for screw grade \geq 8.8	Tightening torque for screw grade \geq 4.6
		N_{rec} [kN]	N_{rec} [kN]	N_{rec} [kN]	V_{rec} [kN]	V_{rec} [kN]	T_{inst} [Nm]	T_{inst} [Nm]
FCN Clix P 6	559757	2.5	3.0	3.0	1.0	1.0	10	—
FCN Clix P 8	559758	3.0	4.0	4.0	1.5	2.0	20	—
FCN Clix P 10	559759	4.0	5.0	8.0	2.0	2.5	40	—
FCN Clix P 12	559760	4.0	5.0	8.0	2.0	3.0	50	—
FCN Clix M 6	559761	—	3.0	3.0	—	—	—	5
FCN Clix M 8	559762	—	4.0	4.0	—	—	—	10
FCN Clix M 10	559763	—	5.0	8.0	—	—	—	15
FCN Clix M 12	559764	—	5.0	8.0	—	—	—	20