

**TermoZ CS II**

Permissible tension loads for a single anchor<sup>1)2)</sup> for multiple use for non-structural applications.  
For the design the complete current assessment ETA-14/0372 has to be considered.

						Beton und Mauerwerk			
Type CS II	Brick raw density $\rho$ [kg/dm <sup>3</sup> ]	Minimum compressive brick strength $f_b$ [N/mm <sup>2</sup> ]	Effektive Verankerungstiefe $h_{ef} \geq$ [mm]	Depth of drill hole <sup>3)</sup> $h_{1,Flush} / h_{1,LCSK}$ [mm]	Minimum member thickness $h_{min}$ [mm]	Permissible tension load <sup>1)</sup> $N_{perm}$ [kN]	Minimum spacing <sup>4)</sup> $s_{min}$ [mm]	Minimum edge distance <sup>4)</sup> $c_{min}$ [mm]	
Concrete	-	$\geq C12/15$	25	40 / 55	100	0.50	100	100	
	-	$\leq C50/60$	25	40 / 55	100	0.50	100	100	
Weather resistant concrete shell	-	$\geq C20/25$	25	40 / 55	$\geq 40$	0.50	100	100	
Solid Clay bricks e.g. acc. to DIN EN 771-1:2015, Mz	$\geq 1.8$	20	25	40 / 55	100	0.50	100	100	
Calcium silicate solid bricks, e.g. acc. to DIN EN 771-2:2015, KS	$\geq 1.4$	20	25	40 / 55	100	0.50	100	100	
	$\geq 1.4$	12	25	40 / 55	100	0.50	100	100	
Solid lightweight concrete block, e.g. acc. to DIN EN 771-3:2015, Vbl	$\geq 1.4$	8	25	40 / 55	100	0.40	100	100	
Solid concrete block, e.g. acc. to DIN EN 771-3:2015, Vbn	$\geq 2.0$	20	25	40 / 55	100	0.50	100	100	
	$\geq 2.0$	12	25	40 / 55	100	0.50	100	100	
Vertically perforated clay bricks e.g. acc. to DIN EN 771-1:2015, HLz	$\geq 0.9$	12	25	40 / 55	100	0.22	100	100	
	$\geq 0.9$	12	25	40 <sup>5)</sup> / 55 <sup>5)</sup>	100	0.33	100	100	
	$\geq 1.6$	48	25	40 / 55	100	0.50	100	100	
	$\geq 1.6$	48	25	40 <sup>5)</sup> / 55 <sup>5)</sup>	100	0.50	100	100	
Hollow calcium silicate brick, acc. to DIN EN 771-2:2015, KSL	$\geq 1.4$	12	25	40 / 55	100	0.50	100	100	
Hollow brick lightweight concrete, e.g. acc. to DIN EN 771-3:2015 Hbl	$\geq 0.9$	4	25	40 / 55	100	0.17	100	100	
Hollow brick concrete, e.g. acc. to DIN EN 771-3:2015 Hbn	$\geq 1.2$	10	25	40 / 55	100	0.50	100	100	
	$\geq 1.2$	8	25	40 / 55	100	0.50	100	100	
	$\geq 1.2$	6	25	40 / 55	100	0.37	100	100	
	$\geq 1.2$	4	25	40 / 55	100	0.25	100	100	
Lightweight aggregate concrete acc. to DIN EN 1520:2011-6, LAC	$\geq 0.9$	6	25	40 / 55	100	0.50	100	100	
	$\geq 0.9$	6	25	40 / 55	100	0.50	100	100	
Autoclaved aerated concrete blocks, e.g. AAC acc. to DIN EN 771-4:2015	$\geq 0.5$	4	25	40 <sup>5)</sup> / 55 <sup>5)</sup>	100	0.22	100	100	
	$\geq 0.5$	4	45	60 <sup>5)</sup> / 75 <sup>5)</sup>	100	0.37	100	100	

<sup>1)</sup> Plastic anchor for fixing of external thermal insulation composite systems with rendering acc. to ETA data. Only tension wind loads are permitted. The partial safety factors for material resistance as regulated in the assessment as well as a partial safety factor for load actions of  $\gamma_L = 1.5$  are considered.

<sup>2)</sup> The given loads are valid for installation and use of fixations in dry base material for temperatures in the substrate up to +24 °C (resp. short term up to +40 °C).

<sup>3)</sup> Depth of the drilled hole to the deepest point for flush or countersunk installation. Drilling method Hammer drilling. For details on installation data, see ETA.

<sup>4)</sup> Minimum possible axial spacing and edge distances acc. to ETA.

<sup>5)</sup> Rotary drilling.