



Air conditioner on the outer wall

Applications

- · Universal fixing for air conditioners
- MCE Klima Klik air conditioner fixing onto walls with max. fixing distance of 760 mm on the horizontal channel
- Please consider: load bearing capacity of the wall and the quality of the substrate

Advantages

- The complete kit including anti vibration damper, plugs and screws offers an optimised installation security.
- The bracket with quick snap (Klik) simplifies and shortens the installation.
- The horizontal channel of the MCE Klima Klik allows a flexible adjustment of the brackets and simplifies the installation additionally.
- The MCE Klima Klik horizontal channel with included horizontal level tool enables the adjustment without additional tools.


Properties


- · Material: steel
- · Coating: powder coating
- · Colour: RAL 9002


Installation Klima Easy Klik












Installation Klima Klik 420



















Klima Easy Klik


Klima Klik 420

Technical data

		Length	Length	Length	L4	static load load case 1 F _{rec}	Max. recommended static load load case 2	
	Item no.	[mm]	[mm]	[mm]	[mm]	[kN]	[kN]	[pcs]
Item								
KLIMA EASY KLIK	521760	400	420	380	-	1.00	1.00	1
KLIMA KLIK 420	521761	400	420	380	780	1.00	1.00	1

The loads are valid for the use in pairs (two consoles).

Load case 1



Load case 2

