Nail disc NSB

The secure cable fixing in wall slots.





Cable fixing



Cable fixing in slots

Applications

· For fixing cables in wall slots

Advantages

- The nail disc NSB allows for use in two slot widths.
- The vaulted structure of the nail disc ensures an optimal contact pressure and, as such, for a secure hold.
- · The flat nail disc only protrudes slightly,

Building materials

- · Vertically perforated brick
- Pumice
- · Lightweight aggregate concrete
- · Aerated concrete
- · Hardboard
- · Wood
- · Chipboard
- · Plywood
- · Solid panel made from gypsum


and can thus be easily plastered over.


 The nail disc NSB is made from highstrength polypropylene. The nail is made from hardened, galvanised steel. The tried and tested material combination for in-wall installation.

Functioning

- · Pull in cable.
- Align the nail disc with either dimensions 27 mm or 34 mm, depending on the slot width, and hit the nail in with a hammer.
- The cables are fixed in the wall slots by the curved washer.

Installation NSB





Technical data

Nail disc NSB

NSB

		Dimension of nail	Dimension of disc	Sales unit
		axb	b x l	
	Item no.	[mm]	[mm]	[pcs]
Item				
NSB 2/40	048308	2 x 40	27 x 34	200
NSB 2/50	048309	2 x 50	27 x 34	150
NSB 2/60	048310	2 x 60	27 x 34	100
NSB 3/40	048311	3 x 40	27 x 34	150
NSB 3/50	048312	3 x 50	27 x 34	150
NSB 3/60	048313	3 x 60	27 x 34	100