

Hose clamp SGS

The hose clamp for large hoses, pipe or ducting

2



Outlet valve with hose

Applications


- Sealing of hoses.
- Fixing hoses to adapters.

Advantages

- The crimped band edges offer protection against damage to the hose.
- The short base of the hosing allows an ideal adjustment and high, radial forces on the hose diameter.
- The screw's combination cross-drive thread enables installation flexibility.

Properties


- Material class: W2
- Worm: CQ 15 (material no. 1.1132) acc. to DIN EN 10263
- Housing and band: chromium steel (material no. 1.4016) acc. to DIN EN 10088 or equivalent corrosion-resistant steel



SGS

Technical data

		Clamping range	Width x thickness clamp band	Sales unit
	Item no.	D [mm]	b x s [mm]	[pcs]
Item				
SGS 9 W2 8 - 12	045517	8 - 12	9.0 x 0.6	100
SGS 9 W2 10 - 16	045518	10 - 16	9.0 x 0.6	100
SGS 9 W2 12 - 20	045519	12 - 20	9.0 x 0.6	100
SGS 9 W2 16 - 27	045520	16 - 27	9.0 x 0.6	100
SGS 9 W2 20 - 32	045521	20 - 32	9.0 x 0.6	100
SGS 9 W2 25 - 40	045522	25 - 40	9.0 x 0.6	100
SGS 9 W2 32 - 50	045523	32 - 50	9.0 x 0.6	100
SGS 9 W2 40 - 60	045524	40 - 60	9.0 x 0.6	25
SGS 9 W2 50 - 70	045525	50 - 70	9.0 x 0.6	25
SGS 9 W2 60 - 80	045526	60 - 80	9.0 x 0.6	25



SGS

Technical data

Item	Item no.	Clamping range D [mm]	Width x thickness clamp band b x s [mm]	Sales unit [pcs]
SGS 9 W2 70 - 90	045527	70 - 90	9.0 x 0.6	25
SGS 9 W2 80 - 100	045528	80 - 100	9.0 x 0.6	25
SGS 9 W2 90 - 110	045529	90 - 110	9.0 x 0.6	25
SGS 9 W2 100 - 120	045530	100 - 120	9.0 x 0.6	25
SGS 9 W2 110 - 130	045531	110 - 130	9.0 x 0.6	25
SGS 9 W2 120 - 140	045532	120 - 140	9.0 x 0.6	25