

# Spiral duct hanger LRB / LRBN

Fastening components - Spiral duct hanger LRB and LRBN

8



Spiral duct pipe with sound insulated hanger

### Applications


- Fastening component with sound-insulation for spiral ducts.
- For use in dry interior areas.

### Advantages


- The multiple holes on the duct hangers allow a quick and easy fastening with self-drilling screws or rivets.
- The duct hangers sound-insulation element reduces the transfer of vibration and noise.
- The center hole in the duct hangers allows the simple alignment and height adjustment of the threaded rod.
- The riveted version gives the ceiling hanger increased stability.

### Properties

- Material LRB: steel DD11 (material no. 1.0332) acc. to DIN EN 10111
- Material LRBN: steel S235JR (material no. 1.0038) acc. to DIN EN 10025
- Zinc plating: electro zinc-plated
- Sound insulation: for DIN 4109
- Temperature range: -50 °C to +110 °C
- Hardness: 45 ± 5° Shore A
- Fire behaviour: DIN 4102: Class B2



LRB



LRBN

### Technical data

Item	Item no.	For thread	Max. recom. static load (centr. tension)	Sales unit
			[kN]	[pcs]
LRB	024675	M8	0.50	50
LRBN	077613	M8, M10	0.90	50

See also:



Product family Profile connecting screw  
FPS-FPB Page 261