# **U-Clamp FUBD**

The easy handling pipe and cable clamp for direct attachment of lines to FUS mounting channels





Supply lines fixed to FUS channel

## **Applications**

- Fast installation of metal and plastic pipes, flexible plastic pipes or cables without sound insulation requirements directly to FUS installation channels.
- Fits to FUS channels FUS 21, FUS 41, FUS 62, FUS 21D, FUS 41D, FUS 62D.
- · For use in dry interior areas.


### **Advantages**


- The FUBD without soundproofing is ideal for use in industrial applications, for example, for fixing lightweight flexible supply lines in the immediate area of production machines.
- Locking screw with hexagonal and slot drive.
- Quick adaptation to the desired outside pipe diameter by fastening the pressure pan.
- No loss of parts due to preassembled parts.
- Time- and cost-saving installation without the need of accessories like threaded rods or sliding nuts.

#### **Properties**

- Material U-Strap: steel S235JRC (material no. 1.0122) acc. to EN 10025
- · Zinc plating U-Strap: hot-dip galvanised
- Material pressure pan: steel DX51D acc. to DIN EN 10346
- Zinc plating pressure pan: electro zincplated
- Material locking screw: steel 4.6 acc. to EN 20898-1
- Locking screw: with hexagonal SW10 and slot head

#### **Installation FUBD**





# **Technical data**

		Clamping range	Height	Width x thickness clamp band	Locking screw	Sales unit
		D	Н	b x s		
	ltem no.	[mm]	[mm]	[mm]		[pcs]
Item						
FUBD 40	539564 <sup>1)</sup>	36 - 40	71	25 x 1.75	M6	100
FUBD 48	558148	44 - 48	85	25 x 2.0	M8	50
FUBD 52	539566	48 - 52	90	25 x 2.0	M8	50
FUBD 60	539567 <sup>1)</sup>	56 - 60	98	30 x 2.25	M8	50
FUBD 76	539568 <sup>1)</sup>	70 - 76	113	30 x 2.75	M8	25
FUBD 94	539569 <sup>1)</sup>	88 - 94	141	30 x 2.75	M8	20
FUBD 100	539570 <sup>1)</sup>	94 - 100	147	30 x 2.75	M8	10

<sup>1)</sup> Delivery time on request.

2